

Release Version v2.3 (2015/01/14)

New Features

1. Support NUUO Crystal™ and Titan NVR with Live view, alarm and playback (Refer user manual for detail support functions and alarms)
2. Support Mainconsole Edge Motion Event
3. Support MainConsole Failover with Live View and Playback
4. Support H.265

Enhancement

1. Control Multiple PTZ camera in Single PTZ Control Panel
2. Set a Default Matrix for Live View Navigation
3. Multiple Remote Desktop Login Mainconsole

Known Issue

1. Cannot apply the stream profile from Crystal / Titan to Mainconsole / NVRmini / NVRSolo, and vice versa.
2. On CMS Matrix, when camera from Crystal lost the connection, it will only show freeze image and do not have disconnect OSD.
3. The stream profile value of Crystal and Titan is incorrect.
4. After adding alarms from Crystal or Titan, please wait around 1~2 minutes, so CMS side can receive alarms correctly
5. Crystal and Titan do not support Set Layout profile.

Support OS

1. Windows XP 32 bit
2. Windows Vista 32 bit
3. Windows 7 32 bit and 64 bit
4. Server 2008 R2 (64 bit)
5. Server 2012 R2
6. Windows 8 64 bit (Need to disable Windows UAC before starting NCS system)
7. Windows 8.1 32 bit and 64 bit

Support NUUO product line

1. Mainconsole: 6.1.1 or later (DVR card only support 6000S/7000S/7100/8000HD)
2. NVRmini2: 1.6.1 or later
3. NVRsolo: 1.0 or later
4. Crystal: 3.1.0 or later
5. Titan NVR: 1.7.0 or later.

Release Version v2.1 (2015/4/30)

New Features

- NCS Client
 - A. Support live video scramble (with Mainconsole v5.2)

Enhancement

- NCS Client
 - A. Support offline mode
 - a. When server has new configuration update by other user, the user can choose login again to update the configuration or keep as offline mode.
 - b. In offline mode, user will run out-of-date configuration and still can do live view/backup/export.
 - c. In offline model, alarm and server status won't be updated and some options will be disabled and be gray out indicating not available.

Support OS

- Windows XP 32 bit
- Windows Vista 32 bit
- Windows 7 32 bit and 64 bit
- Server 2008 R2 (64 bit)
- Server 2012 R2
- Windows 8 64 bit (Need to disable Windows UAC before starting NCS system)
- Windows 8.1 32 bit and 64 bit

Support NUUO product line

- Mainconsole: 4.1.0 or later (DVR card only support 6000S/7000/7000S/7100/8000HD)
- NVRmini: 2.6
- NVRmini2: 1.6.1 or later
- NVRsolo: 1.0 or later

Release Version v2.0 (2014/5/12)

New Features

- NCS Client
 - A. Support Camera Multi-Stream (with Mainconsole v5.0)
 - B. Central Manual Backup: Support both Alarm & Video central backup
 - C. Support lock screen: Able to lock window in full screen to ensure focus on NCS client
 - D. Add Camera Link: Able to add direct IP address links to each individual camera
 - E. Add Hotkeys to set alarm status for Alarm Real-Time/Output/Output2 and Alarm Management windows

Enhancement

- NCS Client
 - A. All new Alarm Management interface - Live View & Instant Playback on one screen
 - B. Simplifying NCS Client menu layout
 - C. Support for NVRmini2/NVRsolo 2-way audio
 - D. Support for NVRmini2/NVRsolo snapshot to CMS

Fixed Bug

- NCS Client
 - A. Only able to "select one" PTZ Camera preset point on NCS Client
 - B. With live view pop-up window, when alarm keeps occurring, the 4th pop-up window (most recent alarm) overtakes the 3rd pop-up window (2nd recent alarm) instead of the oldest alarm. Fixed to overtake the oldest pop-up window

Known Issue

- NCS Client
 - A. If an Alarm Note is already written in Alarm Management window, and its alarm status is then changed from Real-Time Alarm list using Hotkey functions, the Alarm Note will appear as blank. However you can still find the Alarm Note details with Advance Alarm Search (under Tools)

Support OS

- Windows XP 32 bit
- Windows Vista 32 bit
- Windows 7 32 bit and 64 bit
- Server 2008 R2 (64 bit)
- Server 2012 R2
- Windows 8 64 bit (Need to disable Windows UAC before starting NCS system)
- Windows 8.1 32 bit and 64 bit

Support NUUO product line

- Mainconsole: 4.1.0 or later (DVR card only support SCB-6000/6000S/7000/7000S/7100/8000HD)
- NVRmini: 2.6
- NVRmini2: 1.6.1 or later
- NVRsolo: 1.0 or later