

## Release Version v3.0.1 (2014/02/14)

### Modules:

Device Pack v 3.0.1

### Supported Systems:

NVRmini 2 v 1.7.1 and above

### Bug fixed:

NVRmini 2:

1. Fixed the issue that cannot login web client.

## Release Version v3.0.0 (2014/2/5)

### Modules:

Device Pack v 3.0.0

### Supported Systems:

Mainconsole	v 4.1.12 and above*
NVRmini 2	v 1.7.1 and above
NVRsolo	v 1.1.1 and above
Titan NVR	v 1.6.2 and above
Crystal Titan	v 2.0.3 and above

\*For Mainconsole multi stream and setting function, please upgrade to Mainconsole v5.0.0 and above first.

### New Camera Supported:

<b>Arecont</b>	AV3145 , AV5245 and Generic model
<b>Axis</b>	M3025, M3026 and P5415
<b>Dlink</b>	DCS-6045L
<b>Dynacolor</b>	NH720-20N8 and NH820-20N8
<b>Eneo</b>	PXB-2180Z03, PXC-2080CS and PXC-2080Z03
<b>Fine</b>	CDB-HFD720, CDB-MV720F-H, CDV-MD602, CDV-P360-5 (fisheye camera), TCP-BF128, TCP-HDVB720-H and TCP-MB602
<b>Samsung</b>	SNB-5003, SNB-5004, SND-5083, SND-5084 and SNV-5084
<b>Sony</b>	SNC-EB600, SNC-EB600B, SNC-EB630B, SNC-EM601, SNC-EM602R, SNC-EM630, SNC-EM631, SNC-EM632R, SNC-VB635, SNC-VM601, SNC-VM602R, SNC-VM631 and SNC-VM632R
<b>Sunell</b>	SN-IPR54/31UDN
<b>Truen</b>	TN-B200CE, TN-B202CEIR, TN-D1202CE, TN-P1220CS, TN-P1222CGPLX, TN-P1230CS, TN-P3220CS, TN-P3220CSIR and TN-P3220CTIR
<b>Vivotek</b>	FD8137H, FD8137HV and IP8364
<b>Zavio</b>	B7510 and D4210

## FW upgrade:

<b>Axis</b>	P7210 (FW 5.50.2)
<b>Centrix</b>	Generic model (FW cx20131107NSA)
<b>Dlink</b>	DCS-3010, DCS-3714 and DCS-5222LB1(FW : v1.11.00)
<b>Eneo</b>	PXB-1080Z03, PXB-2080MIR, PXB-2080Z03, PXD-2080MIR and PXD-2080Z03 (FW 4.23.49-ds)
<b>Sony</b>	SNC-EM600, SNC-VB630 and SNC-VM630

## New Feature:

Mainconsole:

1. Support multi stream setting function with Mainconsole v5.0.0 and above on Axis PQM series, Arecont all series, Vivotek 8000 series and Samsung SNB-5003, SNB-5004, SND-5083, SND-5084 and SNV-5084 from DP v3.0.0.
2. Support multi stream function with requested cameras. (please refer to [http://www.nuuo.com/SupportCamera.php?node\\_id=4#4](http://www.nuuo.com/SupportCamera.php?node_id=4#4))

## Enhancement:

1. Adjust Samsung camera SNP-3120V, SNP-3430H, SNZ-5200, SPE-100 PTZ speed to 3 or 1.
2. D-Link China camera DCS-V70M-21H, DCS-V70M-21H2 multi-stream:
  - i. Adjust fps range from 15 to 20.
  - ii. Adjust 2<sup>nd</sup> stream resolution to 640x480.
  - iii. Adjust 2<sup>nd</sup> stream bitrate to 1000kbps.

## Notice:

1. Samsung:
  - a. SNB-5003, SNB-5004, SND-5083, SND-5084 and SNV-5084 :
    - i. Support 64 preset points.
    - ii. Default value of Talk will setup to 5.
    - iii. When change audio setting on camera web, the previous connection will be interrupted and re-connect. (camera firmware issue)
2. Dynacolor
  - a. NH820-20N8, NH720-20N8
    - i. When using MJPEG format, camera reply is slow. (camera firmware issue)
    - ii. It would not support motion detection when camera resolution is 1920x1080 (Low Latency). (camera firmware issue)

- iii. Camera does not support MJPEG format with 1280x720 (Low Latency). (camera firmware issue)
- 3. Sunell
  - a. SN-IPR54/31UDN
    - i. Due to Onvif limitation, some framerate and bitrate cannot setup.
- 4. Fine
  - a. CDV-MD602
    - i. Motion detection may fail when select 30 fps mode. (camera firmware issue)
- 5. D-Link
  - a. DCS-3010
    - i. Motion detection may fail after setting camera parameter. (camera firmware issue)
    - ii. Camera may not work when setup bitrate to 8000kbps. (camera firmware issue)
    - iii. Not support dual stream.
    - iv. The live view may delay when setup high resolution. (camera firmware issue)
  - b. DCS-5222LB1
    - i. Not support talk. (camera firmware issue)
    - ii. Not support preset. (camera firmware issue)
    - iii. Direction of PTZ is opposite. (camera firmware issue)
    - iv. The live view may delay when setup high resolution. (camera firmware issue)
  - c. DCS-3714
    - i. Not support 8M bitrate. (camera firmware issue)
  - d. DCS-6045L
    - i. It may need to reboot again after a period of time. (camera firmware issue)
- 6. Arecont
  - a. Due to camera performance, camera fps may not reach to the frame rate configuration.
  - b. Audio function may not work after connect/disconnect, and need to reboot camera.
- 7. Eneo
  - a. Only support RTSP port 554 (camera firmware issue)
  - b. Only integrate NTSC mode.
  - c. Audio will be discontinuous under fps 1.
  - d. Camera fps may not reach to camera setting under high resolution, frame rate and quality.
  - e. Not support brightness, contrast, saturation on Mainconsole (camera firmware issue)
  - f. Audio out is not supported with Mainconsole (camera firmware issue)

## Bug fixed:

### Mainconsole:

1. [Onvif] Fixed the issue that causes Mainconsole error when adding cameras

### NVRmini 2:

1. [IPPower] Fixed the issue that causes live view delay and incorrect camera fps display.
2. [Vivotek] Fixed the issue that causes FD8136 dual stream do not display correctly.
3. [RTSP] Fixed the issue that CPU loading will increase after audio function turn off.

### NVRsolo:

1. [IPPower] Fixed the issue that causes live view delay and incorrect camera fps display.
2. [RTSP] Fixed the issue that CPU loading will increase after audio function turn off.

### Titan NVR:

1. [IPPower] Fixed the issue that causes live view delay and incorrect camera fps display.
2. [Sony] Fixed the issue that causes Sony camera to disconnect.
3. [RTSP] Fixed the issue that CPU loading will increase after audio function turn off.

### Crystal Titan:

1. [Sony] Fixed the issue that causes Sony camera PTZ speed delay.
2. [IPPower] Fixed the issue that causes live view delay and incorrect camera fps display.
3. [RTSP] Fixed the issue that CPU loading will increase after audio function turn off.

## Release Version v2.20.0 (2013/12/26)

### Modules:

Device Pack v 2.20.0

### Supported Systems:

Mainconsole	v 4.1.12 and above
NVRmini 2	v 1.7.1 and above
NVRsolo	v 1.1.1 and above
Titan NVR	v 1.6.2 and above
Crystal Titan	V 2.0.0 and above

### New Camera Supported:

<b>Arecont</b>	AV2256 and AV2456
<b>Aver</b>	FB2027-1, FB2027-2, FB2027-3, FB2028, FB2028-T1, FB2028-T2, FB2028-TM, FB3027, FB3028-RT1, FB3028-RT2, FB3028-RTM, FD2020, FD3020, FD3020-M, FV2006, FV2028, FV3028, FV3028-RT, FV3028-RTM, FX2000, FX3000-R, SF2121H-BHR-30, SF2121H-BHR-50 and SF2121H-R
<b>Axis</b>	M3024-L, P5414, Q1765-LE, Q6044 and Q6045
<b>Dlink</b>	DCS-5222LB1
<b>DlinkCN</b>	DCS-H41-11D/I and DCS-H41-12D/I
<b>Dynacolor</b>	NA083 (fisheye camera)
<b>Fine</b>	MD-D3622Q-H, SP-HP2330Q-IP, TCP-336AM, TCP-IRH5080-50 and TCP-IRH5080-70
<b>Forenix</b>	IPB-1080BL, IPB-1080BM, IPD-1080CD, IPV-1080CD and IPX-1080DN
<b>Hikvision</b>	DS-2CD7253F-EIZ
<b>Messo</b>	NCR858, NCR878, NDF821, NDF821PRO, NDF831, NDF831PRO and NDR891PRO
<b>Pelco</b>	D5220, IL10 and IM10
<b>Sony</b>	SNC-EB630, SNC-EM600, SNC-VM600 and SNC-VM630
<b>Vivotek</b>	FD8135H, FD8164, FD8164V, SD83x4, SD83x6

### FW upgrade:

<b>Dlink</b>	DCS-2310L, DCS-2332L and DCS-6010L (FW V1.02.00)
<b>MegaIP</b>	NCD-2003PR and NMX-2003P (FW mega-web-51110.2.1262.100.bin )
<b>Santec</b>	SNC-3302, SNC-3322, SNC-4302, SNC-6202, SNC-6302,

## Sony

SNC-6315IRH and SNC-8322I/HO (firmware\_1.0.3.447)

SNC-VB600 (FW 1.9.2)

### Enhancement:

3. Add Brickcom FD-301Af and VD-301Af to 50xA model

### Notice:

#### 8. IP Power:

##### a. Generic:

- i. Focus function does not test with NUUO product.

#### 9. Hikvision:

##### a. DS-2CD7253F-EIZ

- i. Only supports zoom in/out in the PTZ-control.
- ii. When resolution is 1600x1200 and 1600x912, the range of framerate does not synchronize with web.
- iii. 2nd stream format must be the same with main stream except MJPEG.
- iv. UPnP search cannot get a valid mac address. (NVRmini 2/NVR Solo/Titan NVR/Crystal Titan)

#### 10. Aver

- a. MJPEG could not reach to the framerate which user setups. (camera performance issue)
- b. UPNP search failure when change web port from 80 to others.

#### 11. Sony

- a. In certain scenarios i.e. under high frame rate or resolution, camera might have limitation. For further information, please visit Sony A&E Portal: <https://www.security.sony.biz/ssp/ae/homeDisplay.do> (SNC-EB630, SNC-EM600, SNC-VB600, SNC-VM600 and SNC-VM630)
- b. Audio (G726 40kbps, 32kbps, 16kbps) is non-smooth or muted with Titan NVR (SNC-VB600, SNC-VM600 and SNC-VM630)

#### 12. Messoa

- a. It takes 10 sec or more to setup parameter setting.
- b. It will get wrong parameter setting after setup.
- c. Not support talk. (Mainconsole)
- d. Not support auto detection. (NVRmini 2/NVR Solo/Titan NVR/Crystal Titan)

#### 13. D-Link

##### a. DCS-6010L:

- i. When finish resolution parameter setting, fisheye setting will random set back to default setting (Mount type: Desktop; Display Mode: 4R). (Mainconsole)

- b. DCS-2332L, DCS-2310L
  - i. Bitrate List will not change by select different resolution.

## 14. Vivotek

- a. FD8164
  - i. Brightness and Contrast range from -5 to 5 instead of 0 to 100 in web. (camera firmware issue)
- b. SD8316E
  - i. Brightness and Contrast range from -5 to 5 instead of 0 to 100 in web. (camera firmware issue)
- c. FD8135H
  - i. Resolution list does not synchronize with the list on web. (camera firmware issue)
  - ii. When format is setup to MPEG4, resolution is 1280 x 800 and quality is best, the maximum FPS can only reach 20. (NVRmini 2/NVR Solo/Titan NVR/Crystal Titan) (camera firmware issue)

## 15. Fine

- a. MD-D3622Q-H:
  - i. When use Pan speed bar to control Pan speed, Tilt speed will be the same. (Mainconsole)
- b. TCP-336AM:
  - i. When format is MPEG4, resolution is 1920 x 1080 and quality is excellent, the maximum FPS can only reach 20.

## 16. Pelco

- a. D5220
  - i. Preset point name cannot change, and will not synchronize with camera web. (Mainconsole)
  - ii. Video parameter (brightness, contrast, saturation) will not synchronize with camera web. (Mainconsole)
  - iii. When resolution or quality is high, framerate would not reach its setting. (Mainconsole)
  - iv. It may cause Mainconsole unstable when change protocol. (UDP->HTTP, HTTP->UDP)
- b. IM10 and D5220
  - i. It will need to disable second profile on web first and parameter setting can be changed.

## 17. MegaIP

- a. Getting bitrate value would not synchronize with camera web. (Camera onvif issue)



- b. Setting quality value would not synchronize with camera web. (Camera onvif issue)
- c. After setting parameter on camera, camera would restart. After it completed, then can get parameter setting.
- d. Only when http port is 80, motion detection and DI/DO can work.

## Bug fixed:

Mainconsole:

1. [D-Link] Fixed VBR setting issue.

NVRmini 2:

1. [Fine] Fixed the issue that TCP-HFB1080D does not support UPnP.
2. [Samsung] Adjusted SNP-5300 PTZ default speed to 3.
3. [Sony] Fixed the issue that all Sony cameras might disconnect.

NVRsolo:

1. [Fine] Fixed the issue that TCP-HFB1080D does not support UPnP.
2. [Samsung] Adjusted SNP-5300 PTZ default speed to 3
3. [Sony] Fixed the issue that all Sony cameras might disconnect.

Titan NVR:

1. [Fine] Fixed the issue that TCP-HFB1080D does not support UPnP.
2. [Sony] Fixed the issue that all Sony cameras might disconnect.
3. [Samsung] Adjusted SNP-5300 PTZ default speed to 3

Crystal Titan:

1. [Sony] Fixed the issue that all Sony cameras might disconnect.

## Release Version v2.19.0 (2013/11/26)

### Modules:

Device Pack v 2.19.0

### Supported Systems:

Mainconsole	v 4.1.12 and above
NVRmini 2	v 1.7.1 and above
NVRsolo	v 1.1.1 and above
Titan NVR	v 1.6.2 and above

### New Camera Supported:

<b>3Svision</b>	N1011, N1012, N1031, N1032, N3011, N3012, N3031, N3032, N6011, N6012, N6013, N6014, N6015, N6016, N6031, N6032, N6033, N6034, N6035, N6036, N6037, N6038, N8011, N8012, N8031, N8032, N9012, N9032, N9033 and N9034
<b>Arecont</b>	AV5455DN-F, AV3456DN-F
<b>Axis</b>	M2014
<b>DigitalWatchdog</b>	DWC-MD421 and DWC-MV421
<b>Dlink</b>	DCS-2330L, DCS-2132LB1, DCS-3714, DCS-5615 and DCS-7110B1
<b>Fine</b>	TCP-HFB1080D
<b>Hikvision</b>	DS-2CD2612F-IS, DS-2CD2632F-IS, DS-2CD2712F-IS and DS-2CD2732F-IS
<b>i-Mege</b>	G1102E
<b>IP Power</b>	Generic
<b>Mobotix</b>	D15D-Sec, D15D-Sec-DNight, D15D-Sec-Night-Pano, D15D-Sec-Pano, Generic, M15D-Sec, M15D-Sec-DNight, M15M-Sec, S14D-Sec, S14D-Sec-Night, S14M-Sec, S15D-Sec, S15M-Sec and S15M-Sec-Night
<b>Neovista</b>	NV-CB1-36, NV-DP1RP-3312-15, NV-CB1R-36-6, NV-CB1RW-36-6, NV-CB3PL-28, NV-CB3WL-28, NV-DM1P-28, NV-BT3RP-3105-30 and NV-PT13RP-4-15
<b>RIVA</b>	RC1100, RC1100M, RC1202HD, RC2100M, RC2102HD, RC302HD, RC3100, RC3102HD, RC3203HD, RC3302, RC3500, RC3500M, RC3502HD, RC3502HDIR, RC3702, RC4100, RC5500, RC5510, RC6500, RC6602HD, RC6700, RC6802HD, RCC100HD, RE1000 and RE4000
<b>Sunell</b>	SN-VSR54/04
<b>Vivotek</b>	IP8173H, IP8337H and IP8336W

**Zavio** V1100

## FW upgrade:

<b>ATV</b>	IPFD2MT (FW HSNCT3-v2.1.71)
<b>Santec</b>	SNC-3305, SNC-5312IR, SNC-5315IR, SNC-6212IR, SNC-6312IRH, SNC-6315IRH (firmware_1.0.2.386)
<b>Hikvision</b>	DS-2CD7153-E

## Enhancement:

1. Add Brickcom OB-300-NP-AD with zoom and focus to 30xN model
2. Add Brickcom OSD-200 to 20xP model

## Notice:

1. IP Power:
  - a. Generic:
    - i. Focus function is not test on NUUO product.
    - ii. The maximum resolution is depends on camera.
    - iii. Some framerate and bitrate cannot setup due to Onvif restriction.
2. i-Mege:
  - a. G1102E :
    - i. No support on-edge motion when video format is MJPEG.
    - ii. Support UPnP Search after Mainconsole v4.1.18.
    - iii. Camera connection is not stable. (firmware issue)
3. Mobotix:
  - a. D15D-Sec, D15D-Sec-DNight, D15D-Sec-Night-Pano, D15D-Sec-Pano, M15D-Sec, M15D-Sec-DNight, M15M-Sec, S14D-Sec, S14D-Sec-Night, S14M-Sec, S15D-Sec, S15M-Sec and S15M-Sec-Night
    - i. Please setup on Mobotix web setting page first for display mode, ExtIO and on-edge motion.
    - ii. Not support audio when video format is MJPEG.
4. Hikvision:
  - a. DS-2CD2732F
    - i. When resolution is 2048x1536, the range of framerate does not synchronize with web.
  - b. DS-2CD7153-E

- i. When resolution is 1600x1200, the range of framerate does not synchronize with web.
- ii. Except MJPEG, 2nd stream format will be the same as main stream format.

## 5. Santec:

- a. SNC-3305, SNC-5312IR, SNC-5315IR, SNC-6212IR, SNC-6312IRH, SNC-6315IRH
  - i. When resolution is 2048x1536 and PAL mode, the range of framerate does not synchronize with web.
  - ii. With high resolution there is noise with audio.
  - iii. The bitrate of 2nd stream, minimum mode, is 200Kbps. (firmware issue)

## 6. Sunell:

- a. Audio only available on channel 1 and channel 2.
- b. DI2 cannot work correctly.

## 7. Fine:

- a. The response of camera setting is slow.
- b. Not support UPnP search on NVRmini 2, NVRsolo and Titan NVR.

## 8. Zavio:

- a. Audio in/out does not support AMR.

## 9. D-Link:

- a. DCS-2132LB1 and DCS-2330L do not support TCP/UDP. (firmware issue)
- b. DCS-2330L does not support talk. (firmware issue)

## Bug fixed:

### Mainconsole:

1. [Onvif/Onvif] Fixed the issue that Mainconsole will dump when connecting.
2. [Santec] Fixed the issue that SNC-4302, SNC-8322I/HO, SNC-3322 will dump when connecting.
3. [Fine] Fixed the issue that TCP-MH859 does not support MJPEG with resolution 2048x1536 and 2592x1944.
4. [Vivotek] Fixed multicast stream issue.
5. [Axis] Fixed the issue that P8221 output cannot work.

### NVRmini 2:

1. [Fine] Fixed the issue that TCP-MH859 does not support MJPEG with resolution 2048x1536 and 2592x1944.
2. [Vivotek] Fixed multicast stream issue.
3. [Axis] Fixed M3007 unable to connect issue.

4. [Axis] Fixed the issue that P8221 output cannot work.

#### NVRsolo:

1. [Fine] Fixed the issue that TCP-MH859 does not support MJPEG with resolution 2048x1536 and 2592x1944.
2. [Vivotek] Fixed multicast stream issue.
3. [Axis] Fixed M3007 unable to connect issue.
4. [Axis] Fixed the issue that P8221 output cannot work.

#### Titan NVR:

1. [DynaColor] Fixed the issue that Live View shows "No Data" on the iViewer issue.
2. [Hikvision] Fixed the issue that Generic model motion does not work issue.
3. [Fine] Fixed the issue that TCP-MH859 does not support MJPEG with resolution 2048x1536 and 2592x1944.
4. [Vivotek] Fixed multicast stream issue.
5. [Axis] Fixed M3007 unable to connect issue.
6. [Axis] Fixed the issue that P8221 output cannot work.

## Release Version v2.18.0 (2013/10/28)

### Modules:

Device Pack v 2.18.0

### Supported Systems:

Mainconsole v 4.1.12 and above  
NVRmini 2 v 1.7.1 and above  
NVRsolo v 1.1.1 and above  
Titan NVR v 1.6.2 and above

### New Camera Supported:

**Arecont** AV2455DN-F  
**ATV** HDG-M120 and IPFD2MT  
**Brickcom** MD-300Np-360 and MD-500Ap-360 (fisheye camera)  
**Dlink** DCS-940L  
**DlinkCN** DCS-V70M-21H2  
**Eneo** PXB-2080MIR, PXD-2080MIR and PXD-2080Z03  
**Etrovision** EV8582U-BL, N51A-ML, N50U-ML, N51U-ML and N71U-ML  
**Fine** TCP-MH859  
**Forenix** FBX-200CL, FBU-201LWD and FDM-200LWD  
**Hikvision** DS-2CD2212-I3, DS-2CD2612F-I, DS-2CD2712F-I  
**Honeywell** H3D1F and H3D2F  
**Levelone** WCS-0050  
**Panasonic** DG-SC385  
**Samsung** SNF-7010 (fisheye camera) and SND-3082  
**Vivotek** IP8371E

### FW upgrade:

**Forenix** FBU-200LWD, FBX-200LWD and FVD-200LWD  
**Hikvision** DS-2CD2112-(I), DS-2CD2212-I5 and DS-2CD2312-I (FW 5.0.2)  
**Sony** SNC-CH120 (FW 1.80)  
**DlinkCN** DCS-N40M-22H3, DCS-V40M-12H, DCS-N70M-21H3,  
DCS-N31M-21H3 DCS-V40M-32H2, DCS-V70M-11H and  
DCS-V70M-21H2 (VB1.0.29)

<b>Everfocus</b>	EDN1220 and EDN1320 (FW 1.0.8)
<b>Zavio</b>	B7320 (FW M3.1.5.17)

## Notice:

1. EverFocus:
  - a. EDN1220, EDN1320: Not support Mpeg4 (Firmware issue)
  - b. EDN1320: Not support 160x128 in profile3 (Firmware issue)
2. Fine:
  - a. TCP-MH859: Not support M-Jpeg with resolution 2048x1536 and 2592x1944.
3. ATV:
  - a. HDG-M120: Does not implement Audio-out (Talk)
  - b. HDG-M120: UPNP search failure if changed web port 80 to others
  - c. HDG-M120: Not support UDP connection
  - d. HDG-M120: Camera reply slowly if set maximum video parameters
  - e. HDG-M120: The bitrate of stream 3 setup will fail at 100 kbps, but work at 200 kbps.
  - f. IPFD2MT: Not support UPNP search
  - g. IPFD2MT: MJPEG could not setup 1280x1024 and 1280x720 resolution at web, but camera still reply OK.
4. Hikvision:
  - a. DS-2CD2012-I: Sub stream resolution must be smaller than Main stream resolution.
5. Sony:
  - a. SNC-CH120: Not support SolidPTZ mode
6. Brickcom:
  - a. 30xN: It does not support talk, IO on MD-300Np-360.
  - b. 30xN: It does not support MD when format is MJPEG and MPEG4 on MD-300Np-360.
  - c. 50xA: It does not support talk on MD-500Ap-360
  - d. 50xA: It does not support MD when format is MJPEG and MPEG4 on MD-500Ap-360.
7. Forenix:
  - a. It does not support UPnP and auto detection.
  - b. Camera will crash if open camera web under win XP.
  - c. The setting of brightness was wrong via CGI command. It will sync setting of grayscale.
  - d. The sound is weak with audio under format G.726.
8. Etrovision:
  - a. N71U-ML, N50U-ML, N51U-ML and N50A-ML
    - i. Only support focus and zoom.
    - ii. It is noise with audio.

- iii. Only support motion under H.264.
  - iv. Not support talk.
  - v. Dual stream will disconnect if main stream sets MPEG4, 1080P and FPS over 20.
  - b. EV8582U-BL
    - i. Only support motion under H.264.
9. Zavio:
- a. Not support audio in.
10. Arecont:
- a. AV2455DN (fw65220) would reboot after connecting DO port.
  - b. AV2455DN (fw65220) cannot reach 30fps due to camera performance issue.
11. Honeywell:
- a. H3D2F: Only support Zoom and Focus, not support Pan and Tile. (Mainconsole)
  - b. H3D2F: Only support Zoom, not support Pan and Tile. (NVRmini 2, NVRsolo, Titan NVR)

## Bug fixed:

### Mainconsole:

1. [Onvif/Onvif] Fix the issue that it will cause Mainconsole crash when get incorrect preset name.
2. [DLinkCN] Fix the issue that it will not work on Pan, tilt with DCS-H90-31D2.
3. [D-Link] Fix DI/DO fail issue with DCS-6915.
4. [Hikvision] Fix the issue that it will cause crash when get incorrect RTSP video packet.

### NVRmini 2:

1. [D-Link] Fix dual stream disconnect issue on DCS-5010L.
2. [Samsung] Fix the issue that the motion detection does not work on SNO-7082.
3. [Vivovtek] Fix VS8801 dual stream incorrect channel display issue.
4. [Axis] Fix P5532-E dual stream disconnect issue.
5. [Hikvision] Fix the issue that it will cause crash when get incorrect RTSP video packet issue.

### NVRsolo:

1. [Samsung] Fix the issue that the motion detection does not work on SNO-7082.
2. [Vivovtek] Fix VS8801 dual stream incorrect channel display issue.
3. [Axis] Fix P5532-E dual stream disconnect issue.
4. [Hikvision] Fix the issue that it will cause crash when get incorrect RTSP video packet issue.



## Titan NVR:

1. [Fine] Fix dual stream disconnect on WB-H814 issue.
2. [Samsung] Fix the issue that the motion detection does not work on SNO-7082.
3. [Vivovtek] Fix VS8801 dual stream incorrect channel display issue.
4. [Axis] Fix P5532-E dual stream disconnect issue.
5. [Hikvision] Fix the issue that it will cause crash when get incorrect RTSP video packet issue.

## Release Version v2.17.1 (2013/09/30)

### Modules:

Device Pack	v 2.17.1
-------------	----------

### Supported Systems:

NVRmini 2	v 1.7.1 and above
NVRsolo	v 1.1.1 and above
Titan NVR	v 1.6.2 and above

### Bug fixed:

NVRmini 2:

2. Fix that ACTi camera dump issue.

NVRSolo:

1. Fix that ACTi camera dump issue.

Titan NVR:

1. Fix that ACTi camera dump issue.

## Release Version v2.17.0 (2013/09/26)

### Modules:

Device Pack v 2.17.0

### Supported Systems:

Mainconsole v 4.1.12 and above  
NVRmini 2 v 1.7.1 and above  
NVRsolo v 1.1.1 and above  
Titan NVR v 1.6.2 and above

### New Camera Supported:

**Axis** M7010, P1214, P3353 and Q7411  
**Dlink** DCS-7413 B1  
**DlinkCN** DCS-N20M-10H2, DCS-N30M-51H2, DCS-N40M-53H2, DCS-N70M-20H2, DCS-N40M-32H2, DCS-V30M-50H, DCS-V30M-51H, DCS-V40M-32H, DCS-V40M-33H, DCS-V70M-20H, DCS-V70M-21H, DCS-V70M-50H and DCS-N70M-50H2  
**InscapData** NVC3033H-DN and NVC360H-DN-IR  
**Levelone** FCS-5061, FCS-3101 and FCS-4101  
**Panasonic** BB-ST162, BB-SW172, BL-VT104W, BL-VP164W, DG-SF132, DG-SP102 and WV-SF438 (fisheye camera)  
**Samsung** SNP-5300, SNP-6200RH  
**Sony** SNC-CX600W, SNC-VB600B, SNC-VM600B and Generic  
**Vivotek** IP8130, IP8130W, IP8131, IP8131W and SD8363E

### FW upgrade:

**Arecont** AV1115, AV1125, AV1145, AV1255, AV2115, AV3115, , AV3125, AV5125, AV10115, AV10255 (FW 65218), AV3116 (FW 65219), AV5155 (FW 65152), AV8365, AV20185 and AV20365 (FW 65183)  
**Dlink** DCS-2310L (FW v1.01.10)  
**Panasonic** WV-SF132, WV-SP102 (1 Application: 1.81, 2 Image date:1.03), WV-ST162, WV-SW172 (1 Application: 1.81, 2 Image data: 1.04)  
**Sony** SNC-VB630 (FW 1.7.0)  
**Vision Hitech** Vision M3i (FW 1.1.2.46), Vision SM3Ti (FW1.1.4.1 20130816) and Vision Mi(FW 1.1.2.46)

## Notice:

### 1. Feature added:

- a. Support Samsung camera search tool.  
Testing model:
  1. SNB-3002 / SND-3082/F / SNV-3082
  2. SNB-7002 / SND-7082/F / SNV-7082 / SNO-7082R
  3. SNV5080R
  4. SNO5080R
  5. SNB-5000A / SND5080F / SNV5080
  6. SNP-5300
  7. SNP-6200RH
- b. Dual Stream default format change to H.264 for Arecont camera and Vivotek camera.
- c. For Mini2/Solo/Titan, Arecont cameras do not use TFTP to get stream. Always use RTSP or HTTP method to get stream.
- d. Samsung dual stream structure changed. When main stream format is H264, dual stream format will be MJPEG. When main stream format is MJPEG, dual stream format will be H264.

### 2. Known issue:

- a. It cannot use G726 16kbps on Panasonic talk function.
- b. VisionHitech
  1. VISION M3Ti
    - i. It can not use Autofocus function. (camera firmware issue)
    - ii. It will not support audio setup. (camera firmware issue)
  2. VISION M3i
    - i. It can not support Quality with MJPEG. (camera firmware issue)
    - ii. The real FPS could not reach original value on Web when setup maximum setting of camera parameters, for example setting is H.264 within 1920x1080, 30 fps, and 7 quality but can get 15 fps only; setting is MJPEG within 1280x720, 30fps but can get 5~6 fps only.
3. VISION Mi
  - i. It will not support audio setup. (camera firmware issue)
  - ii. It can not support Quality with MJPEG. (camera firmware issue)
  - iii. The real FPS could not reach original value on Web when setup maximum setting of camera parameters, for example setting is H.264 within 1920x1080, 30 fps, and 7 quality but can get 15 fps only; setting is MJPEG within 1280x720, 30fps but can get 5~6 fps only.

c. Levelone

1. FCS-3101 and FCS-4101
  - i. Not support video parameter. (camera firmware issue)
  - i. Not support bitrate 20Kbps.
2. FCS-5061
  - i. It will have talk audio with noise under win XP system issue.
  - ii. With the maximum value of video settings (fps, bitrate) change protocol will cause MainConsole crash.

d. Arecont

1. When use firmware 65218 Arecont camera needs to be used in close-network.
2. Arecont camera might not meet the frame setting due to camera performance.
3. Arecont camera's dual stream bitrate might be larger than 500kbps due to high resolution.

## Bug fixed:

Mainconsole:

1. Fix that RTSP timeout causes Samsung camera disconnect issue.
2. Fix that Panasonic BL-VT164 cannot use PTZ issue.
3. Fix that DynaColor V6 disconnect issue.
4. Fix that Zavio P5111, P5116, P5210 PTZ speed range is not synchronize between camera setting and web.

NVRmini 2:

1. Fix that RTSP timeout causes Samsung camera disconnect issue.

Titan NVR:

1. Fix that Samsung SNP-3302/H cannot use PTZ issue.
2. Fix that Hikvision Generic cannot use focus function issue.
3. Fix the issue that original stream will disconnect when switch between original and low/minimized stream.

## Release Version v2.16.0 (2013/08/26)

### Modules:

Device Pack v 2.16.0

### Supported Systems:

Mainconsole v 4.1.12 and above  
NVRmini 2 v 1.7.1 and above  
NVRsolo v 1.1.1 and above  
Titan NVR v 1.6.2 and above

### New Camera Supported:

**3S** N5012  
**Arecont** AV2255AM and AV5255AM  
**BOSCH** NBC-225-P, NDC-225-PI, NBC-255-P, NDC-255-P, NTC-255-PI, NBC-265-P, NDC-265-P, NDN-265-PIO, NBC-274-P, NBC-274-PT and NBC-274-PM  
**Dlink** DCS-6004L, DCS-6005L  
**DlinkCN** DCS-H70-21D/M  
**Eneo** PXB-2080Z03 and PXD-2080Z03  
**Grundig** GCI-H2505B, GCI-K0589T(H), GCI-K0779P, GCI-K1523VS, GCI-K1526VS, GCI-K1585V, GCI-K1586V and GCI-K2505B  
**Milesight** MS-C2351, MS-C2361, MS-C2362, MS-C2372, MS-C2451, MS-C2471, MS-C2651, MS-C2661, MS-C2662, MS-C2671, MS-C2672, MS-C2681, MS-C2682, MS-C2951, MS-C3351, MS-C3356, MS-C3361, MS-C3362, MS-C3366, MS-C3372, MS-C3376, MS-C3651, MS-C3656, MS-C3658, MS-C3661, MS-C3662, MS-C3666, MS-C3671, MS-C3672, MS-C3673, MS-C3676, MS-C3678, MS-C3681 and MS-C3682  
**Panasonic** BL-VP101, BL-VP104 and BL-VT164  
**Samsung** SNO-6084 and SNV-6084  
**Sunell** Generic model  
**Vivotek** AF5127, AF5127V, SF8172, SF8172V, FE8172V (the above models are fisheye camera . SF8172 and SF8172V support PPTZ), AB5353H

## FW upgrade:

<b>Arecont</b>	AV1255 (FW 65218), AV3255 (FW 65218), AV5115DN (FW 65218), AV8185DN (FW 65183) and AV8365DN (FW 65183)
<b>CNB</b>	IDC 4000T(FW T1-1.0.13.0424) and INS 2000 (FW XNET.A1-2.01.13.0204)
<b>Dlink</b>	DCS-2103 (FW 1.20), DCS-2130 (FW 1.20), DCS-2210 (FW 1.20) and DCS-2230 (FW 1.20)
<b>Everfocus</b>	EVS-410 (Firmware upgrade to v1.0.21)
<b>Samsung</b>	SND-3082, SND-3082/F and SNB-3002 (snb3002_Series_2.10_130416), SNV-5080R (FW snv5080r_3.10_130416), SNO-5080R (FW snb5000_Series_3.10_130416) and SND-5080F, SNB-5000A and SNV-5080 (FW snb5000_Series_3.10_130416) and SNB-7002, SNV-7082, SND7082/F and SNO-7082R (FW snb7002_series_1.06_130402), SNB-6003, SNB-6004, and SND-6083 (FW snb6004_Series_1.00_130412)
<b>Sunell</b>	IPS54-70DN-ZR18, SN-IPC54-40EDN and SN-IPD54-12VDN

## Enhancement:

1. Samsung: For SNP-5200 and SNP-6200 change the default speed to 3 or 4.

## Notice:

1. Feature added:
  - a. Dual Stream default format change to H.264 for Axis MPQ series camera, Vivotek Generic model and new supported camera above (except support by design camera).
2. Known issue:
  - e. For Samsung SNB-7002, SNV-7082, SND7082/F and SNO-7082R, it will have no image issue via RTSP when Frame rate sets to 1.
  - f. For Samsung SND-3082, SND-3082/F and SNB-3002, it cannot setup video parameter: brightness.
  - g. For Samsung SNB-7002, SNV-7082, SND7082/F and SNO-7082R, the resolution will be 800\*448 & 320\*176 when sets to 800\*450 & 320\*180.
  - h. For Samsung all cameras: Video GOP appear as 1 ~15, but the value actually will be 1 ~149 in web.
  - i. For Everfocus EVS410

1. It can setup MJPEG high resolution only up to 10 fps.
  2. Not support RS-485 PTZ.
- j. For Sunell Generic
1. Focus, Talk function are not test with NUUO product.
  2. The maximum resolution is depending on camera.
  3. It cannot set some framerate and bitrate due to Onvif limitation.
  4. Camera firmwave must be v1.6\_build044014\_148 or above then can use generic model.
- k. For Grundig GCI-K1586V, GCI-K0779P, GCI-K2505B
1. It will have audio noise issue when camera resolution is 1920x1080 or Q factor is 70.
  2. It will fail when Get camera parameter resolution is 1920x1080 or Q factor is 70.
  3. GCI-K2505B framerate setting will fail when select TV system Autoir option WDR 25fps, autoir25fps and WDR 30fps.
- l. For CNB INS2000
1. Not support Digital input(DI). (camera firmware issue)
  2. Dual stream format could be MJPEG, MPEG4 or H.264. It will be same as main stream format
- For CNB IDC4000T
1. It will show incorrect bitrate "1M" when sets Video MPEG with CBR in 4000 bitrate on camera web.
  2. It will trigger DO simultaneously when trigger DI.
  3. Dual stream default format is MPEG4.
- m. For D-Link DCS-2103
1. It will not support Talk function on camera web and MainConsole. (camera firmware issue)
- n. For Mileight MS-C2351, MS-C2361, MS-C2362, MS-C2372, MS-C2451, MS-C2471, MS-C2651, MS-C2661, MS-C2662, MS-C2671, MS-C2672, MS-C2681, MS-C2682, MS-C2951, MS-C3351, MS-C3356, MS-C3361, MS-C3362, MS-C3366, MS-C3372, MS-C3376, MS-C3651, MS-C3656, MS-C3658, MS-C3661, MS-C3662, MS-C3666, MS-C3671, MS-C3672, MS-C3673, MS-C3676, MS-C3678, MS-C3681 and MS-C3682 FW issue:
1. It cannot use RateControl.
  2. It cannot trigger Motion and DI in the same time.



3. It will have no response when send cgi commend.
  4. It will not support UPnP.
  5. There is one level of difference between video parameter and camera web on Mainconsole.
- o. For Milesight MS-C3651
1. It will not support Digital input(DI). (camera firmware issue)
- p. For Milesight MS-C3658
1. It will show wrong frame rate value on Mainconsole when change resolution from 2560x1920 to other resolution.
- q. For 3SVision N5012
1. It will always show HTTP port 80 when use UPnP search.
- r. For Arecont models
1. AV5155, AV5255, AV2255 need to be connected in close-network. It will operate abnormally in open-network.
  2. AV5255, AV2255 not support audio function due to camera firmware issue.
  3. AV5255, AV2255 will have broken image when use H264 (TCP/UDP) with high bitrate setting (>16384).
  4. AV8185DN and AV8365DN
    - Four channels need to use the same protocol and format.
    - The image will flash when the main stream is MJPEG and use dual stream.
- s. For Vivotek SF8172 and SF8172V
1. Due to camera CPU decode performance issue, the first 1080p stream can reach up to 30 fps, but the second 1080p stream cannot.

## Bug fixed:

Mainconsole:

5. Onvif: Fix the issue that enable auto reboot, sometimes it does not start the recording schedule.

NVRmini 2:

1. Vivotek: Fix FE8172V auto detect issue.

## Titan NVR:

4. Fix the issue that Generic RTSP model will disconnect in NuClient live view but it is still recording.
5. Fix the issue when reboot Titan NVR, the IP cameras will disconnect and do not record.

## Release Version v2.15.0 (2013/07/29)

### Modules:

Device Pack v 2.15.0

### Supported Systems:

<b>Mainconsole</b>	<b>v 4.1.12 and above</b>
<b>NVRmini 2</b>	<b>v 1.7.0 and above</b>
<b>NVRsolo</b>	<b>v 1.1.0 and above</b>
<b>Titan NVR</b>	<b>v 1.6.1 and above</b>

### New Camera Supported:

<b>Dlink</b>	DCS-3511, DCS-3530, DCS-5010L, DCS-5020L, DCS-5211L, DCS-5222L, and DCS-6314
<b>DlinkCN</b>	DCS-H70-21D/M
<b>Eneo</b>	PXB-1080Z03, PXB-2080Z03IR and PXB-3080Z20
<b>Forenix</b>	C2002, C2002-W, D2000-FD3, D2000-VD3, D2000-VP2, FBU-200LWD, FBU-300LWD, FDM-300LWD, FVD-200LWD, FVD-200LWD, FVD-300LWD, T2000-FB1, T2000-FB2, T2000-VB3, VQ2100, VQ2200, VQ2210C, VQ2300 and VQ2310
<b>LG</b>	LND7300, LNP2810T, LNU5100R, LNV5100R and LNV7300
<b>Sony</b>	SNC-ER585
<b>Vitek</b>	VT-20VN-M, VTC-IR401, VTC-IR402, VTD-134FNIB, VTD-134FNIBP, VTD-134FNIWP, VTD-13FN, VTD-13V210NIB, VTD-13V210NIBP, VTD-13V210NIW, VTD-13V210NIWP, VTD-20V210NIB, VTD-20V210NIBP, VTD-20V210NIW, VTD-MV13V210NBP, VTD-MV13V210NP, VTD-MV13VR210NBP, VTD-MV13VR210NP, VTD-MV20V210NBP, VTD-MV20V210NP, VTD-MV20VR210NBP, VTD-MV20VR210NP, VT-PTZ220 and VT-PTZ220NP
<b>Vivotek</b>	FD8133V, FD8166 and FE8173 (fisheye camera)
<b>Zavio</b>	D7510
<b>3M</b>	ANPR

## FW upgrade:

<b>ACTi</b>	ACD2000Q (FW v3.04.06-AC), KCM-3911 and KCM-7911 (FW 5.10.02)
<b>Arecont</b>	AV2115DN (FW 65218) and AV3116DN (FW 65219)
<b>Dynacolor</b>	Nv223 (add motorize zoom function detect) (FW z120130417NSA)
<b>Everfocus</b>	EHN3260 (v1.2.2)
<b>Fine</b>	CDV-2M360(VB1.0.32_F, fisheye camera), CDV-5VM501(HD_VC1.0.18_F) and TCP-HDVB800(VC1.0.18)
<b>Grandstream</b>	GXV-3501 (add preset function on Mainconsole)
<b>Vivotek</b>	VS8401 (add dual stream) (0201b)
<b>Zavio</b>	P5111 and P5116 (M2.1.6.02)

## Notice:

3. Feature added:
  - b. Add preset function on Grandstream GXV3501/GXV3504.
4. Known issue:
  - t. Fine
    1. CDV-5VM501
      - i. It will have Image broken issue with MJPEG in 2592x1944 and 2048x2048 via RTSP
      - ii. Unstable stream with H.264 via RTSP
  - u. Sony SNC-ER585  
It will have image broken issue with MPEG4 texture during resolution switch. (Titan NVR)
  - v. ACTi ACD2000Q
    1. Not support framerate 8 due to camera firmware issue.
  - w. Eneo PXD-2080Z03IR
    1. Only support RTSP port 554 due to camera firmware issue.
    2. Only integrate NTSC mode due to camera firmware issue.
    3. It will have discontinuous issue on audio when fps under 1.
    4. Camera framerate may not enough under high resolution, framerate and quality settings.
    5. Not support brightness, contrast and saturation due to camera firmware issue.(IP+)
  - x. Vitek
    1. VTC-IR401, VTC-IR402
      - i. Only support RTSP port 554 due to camera firmware issue.
      - ii. Only integrate NTSC mode due to camera firmware issue.

- iii. It will have discontinuous issue on audio when fps under 1.
  - iv. Camera framerate may not enough under high resolution, framerate and quality settings.
  - v. Not support UPnP due to camera firmware issue.
  - vi. Not support brightness, contrast and saturation due to camera firmware issue.(IP+)
2. VTD-13FN, VT-20VN-M, VTD-134FNIB, VTD-134FNIBP, VTD-134FNIWP, VTD-13FN, VTD-13V210NIB, VTD-13V210NIBP, VTD-13V210NIW, VTD-13V210NIWP, VTD-20V210NIB, VTD-20V210NIBP, VTD-20V210NIW, VTD-MV13V210NBP, VTD-MV13V210NP, VTD-MV13VR210NBP, VTD-MV13VR210NP, VTD-MV20V210NBP, VTD-MV20V210NP, VTD-MV20VR210NBP and VTD-MV20VR210NP
- i. Only support RTSP port 554 due to camera firmware issue.
  - ii. Only integrate NTSC mode due to camera firmware issue.
  - iii. Camera framerate may not enough under high resolution, framerate and quality settings.
  - iv. Not support UPnP due to camera firmware issue.
  - v. Not support brightness, contrast, saturation due to camera firmware issue.(IP+)
3. VT-PTZ220NP and VT-PTZ220
- i. Only support RTSP port 554 due to camera firmware issue.
  - ii. Only integrate NTSC mode due to camera firmware issue.
  - iii. Camera framerate may not enough under high resolution, framerate and quality settings.
  - iv. It will have discontinuous issue on audio when fps under 1.
  - v. Not support UPnP due to camera firmware issue
  - vi. Preset, preset name and PTZ speed cannot synchronize to camera web due to camera firmware issue.
  - vii. Not support brightness, contrast and saturation due to camera firmware issue.(IP+)
- y. 3M
- 1. ANPR only integrate MJPEG 1<sup>st</sup> stream video.
- z. Zavio
- 1. D7510
    - i. It will only support framerate 1~15.
    - ii. It will cause delayed image and broken voice when connect stream via RTSP over HTTP in high video quality.
  - 2. P5116 and P5111

- i. It will only support pan and tilt when use PTZ.
- ii. It will not support audio when use AMR 7.95 format.
- iii. The max framerate of MPEG4 and MJPEG is up to 20 FPS in 1280x800.

## Bug fixed:

### Mainconsole:

1. Fix UDP NVC 1000 will disconnect randomly and show "connecting" all the time.
2. Fix when click PTZ focus panel cause terminate abnormal issue.
3. Fix terminate abnormal issue when use Onvif null-pointer.

### NVRmini 2:

2. Fix terminate abnormal when use Onvif null-pointer.
3. Fix no video display by setting MJPEG and MPEG4 format with Vivotek FD8135H.

### NVRsolo:

1. Fix cannot connect to Eneo PXD-1020F02 issue.
2. Fix when connect Santec SNC-3302, SNC-5312, SNC-5315, SNC-6202, SNC-6212IR and SNC-6312IRH will cause solo crash issue.
3. Fix terminate abnormal when use Onvif null-pointer.
4. Fix no video display by setting MJPEG and MPEG4 format with Vivotek FD8135H.

### Titan NVR:

6. It will cause system terminate abnormal when connect with Bosch NTC 265PI/NDN-265PIO.
7. Fix cannot connect Honeywell HDEZ20HDEX (firmware H20120808NSA) issue.
8. Fix terminate abnormal when use Onvif null-pointer.
9. Fix no video display by setting MJPEG and MPEG4 format with Vivotek FD8135H.

**Release Version v2.14.0 (2013/06/26)**

## Modules:

Device Pack v 2.14.0

## Supported Systems:

Mainconsole v 4.1.0 and above  
NVRmini 2 v 1.5.0 and above  
NVRsolo v 1.0.0 and above  
Titan NVR v 1.3.0 and above

## New Camera Supported:

**ACTi** D61, E25, E66 and KCM8211  
**Arecont** AV12186  
**Brickcom** 20xp and 300N series  
**DigitalWatchdog** DWC-MPA20M  
**Dlink** DCS-6115, DCS-6315, Super Model  
**Everfocus** EMN 2320 and ETN 2110  
**Fine** C3000/C3000-W, CDV-3VM800, CDB-5VM551, CDB-MV1080F  
TCP-HP1080 and TCP-VM359  
**Samsung** SNB-6003, SNB-6004, SND-6083 and SND-6084  
**Vivotek** FD8363, FD8163 and Generic  
**Zavio** B7320 and F3210

## FW upgrade:

**ACTi** D11, D12, D21, D22, D31, D32, D41, D42, D51, D52, D54, D55, D62, D64, D65, D71, D72, D81, D82, E11, E12, E13, E21, E22, E23, E24, E26, E31, E32, E33, E34, E41, E42, E43, E44, E45, E46, E51, E52, E53, E54, E55, E56, E61, E62, E63, E64, E65, E67, E71, E72, E73, E74, E81, E82, E83, E84, E85, E86, E87, E91, E92 (FW 6.03.17) and KCM8111(FW 5.10.02)  
**Vivotek** FD8161 (FW 0105b)

## Notice:

5. Known issue:

c. ACTi

甲、 For D and E series camera

Fix the Fragment IP assembly timer handler panic to reboot.

乙、 E13 and the certificate

It will disconnect with NUUO product abnormally.

丙、 E84 and the certificate

If select resolution 640x360, it will have incorrect value on parameter setting.

d. Samsung SND-6083

The talk from the speaker is weak.

e. Fine

甲、 CDB-5VM551

Not support MJPEG with resolution 2592x1944.

乙、 CDV-3VM800

It will cause image broken, and drop frame when use MJPEG with highest fps, resolution and quality through TCP connection.

It will cause CPU heavy loading when use MJPEG with highest fps, resolution and quality through RTSP.

丙、 TCP-HP1080

Received only half of fps with web setting

f. Digital watchdog

甲、 Not support dual stream when select single stream for ONVIF setting at webpage.

乙、 There is a valid resolution 320x0 in profile1 at MJPEG.

丙、 The quality value does not synchronize with webpage quality value.

丁、 It is invalid with frame rate 0.

戊、 There are two port settings on camera web, web port and service port. When NUUO product and camera are located in the same network, you can use this web port as configuring port on NUUO product. If NUUO product and camera are located in different network, you must choose service port. "Go to web" function on NUUO product setting page might direct to the wrong url.

g. D-Link

甲、 Super Model (Tested by DCS-2332L)

It is incorrect with Resolution List and Bitrate List information.

Quality mode switch does not support (CBR/Fix quality)



h. Arecont

甲、 AV12186

DI cannot work.

i. EverFocus

甲、 For EMN2320, no support MPEG4.

乙、 For EMN2320, cannot switch CBR/VBR and only support VBR.

丙、 For EMN2320, no support 720x480, 704x480 and 640x480 resolution.

丁、 For ETN2110, motion detection is not compatible with MPEG4 codec because of camera firmware issue.

j. Zavio

甲、 For F3210, Video resolution cannot change when only setup resolution.

乙、 For F3210, the AMR mode of talk function cannot work.

## Bug fixed:

Mainconsole:

4. Sometimes click liveview will cause Mainconsole crash when using Onvif model.
5. It will fail when Arecont AV-8365DN change format from MJPEG to H264.

NVRmini 2:

1. Samsung 3082:

- (1) The resolution is not listed correctly under camera parameters.
- (2) The selected frame rate is not being achieved.
- (3) Latency in live view

## Release Version v2.13.0 (2013/05/27)

### Modules:

Device Pack v 2.13.0

### Supported Systems:

Mainconsole v 4.1.0 and above

NVRmini 2 v 1.5.0 and above

NVRsolo v 1.0.0 and above

Titan NVR v 1.3.0 and above

### New Camera Supported:

**ACTi** D22, D62, E13, E22, E23, E24, E26, E33, E34, E43, E44, E45, E46, E54, E63, E64, E65, E67, E73, E74, E83, E84, E85, E86 and E87

**Arecont** AV3146 and AV3256

**Centrix** Generic

**CNB** ISMC1063P

**DigitalWatchdog** MD421TIR

**Dlink** DCS-942L

**Dynacolor** Generic

**Everfocus** EDN 1220, EDN 1320, EMN 2220, EPN 4220

**Fine** ACM-B3000 and ACM-R3006, CDV-5VM501 and TCP-VM559

**Guardeon** GDN-D3200IR, GDN-D3200V, GDN-F1300V, GDN-H1300IR and GDN- H3200IR

**Network Camera** C3000 and C3000-W

**JVC** VN-T16, VN-T216, VN-H657U and VN-H657WPU

**Techson** TC-IP213WS

**UDP** IPN100HD, IPN1202HD, IPN2102HD, IPN302HD, IPN3102HD, IPN3202HD, IPN3502HD, IPN3502HD, IPN3502HDIR, IPN6602HD, IPN6802HD, IPX3302HD, IPX3702HD, IPX4202HD and IPX4602HD

**Vivotek** IP8152

**Zavio** D7320

### FW upgrade:

**Eneo** GXC-1710M (upgrade to FW 2.11)

## Notice:

### 6. Known issue:

#### k. ACTi For D and E series camera:

- 甲、NUUO recommend customers use CLOSE network environment as ACTi may shut down and restart automatically in some complex network environment.
- 乙、ACTi will continue to figure out the reason and help to solve this issue.
- 丙、The audio stream of E13 unstable sometimes, even though in VLC and web.

#### l. Centrix Generic model:

- 甲、The bitrate of dual stream cannot come to 500kbps when main stream setting is MJPEG and CIF.
- 乙、Parameter setting will fail when enable multi-stream and resolution higher than 1080p.
- 丙、Camera firmware must be cx20130506NSA or above then can use generic model.

#### m. DynaColor Generic model:

- 甲、Parameter setting will fail when enable multi-stream and resolution higher than 1080p.
- 乙、Camera firmware must be z120130417NSA or above then can use generic model.

#### n. Fine CDV-5VM501 not support UPnP search by camera firmware issue.

#### o. NetworkCamera C3000 and C3000-W not support UPnP search by camera firmware issue.

#### p. TC-IP213WS:

- 甲、Can not trigger motion alarm under H.264 1fps.
- 乙、Can not search camera by UPnP when change http port except 80.
- 丙、H.264 fps may not enough under TCP connection in high quality and frame rate settings.

#### q. Digital Watchdog MD421TIR

- 甲、Not support Zoom, Focus, Talk and VideoParamSetting(MainConsole only)
- 乙、Not support dual stream when select single stream for ONVIF setting at webpage.
- 丙、Setting frame rate to 0 did not work.
- 丁、MJPEG with resolution 320x240 is invalid.
- 戊、Quality value is not synchronized with webpage.
- 己、There are two port settings on camera web, web port and service port. When NUUO product and camera are located in the same network, you can use this web port as

configuring port on NUUO product. If NUUO product and camera are located in different network, you must choose service port. Or "go to web" function on NUUO product setting page might direct to the wrong URL.

r. CNB ISMC1063P

甲、 Not support audio codec G.726 when using TCP connection.

s. Arecont AV3146DN-3310-D and AV3256PM

甲、 The streaming has low FPS under high quality.

t. JVC VN-H657U

甲、 Firmware Issue: MJPEG video stream is unstable over high resolutions such as 1920X1080, 1280x720.

u. JVC VN-T16U

甲、 Firmware Issue: MJPEG video stream is unstable over high resolutions such as 1920X1080, 1280x720.

乙、 Firmware Issue: The Encoder parameters may not sync camera web.

v. JVC VN-H57

甲、 Firmware Issue: MJPEG video stream is unstable over high resolutions.

w. JVC VN-H137

甲、 Firmware Issue: H264 video stream is unstable over low frame rate.

x. Zavio D7320

甲、 Talk function cannot work due to firmware issue.

乙、 When change the HTTP port from 80 into 8080, camera send IP address which including parentheses, such as [192.168.1.66].

丙、 When setting highest video setting with H.264, the fps could not reach up to 20.

y. UDP

甲、 When used UPnP search, if changes the HTTP port from default 80 into 8080 and reboot the camera, it does not carry any port information with reply message.

乙、 IPN3502HD

i. When setting highest video setting in main stream, the second stream will unstable and cannot work both in H.264 and MJPEG.

丙、 IPX4202HD

- i. cgi load failure: #402
- ii. Audio with choppy in higher video setting
- iii. Motion detection cannot disable once it trigger
- iv. Unstable stream with highest video setting, sometimes does not work.

z. EverFocus EDN1220, EDN1320, EMN2220 and EPN4220

甲、 Not support MPEG4.

乙、 Can not switch CBR/VBR and only support VBR.

丙、 EDN1320 no support 720x480, 704x480 and 640x480 resolution.

aa. Vivotek IP8152

甲、 CGI returns a wrong PTZ capability.

## Bug fixed:

Mainconsole:

6. Hikvision 8254: support third stream, preset function can not synchronize with Mainconsole.
7. Hikvision DS-6716HWI: Can not connect the camera except channel 1(Generic).
8. Grandstream GXV3501: Remove "Clean All" Button from Add Preset Point.

NVRmini 2:

2. Hikvision 8254: Preset function can not synchronize with NVRmini2.
3. Hikvision DS-6716HWI: Can not connect the camera except channel 1(Generic).

Titan NVR:

1. Hikvision 8254: Preset function can't synchronize with Titan NVR.
2. Hikvision DS-6716HWI: Can not connect the camera except channel 1(Generic).

NVRSolo:

1. Yodor YUC-H626: Can not auto detect this model.

## Release Version v2.12.0 (2013/04/29)

## Modules:

Device Pack v 2.12.0

## Supported Systems:

Mainconsole v 4.1.0 and above  
NVRmini 2 v 1.5.0 and above  
NVRsolo v 1.0.0 and above  
Titan NVR v 1.3.0 and above

## New Camera Supported:

**ACTi** D11, D12, D21, D31, D32, D41, D42, D51, D52, D54, D55, D64, D65, D71, D72, D81, D82, E11, E12, E21, E31, E32, E41, E42, E51, E52, E53, E55, E56, E61, E62, E71, E72, E81, E82, E91 and E92

**Axis** M3007 (fisheye camera)

**CNB** IBP5030CR, IDC4050F, IDC4050IR, IDC4050VF, IDC4050VR, IDP4030VR, IDP5035VR, IGC2050F, IGP1030, IGP2035F, ISS4032Z28W, IVC5055VR, IVP4030VR, IVP5035VR, IXC2050IR, IXP3035VR, NGE2055F, NXE3055VR, NXE3055MR, NDE5055MF, NVE5055VR, NVE5055MF and NDE5055VR

**Dahua** IPC-HDBW3101, IPC-HDB3101 and IPC-HFW3101C

**Dlink** DCS-2332L, DCS-3715, DCS-3716, DCS-6010L (fisheye camera), DCS-6616, DCS-6817B1, DCS-6915 and DCS-7513

**Etrovision** EV8180A, EV8580A, EV8581A, EV8780A, EV8781A and EV8782A

**Fine** ACM-V3002

**Hikvision** DS-2CD2012-I, DS-2CD2112-(I), DS-2CD2212-I5 and DS-2CD2312-I

**i-Mege** B3210E, G2212E, G2213E, G2214H, G3211E, N3211E and V2211E

**Network Camera** 3MP\_BOX, 3MP\_FD, 3MP\_IR and 3MP\_VD

**On Electronics** CFB-10MP (IP+ only), CFB-13MP, CFB-20MP, CFB-30MP, CFV-20MP/LIR35 (IP+ only) ,CFV-13MP/LIR35, MDV-10MP (IP+ only), MDV-20MP, MDV-20MP-AV (IP+ only), MDV-30MP, MDV-30MP-AV (IP+ only), MDV-13MP/LIR20 (NAS only)

**Planet** ICA-H652-PA-220

**Saerim** SR-IDC4050IR, SR-IDC4050VR, SR-IDC4050F, SR-IGC2050F, SR-IVC5055VR, SR-IDC4050VF, SR-IXC2050IR, SR-IGP2035F, SR-IDP4030VR, SR-IXP3035VR, SR-ISS4032Z28W, SR-IVP4030VR, SR-NGE2055F, SR-NXE3055VR, SR-NXE3055MR, SR-NDE5055VR, SR-NDE5055MF, SR-NVE5055VR, SR-NVE5055MF

**Sunell** SN-IPV54/31UDN, SN-IPC54/31EDN, SN-IPR54/31AKDN, SN-IPR54/31APDN

	SN-IPD54/31VDN, SN-IPD54/31VDR, SN-IPV54/31ZDR, SN-IPV54/31UDR, SN-IPC54/14EDN, SN-IPR54/14AKDN, SN-IPR54/14APDN, SN-IPD54/14VDN, SN-IPD54/14VDR, SN-IPV54/14ZDR and SN-IPV54/14UDR
<b>Vivotek</b>	PD8136
<b>Zavio</b>	D5210 and D7210

## FW upgrade:

<b>BOSCH</b>	NTC-265-PI and NDN-265-PIO (upgrade to FW 5.70.0311)
<b>Levelone</b>	WCS-6020 (upgrade to FW 1.1.4.1) and WCS-6050 (upgrade to FW 1.0.4.2)
<b>Santec</b>	SNC-3302, SNC-3305, SNC-5312IR, SNC-5315IR, SNC-6202, SNC-6212IR, SNC-6302, SNC-6312IRH and SNC-6315IRH (upgrade to FW 1.0.2.332)
<b>Samsung</b>	SND-5010, SNB-5001, SND-5011, SND-5061, SNB-7001, SNB-7002, SND-7011, SND-7061, SND-7082 and SNV-7082 add bitrate option on H.264 3072/5120/6144/7168/9216/11264/12288/13312/14336

## Notice:

### 7. Known issue:

#### bb. ACTi For D and E series camera:

甲、NUUO recommend customers use CLOSE network environment as ACTi may shut down and restart automatically in some complex network environment.

乙、ACTi will continue to figure out the reason and help to solve this issue..

#### cc. iMege G2212E : If http port does not 80, UPnP search will fail.

#### dd. LevelOne WCS-6020, WCS-6050

甲、When select high resolution, camera's frame rate will less than 30fps.

乙、PTZ Home will stop when disable the home button at titan.

丙、Image broken at high resolution.

丁、Not support AAC codec.

#### ee. D-Link

##### 甲、DCS-3715

- i. Sometimes video setting can't get the correct parameters2. Camera web setting is very unstable and got slowly respond, especially in higher video parameter

- ii. When 1920x1080, 25 fps, and 8M bitrate, will get incorrect parameter or long respond time
- iii. cgi respond slowly.
- 乙、DCS-6817B1
  - i. PTZ Autopan does not work
  - ii. When enable mic only, the camera does not send any audio package.
- 丙、DCS-6915
  - i. Not support talk
- 丁、DCS-2332L
  - i. In H.264 format, setting 1 fps and under 512kbps with max resolution cause unstable connection.
- ff. Dahua
  - 甲、IPC-HDBW3101, IPC-HDB3101 and IPC-HFW3101C
    - i. FW issue, bit rate range is different between camera web and response to cgi.
- gg. Hikvision
  - 甲、DS-2CD2012-I
    - i. DS-2CD2012-I FW issue: not support PTZ function but web setting can enable this option.
- hh. Planet
  - 甲、ICA-H652-PA-220
    - i. Camera response slow.
    - ii. IO trigger time will delay about 3 secs.
    - iii. Audio has some noise in web site.
- ii. Santec
  - 甲、SNC-6302, SNC-3305, SNC-63115IRH
    - i. M-JPEG on high resolution and quality may not get parameter.
    - ii. Audio has some noise in high resolution.
- jj. Sunell SN-IPV54/31UDN:
  - 甲、FW issue: Camera will reboot when MJPEG 2048x1536, 1920x1080 and quality 9.
- kk. Bosch NDN-265-PIO:
  - 甲、It can't set resolution below 1280x720 when stream2 property set to "Copy Stream 1".
  - 乙、When H.264 quality is set to "0", the camera will Auto-adjust the quality setting. For minimum quality, the value should be "100".
  - 丙、Audio AAC can't work due to NUUO platform issues.
- ll. Etrovision EV8180A, EV8580A, EV8581A, EV8780A, EV8781A and EV8782A
  - 甲、Not support Talk.
  - 乙、With four profiles mode only support resolution 640x480. (camera limitation)



丙、 Not support MPEG4 in NVRmini 2/NVRsolo/TitanNVR.

丁、 Motion Detection only works on H.264.

戊、 It needs to reboot after changing HTTP port.

mm. Fine ACM-B3000, ACM-V3001, ACM-V3002, ACM-R3002

甲、 MJPEG only support when MPEG4/H264's resolution is lower than 1280x720 in Mainconsole.

nn.CNB

甲、 IGC2050F, IDC4050F, IDC4050IR, IDC4050VF, IDC4050VR, IVC5055VR and IXC2050IR

i. FW issue: cannot set bitrate 128kbps when the resolution is D1 or VGA.

ii. When selects MJPEG, 1fps, the actually received fps is 6.

乙、 IGP1030, IBP5030CR, IVP4030VR and IDP4030VR

i. In the MJPEG format, the fps is not enough when resolution is XGA or SXGA.

丙、 IGP2035F, IDP5035VR, ISS4032Z28W, IVP5035VR, IXP3035VR

i. Cannot set bitrate 128kbps when the resolution is D1 or VGA. It is firmware issue.

丁、 NGE2055F, NDE5055MF, NDE5055VR, NVE5055MF, NVE5055VR NXE3055MR, and NXE3055VR

i. Not support UDP connection.

ii. Video connection cannot establish when the setting of bitrate is 9M or 10M.

oo. Saerim

甲、 SR-IGC2050F, SR-IDC4050F, SR-IDC4050IR, SR-IDC4050VF, SR-IDC4050VR, SR-IVC5055VR and SR-IXC2050IR

i. Cannot set bitrate 128kbps when the resolution is D1 or VGA. It is firmware issue.

ii. When it selects MJPEG, 1fps, the actually received fps is 6.

乙、 SR-IGP2035F, SR-IDP4030VR, SR-ISS4032Z28W, SR-IVP4030VR, and SR-IXP3035VR

i. Cannot set bitrate 128kbps when the resolution is D1 or VGA. It is firmware issue.

丙、 SR-NGE2055F, SR-NDE5055MF, SR-NDE5055VR, SR-NVE5055MF, SR-NVE5055VR, SR-NXE3055MR, and SR-NXE3055VR

i. Not support UDP connection.

ii. Video connection cannot establish when the setting of bitrate is 9M or 10M.

pp. Zavio D5210 and D7210

甲、 The audio function of AMR7.95 cannot work.

乙、 The talk function with AMR codec cannot work.

丙、 The max frame rate of MPEG4 is up to 20 FPS in 1280x800. It is the limitation of hardware.

## Bug fixed:

Mainconsole:

9. Forenix\_ACDV-3VM501: can't not choose h264 video format, cause by auto detect incorrect vendor and model name in DP 2.7 and behind, solve by add model name in corresponding function.

10. Samsung SPE-100: Incorrect maximum fps support.

NVRmini 2:

4. VisionHitech Mi series can't connect.

Titan NVR:

3. Hikvision\_DS-6101HFI-IP: LiveView do not have image.

4. Hikvision\_DS-2CD752MF-FB: LiveView do not have image when change stream profile from original to low or min.

5. VisionHitech Mi series can't connect.

## Release Version v2.11.0 (2013/03/26)

### Modules:

Device Pack

v 2.11.0

## Supported Systems:

Mainconsole	v 4.1.0 and above
NVRmini 2	v 1.5.0 and above
NVRsolo	v 1.0.0 and above
Titan NVR	v 1.3.0 and above

## New Camera Supported:

<b>ACTi</b>	KCM8111
<b>ADT</b>	ADT-VSDVS-4C, ADT-VSDVZ5MP-VF3090IRI and ADT-VSDVZ5MP-VF3090IRO
<b>American Dynamics</b>	ADCI600-D131
<b>BOSCH</b>	NDC-225, NWC-455, NWC-495, NWD-455, NWD-495 and VIP-X1XF-E
<b>CNB</b>	IDC4050VR, IDP5035VR, IVC5055VR, IVP5035VR, IXC2050IR, IXP3035VR, NDE5055VR, NVE5055VR and NXE3055VR
<b>Dlink</b>	DCS-2136L, DCS-3010, DCS-5010L
<b>Dlink CN</b>	DCS-N70M-21H3, DCS-V70M-21H2, DCS-V70M-11H, DCS-N40M-22H3, DCS-V40M-12H, DCS-V40M-32H2, DCS-N31M-21H3, DCS-V30M-51H2, DCS-N62-40H2, DCS-N40M-81H3
<b>Etrovision</b>	EV8180Q-XD and EV8782Q-BD
<b>Fine</b>	ACM-R2001, CDB-MV720F, CDV-P360 (Fisheye camera, support on Mainconsole only), TCP-HFB720
<b>Hikvision</b>	Generic model support second stream
<b>LevelOne</b>	FCS-1132, FCS-3052, FCS-5052 and FCS-5062
<b>Saerim</b>	SR-IDC4050F, SR-IDC4050VR, SR-IDP4030VR, SR-IGC2050F, SR-IGP2035F, SR-NDE5055VR, SR-NGE2055F, SR-NVE5055VR ,SR-IXP3035VR and SR-NXE3055VR
<b>Sunell</b>	SN-IPC54/40EDN, SN-IPD54/40VDN, SN-IPR54/40AKDN, SN-IPR54/40APDN, SN-IPV54/40UDN and SN-IPV54/40UDR
<b>Techson</b>	TCIP-Typ213MDN22x
<b>Zavio</b>	F3102, F3107, F3115

## FW upgrade:

<b>Sony</b>	SNC-CH210 (FW v1.78) , SNC-CH260 (FW v1.78), SNC-DH120 (FW v1.78) and SNC-ER550 (FW v1.78)
-------------	--

## Notice:

### 8. Known issue:

qq. American Dynamics ADCi600-D131

甲、Not support UPnP search.

乙、Not support motion detection at MJPEG mode.

rr. Fine CDB-MV720F

甲、Frame rate cannot reach 30fps.

ss. Fine ACM-R2001

甲、Frame rate may not enough about 2~8 fps because of camera design.

tt. Sunell SN-IPC54/40EDN

甲、MJPEG 2592x1920 will image broken due to camera FW issue.

乙、Camera will reboot when MJPEG 2048x1536 and quality 9 due to camera FW issue.

uu. Sunell VSR54/01

甲、MJPEG 2592x1920 will image broken due to camera FW issue.

乙、DI can't work correctly due to camera FW issue.

vv. Etrovision EV8180Q-XD, EV8782Q-BD

甲、Not support Talk.

乙、Under four profile mode only support resolution 640x480. (camera limitation)

丙、Not support MPEG4 in NVRmini 2/NVRsolo/TitanNVR.

丁、Motion Detection only works on H.264.

戊、It needs to reboot after changing HTTP port.

ww. LevelOne FCS-1132, FCS-3052, FCS-5052, FCS-5062

甲、The Motion Detection of MPEG4 is error.

乙、In Night mode, the Saturation cannot set. It is FW issue. (FCS-5062)

xx. Sony SNC-CH210, SNC-CH260, SNC-DH120, SNC-ER550

甲、Dual stream cannot enable when H.264, 30fps, 1280x720(SNC-CH210, SNC-DH120, SNC-ER550) or H.264, 30fps, 1920x1080(SNC-CH260) is selected for Image1.

乙、The number of connection is 1 for JPEG and 2 for H264 and MPEG4 at the same time.

丙、The PTZ function only support zoom in/out, focus near/far and auto focus function. (SNC-CH260, SNC-DH120)

丁、The connection cannot established with high probability when selected JPEG, high resolution and high quality. (SNC-DH120, SNC-ER550)

yy. Zavio F3102, F3107, F3115

甲、Under AMR 7.95 mode cannot use talk and audio function.

乙、The max frame rate of MPEG4 is up to 20 FPS in 1280x800. It's camera limitation.

zz. D-Link

甲、DCS-2136L:

- i. Constant bit rate cannot set bigger than 4M
- ii. In camera web video setting and NUUO camera setting page, when mode is MJPEG, set the fixed quality to "Excellent" and save, then change the Mode to H.264, the "Fixed quality" should also be "Excellent", but the "Good" option is show up due to camera FW issue.
- iii. When select resolution "176x144", it will display incorrect image

乙、DCS-3010:

- i. Firmware Issue: Not support Talk
- ii. Firmware Issue: Bitrate setting  
(more than 2Mbps will cause broken-image and image delay)

aaa. D-Link China:

甲、DCS-N62-40H2

- i. Firmware Issue: Not support Motion Detection
- ii. Firmware Issue: Bitrate List on web shows 3Mbps  
(the truly Bitrate value of camera could be 3Mbps or 2.5Mbps)
- iii. Speed setting only support pan speed(synchronized with Tilt speed)

乙、DCS-N40M-81H3

- i. Not support TCP/UDP

bbb. Hikvision Generic model:

- 甲、The camera setting will be failed, when sub stream resolution bigger than main stream resolution in Rapter platform.

ccc. ADT-VSDVS-4C

甲、Talk can't be use after setup audio codec.

乙、Tilt up and down can't be use.

丙、Name of preset point only support a-z A-Z @-\_!

ddd. ADT-VSDVZ5MP-VF3090IRI and ADT-VSDVZ5MP-VF3090IRO

甲、Audio codec is wrong under AMR.

乙、Camera may not connect under highest resolution, highest bit rate and lower frame rate.

丙、Tilt up and down cannot use.

eee. TCIP-Typ213MDN22x

甲、Not support auto detection.

乙、Not support DI/DO and audio.

丙、Not support setup PTZ speed.

丁、Video stream will have low frame rate with high quality under MJPEG.

戊、Not support UPnP search.(Mainconsole)

己、The frame rate does not synchronize with web under MJPEG.

fff. BOSCH NWD-495, NWC-495, NWD-455, NWC-455

甲、 Auto detect model unsupported

乙、 H.264 supports up to a maximum of 2CIF as this utilizes the Baseline Profile.

丙、 When H.264 quality is set to '0', the camera will auto-adjust the quality setting. For minimum quality, the value should be '100'.

丁、 When MJPEG quality is set to '0', the camera will auto-adjust the quality setting. For minimum quality, the value should be '1'.

戊、 MJPEG frame rate depends on camera load. Value in settings dialog is not representative of actual frame rate

ggg. BOSCH NDC-225

甲、 When H.264 quality is set to '0', the camera will auto-adjust the quality setting. For minimum quality, the value should be '1'.

乙、 MJPEG quality depends on camera load. Value in settings dialog is not representative of actual quality.

丙、 Audio Codec support g711, not support L1, AAC.

hhh. BOSCH VIP X1 XF E

甲、 When H.264 quality is set to '0', the camera will auto-adjust the quality setting. For minimum quality, the value should be '1'.

乙、 MJPEG quality depends on camera load. Value in settings dialog is not representative of actual quality.

丙、 Audio Codec support g711, not support L1, AAC.

丁、 The resolution of profile-2(Mjpeg) will be limited to CIF, if the resolutions of profile-0(h264) and profile-1(h264) set by CIF.

戊、 H.264 video stream supports maximum resolution of 704x576 (PAL) and 704 x 480 (NTSC) only. Full D1 (720 x 576) is not supported.

iii. Histream HH9801B-MPC-TD(HIHD\_T\_IR)

甲、 (MainConsole)Firmware Issue: Not support Motion Detection, DI, DO, video setting(Brightness/Contrast/Saturation)

乙、 (Mini2/Titan/Solo) Only support main stream video, camera setting(1920x1080, 1280x960, 1280x720). The other resolution not mentioned above are not supported.

## Bug fixed:

Mainconsole:

1. Zavio V111T: The zoom in/out cannot stop.
2. Sunell: DI can't work. (except VSR54/01 fw issue can not fix)
3. Bolide: DI can't work.

4. Brickcom VS-01Ap: Cannot PTZ via joystick.
5. JVC VN-H\*: Connect by http will cause CPU loading high, disable it.

#### NVRmini 2:

1. Grundig\_GCI-K0523T, Grundig\_GCI-H0503B: After selected H.264 video format in NVRmini2, the video format will back to MJPEG.
2. Vivotek VS8801: There is no image for dual stream.
3. Sunell: DI can't work. (except VSR54/01 fw issue can not fix)
4. Bolide: DI can't work.
5. CNB IXC2050IR and IDC4050VR: disconnect after several hours.
6. JVC VN-H\*: Connect by HTTP will cause CPU loading high (camera FW issue). NUUO suggest not connect via HTTP.

#### Titan NVR:

6. Vivotek VS8801: There is no image for dual stream.
7. Sunell: DI can't work. (except VSR54/01 FW issue cannot fix)
8. Bolide: DI can't work.
9. CNB IXC2050IR and IDC4050VR: disconnect after several hours.
10. JVC VN-H\*: Connect by HTTP will cause CPU loading high (camera FW issue). NUUO suggest not connect via HTTP.

## Release Version v2.10.0 (2013/02/26)

#### Modules:

Device Pack v 2.10.0

## Supported Systems:

Mainconsole	v 3.5.0 and above
NVRmini 2	v 1.5.0 and above
NVRsolo	v 1.0.0 and above
Titan NVR	v 1.3.0 and above

## New Camera Supported:

<b>ADT</b>	ADT-VSDVZ3MP-VF3010IRO
<b>Beward</b>	N100, N120, N300, N320, N600 and N630
<b>CNB</b>	IDP5035VR, IGC2050F, IGP2035F, IVP5035VR, IXP3035VR and NGE2055F
<b>Dynacolor</b>	NA083(IP+ only)
<b>Dlink</b>	DCS-2210, DCS-5020L
<b>Eneo</b>	PXD-1010F02 and PXD-1020F02
<b>Honeywell</b>	HDZ20HD, HDZ20HDE, HDZ20HDEX and HDZ20HDX
<b>Vivotek</b>	CC8130, FD8151V and IP8372
<b>Zavio</b>	B5010, B5111, B5210, D3100, D3200, D5112, F7210 and F3110

## FW upgrade:

<b>Levelone</b>	FCS-4041, WCS-6020 and WCS-6050
<b>Panasonic</b>	WV-SC385 and WV-SP105
<b>Sunell</b>	SN-IPD54/12VDN
<b>D-Link</b>	DCS-7413, DCS-6511

## Onvif support:

1. For ONVIF partner, NUUO only guarantee camera video connection (1st stream) with ONVIF test report.
2. Onvif Product line support: Titan(Profile S v12.06), Mini2(Profile S v12.06), Mini (Onvif v1.01) Solo (Profile S v12.06) and Mainconsole(Profile S v12.06)

## Notice:

9. Known issue:
  - jjj. Sunell SN-IPD54/12VDN Can't test DI due to HW broken.
  - kkk. CNB IGP2035F/IXP3035VR/IDP5035VR/IVP5035VR, Failed to set bitrate to 128k over VGA/D1.



### III. ADT ADT-VSDVZ3MP-VF3010IRO

1. Audio codec is wrong under AMR.
2. Camera may not connect under highest resolution, highest bitrate and lower framerate.

### mmm. D-Link

1. DCS-6511: camera framerate is lower than user setting.
2. DCS-7413: When framerate is 1, camera connection isn't stable.

Not support MPEG4, TCP, UDP

3. DCS-5020L: (Titan/Mini2) Not support Audio
4. DCS-2210: Camera web and MainConsole can't be set simultaneously.

### nnn. DynaColor NA083 Parameter setting will fail when Mjpeg quality bigger than 60

### ooo. Eneo PXD-1010F02,PXD-1020F02 Parameter setting will fail when Mjpeg quality bigger than 60

### ppp. Honeywell HDZ20HD,HDZ20HDE,HDZ20HDEX,HDZ20HDX Parameter setting will fail when Mjpeg quality bigger than 60

### aa. OEM N73200, the AMR mode of audio doesn't work correctly and the frame rate of MPEG4 is up to 20 due to the limitation of hardware.

### bb. Zavio

1. For F7210, due to audio and PTZ malfunction, the two functions can't be verified unless new camera sample is provided. Thus, audio and PTZ function for F7210 is not guaranteed.
2. For D3100, there is no audio and the UPnP doesn't include port settings. The two are known as FW issue.
3. For D3200 and F3110, the AMR mode of audio doesn't work correctly and the frame rate of MPEG4 is up to 20 due to the limitation of hardware.
4. For B5210, the frame rate is not enough when using TCP and HTTP connection.

### cc. Beward

1. For N300/320, only camera link is received for camera intergration. Thus, NUUO only guarantee video function.
2. For N100/120, audio will be disappeared after switch settings for a few times. (FW issue)

### qqq. LeveOne

- 甲、 For FCS-4041, High video parameter causes slow CGI command response.

## Bug fixed:

Mainconsole:

- Fix Zavio F210A motion detection cannot be triggered.

NVRmini 2:

- None

Titan NVR:

- Fix Titan can't login after connecting Samsung SNB-1001 several hours.

## Release Version v2.9.5 (2013/02/01)

### Modules:

Device Pack

v 2.9.5

## Supported Systems:

Mainconsole	v 3.5.0 and above
NVRmini 2	v 1.5.0 and above
Titan NVR	v 1.3.0 and above

## New Camera Supported:

none

## Bug fixed:

Mainconsole:

- Mainconsole would probably occur unexpected crash when first launch.

## Release Version v2.9.0 (2013/01/21)

### Modules:

Device Pack	v 2.9.0
-------------	---------

## Supported Systems:

Mainconsole	v 3.5.0 and above
NVRmini 2	v 1.5.0 and above
Titan NVR	v 1.3.0 and above

## New Camera Supported:

<b>3Svision</b>	S4071
<b>Arecont</b>	AV1145-04-W, AV1145-3310-D, AV1145-3310-W, AV1255, AV2145-04-D, AV2145-04-W, AV2145-3310-D, AV2145-3310-W, AV3255 and AV10255
<b>AXIS</b>	M1013, M1144, M3006, P1204, P1354 and Q7424
<b>Beward</b>	N100, N120, N300, N320, N600 and N630 (Mainconsole support only)
<b>Bullwark</b>	BLW-510MP-BS
<b>Dlink</b>	DCS-5605, DCS-5635, DSC-932L, DCS-6210, DCS-7110, DCS-2230, DCS-6513 and DSC-6915
<b>Everfocus</b>	EDN2210 and EPN4220
<b>Fine</b>	3MP_BOX, 3MP_FD, 3MP_IR,3MP_PT, 3MP_VD and CDB-HD280
<b>Forenix</b>	C2200, C2200-W, FBX-200, FBX-300WD, FDM-200, FDM-300WD, FVD-200, FVD-300WD, M0202-BH01, M0202-BH02, M0202-BH03, M7202-DB03, M4202-DB03 and M4202-DB02
<b>Hikvision</b>	DS-2DF1-572
<b>Levelone</b>	WCS-6020 and WCS-6050
<b>MegaIP</b>	NCD-2003PR and NMX-2003P
<b>Messoa</b>	NCB855, NCC800 and NIC950
<b>NTIC</b>	HVS-D1-V3
<b>OEM</b>	N73110
<b>Probe</b>	PID-H1300
<b>Samsung</b>	SND-5010
<b>Santec</b>	SNC-3305, SNC-5315IR, SNC-6202 and SNC-6315
<b>Sunell</b>	IPS54/71DN/Z18 and IPS54/80DR
<b>TP-LINK</b>	TL-SC3130v2 and TL-SC3130Gv2
<b>VisionHitech</b>	Vision SM3Ti
<b>Vivotek</b>	IP8172
<b>Yudor</b>	YUC-H626, YUC-H7926 and YUC-Hi26
<b>Zavio</b>	B5010, B5210, D3100, and F7210

## FW upgrade:

<b>Arecont</b>	AV8185 and AV8365
----------------	-------------------

<b>Messoa</b>	NIC950
<b>Probe</b>	PIC-H2010, PIN-H1310 and PMI-H2000

## Onvif support:

3. For ONVIF partner, NUUO only guarantee camera video connection (1st stream) with ONVIF test report.
4. Onvif Product line support: Titan(Profile S v12.06), Mini2(Profile S v12.06), Mini (Onvif v1.01) and Mainconsole(Profile S v12.06)

## Notice:

### 10. Known issue:

rrr.Yudor YUC-H626, YUC-Hi26, YUC-H7926:

In website, when bitrate mode is "CBR" and change stream mode from "Advanced mode" to "Basic mode". Quality will not synchronized to web.

sss. Santec SNC-6315:

M-JPEG on high resolution and quality may not get parameter.

ttt. VisionHitech Vision SM3Ti,

1. Sometimes can't get camera parameter normally due too camera response too slow, but there is chance to recover after reboot.

2. Audio may discontinuously under high resolution, framerate and bitrate settings.

uuu. LevelOne WCS-6020, WCS-6050

甲、WCS-6050 not support MJPEG 1280x1024

乙、Not support preset

丙、Camera's framerate is less than 30fps at high resolution.

丁、PTZ Home is stopped when the button is released at titan.

戊、Broken textures at high quality.

己、Not support AAC codec. Users have to set AMR codec via camera web.

vvv. Everfocus EDN2210 :

Sometimes can't get camera's parameter at high resolution.

www. Beward

1. For N300/320, only camera link is received for camera intergration. Thus, NUUO only guarantee video function.
2. For N100/120, audio will be disappeared after switch settings for a few times. (FW issue)

xxx. 3SVision S4071

1. The quality setting of M-JPEG is unavailable.
2. When the server attaches two or more channels, the maximal framerate is unstable.

yyy. Zavio

1. For F7210, due to audio and PTZ malfunction, the two functions can't be verified unless new camera sample is provided. Thus, audio and PTZ function for F7210 is not guaranteed.
2. For D3100, there is no audio and the UPnP doesn't include port settings. The two are known as FW issue.

zzz. TP-LINK TL-SC3130v2 and TL-SC3130Gv2

Not support audio with AMR 7.95.

aaaa. Messoa NCC800, NCB855

1. Set parameter will take 10 sec or more to setup.
2. Get parameter may wrong after set parameter.
3. Broken textures on connected in 1~4sec at MPEG4.
4. Not support auto detection.
5. For NCB855, setup bit rate of MPEG4 will response wrong parameter.

bbbb. Messoa NIC950

1. Not support UPnP.
2. Not support auto detection.
3. Not support motion detection on MJPEG.
4. Not support DI and DO.

cccc. Probe PID-H1300

Auto detection fail. (FW issue)

dddd. D-Link

1. DCS-7110: not support Preset and HTTP protocol
2. DCS-6915: not support Preset, Audio 40kbits mode, Talk, Motion Detection and Flip.
3. DCS-2230: Quality setting fail in MJPEG

4. DCS-6210: Flip/Mirror acts contrary
5. DCS-6513: Preset issue(1st point position will be covered by 2<sup>nd</sup> point position), Talk voice abnormal
6. DCS-5635: Not support autopan speed setting and MPEG4 format in HTTP
7. DCS-5605: Not support MPEG4 format in HTTP

eeee. Bullwark

BLW-510MP-BS: Get parameter will fail when Mjpeg quality bigger than 60.

ffff.Axis

P1354: Not support AAC in MJPEG. Not support AAC in H264 in Titan and Mini2 v1.6, but support in Mini2 v1.5.

## Bug fixed:

Mainconsole:

- Hikvision Generic:
  1. If device not support PTZ function, PTZ push-button will not be disable.
  2. Autodetect function can't find generic model.
  3. MD delay
  4. There are broken texture when use high resolution and low frame rate.
- Messoa:
  1. The default values of video parameter are different from camera web on MainConsole.

NVRmini 2:

- Hikvision Generic:
  - 1.If device not support PTZ function, PTZ push-button will not be disable.
  - 2.Autodetect function can't find generic model.
- CNB IDC4000T:
  - 1.the device can not connect and can not set up on camera web page after a period of time.

Titan NVR:

- Hikvision Generic:
  - 1.If device not support PTZ function, PTZ push-button will not be disable.
  - 2.Autodetect function can't find generic model.

- CNB IDC4000T:
  - 1.the device can not connect and can not set up on camera web page after a period of time.

## Release Version v2.8.0 (2012/12/19)

### Modules:

Device Pack

v 2.8.0



## Supported Systems:

Mainconsole	v 3.5.0 and above
NVRmini 2	v 1.5.0 and above
Titan NVR	v 1.3.0 and above

## New Camera Supported:

<b>ACTi</b>	KCM5511
<b>Arecont</b>	AV8185DN, AV8365DN, AV20185DN and AV20365DN
<b>AXIS</b>	M3005
<b>Bolide</b>	BN1009/PTZ3GIP, BN1009/PTZWDRIP, BN1009M/PTZ-18, BN2002IP, BN2002WDRIP, BN2009AVAIRIP, BN2009IRIP, BN2009WDRVAIRIP, BN2035IRIP, BN2035WDIRIP, BN5002M-A, BN5009M-A and BN5035M-A
<b>BOSCH</b>	NTC-265-PI and NDN-265-PIO
<b>Corum</b>	CS-150-IO, CS-195-IO, CS-310-IO, CS-320-IO, CS-390-IO, CS-410-IO and CS-425-IO
<b>Dlink</b>	DCS-2310L, DCS-3112, DCS-6314, DCS-6915(Mainconsole support), DCS-7413 and DCS-7513
<b>Eneo</b>	GXB-1720M-IR, GXC-1605M, GXC-1606M-IR, GXC-1720M, GXD-1610M-IR, and GXD-1720M-IR
<b>Everfocus</b>	EPN4220
<b>Hikvision</b>	DS-2CD8253F-EI, DS-2CD8264FWD-(EIS), DS-2CD864FWD-E, DS-2DF1-572 (Mainconsole support) and Generic
<b>ITX</b>	NCD-2003PR(Mainconsole support), NMX-2003P(Mainconsole support)
<b>LevelOne</b>	WCS-6020(Mainconsole support), WCS-6050 (Mainconsole support)
<b>LG</b>	LDW2010, LSW900, LSW901, LSW2010, LVS201, LVS301, LVS311, LVW700, LVW701, LVW900, LVW901, LW352, LW355, LW9226, LW9226I, LW9228, LW9228I
<b>Rover</b>	RV19BMVP and RV19BMVIR
<b>Samsung</b>	SNB-5001, SND-5011 and SND-5061
<b>Sony</b>	SNC-VB600 and SNC-VB630
<b>Tiandy</b>	TC-NS324S2-V2.1
<b>Vivotek</b>	IP8172(Mainconsole support)
<b>Yudor</b>	YUC-H696, YUC-766R-30, YUC-H796R, YWS-H01DP and YWS-H04S

## FW upgrade:

<b>Panasonic</b>	DG-SW155, WV-SP135E and WV-SW155
------------------	----------------------------------

## Notice:

Known issue:

### I. ACTi KCM5511

Pitch of G.711 audio is not correct.

Not support motion detection in M-JPEG.

### II. CORUM

Under particular operation, the quality or resolution of video parameter can't be set. It needs set quality on camera web again.

The particular operations sequence is as follows:

In Advanced Mode -> use VBR -> Apply -> use CBR -> Apply -> change to Basic Mode -> Apply

CS-425-IO and CS-195-IO: Not support 2<sup>nd</sup> stream in maximum frame rate of 1080p.

CS-230-IO: Cannot setup saturation. (IP+)

CS-390-IO: Not support UPnP.

CS-150-IO, CS-195-IO, CS-320-IO, CS-390-IO, CS-410-IO and CS-425-IO: When input under N.C status, needs trigger input more than 10 sec if you want to cancel event of input.

### III. Sony SNC-VB600,SNC-VB630

Not support Motion Detection.

Not support Audio.

Alarm Input doesn't work.

### IV. VIVOTEK IP8172

Not support CBR mode (MainConsole).

MJPEG not support audio.

Not support AAC audio.

### I. LevelOne WCS-6020, WCS-6050

Camera does not stable at bad network environment. For example, UPNP search failed, no video...etc.

Not support preset

WCS-6050 not support MJPEG 1280x1024

## II. Hikvision

DS-2CD8264FWD-(EIS): Not support PTZ

DS-2CD864FWD-E: Not support DI, G726 talk, zoom in/out

DS-2CD8253F-EI: Not support audio but the clickbox is opened(cgi issue).

## III. D-Link

DCS-6915: Not support talk, Motion Detection, DI, DO

DCS-3112: Not support Preset

## IV. Bolide

All Bolide models changing MJPEG resolution may get Fail message due to camera FW issue.  
(MainConsole/Mini2/Titan)

All Bolide models AutoDetect model may fail due to incorrect model name response.  
(IP+/Mini2/Titan)

BN2002WDRIP, BN5002M-A: AlarmIn message is unstable.

## V. Bosch NTC-265-PI:

MJPEG Quality always get 70 (Camera Firmware Issue). (MainConsole)

H264, MJPEG set Quality 0 but get 24 (Camera Firmware Issue). (MainConsole /Mini2/Titan)

MJPEG lag (Camera Firmware Issue). (MainConsole)

Audio Codec supports g711, not support L1, AAC. (MainConsole /Mini2/Titan)

## VI. Tiandy TC-NS324S2-V2.1

Audio at titan is bad.

Only support streaming

## VII. ITX NCD-2003PR:

When set Anti-Flicker Mode to 50Hz, Mainconsole would get wrong Max of FPS(30).  
(Firmware issue)

## VIII. LG LW9226:

Audio out sound level is too small (with high impedance).

## IX. LG LVS201:

Video image has some noise in the bottom line when video resolution at QCIF.

### **Bug fixed:**

Mainconsole:

- Samsung SND-3082 video will disconnect after continuous control PTZ several minutes.
- Panasonic DG-SF334 force setting bitrate value when codec is H264.

NVRmini 2:

- AMTK AM2221D, AM2231D preset name can't contain blanks.

Titan NVR:

- AMTK AM2221D, AM2231D preset name can't contain blanks.
- Sony SNC-EP580 PTZ speed is too slow.

## Release Version v2.7.2 (2012/11/28)

**Modules:**

Device Pack v 2.7.2

## Supported Systems:

Mainconsole	v 3.5.0 above
NVRmini 2	v 1.5.0 above
Titan NVR	v 1.3.0 above

## New Camera Supported:

**AXIS** M3005 (For Mini2 and Titan only)

## Release Version v2.7.0 (2012/11/19)

### Modules:

Device Pack	v 2.7.0
-------------	---------

## Supported Systems:

Mainconsole	v 3.5.0 above
NVRmini 2	v 1.5.0 above
Titan NVR	v 1.3.0 above

## New Camera Supported:

<b>Airlive</b>	OD-325HD
<b>AMTK</b>	AM2030D, AM2110D, AM2120D, AM2221D, AM2231D, AM2530D, AM2570D, AM2590D, AM2630D and AM2730D
<b>Asoni</b>	CAM613M, CAM614, CAM615, CAM616M, CAM619M, CAM620, CAM624M, CAM625M, CAM627M, CAM628M, CAM630, CAM632, CAM633, CAM634M, CAM637M, CAM638, CAM639(Mini2/Titan only), CAM640, CAM641(Mini2/Titan only), CAM642M, CAM647, CAM656D, SVR610, SVR611, SVR640
<b>AXIS</b>	P5544
<b>Bosch</b>	NDC-274-P and NDC-274-PT
<b>Camtron</b>	HLC-81AD/P, HLC-83V, HLC-83V/W, HLC-84V and HLC-84V/W
<b>Corum</b>	CS-270-IO
<b>Forenix</b>	NPB-720, NPB-720A, NPB-720U, NPD-720K and NPD-720R
<b>Hikvision</b>	DS-6601HFHI (Mainconsole only)
<b>Histream</b>	HIHD_64
<b>Lilin</b>	IPD2220ES, IPG1022ESX, IPG1022ES, IPR320ESX, IPR434ESX, IPR7424ESX (Mini2/Titan support)
<b>Messoa</b>	NCR-875PRO, NDR-891, NIC-990
<b>Samsung</b>	SNB-7001, SNB-7002, SND-7011, SND-7061, SND-7082 and SNV-7082
<b>Tiandy</b>	TC-NH9106S2-MP
<b>JVC</b>	VN-H37U, VN-H57U, VN-H137U, VN-H157WPU, VN-H237U, VN-H257U, VN-H257VPU, VN-V685U, VN-V686BU, VN-V686WPBU (Mini2/Titan support, Mainconsole have supported on DP v2.5)

## Notice:

18. Known issue:

dd. BOSCH NDC-274-P

- MJPEG Quality always get 70 (Camera Firmware Issue).
- MJPEG set Quality 0 but get 24 (Camera Firmware Issue).
- MJPEG lag (Camera Firmware Issue).

- ee. Airlive OD-325HD and AMTK AM2030D, AM2110D, AM2120D, AM2221D, AM2231D, AM2530D, AM2570D, AM2590D, AM2630D and AM2730D Always can use http port 80 to connect after changing http port by FW issue.
- ff. Airlive OD-325HD and AMTK AM2590D, AM2030D, AM2570D, AM2530D, AM2630D, AM2730D Initial output status will not synchronize to real output voltage by HW issue.
- gg. AMTK AM2221D, AM2231D preset name can't contain blanks.
- hh. Histream HIHD\_64 camera response very slow, when change video parameter, there is high opportunity to disconnect. Just wait for a while, or reboot camera, and then be able to reconnect.
- ii. Hikvision DS-6601HFHI
  - UPnP search can't find the camera.
  - Can't change port on camera web site.
  - Talk sound is not fluent
- jj. Messoa NDR891 and NCR875PRO
  - Set parameter will take 10 sec or more to setup(Camera Firmware Issue).
  - Get parameter may wrong after set parameter(Camera Firmware Issue).
  - Broken textures on connected in 1~4sec at MPEG4(Camera Firmware Issue).
  - Not support auto detection.
  - Setup bit rate of MPEG4 will response wrong parameter on Mini2/Titan(Camera Firmware Issue).
  - Not support talk on MainConsole.
  - The default values of video parameter are different from camera web on MainConsole.
- kk. Messoa NIC990
  - Can't set frame rate(Camera Firmware Issue).
  - Only support H.264.
  - Not support dual stream on 1080P(Camera Firmware Issue).
- ll. Camtron HLC-81AD/P doesn't support autodetect & search
- mm. LILIN IPD2220ES, IPG1022ESX, IPG1022ES, IPR320ESX, IPR434ESX, IPR7424ESX Video parameter does not synchronize to ONVIF option.
- nn. LILIN IPR434ESX does not support dualstream at 2048x1536
- oo. Tiandy TC-NH9106S2-MP
  1. Not support ONVIF event (MD, I/O).
  2. Not support minor stream.
  3. Not support dual stream.

## Bug fixed:

Mainconsole:

- Fine SP-HP2020Q-IP patrol cause IP+ dump.
- Levelone FCS-3091 can't use talk function.

#### NVRmini 2:

- CNB IDP4000VD open dualstream failed.
- Vivotek SD8XXX series preset issue.
- Panasonic WV-SW395, WV-SW396 preset issue.

#### Titan NVR:

- CNB IDP4000VD open dualstream failed.
- Vivotek SD8XXX series preset issue.
- Panasonic WV-SW395, WV-SW396 preset issue.

## Release Version v2.6.0 (2012/10/19)

### Modules:



Device Pack v 2.6.0

## Supported Systems:

Mainconsole	v 3.5.0 above
NVRmini 2	v 1.5.0 above
Titan NVR	v 1.3.0 above

## New Camera Supported:

<b>Axis</b>	M1014 , M1143-L, M3004, M7014, P7224 and Q7406 DCS-2130 (Titan/Mini2 support and Mainconsole already support on v2.5) and DCS-3716
<b>D-Link</b>	
<b>Everfocus</b>	EDN3160, EDN3260, EDN3340, EHN3160, EHN3260, EHN3340 and EPN4122
<b>Forenix</b>	ACD-3VM501 and NPB-720BM
<b>Jetstor</b>	JS-C1100, JS-C2100, JS-WGP-100-CB, JS-B0100, JS-B0100-W, JS-B0131, JS-BB1100-R30, JS-B1100, JB-B1204-R25, JS-D0100, JS-D1100, JS-D1130, JS-D1204, JS-ISD0200x18 and JS-OSD0200x20
<b>Levelone</b>	FCS-3071-V2
<b>Samsung</b>	SNP-6200, SNP-6200H, SNP-6200HP, SNP-6200P
<b>Shany</b>	SNC-21XX ( SNC-WD2112MDN, SNC-WD2122DN, SNC-WDL2132DN, SNC-WDL2142DN) SNC-22XX ( SNC-2212MDN, SNC-2222DN, SNC-L2232DN) SNC-23XX (SNC-WD2312MDN, SNC-WD2322DN, SNC-WDL2132DN, SNC-WDL2332DN)
<b>Sunell</b>	IPS54/70DN/Z18, IPS54/70DN/ZR18, IPS54/70DR/Z18, IPS54/70DR/ZR18, SN-IPC54/11FDN, SN-IPC54/11DN, SN-IPC54/11EDN, SN-IPV54/11DN, SN-IPV54/11DR, SN-IPD54/11VDN, SN-IPD54/11VDR, SN-IPV54/11UDN, SN-IPV54/11UDR, SN-IPR54/11DN, SN-IPR54/11ANDN, SN-IPV54/11ZDR, SN-IPR54/11ALDN, SN-IPR54/11AKDN, SN-IPD54/12VDN, SN-IPC54/12DN, SN-IPC54/12EDN, SN-IPC54/12FDN, SN-IPV54/12DN, SN-IPV54/12DR, SN-IPD54/12VDR, SN-IPV54/12UDN, SN-IPV54/12UDR, SN-IPR54/12DN, SN-IPR54/12ANDN, SN-IPV54/12ZDR, SN-IPR54/12ALDN, SN-IPR54/12AKDN and VSR54/01
<b>Techson</b>	TCIP-220MDN, TCIP-230WDRMDN, TCIP-213WDRMDN, TCIP-D213WDRDN TCIP-D220DN, TCIP-D230WDRDN, TCIP-LD213WDRMDN, TCIP-LD220MDN, TCIP-LD230WDRMDN and TCIP-LPro213WDRMDN (Mini2 and Titan support, Mainconsole already support on DP v2.5)
<b>Zavio</b>	D5113, D7111, F1100 and F1105

## Notice:

### 19. Known issue:

- pp. Sunell SN-IPD54/12VDN, VSR54/01 autodetect fail due to camera FW issue.  
IPS54/70DN/ZR18 VSR54/01 changing MJPEG resolution may get Fail message due to camera FW issue. Can't support G711 A-law(Onvif issue)
- qq. Axis P7224 can't use second audio in (All). Support G.711 only (mini2/Titan).
- rr. Forenix NPB-720BM doesn't support On-edge motion under TCP or UDP protocol.
- ss. Digital WatchDog DWC-MPA20M does not support On-edge motion detection.
- tt. Digital WatchDog DWC-MPA20M, if switching between profiles constantly(about 5~10 times), sometimes the camera is just disconnected and no longer connected again until rebooting it
- uu. 2.5 and 12.5 framerate can't be show at EPN4122.

## Bug fixed:

### Mainconsole:

- Can't connect over 3 Pelco IP110 devices.
- Icantek icanview240 can't use PTZ.
- Probe connection failed after several minute.
- EverFocus ONVIF camera responses LAN address in NAT environment.

### NVRmini 2:

- Panasonic WV-SW395 PTZ speed moving angle too much.
- Probe connection failed after several minute.
- Vivotek some PTZ models can't control PTZ when PTZ speed is 0 in the camera web interface.
- EverFocus ONVIF camera responses LAN address in NAT environment.

### Titan NVR:

- Panasonic WV-SW395 PTZ speed moving angle too much.
- Probe connection failed after several minute.
- Vivotek some PTZ models can't control PTZ when PTZ speed is 0 in the camera web interface.
- EverFocus ONVIF camera responses LAN address in NAT environment.

## Release Version v2.5.0 (2012/09/18)

## Modules:

Device Pack v 2.5.0

## Supported Systems:

Mainconsole v 3.5.0 above

NVRmini 2 v 1.5.0 above

Titan NVR v 1.3.0 above

## New Camera Supported:

**ACTi** KCM5611 and KCM7911

**Axis** Q1604 and Axis (for IP camera and video servers' Video only)

**Dahua** SD65XX-HN and SD69XX-HN

**D-Link** DCS-2130 (Mainconsole only)

**Ernitec** Mercury SX 302, Mercury SX 302IR, Mercury SX 302M, Orion SX 802IH, Orion SX 802OPH, SX 605, Vega SX 102 and Vega SX 102IH

**Guardeon** GDN-V1300D, GDN-DV1300IR and GDN-D1300IR

**Honeywell** HCD5MIH, HD3MDIH and HD4MDIH

**JVC** VN-H257U, VN-H257VPU, VN-H37U, VN-V685U, VN-V686BU and VN-V686WPBU(Mainconsole only)

**LG** LNB3100, LNB5100, LND3100, LND5100, LNP2800, LNP2800I, LNP3700, LNP3700T, LNV5100, LNV5110, LW130W, LW332, LW335, LW342, LW345, LW6324, LW6354, LW6424, LW6454 and LW9422

**Vivotek** FE8171V (Mainconsole only and Titan/Mini2 already support on v1.13) and FE8172V

## Notice:

20. Known issue:

- a. ACTi KCM5611 does not support RS-485 (not support Pan/Tilt).
- b. Dahua SD65XX-HN, SD69XX-HN does not support motion detection at MJPEG.  
MJPEG bitrate can't set over 8192 kbps.
- c. Axis Generic support video only.
- d. Axis Q1604 does not support AAC at MJPEG and not support H264 CBR mode.
- e. Guardeon does not support audio in with 16KHz sampling rate.
- f. LG series can't support dual-stream when video parameter is H264, 1920x1080(or above),  
over 20fps.
- g. LG Speed Dome models (LW9422, LNP3700T) PTZ will stop automatically when press bottom  
over 10 sec. Focus near/far needs to setup the focus mode in camera's OSD. Adjust zoom  
speed is useless.
- i. Vivotek FE8172V, not support CBR mode. Not support audio at MJPEG. Not support AAC  
audio. When resolution is 1360x786, video stream would have a white line at the left-bottom  
of the frame. If set to Full HD mode, the low profile video stream would have a color line at  
the bottom of frame.

## Bug fixed:

### Mainconsole:

- Fix Santec SNC-8322 PTZ "down-left "
- Fix Dynacolor NV053, NV223 autofocus
- Probe PIC-H2010 with wrong MAX framerate support.
- Zavio B7210, F7210 with wrong resolution support.

### NVRmini 2:

- Panasonic WV-SC385 can't get preset point.
- Sunell SN-IPS54/60DN/Z18/WI Motion Detection failed after 60sec.

### Titan NVR:

- Panasonic WV-SC385 can't get preset point.
- Sunell SN-IPS54/60DN/Z18/WI Motion Detection failed after 60sec.

## Release Version v2.4.0 (2012/08/20)

## Modules:

Device Pack v 2.4.0

## Supported Systems:

Mainconsole v 3.5.0 above

NVRmini 2 v 1.5.0 above

Titan NVR v 1.3.0 above

## New Camera Supported:

**ACTi** TCM1111, TCM3111, TCM4511, TCM5111 and TCM6630

**Alphatech** AT-IMF5736 and AT-IMV5756

**Brickcom** 30xN

**Grundig** GCI-K1526V and GCI-K1812W

**Probe** PIC-2010T and PIN-H1310

**Sunell** SN-IPS54/60DN/Z18/WI

**Techson** TCIP-213WDRMDN, TCIP-220MDN, TCIP-230WDRMDN, TCIP-D213WDRDN, TCIP-D220DN, TCIP-D230WDRDN, TCIP-LD213WDRMDN, TCIP-LD220MDN, TCIP-LD230WDRMDN and TCIP-LPro213WDRMDN (Mainconsole only)

**Vidosec** ICS-20W, ID-20, IRD-20 and IRW-20W

**Vivotek** BB5116, BB5315, BD5115 and FD8131

**3Svision** N3071, N6072, N6073, N6074, N6075, N6076, N6077 and N9071

## Notice:

21. Known issue:

- a. ACTi TCM6630, DI/DO useless, FW issue.
- b. AlphaTech models, 2nd profile's framerate will be limited to 15fps when 1st profile set resolution to 1600x1200. Framerate only support 3~25fps.
- c. Brickcom 30xN, Cover FB-300Np, WFB-300Np, MD-300Np. MD-300Np is no support DI/DO and one way audio only.
- d. Grundig models, camera become slow response (or not response) when set resolution, compression and framerate near the maximum value, audio will not smooth at the same time. Suggest modify GOV length to small value when video framerate lower than 5.
- e. Probe series, will access failed when add more than 1 channel to the same camera.
- f. Sunnell SN-IPS54/60DN/Z18/WI, dual-stream will connect failed when camera is too busy.

## 22. Bug fixed:

### Mainconsole:

- Brickcom VS-04A, can't be selected in the camera support list.

### NVRmini 2:

- ACTi CAM6610, adjust PTZ speed to adequate speed.
- Grundig C3075, increase the PTZ control latency.
- Sunnell camera can't disconnect automatically when press disconnect button.

### Titan NVR:

- ACTi CAM6610, adjust PTZ speed to adequate speed.
- Grundig C3075, increase the PTZ control latency.
- Sunnell camera can't disconnect automatically when press disconnect button.

## Release Version v2.3.0 (2012/07/18)

## Modules:

Device Pack v 2.3.0

## Supported Systems:

Mainconsole v 3.5.0 above

NVRmini 2 v 1.5.0 above

Titan NVR v 1.3.0 above

## New Camera Supported:

**Alphatech** AT-IMF5739 and AT-IMF5750

**Basler** BIP2-D1920c-DN

**Dynacolor** na063

**Mobotix** M24M-Sec

**Santec** SNC-3322 and SNC-8322I/HO

**Telview** IPB612P-ICR, IPB630P-ICR, IPD612-VP-VF-IR, IPD630-VP-VF-IR, IPE600, IPW612, IPW630, IPW630P, IPZ611, VIS611, VIS614 and VIT621

**Vivotek** FD8335H, FD8372 and IP8361

## Notice:

23. Known issue:

a. Alphatech AT-IMF5739, AT-IMF5750

2nd profile's framerate will be limited to 15fps when 1st profile set resolution to 1600x1200.

Framerate only support 3~25fps.

b. Basler BIP2-D1920c-DN

Not support Audio & Talk

c. Dynacolor na063

Video parameter can't sync with camera web interface, need to refresh the browser.

Talk quality is not clear.

Camera efficiency will done when set high resolution & quality stream.

d. Mobotix M24-Sec

Audio only support on MxPEG.

Motion event works abnormal until first time trigger.

Resolution of dual-stream can't bigger then main-stream.

e. Vivotek FD8372

Mpeg4 support first 2 maximum resolutions are 1920x1920 & 1920x1536.

## 24. Bug fixed:

Mainconsole:

- Etrovision EV8180U black video when set resolution to 1920x1080.

NVRmini 2:

- CNB IDC4050IR, IDC4050F dualstream doesn't work.

Titan NVR:

- CNB IDC4050IR, IDC4050F dualstream doesn't work.

## Release Version v2.2.1 (2012/07/05)



## Modules:

Device Pack v 2.2.1

## Supported Systems:

Mainconsole v 3.5.0 above

NVRmini 2 v 1.5.0 above

Titan NVR v 1.3.0 above

## Notice:

### 1. Bug fixed:

For Eneo GCD1710M-IR, please remove DP v2.2.0 first then install DP v2.2.1 and reset

Mainconsole:

- a. Eneo camera model correct to GXD-1710M-IR
- b. Axis P7210 can not view the correct video channels with Codec H264.

NVRmini 2:

- a. Eneo camera model correct to GXD-1710M-IR

Titan NVR:

- a. Eneo camera model correct to GXD-1710M-IR

**Release Version v2.2.0 (2012/06/19)**

## Modules:

Device Pack v 2.2.0

## Supported Systems:

Mainconsole v 3.5.0 above

NVRmini 2 v 1.5.0 above

Titan NVR v 1.3.0 above

## New Camera Supported:

**ACTi** KCM-3311 and KCM-7311

**Arecont** AV2116 and AV3116

**Axis** M7014, P3354, Q1604, Q7414 (NVRmini 2, Titan NVR only)  
P3364

**Brickcom** OB-100Ap, VS01A, PZ-040D and PZ040E

**Eneo** GXB-1710M-IR, GXC-1710M and GCD-1710M-IR

**Hikvision** DS-2CD7153-E

**Mobotix** D-14D Sec

**Samsung** SNB-1001, SND-1011, SND-1080, SNO-1080R, SNV-1080 and SNV-1080R

**Vivotek** FD8372, FD8136, IP8133, PT8133, SD8362

## Notice:

1. Known issue:

- a. Hikvision DS-2CD7513-E  
this camera can not set framerate 15~22 when resolution is 1600x1200,1600x912.  
sometimes camera can't set resolution 1600\*1200 、1600\*912 、1280\*960.
- 2. Bug fixed:  
Mainconsole:
  - b. ACTi KCM-5211 PTZ function will be useless after 1 week. (Need upgrade FW V5.05.07 & ISP V1.02.02)
  - c. Samsung SND-3080 can not get the parameter of the video stream.NVRmini 2:  
None  
Titan NVR:
  - a. Axis Q7406 can not support PTZ control.
  - b. Axis P7210 can not view the correct video channels with Codec H264.
  - c. UDP IPE3500M disconnect automatically after 24hours.
  - d. Vivotek SD83x2, SD83x3 can not adjust the PTZ speed.
  - e. Zavio B7201 video broken in LiveView.

**Release Version v2.1.0 (2012/05/21)**

## Modules:

Device Pack v 2.1.0

## Supported Systems:

Mainconsole v 3.5.0 above  
NVRmini 2 v 1.5.0 above  
Titan NVR v 1.3.0 above

## New Camera Supported:

**Axis** P3367, P7210, P7214, P8513, P8514, Q1602, Q1602-E, Q1922 and Q1922  
**Brickcom** 130N series and 50xA series  
**CNB** IDC4000T  
**COP** 15-WS01D-E  
**Guardliner** SPmicro-412  
**Hikvision** DS-2CD853F-E  
**Panasonic** WV-SC386, WV-SP508, WV-SP509, WV-ST162, WV-ST165, WV-SW172, WV-SW174W, WV-SW175, WV-SW314, WV-SW316/L, WV-SW558 and WV-SW559  
**Samsung** SNP-3302/H  
**Santec** SNC-3342 and SNC-6332  
**Vision Hi-Tech** I series, Mi series, M3i series and NVS102  
**Vivotek** FD8134-SS, IP7160-SS, IP7161-SS, IP8151-SS, IP8161-SS, IP8162P-SS, IP8332-SS, SD8121-SS, SD8362E, SD8362-SS, SD8323E-SS  
**3SVision** N3072, N5071 and N8072

## Notice:

3. Known issue:

- a. Brickcom 130N series need waiting 15s to finish adjust the zoom/focus.
  - b. Brickcom 50xA series need waiting a period of time to reconnect stream success when switch the video resolution higher than 1920x1080.
  - c. Hikvision DS-2CD853F-E can't set framerate 15~22 in Max resolution.
4. Bug fixed:
- Mainconsole:
- Fixed Sony SNT-V704 can't connect failed.
  - Fixed UDP camera image gray out or break randomly when config different resolutions.
- NVRmini 2:
- Fixed Axis M7001 can't use dualstream.
- Titan NVR:
- None

**Release Version v2.0.0 (2012/04/18)**

## Modules:

Device Pack v 2.0.0

## Supported Systems:

Mainconsole v 3.5.0 above  
NVRmini 2 v 1.5.0 above  
Titan NVR v 1.3.0 above

## New Camera Supported:

<b>ACTi</b>	KCM-3211, KCM-3911
<b>Arecont</b>	AV20185CO, AV20365CO, D4F series
<b>Axis</b>	M3113-R, M3113-VE, Q6032
<b>Bullwark</b>	BLW-230MP-BS, BLW-230MP-DS, BLW-IN220X-S, BLW-IR230MP-DSM, BLW-IR230MP-SM and BLW-OUT220X-S
<b>Centrix</b>	B13H, C10, C10-W, D13HD, W13H
<b>Dynacolor</b>	NH720-20N1, NH820-20N1, nv103, nv223, nv053 and nv063
<b>Forenix</b>	B0202
<b>GE</b>	TVC-MP2B-S
<b>Hikvision</b>	DS-2CD754F-EI, DS-2CD8254F-EIS, DS-2CD752MF-E, DS-2CD754F-E, DS-2CD854F-E and DS-2CD883F-E
<b>IQinvision</b>	IQeye863N, IQeye865N, IQM30N, IQM31N, IQM32N and IQD32S
<b>Levelone</b>	FCS-0071, FCS-1122, FCS-5061 and WCS-0050(Mainconsole only)
<b>Panasonic</b>	WV-SC384, WV-SC385, WV-SF332, WV-SF335E, WV-SW355(above add I/O), WV-SW396
<b>Rover</b>	RV1WAD, RV01AD, RV01AT, RV04AD, RV1WAG, RV79AD, RV7RAD, RV7RAG, RV81AD, RV81AG, RV84AD, RV84AM, RV84AV and RV87ZA
<b>Samsung</b>	SNB-3002, SNO-7080RP, SNP-3371, SNP-3371TH, SPE-400, SND-3082 (F) and SNV-3082
<b>Vivotek</b>	FD8135H, FD8335H, IP8335H, PT8133 and PT8133W
<b>Zavio</b>	B7210, D7110, F1100(Mainconsole only), F1105(Mainconsole only), F3101, F3106, F3201, F3206 and F531E

## Notice:

5. **From DP v2.0, Mainconsole/NVRmini 2 (from v1.5)/Titan NVR (from v1.3) share same device pack.**

6. Known issue:
  - a. ACTi : KCM3211's PTZ only support Zoom and Focus.
  - b. Arecont: AV20185 include AV20185DN, AV20185CO, AV20365 include AV20365DN, AV20365CO
  - c. Bullwark: BLW-IR230MP-SM 1920x1080 MJPEG Bit rate too high will affect camera parameter can not sync to camera information
  - d. Forenix: not support search and auto detected (camera FW issue)
  - e. Hikvision: 1.DS-2CD8254F-EIS 、DS-2CD854F-E 、DS-2CD883F-E can't set framerate 15~22 in Max resolution, DS-2CD8254F-EIS 、DS-2CD854F-E 、DS-2CD883F-E image broken when resolution over 1600x1200
  - f. IQinvision: IQM3xN series not support audio in M-JPEG
  - g. Panasonic: WV-SC385 and WV-396 support continuous PTZ
  - h. Samsung: SNP-3301, SNP-3370: H264 can't support QCIF resolution
  
7. Bug fixed:

Mainconsole:

  - a. Fix Vivotek IP7361 motion detection works failed when set motion area more than 2.
  - b. Santec: SNC-4302  
1080P and 800x600 don't support flip and rotate, Model I/O revise and Quality setting fail issue

NVRmini 2:

  - a. Fix AV8185DN can't get correct video framerate, quality & compression after setting video parameter when adding the same model with a server over two times.

Titan NVR:

  - a. Fix Panasonic WV-SC385. The speed of PTZ is very slow in the Titan NVR.

## Release Version v1.19.0 (2012/02/29)

## Modules:

Device Pack v 1.19.0

## Supported Systems:

MainConsole v 3.3.0 above

## New Camera Supported:

<b>Dynacolor:</b>	V2 series
<b>iCANTEK:</b>	iCanView322MP, iCanView340MP
<b>Messoa:</b>	NIC990PRO-HP
<b>Micronet:</b>	SP5523W, SP5563HTM, SP5581HDC, SP5582HTM, SP-5584HTM, SP5591HTM SP5923,
<b>Pelco:</b>	IP110, SpectraIV-IP
<b>Santec:</b>	SNC-3302, SNC-4302, SNC-5312IR, SNC-6302, SNC-6312IRH, SVS-3001
<b>Truen:</b>	TCAM-5x10, TCS-2000

## Notice:

- c. Firmware Upgrade
  - iCANTEK: iCanView332MP, iCanView362MP
  - Truen: TCAM-570
- d. Known issue:
  - i. Messoa: NIC990PRO-HP
    - Only support video and PTZ. Other parameters setting, audio and DI/DO are not available due to firmware issue.
  - j. Pelco : IP110, SpectraIV-IP
    - Only support MPEG4 image, not support parameter setting. SpectraIV-IP only support 704x240. IP110 only support 704x480.
  - k. Micronet: SP5923
    - 1080P and 800x600 don't support flip and rotate.
  - l. Micronet: SP5581HDC
    - Not support talk.
  - m. Santec: SNC-4302
    - 1080P and 800x600 don't support flip and rotate.
  - n. Truen: TCAM-570
    - MJPEG not support audio.
  - o. Truen: TCAM-2000



- Not support below resolutions:
    - Composite NTSC 352x240, 720x240
    - HDMI 1080i60 352x240, 720x240, 640x360
  - Echo would occur after stop talk function
- e. Bug fixed:
- a. ACTi: KCM-5211 Auto-Focus behavior did not sync with camera web.
  - b. Vivotek: VS8401 would connect with incorrect channels.
  - c. CNB: ISS2965x can't Zoom In/Out by joystick.
  - d. Corumcctv: MainConsole would hang and stop after disconnecting the video stream.

**Release Version v1.18.0 (2012/01/03)**

## Modules:

Device Pack v 1.18.0

## Supported Systems:

MainConsole v 3.3.0 above

## New Camera Supported:

**Hikvision:** DS-2CD783F-E, DS-2CD783F-EI, DS-2DF1-5702, DS-2DF1-570A, DS-2DF1-5732, DS-2DF1-573A, DS-2DF1-57A  
**Lilin:** IPD2220ES, IPG1022ES, IPR320ESX, IPR722S, IPR7424/8ESX  
**Sony:** SNC-EP521, SNC-EP550, SNC-EP580, SNC-ER550  
**Vision Hi-Tech:** VISION i series, VISION M3i series, VISION NVS102  
**Vivotek:** IP8335H

## Notice:

- f. Bug fixed
- p. PELCO: D5118 cannot operate PTZ feature by joystick.
- q. PELCO's cameras: The video format does not sync with web's setting.
- r. Fine: TCP-690 cannot be connected.
- s. AXIS: P5534-E cannot set PTZ preset positions.
- t. iCANTEK: iCanView362MP, iCanView332MP :  
The audio stream would cause IP+ crash.
- g. Known issue:
  - Lilin: IPG1022ES, IPD2022ES and IPR7424/8ESX  
The audio inputs only support HTTP protocol.
  - Hikvision: DS-2DF1-57xx series  
The H.264 stream displays not smoothly.

## Release Version v1.17.0 (2011/12/01)

## Modules:

Device Pack v 1.17.0

## Supported Systems:

MainConsole v 3.3.0 above

## New Camera Supported:

<b>ACTi:</b>	KCM-5211E, KCM-5311E
<b>AMTK:</b>	AM2110D, AM2231D, AM2590D
<b>Etrovision:</b>	EV8281U, EV8285Q, EV8286Q
<b>Hikvision:</b>	DS-2CD753F-E, DS-2CD753F-EI, DS-2CD754F-E, DS-2CD754F-EI, DS-2CD754FWD-E, DS-2CD754FWD-EI, DS-2DF1-572
<b>Panasonic:</b>	WV-SF132, WV-SF135, WV-SW152/M, WV-SW155/M
<b>UDP:</b>	IPE1100M, IPE3100, IPE3500, IPE4100, IPE5500, IPE6500, IPE7500
<b>Vision Hi-Tech:</b>	Vision Mi series
<b>Vivotek:</b>	MD7560X
<b>Zavio:</b>	F3201, F7210

## Notice:

- h. Bug fixed
- u. Mainconsole breakdown when closing and restarting Mainconsole after Onvif models operate  
**Start patrol.**
- v. SAE-E588HDE18C can't control **Zoom In/Out** by joystick.
- w. PELCO-D5118 doesn't store the relative parameter of ptz speed after change it and restart Mainconsole.
- i. Known issue:
  - Hikvision DS-2CD753-E, DS-2CD753-EI, DS-2CD754-E, DS-2CD754-EI, DS-2CD754FWD-E, DS-2CD754FWD-EI do not support PTZ preset using RS-485.
- j. Firmware Upgrade:
  - Arecont: AV3135
  - Samsung: SNB-5000, SND-5080/F, SNP-5200H, SNV-5010, SNZ-5200
  - UDP: NVC1000

## Release Version v1.16.0 (2011/11/04)

## Modules:

Device Pack v 1.16.0

## Supported Systems:

MainConsole v 3.3.0 above

## New Camera Supported:

<b>Brickcom:</b>	MD-100AP
<b>CNB:</b>	IDC4050F, IDC4050IR, IDC4050VF, IDC4050VR, IGC2050F, ISMC1063x, IS1765x, ISS2965x, ISSM2063x, IVC5055VF, IVC5055VR, IXC2050IR,
<b>Dahua:</b>	HDB3300N, HDB3300P, HDBW3300N, HDBW3300P, HF3110N, HF3110P, HF3211P, HF3300N, HF3300N-W, HF3300P, HF3300P-W
<b>Etrovision:</b>	EV3150A, EV3151, EV3151A, EV6150A-BI, EV6150A-CI, EV6151A, EV6153A, EV6156A, EV6250A-EI/EO, EV6251A-FI/FO, EV6252A-GI/GO, EV6252A-GI/GO, EV6353A-DO, EV6353A-EO, EV6353A-FO, EV6355A/AP-BO, EV6355A/AP-CO, EV6551A/AP-BI, EV6551A/AP-CI, EV6551A/AP-DI, EV6552A/AP, EV6552R/RP, EV6580A/AP-B/C, EV6581A/AP, EV6750, EV8150A, EV8180A, EV8180A-D, EV8180F, EV8180Q, EV8180Q-D, EV8180U, EV8180U-D, EV8280U, EV8285U, EV8383F, EV8580A-B, EV8580A-C, EV8580A-DB, EV8580A-DC, EV8580F, EV8580Q-C, EV8580Q-DB, EV8580Q-DC, EV8580U-B, EV8580U-C, EV8580U-DB, EV8580U-DC, EV8580U-DM, EV8580U-M, EV8581A-C, EV8581A-DB, EV8581A-DC, EV8581Q-C, EV8581Q-DB, EV8581Q-DC, EV8581U-B, EV8581U-C, EV8581U-DB, EV8581U-DC, EV8582A-D, EV8780A, EV8780U, EV8781A-C, EV8781A-DC, EV8781F, EV8781Q-C, EV8781Q-DC, EV8781U-C, EV8781U-DC, EV8781U-DM, EV8781U-M, EV8782A, EV8782A-DB, EV8782Q, EV8782Q-DB, EV8782U, EV8782U-DB
<b>Shany:</b>	SNC-10XX, SNC-20XX, SNC-81XX, SNC-91XX, SNC-D1XX
<b>USAG:</b>	US-AVC4-2-600NR-I2
<b>Vivotek:</b>	IP8133W, IP8331, MD8562
<b>Samsung:</b>	SNV-7080, SNV-7080R

## Notice:

### 1. Bug fixed:

- AXIS P1346: Support all of AAC audio codec setting.
- Arecont AV2125: Fix the image would turn to green when using UDP connection
- Shany: Fix 1080P resolution name.

- Zavio D611E: Fix connection issue
2. Known issue:
- CNB: 2M pixel models do not support UDP connection.
  - Dahua: All models only support Pan & Tilt feature using RS-485 to control the external device.
  - Etrovision: xx8x/xx5x series do not support talk function, 8150A and related models do not support VGA resolution.
  - USAG: Does not support PTZ feature using RS-485.
  - Samsung: 3120x, 3430H, 5xxx and 7xxx series only support TCP connection.
3. Firmware Upgrade:
- Samsung: SND-7080, SNO-5080R, SNP-3120, SNP-3120V, SNP-3430H, SNV-3120, SNV-5080R

**Release Version v1.15.0 (2011/10/03)**

## Modules:

Device Pack v 1.15.0

## Supported Systems:

MainConsole v 3.3.0 & v 3.3.2 & v 3.3.12 & v 3.4 & 3.4.1 & 3.5.0 & 3.5.10 & v 3.5.18

## New Camera Supported:

**Arecont:** AV20185DN, AV20365DN

**Probe:** PIC-500, PIC-501, PIC-H1310T, PIC-H2010T, PID-500, PID-501, PID-H1000, PID-H2010T, PIK-H2010T, PIN-H1310T, PIN-H2010T, PIP-H1000, PIS-400, PK-H1310T, PMI-400, PMI-403, PMI-410, PMI-H2000, PTI-400, PTI-401, PTI-402, PTI-403, PTI-500, PTI-501, PTI-502, PTI-503, PTI-H1302, PTI-H2100

**Shany:** SNC-21X0, SNC-21XX, SNC-22XX, SNC-23XX, SNC-HD2XX, SNC-HD81X2, SNC-HD91X2, SNC-HD91XX, SNC-RX01N

**Vivotek:** SD83x1E, SD83x2E, SD83x3E, VS8401

**Zavio:** F3106, F7110

## Notice:

4. New feature:

- Onvif 1.02 PTZ feature is supported.

5. Bug fixed:

- LevelOne FCS-5041: login in with wrong password will cause system crash.

6. Known issue:

7. Probe series don't support IO feature/audio in.

8. Shany series will show B/W image when set camera parameter very low quality in MJPEG codec.

## Release Version v1.14.0 (2011/09/02)

## Modules:

Device Pack v 1.14.0

## Supported Systems:

MainConsole v 3.3.0 & v 3.3.2 & v 3.3.12 & v 3.4 & 3.4.1 & 3.5.0

## New Camera Supported:

<b>ACTi:</b>	KCM5211, KCM5311, KCM7211
<b>Arecont:</b>	AV1115, AV1125, AV2115, AV2125, AV3115, AV3125, AV5115, AV5125, AV10115
<b>AXIS:</b>	M3114-VE, Q6035, Q6035-E
<b>CORUM:</b>	CS-190-IO, CS-190-IP, CS-190-IW, CS-265-IO, CS-265-IP, CS-265-IW, CS-285-IP, CS-325-IO, CS-325-IP, CS-385-IO, CS-385-IP, CS-390-IO, CS-390-IP, CS-410-IP, CS-410-IW, CS-415-IP, CS-415-IW
<b>Forenix:</b>	ACDV-3VM501, AEP-Q2018H-IP, AEP-Q2018HW-IP, AEP-Q2026H-IP, AEP-Q2026HW-IP, AEP-Q2036H-IP, AEP-Q2036HW-IP, ASP-PTIR737-IP, ASP-PTIR737-LA-IP, ATCP-IRH5030C, ATCP-IRH5040C, ATCP-MH802, ATCP-MH802DN, ATCP-MH802DN/WI, ATCP-MH802WI, ATCP-VM501, B0100, B1100, C1100, C1100-W, D0100, D1100, D2100
<b>Messo:</b>	NIC910HPRO, NIC930HPRO, NIC950HPRO
<b>SONY:</b>	SNC-EP520, SNC-ER520, SNC-ER521, SNC-ER580
<b>UDP:</b>	IPE3500M, NVC4000, NVC4000-R12, NVC4000-R40
<b>Vivotek:</b>	IP8352, PZ81x1, PZ81x1W

## Notice:

### 9. New feature:

- Onvif 1.02 support is officially released on Device Pack 1.14.0 but non-support PTZ feature.
- ACTi  
TCD2500 supports PTZ feature.
- Grandstream  
GXV series supports talk and PTZ features

### 10. Bug fixed:

- PANASONIC WV-NM100 has probabilities cause system crash.
- ACTi ACM1431 Audio disabled issue.

## Release Version v1.13.0 (2011/08/02)

## Modules:

Device Pack v 1.13.0

## Supported Systems:

MainConsole v 3.3.0 & v 3.3.2 & v 3.3.12 & v 3.4 & 3.4.1 & 3.5.0

## New Camera Supported:

<b>ACTi:</b>	KCM7111
<b>AXIS:</b>	M5013, M5014, P5512, P5512-E, P5522, P5522-E
<b>Brickcom:</b>	VS-04A
<b>Everfocus:</b>	EQN2200, EQN2201
<b>Grandstream:</b>	GXV-3501, GXV-3504, GXV-3601, GXV-3601HD, GXV-3601LL, GXV-3611HD, GXV-3611LL, GXV-3615, GXV-3651, GXV-3662HD
<b>Panasonic:</b>	WV-SW352, WV-SW355
<b>Pelco:</b>	D-5118
<b>Samsung:</b>	SNP-3301, SNB-7000
<b>Vivotek:</b>	FE8171V

## Notice:

### 11. New feature:

- **AXIS**  
P1346, P5534 support AAC codec
- **Vivotek**  
VS8102 supports continuous PTZ

### 12. Bug fixed:

- **Truen**  
Adjust TCAM-570 PTZ moving distance sync with web client.
- **SAE**  
DR-E588-HD18 can't control PTZ by joystick.
- **AXIS**  
Supported Q7401 to 64 preset point.
- **Fine**  
MainConsole will hang out when single TCP-VM501 setup four connections at the same time.

## Release Version v1.12.0 (2011/07/01)

## Modules:



Device Pack v 1.12.0

## Supported Systems:

MainConsole v 3.3.0 & v 3.3.2 & v 3.3.12 & v 3.4 & 3.4.1 & 3.5.0

## New Camera Supported:

**Everfocus:** EAN3200, EHN3200, EDN3240, EZN3240

**Samsung:** SNB-1000, SND-7080, SNO-5080R, SNP-3120V, SNP-3370, SNP-3430H, SNP-5200, SNP-5200H, SNV-5010, SNV-5080R, SNZ-5200

**VIVOTEK:** FD8162, FD8361L, FD8362, FD8362E, SD8362E

## Notice:

13. Bug fixed:

- Fix Sony preset name length issue.
- Fix Panasonic WV-SP105 auto detect failure.

## Release Version v1.11.0 (2011/05/31)

### Modules:

Device Pack v 1.11.0

## Supported Systems:

MainConsole v 3.3.0 & v 3.3.2 & v 3.3.12 & v 3.4 & 3.4.1 & 3.5.0

## New Camera Supported:

<b>ACTi:</b>	KCM5111, TCM4001
<b>AXIS:</b>	P3346, P3346-V, P3346-VE
<b>CTCunion:</b>	DVS-8501E, DVS-8504E
<b>Panasonic:</b>	DG-SF334, WV-SF342, WV-SF346
<b>Samsung:</b>	SNB-5000, SND-5080/F, SNV-3120, SNV-5080
<b>Santec:</b>	SNC-3903M, SNC-5321MIR, SNC-6163ID, SNC-6223MIR, SNC-6303M, SNC-P3603M
<b>Sony:</b>	SNC-DH110/B, SNC-DH110/W, SNC-DH110T/B, SNC-DH110T/W
<b>Vidosec:</b>	ICS-13, ICS-20F, ID-20
<b>VIVOTEK:</b>	IP8362, MD7530, VS8801
<b>UDP:</b>	NVC1000

## Notice:

1. Bug fixed:
  - Fix Dallmeier preset function dump
  - ONVIF check startcode if using RTSP for H264 codec
  - Fix Vivotek IP 7133 can't use AAC codec issue

## Release Version v1.10.0 (2011/04/15)

## Modules:

Device Pack v 1.10.0

## Supported Systems:

MainConsole v 3.3.0 & v 3.3.2 & v 3.3.12 & v 3.4 & 3.4.1

## New Camera Supported:

<b>Arecont:</b>	AV1325, AV2825, AV8185DN, AV8365DN
<b>AXIS:</b>	P1347, P1347-E, P5532, P5532-E, P5534-E, Q1921, Q1921-E
<b>D-link:</b>	DCS-6511, DCS-7410
<b>Fine:</b>	EDH-02H, SP-PTIR737-LA-IP, TCP-IR590-WD30, TCP-IR590-WD50, TCP-IRH5030C, TCP-IRH5040C
<b>IQinvision:</b>	IQ732N
<b>Panasonic:</b>	WV-SC384, WV-SC385, WV-SW395
<b>Sony:</b>	SNC-DH210/B, SNC-DH210/W, SNC-DH220, SNC-DH220T
<b>vForge:</b>	VFA1
<b>VIVOTEK:</b>	FD8133V, FD8134V, IP8151P, IP8162, IP8162P, MD7560

## Notice:

1. Bug fixed:
  - ACTi CAM7301: auto detection failure issue.
  - Arecont Camera: auto detection failure issue.
  - Axis Q7401 sync preset point issue.
  - Dynacolor NH061: broken image issue (H.264/1280x720).
2. Bosch speed dome V4G series supported by Axis video server (test by model Q7404).

## Release Version v1.9.0 (2011/02/28)

## Modules:

Device Pack v 1.9.0

## Supported Systems:

MainConsole v 3.3.0 & v 3.3.2 & v 3.3.12 & v 3.4 & 3.4.1

## New Camera Supported:

**Arecont:** AV1315, AV2815

**AXIS:** 212 PTZ-V, 215 PTZ-E, 240Q Blade, 241Q Blade, 241S Blade, 243Q Blade, P1343-E, P1344-E, P1346-E, Q1755-E, Q6034-E

**Lilin:** IPS025, IPS030, IPS035, IPS125, IPS130, IPS135, IPS203, IPS212

**Panasonic:** WV-SP102, WV-SP105

**Sony:** SNC-CH260, SNC-CH280, SNC-DH210T/B, SNC-DH210T/W, SNC-DH260, SNC-DH280

## Notice:

1. Dallmeier DDZ40SM-HD: Add TCP connection, DI/DO and two-way audio.
2. Bug fixed: Panasonic WV-NS202A auto detection failure.

**Release Version v1.8.0 (2010/12/31)**

## Modules:

Device Pack v 1.8.0

## Supported Systems:

MainConsole v 3.3.0 & v 3.3.2 & v 3.3.12 & v 3.4

## New Camera Supported:

**ACTi:** TCM7811,

**Hikvision:** DS-2CD7133-E, DS-2CD7153-E

**Levelone:** FCS-0040, FCS-3081, FCS-5051, FCS-5041, WCS-0040

**Lilin:** IPD112ESX, IPD552EX, IPR414ESX, IPR418ESX, IPR454, IPR458

**Sony:** SNC-CH110/B, SNC-CH110/S, SNC-CH220

## Notice:

1. Bug fixed: Users can adjust Arecont camera's resolution by setting four video coordinate values. (Not support Arecont 8000 series cameras.)

**Release Version v1.7.0 (2010/11/12)**

## Modules:

Device Pack v 1.7.0

## Supported Systems:

MainConsole v 3.3.0 & v 3.3.2 & v 3.3.12 & v 3.4

## New Camera Supported:

<b>ACTi:</b>	ACM5811, ACM7511, TCD2100, TCM3001, TCM3011, TCM3401, TCM3411, TCM4201, TCM5001, TCM7011
<b>ARM:</b>	MP13DDNWD, MP13VPDN
<b>Camtron:</b>	IPH3611N, NVE1000A, NVE2000A, NVE4000A
<b>CryptoTelecom:</b>	S-152
<b>Dallmeier:</b>	DDZ40SM-HD
<b>Panasonic:</b>	BL-C210, BL-C230, WJ-GXE500, WV-SF332, WV-SF335, WV-SF336, WV-SP302, WV-SP305, WV-SP306
<b>Samsung:</b>	SNS-100
<b>Sony:</b>	SNC-CH120, SNC-CH160, SNC-CH210/B, SNC-CH210/S, SNC-DH120, SNC-DH120T, SNC-DH140T, SNC-DH160, SNC-DH240T
<b>Truen:</b>	TCAM-570
<b>VIVOTEK:</b>	FD8133, FD8134, IP8132, IP8151, IP8330, IP8332, PZ7132, SD81X1

## Notice:

1. Bug fixed: Panasonic WV-NP502 won't show error message when switching video codec to H.264.

## Release Version v1.6.0 (2010/10/7)

## Modules:

Device Pack v 1.6.0

## Supported Systems:

MainConsole v 3.3.0 & v 3.3.2 & v 3.3.12

## New Camera Supported:

**Arecont:** AV2805

**Camtron:** CMNC-130, CMNC-200, CTNC-5358D, HLC-81A D/P, HLC-83V, HLC-83V/W  
HLC-84V, HLC-84V/W

**Honeywell:** ACUIX, HCD554IP, HD3MDIP, HD4DIP, HD4MDIP, HNVE1

**PELCO:** IX10

**Pixord:** P600, P606, PB630, PD634, PL621, PV6901

**SAE:** ANNA 200M, E588HDE18C, E688HDE10

## Notice:

1. Bug fixed: Fine WB-8211SDU can use PTZ function.

## Release Version v1.5.0 (2010/8/31)

## Modules:

Device Pack v 1.5.0

## Supported Systems:

MainConsole v 3.3.0 & v 3.3.2 & v3.3.11

## New Camera Supported:

**Brickcom:** CB-100A, CB-100Ae, FB-100A, FB-100Ae, FD-100Ae, WCB-100Ae, WFB-100Ae

**Fine:** CDV-3VM301, CDV-3VM501, CDV-3VWD960, CDV-3VWD960H, EP-601HW, EP-908HW, EP-936HW, EP-HTQ935, EP-Q2018H-IP, EP-Q2018HW-IP, EP-Q2026H-IP, EP-Q2026HW-IP, EP-Q2036H-IP, EP-Q2036HW-IP, MD-D1612, SP-PTIR737-IP, TCMA-99, TCMP-99, TCP-IPWD690, TCP-IPWD700DN, TCP-IRV540, TCP-IRV560/50M, TCP-MH802, TCP-VM201, TCP-VM501, WB-H811, WB-H814

**Hikvision:** DS-2CD702NF-E, DS-2CD702PF-E, DS-2CD712NF-E, DS-2CD712PF-E, DS-2CD732F-E, DS-2CD792NF-E, DS-2CD792PF-E, DS-2CD802N-IR1, DS-2CD802N-IR3, DS-2CD802N-IR5, DS-2CD802P-IR1, DS-2CD802P-IR3, DS-2CD802P-IR5, DS-2CD832F, DS-2CD832F-E, DS-2DF1-401H, DS-2DF1-402H, DS-2DF1-601H, DS-2DF1-602H, DS-2DF1-603H, DS-2DF1-604H, DS-2DF1-605H, DS-2DF1-606H, DS-2DF1-607H, DS-2DF1-611H, DS-2DF1-612H, DS-2DF1-613H, DS-2DF1-614H, DS-2DF1-615H, DS-2DF1-616H, DS-2DF1-617H, DS-2DM1-602H, DS-2DM1-603H, DS-2DM1-604H, DS-2DM1-612H, DS-2DM1-613H, DS-2DM1-614H, DS-6101HFI-SATA, DS-6104HCI, DS-6104HCI-SATA

**NetworkCamera:** GE-100-CB, GP-100-CB, WGE-100-CB, WGP-100-CB

**PELCO:** ID10, ID30, IDE20, IDS0, IE10, IE30, IEE10, IEE20, IES0, IMS0, IX30, IXE20, IXS0

**Sony:** SNC-RS44N, SNC-RS44P, SNC-RS46N, SNC-RS84N, SNC-RS84P, SNC-RS86N, SNC-RS86P, SNT-EP104, SNT-EX101

**Vidosec:** IBF-211, ID-209, IDA-210, IP-206M, IS-240

## Notice:

1. Bug fixed: SANYO-HD5600P can change resolution.
2. Onvif supported: AXIS\_P3301, Bosch\_NWC-0455

## Release Version v1.4.0 (2010/8/9)



## Modules:

Device Pack v 1.4.0

## Supported Systems:

MainConsole v 3.3.0 & v 3.3.2 & v 3.3.11

## New Camera Supported:

**iCanTek:** iCanView362MP, iCanView332MP, iCanView350MP, iCanServer612

**SANTEC:** SNC-3901MDN, SNC-P3601M

## Release Version v1.3.0 (2010/7/21)

## Modules:

Device Pack v 1.3.0

## Supported Systems:

MainConsole v 3.3.0 & v 3.3.2

## New Camera Supported:

**ACTi:** TCM-1511

**Arecont:** AV10005

**AXIS:** M1103, M1113, M1054, Q6034

**Panasonic:** BB-HCM547A, BB-HCM701

**SANTEC:** SNC-6201M, SNC-5211MIR

**Sony:** SNT-EX154, SNT-EX101E, SNT-EP154, SNC-CH140, SNC-DH140, SNC-CH180, SNC-CH240, SNC-DH240, SNC-RH164, SNC-RS46P

## Notice:

1. Sony SNC-CH240, SNC-DH240 do not support resolution over 1920x1080

**Release Version v1.2.0 (2010/6/8)**

## Modules:

Device Pack v 1.2.0

## Supported Systems:

MainConsole v 3.3.0 & v 3.3.2

## New Features

1. Support Arecont I/O function

## New Camera Supported:

**ACTi:** ACM-3601, ACM-3603, ACM-3701, ACM-3703, ACM-4001  
TCD-2500, TCM-4101, TCM-5312, TCM-1231, TCM-1232  
TCM-5601, TCM-5611, TCM-3511, TCM-7411

**Arecont:** AV3135, AV1310, AV2110, AV3110, AV5110

**AXIS:** P1346, P5534, Q1910, Q1910-E, M1104, M1114  
M3203, M3203-V, M3204, M3204-V, P3304, M7001

**CNB:** IDC4000T, IVC4000T

**IQeye:** IQ040S, IQ041S, IQ042S, IQD30S, IQD31S  
IQD40S, IQD41S, IQD42S, IQ540S, IQ541S, IQ542S

**Panasonic:** BB-HCM100, BB-HCM110, BB-HCM580, BL-C140A

**Samsung:** SNB-2000, SNB-3000, SND-3080, SNV-3080

**Sanyo:** VCC-HD2500, VCC-HD2500P

**Sony:** SNT-EX104, SNC-DH180, SNC-RH124

**StarDot:** SDH500BN, SDH500B, SDH300B, SDH130BN, SDH130B  
SDH500VN, SDH500V, SDH300V, SDH130VN, SDH130V

## Notice:

1. Bug Fixed: Fixed MainConsole unexpected crash issue with Mobotix Q24M-sec camera.

## Release Version v1.1.1 (2010/5/12)

## Modules:

Device Pack v 1.1.1

## Supported Systems:

MainConsole v 3.3.0 & v 3.3.2

## New Camera Supported:

**CNB:** IBE3815NVR, IBE3815PVR, IBE5810NCR, IBE5810PCR  
IDP4000VD, IDP4000VR, IDP4030VR, IGP1000, IGP1030  
IJB2000, INS2000, IPM3063N, IPM3063P, ISMC1063N, ISMC1063P  
ISS2765NW, ISS2765PW, IVP4000VR, IVP4030VR

**LevelOne:** FCS-7111

## Release Version v1.1.0 (2010/5/4)

### Modules:

Device Pack v 1.1.0

## Supported Systems:

MainConsole v 3.3.0 & v 3.3.2

## New Camera Supported:

**ACTi:** AMU-9401, AMU-9711, TMU-9811, TMU-9911

**Bosch:** NW-455

**Brickcom:** WCB-100A, WFB-100A, FD-100A

**CISCO:** WVC210

**Dynacolor:** nNH221, nNH061, V1, V6

**Everfocus:** EAN-850A, EZN-850, EDN-800, EDN-850H, EAN900, EAN800AW, EAN800A  
EVS200A, EVS200AW, EPN2700, EPN3100, EPN3600

**LevelOne:** FCS-3031, FCS-3051, FCS-1131, FCS-1141, FCS-3071, FCS-0030, WCS-0030  
FCS-1121, FCS-3061, FCS-4020, FCS-1040 v3.0, WCS-2040 v3.0, FCS-1151

**MOBOTIX:** D24M-Basic, D24M-IT, D24M-Sec

**Panasonic:** BB-HCM705A, BB-HCM715A, BB-HCM735A

**Samsung:** SNP-3300A

**SanTec:** SNC-390DN/W, SNC-521IR/W, SNC-565IR/W, SNC-620/W, SNC-670ID/W

**Sanyo:** VCC-HD3500, VDC-HD3500, VDC-HD3500p, VCC-HD2100, VCC-HD2100P  
VCC-HD2300, VCC-HD2300P, VDC-HD3100, VDC-HD3100P  
VCC-HD3300, VDC-HD3300, VDC-HD3300P, VCC-HD4600, VCC-HD4600P  
VCC-HD5400, VCC-HD5400P, VCC-HD5600, VCC-HD5600P

**StarDot:** SD-130, SD-300, SD-500, SDEXP4, SDEXP2

**VIVOTEK:** IP8161, VS8102, FD8161, FD8361

## Notice:

1. Only compatible with NUUO MainConsole v3.3.0 above
2. Must install Main Console software before install device pack v1.1.0