



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| ACD2000Q    | A4Q-220-V3.04.08  | MPEG4 M-JPEG | 4        | 720x480        | *2    | *2     | *2  | *2             | -    | Yes                | Yes                  | -        |                     |
| Note:       | 1.Not support framerate 8 due to camera firmware issue. |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| ACD2100     | A1D-220-V3.08.08-AC                                     | MPEG4 M-JPEG | 1        | 720x480        | 1-way | 2/2    | Yes | Yes            | -    | Yes                | -                    | -        |                     |
| ACD2200     |   | MPEG4 M-JPEG | 4        | 720x480        | 1-way | 8/8    | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACD2300     |   | MPEG4 M-JPEG | 8        | 720x480        | 1-way | 16/16  | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACD2400     | AGD-R2N-V2.05.02-AC                                     | MPEG4 M-JPEG | 16       | 720x480        | 1-way | 32/32  | Yes | Yes            | -    | Yes                | -                    | -        |                     |
| ACM1011     | A1D-220-V3.10.22-AC                                     | MPEG4 M-JPEG | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        |                     |
| ACM1231     |   | MPEG4 M-JPEG | 1        | 1280x1024      | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM1232     |   | MPEG4 M-JPEG | 1        | 1280x1024      | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM1311     |   | MPEG4 M-JPEG | 1        | 720x480        | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM1431     |   | MPEG4 M-JPEG | 1        | 720x480        | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM1432     |   | MPEG4 M-JPEG | 1        | 720x480        | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM1511     |   | MPEG4 M-JPEG | 1        | 1280x1024      | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM3001     |   | MPEG4 M-JPEG | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM3011     |   | MPEG4 M-JPEG | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM3211     |   | MPEG4 M-JPEG | 1        | 720x480        | 1-way | -      | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM3311     |   | MPEG4 M-JPEG | 1        | 720x480        | 1-way | -      | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM3401     |   | MPEG4 M-JPEG | 1        | 1280x1024      | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM3411     |   | MPEG4 M-JPEG | 1        | 1280x1024      | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM3511     |   | MPEG4 M-JPEG | 1        | 1280x1024      | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM3601     | A1D-220-V3.10.22-AC                                     | MPEG4 M-JPEG | 1        | 640x480        | -     | -      | -   | Yes            | -    | Yes                | -                    | -        |                     |
| ACM3603     |   | MPEG4 M-JPEG | 1        | 640x480        | -     | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM3701     | A1D-220-V3.10.22-AC                                     | MPEG4 M-JPEG | 1        | 1280x1024      | -     | -      | -   | Yes            | -    | Yes                | -                    | -        |                     |
| ACM3703     |   | MPEG4 M-JPEG | 1        | 1280x1024      | -     | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format     | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| ACM4000     |  | MPEG4<br>M-JPEG  | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM4001     |  | MPEG4<br>M-JPEG  | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM4100     | A1D-220-V3.09.14-AC  | MPEG4<br>M-JPEG  | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        |                     |
| ACM4200     |  | MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM4201     |  | MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM5001     |  | MPEG4<br>M-JPEG  | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM5601     | A1D-220-V3.08.08-AC  | MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes                | -                    | -        |                     |
| ACM5611     |  | MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| ACM5711     | A1D-220-V3.08.08-AC  | MPEG4<br>M-JPEG  | 1        | 720x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | -                    | -        |                     |
| ACM5811     | A1D-220-V3.12.13-AC  | MPEG4<br>M-JPEG  | 1        | 720x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | -                    | -        |                     |
| ACM7411     | A1D-220-V3.09.14-AC  | MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes                | -                    | -        |                     |
| Note:       | A1D-220-V3.09.14-AC: There is problem at 160x112 resolution.                       |                  |          |                |       |        |     |                |      |                    |                      |          |                     |
| ACM7511     | A1D-220-V3.12.13-AC  | MPEG4<br>M-JPEG  | 1        | 720x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | -                    | -        |                     |
| ACM8201     | A1D-220-V3.10.22-AC  | MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | -    | Yes                | -                    | -        |                     |
| Note:       | A1D-220-V3.09.14-AC: There is problem at 160x112 resolution.                       |                  |          |                |       |        |     |                |      |                    |                      |          |                     |
| ACM8211     | A1D-220-V3.09.14-AC  | MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | -    | Yes                | -                    | -        |                     |
| ACM8511     | A1D-220-V3.11.13-AC  | MPEG4<br>M-JPEG  | 1        | 720x480        | 1-way | 1/1    | Yes | Yes            | -    | Yes                | -                    | -        |                     |
| AMU9401     | A1D-220-V3.10.22-NB  | MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 0/0    | -   | Yes            | -    | Yes                | -                    | -        |                     |
| AMU9711     | A1D-220-V3.10.22-NB  | MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 0/0    | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| B210        | Refer to E416 (V6.09.45)   | H.264<br>MJPEG   | 1        | 3648x2736      | 2-way | 1/1    | Yes | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| Note:       | 1. Does not integrate PTZ(Delivered model can't use RS-485, we didn't workaround). |                  |          |                |       |        |     |                |      |                    |                      |          |                     |
| B27         | Refer to B47(V6.08.30)   | H.264/M<br>JPEG  | 1        | 2048x1536      | 2-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| B47         | V6.08.30   | H.264 /<br>MJPEG | 1        | 2048x1536      | 2-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| B410        | Refer to E416 (V6.09.45)   | H.264<br>MJPEG   | 1        | 3648x2736      | 2-way | 1/1    | Yes | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format  | Video Ch | Max Resolution | Audio | I/O Ch | PTZ  | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|---------------|----------|----------------|-------|--------|------|----------------|------|--------------------|----------------------|----------|---------------------|
| B51         | V6.09.45   | H.264 MJPEG   | 1        | 2592x1944      | 2-way | 1/1    | -    | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| Note:       | 1. Frame rate can not achieve to setting value with resolution above 800x600 in MJPEG.(Camera performance limitation)<br>2. When motion is triggered, frame rate is not unstable with format MJPEG.(Camera performance limitation) |               |          |                |       |        |      |                |      |                    |                      |          |                     |
| B53         | V6.06.16   | H.264 MJPEG   | 1        | 2048x1536      | 2-way | 1/1    | -    | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| Note:       | 1.The camera with highest quality and resolution is unable to achieve 30 fps and audio stutter.[camera performance limitation]   |               |          |                |       |        |      |                |      |                    |                      |          |                     |
| B61         | V6.08.30   | H.264 / MJPEG | 1        | 2592x1944      | 2-way | 2/2    | Yes  | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| B67         | V6.06.16   | H.264 MJPEG   | 1        | 2048x1536      | 2-way | 2/2    | Yes  | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| Note:       | 1.The camera with highest quality and resolution is unable to achieve 30 fps and audio stutter.[camera performance limitation]   |               |          |                |       |        |      |                |      |                    |                      |          |                     |
| B81         | Refer to B61(V6.08.30)   | H.264/MJPEG   | 1        | 2592x1944      | 2-way | 2/2    | Yes  | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| B94         | V6.06.16   | H.264 MJPEG   | 1        | 1280x960       | 2-way | 1/1    | Yes  | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| Note:       | 1.The camera with highest quality and resolution is unable to achieve 30 fps and audio stutter.[camera performance limitation]   |               |          |                |       |        |      |                |      |                    |                      |          |                     |
| B95         | A1D-500-V6.05.23-AC  | H.264 MJPEG   | 1        | 1920x1080      | 2-way | 1/1    | Yes* | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| Note:       | 1. Camera cannot achieve maximum FPS with high resolution and bitrate. (Camera performance limitation)<br>2. Audio has noise. (Camera performance limitation)  |               |          |                |       |        |      |                |      |                    |                      |          |                     |
| CAM5130     |  | MPEG4         | 1        | 720x480        | 1-way | 1/1    | -    | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM5140     |  | MPEG4         | 1        | 720x480        | 1-way | 1/1    | -    | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM5150     |  | MPEG4         | 1        | 720x480        | 1-way | 1/1    | -    | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM5200     |  | MPEG4         | 1        | 720x480        | -     | 1/1    | -    | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM5201     |  | MPEG4         | 1        | 720x480        | 1-way | 1/1    | -    | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM5221     | A1D-M2N-V2.08.11-AC  | MPEG4         | 1        | 720x480        | 1-way | 1/1    | -    | Yes            | -    | Yes                | -                    | -        |                     |
| CAM5300     |  | MPEG4         | 1        | 720x480        | -     | 1/1    | -    | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM5301     |  | MPEG4         | 1        | 720x480        | -     | 1/1    | -    | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM5321     |  | MPEG4         | 1        | 720x480        | -     | 1/1    | -    | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM5500     |  | MPEG4         | 1        | 720x480        | -     | 1/1    | -    | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM6100     |  | MPEG4         | 1        | 720x480        | -     | 2/2    | Yes  | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM6200     | A1D-2.07.14-AC   | MPEG4         | 1        | 720x480        | -     | 2/2    | Yes  | Yes            | -    | Yes                | -                    | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware         | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|-------------------------|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| CAM6220     | A1D-2.07.14-AC          | MPEG4        | 1        | 720x480        | -     | 2/2    | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM6500     |                         | MPEG4        | 1        | 720x480        | 1-way | 2/2    | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM6510     | A1D-M2N-V2.08.11-AC     | MPEG4        | 1        | 720x480        | 1-way | 2/2    | Yes | Yes            | -    | Yes                | -                    | -        |                     |
| CAM6520     |                         | MPEG4        | 1        | 720x480        | 1-way | 2/2    | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM6600     |                         | MPEG4        | 1        | 720x480        | 1-way | 2/2    | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM6610     |                         | MPEG4        | 1        | 720x480        | 1-way | 2/2    | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM6620     |                         | MPEG4        | 1        | 720x480        | 1-way | 2/2    | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM6630     |                         | MPEG4        | 1        | 720x480        | 1-way | 2/2    | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM7100     |                         | MPEG4        | 1        | 720x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM7120     |                         | MPEG4        | 1        | 720x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM7200     |                         | MPEG4        | 1        | 720x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM7220     |                         | MPEG4        | 1        | 720x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM7300     |                         | MPEG4        | 1        | 720x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM7301     |                         | MPEG4        | 1        | 720x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM7320     |                         | MPEG4        | 1        | 720x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM7321     |                         | MPEG4        | 1        | 720x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| CAM7322     |                         | MPEG4        | 1        | 720x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| D11         | V6.03.17                | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| D12         | Refer to D52 (V6.03.17) | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| D21         | Refer to D11 (V6.03.17) | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| D22         | Refer to E13 (V6.03.17) | H264 MJPEG   | 1        | 2592x1944      | 1-way | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| D22FA       | Refer to B51 (V6.09.45) | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| D31         | Refer to D11 (V6.03.17) | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmware         | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|-------------------------|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| D32         | Refer to D52 (V6.03.17) | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| D41         | Refer to D11 (V6.03.17) | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| D42         | Refer to D52 (V6.03.17) | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| D51         | Refer to D11 (V6.03.17) | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| D52         | V6.03.17                | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| D54         | Refer to D11 (V6.03.17) | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| D55         | Refer to D52 (V6.03.17) | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| D61         | V6.03.17                | H264 MJPEG   | 1        | 1280x960       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| D62         | Refer to E84 (V6.03.17) | H264 MJPEG   | 1        | 1920x1080      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| D64         | Refer to D11 (V6.03.17) | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| D65         | Refer to D52 (V6.03.17) | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| D71         | Refer to D11 (V6.03.17) | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| D72         | Refer to D52 (V6.03.17) | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| D72A        | QA-A1D-500-V6.07.24-AC  | H264 MJPEG   | 1        | 2048x1536      | 2-way | 1/1    | -   | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| D81         | Refer to D11 (V6.03.17) | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| D82         | Refer to D52 (V6.03.17) | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| D82A        | QA-A1D-500-V6.07.24-AC  | H264 MJPEG   | 1        | 2048x1536      | 2-way | 1/1    | -   | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| E11         | Refer to D11 (V6.03.17) | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E12         | Refer to D52 (V6.03.17) | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E13         | V6.03.17                | H264 MJPEG   | 1        | 2592x1944      | 1-way | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E21         | Refer to D11 (V6.03.17) | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E210        | E416 (V6.09.45)         | H.264 MJPEG  | 1        | 3648x2736      | 2-way | 1/1    | Yes | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E22         | Refer to E13 (V6.03.17) | H264 MJPEG   | 1        | 2592x1944      | 1-way | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E22FA       | Refer to B51 (V6.09.45) | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| E23         | Refer to E34 (V6.03.17)   | H264 MJPEG   | 1        | 1920x1080      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E24         | Refer to E34 (V6.03.17)   | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E25         | Refer to D61 (V6.03.17)   | H264 MJPEG   | 1        | 1280x960       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E26         | Refer to E34 (V6.03.17)   | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E31         | Refer to D11 (V6.03.17)   | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E32         | Refer to E13 (V6.03.17)   | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E33         | V6.03.17  | H264 MJPEG   | 1        | 2592x1944      | 1-way | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E34         | Refer to D52 (V6.03.17)   | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E38         | V7.00.44  | H.264 MJPEG  | 1        | 1920x1080      | -     | -      | -   | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| Note:       | 1. Frame rate and bit rate can not achieve to setting value.(Camera performance limitation)   |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| E41         | Refer to D11 (V6.03.17)   | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E416        | V6.09.45  | H.264 MJPEG  | 1        | 3648x2736      | 2-way | 1/1    | Yes | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| Note:       | 1. Zoom speed doesn't work.(Camera performance limitation)<br>2. Bit rate is insufficient with format H.264.(Camera performance limitation)<br>PTZ only support zoom & focus. |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| E42         | Refer to D52 (V6.03.17)   | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E43         | Refer to E13 (V6.03.17)   | H264 MJPEG   | 1        | 2592x1944      | 1-way | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E44         | Refer to E84 (V6.03.17)   | H264 MJPEG   | 1        | 1920x1080      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E45         | Refer to E34 (V6.03.17)   | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E46         | Refer to E34 (V6.03.17)   | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E46A        | V6.08.30  | H264 MJPEG   | 1        | 2048x1536      | 2-way | 1/1    | -   | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| Note:       | 1. In high resolution or high quality with MJPEG is unable to achieve framerate setting valueand video will delay.(Camera performance limitation)                             |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| E51         | Refer to D11 (V6.03.17)   | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E52         | Refer to D11 (V6.03.17)   | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E53         | Refer to D52 (V6.03.17)   | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| E54         | Refer to E13 (V6.03.17)  | H264 MJPEG   | 1        | 2592x1944      | 1-way | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E55         | Refer to D11 (V6.03.17)  | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E56         | Refer to D52 (V6.03.17)  | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E61         | Refer to D11 (V6.03.17)  | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E618        | Refer to E816 (V6.09.45)   | H.264 MJPEG  | 1        | 3648x2736      | 2-way | 2/2    | Yes | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E62         | Refer to D52 (V6.03.17)  | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E63         | Refer to E13 (V6.03.17)  | H264 MJPEG   | 1        | 2592x1944      | 1-way | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E64         | Refer to E34 (V6.03.17)  | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E65         | Refer to E34 (V6.03.17)  | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E66         | Refer to D61 (V6.03.17)  | H264 MJPEG   | 1        | 1280x960       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E67         | Refer to E84 (V6.03.17)  | H264 MJPEG   | 1        | 1920x1080      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E71         | Refer to D11 (V6.03.17)  | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E72         | Refer to D52 (V6.03.17)  | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E73         | Refer to E13 (V6.03.17)  | H264 MJPEG   | 1        | 2592x1944      | 1-way | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E73A        | Refer to B51 (V6.09.45)  | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| E74         | Refer to E34 (V6.03.17)  | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E81         | Refer to D11 (V6.03.17)  | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E816        | V6.09.45   | H.264 MJPEG  | 1        | 3648x2736      | 2-way | 2/2    | Yes | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| Note:       | 1.Bit rate can not achieve to setting value in H.264.(Camera performance limitation)<br>2.Stream 2,3 bit rate can not achieve to setting value.(Camera performance limitation)<br>PTZ only support zoom & focus. |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| E82         | A1D-500-V6.07.24-AC  | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| Note:       | 1.Actually camera bitrate may exceed configured value. (Camera firmware issue)<br>2.Main console Flip/mirror checkbox not sync with Web interface. (NUUO server limitation)                                      |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| E83         | Refer to E13 (V6.03.17)  | H264 MJPEG   | 1        | 2592x1944      | 1-way | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E84         | V6.03.17   | H264 MJPEG   | 1        | 1920x1080      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| E85         | Refer to E34 (V6.03.17)   | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E86         | Refer to E34 (V6.03.17)   | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E86A        | Refer to E46A (V6.08.30)  | H264 MJPEG   | 1        | 2048x1536      | 2-way | 1/1    | -   | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| E87         | Refer to E34 (V6.03.17)   | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| E91         | Refer to D11 (V6.03.17)   | H264 MJPEG   | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E92         | Refer to D52 (V6.03.17)   | H264 MJPEG   | 1        | 2048x1536      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| E925        | A1D-500-V6.09.07-AC   | H264 MJPEG   | 1        | 2592x1944      | 1-way | -      | -   | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| Note:       | 1. The camera with highest quality and resolution cannot achieve maximum FPS. (Camera performance limitation)<br>2. The camera cannot achieve maximum Bitrate. (Camera performance limitation)  |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| E95         | V6.06.16  | H.264 MJPEG  | 1        | 1920x1080      | -     | -      | -   | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| E96         | A1D-500-V6.05.23-AC   | H264 MJPEG   | 1        | 2592x1944      | -     | -      | -   | Yes            | -    | Yes                | Yes                  | Yes      |                     |
| Note:       | fisheye camera  |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| Note:       | For E13 and the certificate camera:<br>1. It will auto diconnect with software.<br>For E84 and the certificate camera:<br>2. If set resolution to 640x360, it will get wrong value on get parameter.  |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| E97         | V6.07.23  | H.264 MJPEG  | 1        | 3648x2736      | -     | -      | -   | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| Note:       | 1. The actual framerate may not reach the setting value under high resolution and quality configuration. (Camera performance limitation)<br>2. The 2nd stream's actual bitrate is higher than settings.(Camera firmware issue)<br>3. The function "send mail by event" might fail to attach snapshot under high resolution (NUUO server limitation)<br>4. The motion signal would not stop when disabling motion event if the motion has been triggered. (NUUO server limitation) |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| Generic     | A1D-500-V6.05.23-AC   | H264 MJPEG   | 1        | 3648x2736      | 1-way | 1/1    | Yes | Yes            | -    | -                  | Yes*                 | Yes      |                     |
| Note:       | Test model: B52<br>Support generic dewarp   |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| I51         | Refer to I71(A1D-500-V6.06.16-AC)   | H.264 MJPEG  | 1        | 2592x1944      | 1-way | 2/2    | -   | Yes            | -    | Yes                | Yes                  | Yes      | Supported by design |
| Note:       | fisheye camera  |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| I71         | A1D-500-V6.07.24-AC   | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 2/2    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| Note:       | 1. Fisheye camera<br>2. Camera will automatically restart when it received too many upnp broadcasts in the same domain.   |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| I92         | v6.08.30  | H.264 MJPEG  | 1        | 1920x1080      | *2    | 2/2    | Yes | Yes            | -    | *2                 | Yes*                 | Yes      |                     |
| I94         | V6.06.16  | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 4/2    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      |                     |





- : not available on camera  
\*1: not available on software  
\*2: not test on software  
For multi stream support:  
Yes: multi stream fix to 500kbps/100kbps  
Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks |
|-------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------|
| Note:       | 1.The camera with highest quality and resolution is unable to achieve 30 fps and audio stutter.[camera performance limitation] |              |          |                |       |        |     |                |      |                    |                      |          |         |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks                |
|-------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|------------------------|
| I96         | V6.08.30   | H.264<br>MJPEG           | 1        | 1920x1080      | 2-way | 4/2    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      |                        |
| Note:       | 1. In high resolution or high quality with MJPEG is unable to achieve framerate setting value and audio will stutter.(Camera performance limitation)<br>2. I/O is not synchronized with camera web. (Camera Firmware issue)  |                          |          |                |       |        |     |                |      |                    |                      |          |                        |
| KCM3211     | A1D-311-<br>V5.04.07-AC  | H.264<br>MPEG4<br>M-JPEG | 1        | 2032x1920      | 1-way | 2/2    | Yes | Yes            | -    | Yes                | Yes                  | -        |                        |
| Note:       | KCM3211's PTZ only support Zoom and Focus.   |                          |          |                |       |        |     |                |      |                    |                      |          |                        |
| KCM3311     | A1D-311-<br>V5.05.07-AC  | H.264<br>MPEG4<br>M-JPEG | 1        | 2032x1920      | -     | -      | Yes | Yes            | -    | Yes                | Yes                  | -        |                        |
| KCM3911     | A1D-311-<br>V5.10.02   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 2/2    | -   | Yes            | -    | Yes                | Yes                  | -        |                        |
| Note:       | fisheye camera   |                          |          |                |       |        |     |                |      |                    |                      |          |                        |
| KCM5111     | A1D-311-<br>V5.04.07-AC  | H.264<br>MPEG4<br>M-JPEG | 1        | 2032x1920      | 1-way | 2/2    | -   | Yes            | -    | Yes                | Yes                  | -        |                        |
| Note:       | On-edge motion: H.264 and MPEG4.   |                          |          |                |       |        |     |                |      |                    |                      |          |                        |
| KCM5211E    | Refer to<br>KCM5211  | H.264<br>MPEG4<br>M-JPEG | 1        | 2032x1920      | 1-way | 2/2    | Yes | Yes            | -    | Yes                | Yes                  | -        | Supported<br>by design |
| Note:       | On-edge motion: H.264 and MPEG4.   |                          |          |                |       |        |     |                |      |                    |                      |          |                        |
| KCM5311     | A1D-311-<br>V5.04.07-AC  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 2/2    | Yes | Yes            | -    | Yes                | Yes                  | -        |                        |
| Note:       | On-edge motion: H.264 and MPEG4.   |                          |          |                |       |        |     |                |      |                    |                      |          |                        |
| KCM5311E    | Refer to<br>KCM5311E   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 2/2    | Yes | Yes            | -    | Yes                | Yes                  | -        | Supported<br>by design |
| Note:       | On-edge motion: H.264 and MPEG4.   |                          |          |                |       |        |     |                |      |                    |                      |          |                        |
| KCM5511     | V5.12.12   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      |                        |
| Note:       | 1. When the FPS setting for 2nd stream is 20 in dual mode, it will get false value (30).(Camera firmware issue)<br>2. In single mode, the resolution N1920x1080 in video format H264 actually display N1920x1072.(Camera firmware issue)<br>3 .In dual mode, when stream 1 video format setting changed, some of the stream 2 settings will be changed as well, it makes CGI return wrong stream2 resolution value.(Camera limitation issue) |                          |          |                |       |        |     |                |      |                    |                      |          |                        |
| KCM5611     | A1D-311-<br>V5.12.12-AC  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes                | Yes*                 | Yes      |                        |
| Note:       | 1.Max resolution with stream1 will be affected by stream2 and vice versa (Camera Firmware issue).<br>2.Motion detection does not support with MJPEG format (Camera Firmware issue).<br>3.Response is slow to RS485 (Camera Firmware issue).  |                          |          |                |       |        |     |                |      |                    |                      |          |                        |
| KCM7111     | A1D-311-<br>V5.04.07-AC  | H.264<br>MPEG4<br>M-JPEG | 1        | 2032x1920      | 1-way | 2/2    | -   | Yes            | -    | Yes                | Yes                  | -        |                        |
| Note:       | On-edge motion: H.264 and MPEG4.   |                          |          |                |       |        |     |                |      |                    |                      |          |                        |
| KCM7211     | A1D-311-<br>V5.04.07-AC  | H.264<br>MPEG4<br>M-JPEG | 1        | 2032x1920      | 1-way | 2/2    | Yes | Yes            | -    | Yes                | Yes                  | -        |                        |
| Note:       | On-edge motion: H.264 and MPEG4.   |                          |          |                |       |        |     |                |      |                    |                      |          |                        |
| KCM7311     | A1D-311-<br>V5.05.07-AC  | H.264<br>MPEG4<br>M-JPEG | 1        | 2032x1920      | 1-way | 2/2    | Yes | Yes            | -    | Yes                | Yes                  | -        |                        |
| KCM7911     | A1D-311-<br>V5.10.02   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 2/2    | -   | Yes            | -    | Yes                | Yes                  | -        |                        |
| Note:       | 1. Dual-Stream Resolution 1280x720<br>2. fisheye camera  |                          |          |                |       |        |     |                |      |                    |                      |          |                        |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware             | Video Format              | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|-----------------------------|---------------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| KCM8111     | V5.10.02                    | H.264<br>MPEG4<br>M-JPEG  | 1        | 1920x1080      | 1-way | 2/2    | Yes | Yes            | -    | Yes                | Yes                  | -        |                     |
| KCM8211     | Refer to KCM8111 (V5.10.02) | H.264<br>MPEG4<br>M-JPEG  | 1        | 1920x1080      | 1-way | 2/2    | Yes | Yes            | -    | Yes                | Yes                  | -        |                     |
| Q110        | Refer to B51 (V6.09.45)     | H.264<br>MJPEG            | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| Q112        | Refer to B51 (V6.09.45)     | H.264<br>MJPEG            | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| Q115        | Refer to B51 (V6.09.45)     | H.264<br>MJPEG            | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| Q19         | Refer to B51 (V6.09.45)     | H.264<br>MJPEG            | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| SED2100     |                             | MPEG4                     | 1        | 720x480        | 1-way | 2/2    | -   | Yes            | -    | Yes                | -                    | -        | Supported by design |
| SED2120     | A1D-M2N-V2.08.11-AC         | MPEG4                     | 1        | 720x480        | -     | 2/2    | Yes | Yes            | -    | Yes                | -                    | -        |                     |
| SED2140     |                             | MPEG4                     | 1        | 720x480        | 1-way | 2/2    | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| SED2310Q    |                             | MPEG4                     | 1        | 720x480        | 1-way | 2/2    | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| SED2320Q    |                             | MPEG4                     | 1        | 720x480        | 1-way | 2/2    | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| SED2400     |                             | MPEG4                     | 2        | 720x480        | 1-way | 2/2    | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| SED2420     | A1D-220-V3.08.08-AC         | MPEG4                     | 2        | 720x480        | 1-way | -      | -   | Yes            | -    | Yes                | -                    | -        |                     |
| SED2600     |                             | MPEG4                     | 8        | 720x480        | 1-way | 16/16  | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| SED2610     |                             | MPEG4                     | 8        | 720x480        | 1-way | 16/16  | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| SED26X0     |                             | MPEG4                     | 8        | 720x480        | 1-way | 16/16  | Yes | Yes            | -    | Yes                | -                    | -        | Supported by design |
| TCD2100     | A1D-310-V4.06.09-AC         | H.264<br>MPEG4<br>M-JPEG  | 1        | 720x480        | -     | 1/1    | Yes | Yes            | -    | Yes                | Yes                  | -        |                     |
| TCD2500     | A1D-310-V4.06.08-AC         | H.264<br>MPEG4<br>M-JPEG  | 1        | 720x480        | 1-way | 2/1    | Yes | Yes            | -    | Yes                | Yes                  | -        |                     |
| TCM1111     | A1D-310-V4.12.09-AC         | MJPEG,<br>MPEG4,<br>H.264 | 1        | 1280x1024      | No    | -      | -   | Yes            | -    | Yes                | Yes                  | -        |                     |
| TCM1231     | A1D-310-V4.06.09-AC         | H.264<br>MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes                  | -        |                     |
| TCM1232     |                             | H.264<br>MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes                  | -        | Supported by design |
| TCM1511     | A1D-310-V4.06.09-AC         | H.264<br>MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes                  | -        |                     |
| TCM3001     |                             | H.264<br>MPEG4<br>M-JPEG  | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes                  | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format              | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|---------------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| TCM3011     | A1D-310-V4.07.10-AC  | H.264<br>MPEG4<br>M-JPEG  | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes                  | -        |                     |
| TCM3111     | A1D-310-V4.12.09-AC  | MJPEG,<br>MPEG4,<br>H.264 | 1        | 1280x1024      | No    | -      | -   | Yes            | -    | Yes                | Yes                  | -        |                     |
| TCM3401     |  | H.264<br>MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes                  | -        | Supported by design |
| TCM3411     | A1D-310-V4.06.09-AC  | H.264<br>MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes                  | -        |                     |
| TCM3511     | A1D-310-V4.06.00-AC  | H.264<br>MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes                  | -        |                     |
| TCM4101     |  | H.264<br>MPEG4<br>M-JPEG  | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                | Yes                  | -        | Supported by design |
| TCM4201     | A1D-310-V4.07.15-AC  | H.264<br>MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes                  | -        |                     |
| TCM4301     | A1D-310-V4.05.13-AC  | H.264<br>MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | -      | -   | Yes            | -    | Yes                | Yes                  | -        | Supported by design |
| TCM4511     | A1D-310-V4.12.09-AC  | MJPEG,<br>MPEG4,<br>H.264 | 1        | 1280x1024      | No    | -      | -   | Yes            | -    | Yes                | Yes                  | -        |                     |
| TCM5001     | A1D-310-V4.07.15-AC  | H.264<br>MPEG4<br>M-JPEG  | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes                  | -        |                     |
| TCM5111     | A1D-310-V4.12.09-AC  | MJPEG,<br>MPEG4,<br>H.264 | 1        | 1280x1024      | No    | -      | -   | Yes            | -    | Yes                | Yes                  | -        |                     |
| TCM5311     | A1D-310-V4.05.13-AC  | H.264<br>MPEG4<br>M-JPEG  | 1        | 1280x960       | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes                  | -        |                     |
| TCM5312     |  | H.264<br>MPEG4<br>M-JPEG  | 1        | 1280x960       | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes                  | -        | Supported by design |
| TCM5601     | A1D-310-V4.06.09-AC  | H.264<br>MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | -              | -    | Yes                | Yes                  | -        | Supported by design |
| TCM5611     | A1D-310-V4.06.09-AC  | H.264<br>MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | -              | -    | Yes                | Yes                  | -        |                     |
| TCM6630     | A1D-310-V4.12.09-AC  | MJPEG,<br>MPEG4,<br>H.264 | 1        | 720x480        | 1-Way | 2/1    | Yes | Yes            | -    | Yes                | Yes                  | -        |                     |
| Note:       | DI/DO can't work, FW issue   |                           |          |                |       |        |     |                |      |                    |                      |          |                     |
| TCM7011     | A1D-310-V4.06.09-AC  | H.264<br>MPEG4<br>M-JPEG  | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes                  | -        |                     |
| TCM7411     |  | H.264<br>MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | -              | -    | Yes                | Yes                  | -        | Supported by design |
| TCM7811     | A1D-310-V4.07.15-AC  | H.264<br>MPEG4<br>M-JPEG  | 1        | 1280x960       | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes                  | -        |                     |
| TMU9811     | A1D-310-V4.07.10-NB  | H.264<br>MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | -              | -    | Yes                | -                    | -        |                     |
| TMU9911     | A1D-310-V4.07.10-NB  | H.264<br>MPEG4<br>M-JPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | -              | -    | Yes                | -                    | -        | Supported by design |
| Note:       | ACD / ACM series cameras do not support FW 3.11.11.  |                           |          |                |       |        |     |                |      |                    |                      |          |                     |
| Note:       | Only <b>two</b> I/O are shown on the interface as adding <b>one</b> channel on video server. |                           |          |                |       |        |     |                |      |                    |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks |
|-------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------|
| V21         | H1.03.01   | H264 MJPEG   | 1        | 960x576        | 2-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      |         |
| V23         | H1.03.01   | H264 MJPEG   | 4        | 960x576        | 2-way | 4/4    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      |         |
| V24         | H1.03.01   | H264 MJPEG   | 4        | 960x576        | 2-way | 4/4    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      |         |
| Note:       | 1.Camera is unable to achieve 30fps. (Camera Firmware issue) |              |          |                |       |        |     |                |      |                    |                      |          |         |
| V32         | H2.02.31   | H264 MJPEG   | 16       | 960x576        | 2-way | 16/16  | Yes | Yes            | -    | Yes                | Yes*                 | Yes      |         |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format    | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|-----------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| ADKIL134RT  |   | H.264<br>M-JPEG | 1        | 2592x1944      | 2-way | 2/2    | Yes | Yes            | -    | Yes*                 | Yes      | Supported by design |
| Note:       | 1. The ranges of bitrate and framerate may be different from camera web. (Camera Firmware issue)<br>2. PTZ controls are not supported via ONVIF. (Camera Firmware issue)<br>3. Motion detection is not supported on MJPEG. (Camera performance limitation)<br>4. Bitrate of actual streaming may be different from the setting. (Camera Firmware issue)<br>5. Frame rate of actual streaming may be different from the setting. (Camera Firmware issue) |                 |          |                |       |        |     |                |      |                      |          |                     |
| ADKID134RT  |   | H.264<br>MJPEG  | 1        | 2592x1944      | 2-way | 2/2    | Yes | Yes            | -    | Yes*                 | Yes      | Supported by design |
| Note:       | 1. The ranges of bitrate and framerate may be different from camera web. (Camera Firmware issue)<br>2. PTZ controls are not supported via ONVIF. (Camera Firmware issue)<br>3. Motion detection is not supported on MJPEG. (Camera performance limitation)<br>4. Bitrate of actual streaming may be different from the setting. (Camera Firmware issue)<br>5. Frame rate of actual streaming may be different from the setting. (Camera Firmware issue) |                 |          |                |       |        |     |                |      |                      |          |                     |
| ADKID207VRT |   | H.264<br>MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | -    | Yes*                 | Yes      | Supported by design |
| Note:       | 1. The ranges of bitrate and framerate may be different from camera web. (Camera Firmware issue)<br>2. PTZ controls are not supported via ONVIF. (Camera Firmware issue)<br>3. Motion detection is not supported on MJPEG. (Camera performance limitation)<br>4. Bitrate of actual streaming may be different from the setting. (Camera Firmware issue)<br>5. Frame rate of actual streaming may be different from the setting. (Camera Firmware issue) |                 |          |                |       |        |     |                |      |                      |          |                     |
| ADKID204VRT |   | H.264<br>MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | -    | Yes*                 | Yes      | Supported by design |
| Note:       | 1. The ranges of bitrate and framerate may be different from camera web. (Camera Firmware issue)<br>2. PTZ controls are not supported via ONVIF. (Camera Firmware issue)<br>3. Motion detection is not supported on MJPEG. (Camera performance limitation)<br>4. Bitrate of actual streaming may be different from the setting. (Camera Firmware issue)<br>5. Frame rate of actual streaming may be different from the setting. (Camera Firmware issue) |                 |          |                |       |        |     |                |      |                      |          |                     |
| ADKID207RT  |   | H.264<br>MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | -    | Yes*                 | Yes      | Supported by design |
| Note:       | 1. The ranges of bitrate and framerate may be different from camera web. (Camera Firmware issue)<br>2. PTZ controls are not supported via ONVIF. (Camera Firmware issue)<br>3. Motion detection is not supported on MJPEG. (Camera performance limitation)<br>4. Bitrate of actual streaming may be different from the setting. (Camera Firmware issue)<br>5. Frame rate of actual streaming may be different from the setting. (Camera Firmware issue) |                 |          |                |       |        |     |                |      |                      |          |                     |
| ADKIL207RT  |   | H.264<br>MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | -    | Yes*                 | Yes      | Supported by design |
| Note:       | 1. The ranges of bitrate and framerate may be different from camera web. (Camera Firmware issue)<br>2. PTZ controls are not supported via ONVIF. (Camera Firmware issue)<br>3. Motion detection is not supported on MJPEG. (Camera performance limitation)<br>4. Bitrate of actual streaming may be different from the setting. (Camera Firmware issue)<br>5. Frame rate of actual streaming may be different from the setting. (Camera Firmware issue) |                 |          |                |       |        |     |                |      |                      |          |                     |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmware | Video Format            | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|-------------|-----------------|-------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| ADC-V520    | 0100h           | H.264<br>MPEG4<br>MJPEG | 1        | 1280x800       | *1    | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| ADC-V620PT  | 0102b           | H.264<br>MPEG4<br>MJPEG | 1        | 1280x800       | *1    | -      | Yes | Yes            | Yes  | Yes                  |         |
| ADC-VS420   | 0100d           | H.264<br>MPEG4<br>MJPEG | 4        | 720x576        | *1    | 4      | *2  | Yes            | Yes  | Yes                  |         |





**American Dynamics**  
From Tyco Security Products

- : not available on camera  
\*1: not available on software  
\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name  | Tested Firmware | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|--------------|-----------------|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| ADCi600-D131 | AD00-00-15-11   | MJPEG H.264  | 1        | 1280x720       | 1-way | 2/1    | -   | Yes            | *1   | Yes                  |         |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| AH2816T     | V6.M.2.12779  | H.264<br>MPEG4<br>M-JPEG | 1        | 1536x1536      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |
| Note        | Fisheye camera  |                          |          |                |       |        |     |                |      |                      |                     |
| AM2030D     | refer to AM2590D  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| AM2110D     | refer to AM2120D  | H.264<br>M-JPEG          | 1        | 1600x1200      | 1-way | 0/0    | -   | Yes            | Yes  | Yes                  | Supported by design |
| AM2120D     | 6.B.2.9031  | H.264<br>M-JPEG          | 1        | 1600x1200      | 1-way | 0/0    | -   | Yes            | Yes  | Yes                  |                     |
| AM2221D     | refer to AM2231D  | H.264<br>MPEG4<br>M-JPEG | 1        | 1600x1200      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| AM2231D     | 6.C.2.8943  | H.264<br>MPEG4<br>M-JPEG | 1        | 1600x1200      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |
| Note        | AM2221D, AM2231D preset name can't contain blanks.                                      |                          |          |                |       |        |     |                |      |                      |                     |
| AM2530D     | refer to AM2590D  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| AM2570D     | refer to AM2590D  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| AM2590D     | 6.D.2.9659  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| Note        | Initail output status will not synchronize to real output voltage by HW issue.          |                          |          |                |       |        |     |                |      |                      |                     |
| AM2630D     | refer to AM2590D  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| AM2730D     | refer to AM2590D  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| Note        | All models always can use http port 80 to connect after changing http port by FW issue. |                          |          |                |       |        |     |                |      |                      |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------|----------|----------------|-------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| AV1115      | 65225   | H.264 M-JPEG | 1        | 1280x1024      | -     | *2     | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:       | AV1115 include D4F-AV1115-3312 and D4S-AV1115-3312<br>1. DI can't trigger.<br>2. DO no response via CGI command.  |              |          |                |       |        |     |                |                    |                      |          |                     |
| AV1125      | refer to AV1115 (65225)   | H.264 M-JPEG | 1        | 1280x1024      | -     | *2     | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV1145      | refer to AV1115 (65225)   | H.264 M-JPEG | 1        | 1280x1024      | -     | *2     | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV12176     | 65192   | H.264 MJPEG  | 4        | 2048x1536      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:       | 1. Stream2 cannot achieve maximum bitrate. (Camera Firmware issue)<br>2. Bitrate list is not synchronized with camera web. (Camera Firmware issue)<br>3. Snapshot's resolution is not as same as live view. (Camera Firmware issue)<br>4. Camera cannot achieve maximum fps with MJPEG. (Camera performance limitaiton) |              |          |                |       |        |     |                |                    |                      |          |                     |
| AV1255      | refer to AV1115 (65225)   | H.264 M-JPEG | 1        | 1280x1024      | -     | *2     | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV1300      | 64328   | M-JPEG       | 1        | 1280x1024      | -     | -      | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV1305      | refer to AV1115 (65225)   | H.264 M-JPEG | 1        | 1280x1024      | -     | *2     | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV1310      |   | M-JPEG       | 1        | 1280x1024      | -     | -      | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV1315      | 65191   | M-JPEG H.264 | 1        | 1280x1024      | -     | -      | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV1325      |   | H.264 M-JPEG | 1        | 1280x1024      | -     | -      | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV1355      | 65130   | H.264 M-JPEG | 1        | 1280x1024      | -     | -      | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV1455      | refer to AV1115 (65225)   | H.264 M-JPEG | 1        | 1280x1024      | -     | *2     | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV2000      | 64328   | M-JPEG       | 1        | 1600x1184      | -     | -      | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV2100      | 64328   | M-JPEG       | 1        | 1600x1184      | -     | -      | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV2105      | 64331   | H.264 M-JPEG | 1        | 1600x1184      | -     | -      | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV2110      |   | M-JPEG       | 1        | 1600x1184      | -     | -      | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV2115      | 65225   | H.264 M-JPEG | 1        | 1920x1080      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:       | AV2115 include D4F-AV2115-3312 and D4S-AV2115-3312  |              |          |                |       |        |     |                |                    |                      |          |                     |
| AV2116      | refer to AV2115 (65218)   | H.264 M-JPEG | 1        | 1920x1080      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch  | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------|----------|----------------|-------|---------|-----|----------------|--------------------|----------------------|----------|---------------------|
| AV2125      | 65201   | H.264 M-JPEG | 1        | 1920x1056      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV2146      | refer to AV2115 (65225)   | H.264 M-JPEG | 1        | 1920x1080      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV2155      | 64803   | H.264 M-JPEG | 1        | 1600x1184      | -     | -       | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV2225      | refer to AV2115 (65225)   | H.264 M-JPEG | 1        | 1920x1080      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV2226      | refer to AV2115 (65225)   | H.264 M-JPEG | 1        | 1920x1080      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV2245      | refer to AV2115 (65225)   | H.264 M-JPEG | 1        | 1920x1080      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV2246      | refer to AV2115 (65225)   | H.264 M-JPEG | 1        | 1920x1080      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV2255AM    | 65218   | H.264 M-JPEG | 1        | 1920x1080      | *1    | 1(*1)/1 | Yes | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV2256      | refer to AV2255 (65218)   | H.264 M-JPEG | 1        | 1920x1080      | *1    | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV2455DN-F  | 65220   | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:       | 1. AV2455DN would reboot after connecting DO port.<br>2. Audio function possible doesn't work after connect/disconnect, and need to reboot camera to recover.   |              |          |                |       |         |     |                |                    |                      |          |                     |
| AV2456      | refer to AV2455 (65220)   | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV2805      | refer to AV2115 (65225)   | H.264 M-JPEG | 1        | 1920x1080      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV2815      | 65191   | H.264 M-JPEG | 1        | 1920x1080      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV2825      |   | H.264 M-JPEG | 1        | 1920x1080      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV3100      | 64328   | M-JPEG       | 1        | 2048x1536      | -     | -       | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV3100M     | 64327   | M-JPEG       | 1        | 2048x1536      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:       | 1. DI/DO is not active so that we can't integrate it. (Camera Firmware issue)<br>2. Camera is unable to achieve ordinary FPS due to insufficient performance. (Camera performance limitation)<br>3. The connections at dual stream mode are unstable. (Camera performance limitation)<br>4. Can not search the camera by camera search function. (Camera Firmware issue)<br>5. Auto detect function fail. (Camera Firmware issue) |              |          |                |       |         |     |                |                    |                      |          |                     |
| AV3105      | refer to AV3115 (65225)   | H.264 M-JPEG | 1        | 2048x1536      | -     | 1/*2    | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV3110      |   | M-JPEG       | 1        | 1920X1216      | -     | -       | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------|----------|----------------|-------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| AV3115      | 65225   | H.264 M-JPEG | 1        | 2048x1536      | -     | 1/*2   | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:       | AV3115 include D4F-AV3115-3312 and D4S-AV3115-3312<br>1.DO no response via CGI command. |              |          |                |       |        |     |                |                    |                      |          |                     |
| AV3116      | 65219   | H.264 M-JPEG | 1        | 2048x1536      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV3116DN    | 65219   | H.264 M-JPEG | 1        | 2048x1536      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV3125      | 65218   | H.264 M-JPEG | 1        | 2048x1536      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV3130      | 61906   | M-JPEG       | 1        | 2048x1536      | -     | -      | -   | Need to retest | Yes                | Yes*                 | Yes      | Supported by design |
| AV3135      | 65135   | H.264 M-JPEG | 1        | 2048x1536      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV3145      | 65219   | H.264 M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV3146      | 65219   | H.264 M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note        | 1. The streaming has low FPS under high quality.  |              |          |                |       |        |     |                |                    |                      |          |                     |
| AV3155      | 65113   | H.264 M-JPEG | 1        | 2048x1536      | -     | -      | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV3225      | refer to AV3115 (65225)   | H.264 M-JPEG | 1        | 2048x1536      | -     | 1/*2   | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV3226      | refer to AV3115 (65225)   | H.264 M-JPEG | 1        | 2048x1536      | -     | 1/*2   | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV3245      | refer to AV3115 (65225)   | H.264 M-JPEG | 1        | 2048x1536      | -     | 1/*2   | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV3246      | refer to AV3115 (65225)   | H.264 M-JPEG | 1        | 2048x1536      | -     | 1/*2   | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV3255      | 65218   | H.264 M-JPEG | 1        | 2048x1536      | -     | -      | -   | Yes            | Yes                | Yes*                 | Yes      | Tested by customer  |
| AV3256      | 65219   | H.264 M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note        | 1. The streaming has low FPS under high quality.  |              |          |                |       |        |     |                |                    |                      |          |                     |
| AV3455      | Refer to AV3105(65225)  | H.264 M-JPEG | 1        | 2048x1536      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV3456DN-F  | 65220   | H.264 M-JPEG | 1        | 2048x1536      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV5100      | 61906   | M-JPEG       | 1        | 2560x1600      | -     | -      | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV5105      | 64331   | H.264 M-JPEG | 1        | 2560x1600      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch  | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------|----------|----------------|-------|---------|-----|----------------|--------------------|----------------------|----------|---------------------|
| AV5110      |   | M-JPEG       | 1        | 2560x1600      | -     | -       | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV5115      | 65225   | H.264 M-JPEG | 1        | 2592x1944      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:       | AV5115 include D4F-AV5115-3312 and D4S-AV5115-3312  |              |          |                |       |         |     |                |                    |                      |          |                     |
| AV5125      | 65201   | H.264 M-JPEG | 1        | 2592x1944      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV5155      | 65152   | H.264 M-JPEG | 1        | 2592x1944      | -     | -       | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV5245      | 65221   | H.264 M-JPEG | 1        | 2592x1944      | -     | 1/1     | Yes | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:       | Fps would not meet setting due to camera performance.   |              |          |                |       |         |     |                |                    |                      |          |                     |
| AV5245DN    | 65229   | H.264 M-JPEG | 1        | 2560x1920      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:       | Fisheye camera  |              |          |                |       |         |     |                |                    |                      |          |                     |
| AV5255AM    | 65218   | H.264 M-JPEG | 1        | 2592x1944      | *1    | 1(*1)/1 | Yes | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV5455DN-F  | 65220   | H.264 M-JPEG | 1        | 2592x1944      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV8180      | 65010   | M-JPEG       | 4        | 1600x1184      | -     | -       | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV8185      | 65183   | H.264 M-JPEG | 4        | 1600x1200      | -     | -       | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV8185DN    | 65183   | H.264 M-JPEG | 4        | 1600x1200      | -     | -       | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV8360      | 65010   | M-JPEG       | 4        | 1600x1184      | -     | -       | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV8365      | 65183   | H.264 M-JPEG | 4        | 1600x1200      | -     | -       | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV8365DN    | 65183   | H.264 M-JPEG | 4        | 1600x1200      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:       | AV8185DN and AV8365DN<br>1. Four channels must use the same protocol and format.<br>2. If main stream is Mjpeg, the vision will flash when using dual stream. |              |          |                |       |         |     |                |                    |                      |          |                     |
| AV10005     | 65147   | H.264 M-JPEG | 1        | 3648x2752      | -     | -       | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV10115     | 65225   | H.264 M-JPEG | 1        | 3648x2752      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV10225     | Refer to AV10115(65225)   | H.264 M-JPEG | 1        | 3648x2752      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV10255     | Refer to AV10115(65225)   | H.264 M-JPEG | 1        | 3648x2752      | -     | 1/1     | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name   | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|---------------|---|--------------|----------|----------------|-------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| AV10255PM TIR | 65228   | H.264 M-JPEG | 1        | 3648x2752      | -     | 1/1    | Yes | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:         | 1. Camera is unable to achieve maximum FPS. (camera performance limitation)<br>2. PTZ only support zoom and focus.  |              |          |                |       |        |     |                |                    |                      |          |                     |
| AV10256PM TIR | refer to AV10255P MTIR(65228)   | H.264 M-JPEG | 1        | 3648x2752      | -     | 1/1    | Yes | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV12186       | 65184   | H264 MJPEG   | 4        | 2048x1536      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:         | DI can't work.  |              |          |                |       |        |     |                |                    |                      |          |                     |
| AV12186DN     | refer to AV12186(65184)   | H264 MJPEG   | 4        | 2048x1536      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| AV12366DN     | 65188   | H.264 M-JPEG | 4        | 2048x1536      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:         | Camera is unable to achieve maximum FPS. (camera performance limitation)  |              |          |                |       |        |     |                |                    |                      |          |                     |
| AV20185       | 65183   | H.264 M-JPEG | 4        | 2560x1920      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:         | AV20185 include AV20185DN, AV20185CO  |              |          |                |       |        |     |                |                    |                      |          |                     |
| AV20365       | 65183   | H.264 M-JPEG | 4        | 2560x1920      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| Note:         | 1. AV20365 include AV20365DN, AV20365CO<br>2. On-edge motion: turn off the "enable extended on motion detection" function on camera web.  |              |          |                |       |        |     |                |                    |                      |          |                     |
| AV20175DN     | 65188   | H.264 M-JPEG | 4        | 2560x1920      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| AV40185       | 65186   | H.264 M-JPEG | 4        | 3648x2752      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| Generic       |   | H.264 M-JPEG | 1 or 4   | By camera      | 1-way | 1/1    | Yes | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:         | Support generic dewarp<br>Generic test model: AV5245 and AV12186<br>1. Fps would not meet setting due to camera performance.<br>2. Audio function possible doesn't work after connect/disconnect, and need to reboot camera to recover. |              |          |                |       |        |     |                |                    |                      |          |                     |
| Note:         | For multiple-channel models, such as AV8180 and AV20185DN, there might be some issues if configuring different protocols on each channel. (i.e. the resolution we receive is half of the original)                                      |              |          |                |       |        |     |                |                    |                      |          |                     |
| Note:         | All arecont cameras.<br>1. Fps would not meet setting due to camera performance.  |              |          |                |       |        |     |                |                    |                      |          |                     |
| Note          | One of the cameras in the system must support I/O functions in order to enable the snapshot feature. This is a known issue and we are looking to fix it with the next product version update.   |              |          |                |       |        |     |                |                    |                      |          |                     |





- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format            | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|-------------|---|-------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| FB2027-1    | Refer to FX2000 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FB2027-2    | Refer to FX2000 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FB2027-3    | Refer to FX2000 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FB2028      | Refer to FX2000 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FB2028-T1   | Refer to FX2000 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FB2028-T2   | Refer to FX2000 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FB2028-TM   | Refer to FX2000 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| Note        | 1. MJPEG could not reach up to higher FPS<br>2. UPNP search failure when change web port from 80 to another |                         |          |                |       |        |     |                |      |                      |         |
| FB3027      | 2.5.1057.60   | H.264<br>MPEG4<br>MJPEG | 1        | 2048x1536      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FB3028-RT1  | Refer to FB3027 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 2048x1536      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FB3028-RT2  | Refer to FB3027 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 2048x1536      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FB3028-RTM  | Refer to FB3027 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 2048x1536      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FD2020      | Refer to FX2000 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FD3020      | Refer to FB3027 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 2048x1536      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FD3020-M    | Refer to FB3027 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 2048x1536      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FV2006      | Refer to FX2000 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FV2028      | Refer to FX2000 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FV3028      | Refer to FX2000 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 2048x1536      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FV3028-RT   | Refer to FB3027 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 2048x1536      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| FV3028-RTM  | Refer to FB3027 (FW 2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 2048x1536      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name        | Tested Firmware   | Video Format            | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|--------------------|---|-------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| FX2000             | 2.5.1057.60   | H.264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| Note               | 1. MJPEG could not reach up to higher FPS<br>2. UPNP search failure when change web port from 80 to another |                         |          |                |       |        |     |                |      |                      |         |
| FX3000-R           | Refer to<br>FB3027 (FW<br>2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 2048x1536      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| SF2121H-<br>BHR-30 | Refer to<br>FX2000 (FW<br>2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| SF2121H-<br>BHR-50 | Refer to<br>FX2000 (FW<br>2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |
| SF2121H-R          | Refer to<br>FX2000 (FW<br>2.5.1057.60)  | H.264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  |         |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware                               | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| 205         |   | M-JPEG       | 1        | 640x480        | -     | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| 206         |   | M-JPEG       | 1        | 640x480        | -     | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 206M        |   | M-JPEG       | 1        | 1280x1024      | -     | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 206W        |   | M-JPEG       | 1        | 640x480        | -     | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 207         | 4.40  | MPEG4 M-JPEG | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| 207MW       |   | MPEG4 M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 207W        |   | MPEG4 M-JPEG | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:       | Not support audio in M-JPEG                   |              |          |                |       |        |     |                |      |                      |          |                     |
| 209FD       |   | MPEG4 M-JPEG | 1        | 640x480        | -     | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 209FD-R     |   | MPEG4 M-JPEG | 1        | 640x480        | -     | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 209MFD      |   | MPEG4 M-JPEG | 1        | 1280x1024      | -     | -      | Yes | Yes            | Yes  | Yes                  | -        |                     |
| 209MFD-R    |   | MPEG4 M-JPEG | 1        | 1280x1024      | -     | -      | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| 210         |   | MPEG4 M-JPEG | 1        | 640x480        | -     | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 2100        | 2.31  | M-JPEG       | 1        | 640x480        | -     | -      | -   | -              | -    | -                    | -        |                     |
| 210A        | 4.40  | MPEG4 M-JPEG | 1        | 640x480        | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| 211         |   | MPEG4 M-JPEG | 1        | 640x480        | -     | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 211A        |   | MPEG4 M-JPEG | 1        | 640x480        | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 211M        |   | MPEG4 M-JPEG | 1        | 1280x1024      | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 211W        |   | MPEG4 M-JPEG | 1        | 640x480        | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 212         |   | MPEG4 M-JPEG | 1        | 640x480        | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:       | 212 PTZ and 212 PTZ-V are compatible with 212 |              |          |                |       |        |     |                |      |                      |          |                     |
| 213         |   | MPEG4 M-JPEG | 1        | 704x576        | 2-way | 2/3    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:       | 213 PTZ is compatible with 213                |              |          |                |       |        |     |                |      |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware                               | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| 214         | 4.33  | MPEG4 M-JPEG | 1        | 704x480        | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | 214 PTZ is compatible with 214                |              |          |                |       |        |     |                |      |                      |          |                     |
| 215         |   | MPEG4 M-JPEG | 1        | 704x576        | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:       | 215 PTZ and 215 PTZ-E are compatible with 215 |              |          |                |       |        |     |                |      |                      |          |                     |
| 216FD       |   | MPEG4 M-JPEG | 1        | 640x480        | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 216FD-V     |   | MPEG4 M-JPEG | 1        | 640x480        | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 216MFD      |   | MPEG4 M-JPEG | 1        | 1280x1024      | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 216MFD-V    |   | MPEG4 M-JPEG | 1        | 1280x1024      | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 221         |   | MPEG4 M-JPEG | 1        | 640x480        | -     | 2/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 223M        |   | MPEG4 M-JPEG | 1        | 1600x1200      | 2-way | 2/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 225FD       |   | MPEG4 M-JPEG | 1        | 640x480        | -     | 2/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 231D        |   | MPEG4 M-JPEG | 1        | 704x576        | -     | 4/4    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:       | 231D+ is compatible with 231D                 |              |          |                |       |        |     |                |      |                      |          |                     |
| 232D        |   | MPEG4 M-JPEG | 1        | 704x576        | -     | 4/4    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:       | 232D+ is compatible with 232D                 |              |          |                |       |        |     |                |      |                      |          |                     |
| 233D        |   | MPEG4 M-JPEG | 1        | 704x576        | 2-way | 4/4    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| 2400        |   | M-JEPG       | 4        | 704x576        | -     | 4/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 240Q        |   | M-JEPG       | 4        | 704x576        | -     | 4/4    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 240Q Blade  |   | M-JEPG       | 4        | 704x576        | -     | 4/4    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 241Q        |   | MPEG4 M-JPEG | 4        | 704x576        | -     | 4/4    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 241Q Blade  |   | MPEG4 M-JPEG | 4        | 704x576        | -     | 4/4    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 241QA       | 4.30  | MPEG4 M-JPEG | 4        | 704x576        | 1-way | 4/4    | -   | Yes            | Yes  | Yes                  | -        |                     |
| 241S        |   | MPEG4 M-JPEG | 1        | 704x576        | -     | 4/4    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 241S Blade  |   | MPEG4 M-JPEG | 1        | 704x576        | -     | 4/4    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch     | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|----------------|-------|------------|-----|----------------|------|----------------------|----------|---------------------|
| 241SA       |  | MPEG4<br>M-JPEG          | 1        | 704x576        | 1-way | 4/4        | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 242S        |  | MPEG4<br>M-JPEG          | 1        | 704x576        | -     | 4/4        | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 243Q        |  | MPEG4<br>M-JPEG          | 1        | 704x576        | -     | 1/1        | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 243Q Blade  |  | MPEG4<br>M-JPEG          | 1        | 704x576        | -     | 1/1        | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 243SA       |  | MPEG4<br>M-JPEG          | 1        | 704x576        | 2-way | 4/4        | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 2460        |  | M-JEPG                   | 4        | 704x576        | -     | 4/1        | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| 247S        |  | MPEG4<br>M-JPEG          | 1        | 704x576        | 1-way | 1/1        | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| Generic     |  | H.264<br>MPEG4<br>M-JPEG | Max<br>4 | by Camera      | 2-way | Max<br>4/4 | Yes | Yes            | -    | Yes*                 | Yes      |                     |
| Note:       | Only guarantee stream works fine.  |                          |          |                |       |            |     |                |      |                      |          |                     |
| F41         | 5.85.3   | H.264<br>MJPEG           | 1        | 1920x1080      | *2    | *2(4/4)    | -   | Yes            | *2   | Yes*                 | Yes      |                     |
| Note:       | 1. Does not support ACAP Motion (MainConsole). (Old Motion Setting: <a href="http://IP:PORT/operator/motionDetection.shtml?nbr">http://IP:PORT/operator/motionDetection.shtml?nbr</a>  |                          |          |                |       |            |     |                |      |                      |          |                     |
| F44         | 5.85.3   | H.264<br>MJPEG           | 4        | 1920x1080      | *2    | *2(4/4)    | -   | *2             | *2   | Yes*                 | Yes      |                     |
| Note:       | 1. Frame rate list may not sync with web. (Camera Firmware issue)<br>2. Does not support ACAP Motion (MainConsole). (Old Motion Setting: <a href="http://IP:PORT/operator/motionDetection.shtml?nbr=0&amp;id=13">http://IP:PORT/operator/motionDetection.shtml?nbr=0&amp;id=13</a> )(NUUO server limitation) |                          |          |                |       |            |     |                |      |                      |          |                     |
| M1004-W     | 5.40.5.1   | H.264<br>MJPEG           | 1        | 1280x800       | -     | 1/1        | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| M1011       | 5.00   | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | -     | -          | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| M1011-W     | 5.00   | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | -     | -          | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| M1013       | 5.40.5.1   | H.264<br>M-JPEG          | 1        | 800x600        | 2-way | -          | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| M1014       | 5.40.5   | H.264<br>M-JPEG          | 1        | 1280x800       | -     | -          | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| M1025       | 5.40.5   | H.264<br>MJPEG           | 1        | 1920x1080      | -     | -          | -   | *2             | *2   | Yes*                 | *2       | tested by link      |
| M1031-W     | 5.00   | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | 2-way | -          | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| M1034-W     | 5.40beta1  | H.264<br>M-JPEG          | 1        | 1280x800       | 2-way | -          | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| M1054       | 5.15   | H.264<br>M-JPEG          | 1        | 1024x640       | 2-way | 1/1        | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| M1103       |  | H.264<br>M-JPEG          | 1        | 800x600        | -     | -          | Yes | Yes            | Yes* | Yes                  | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| M1104       | 5.09   | H.264 M-JPEG       | 1        | 1280x800       | -     | -      | -   | Yes            | Yes* | Yes                  | Yes      |                     |
| M1113       | 5.08   | H.264 M-JPEG       | 1        | 800x600        | -     | -      | Yes | Yes            | Yes  | Yes                  | Yes      | *                   |
| M1114-L     |  | H.264 M-JPEG       | 1        | 1280x800       | -     | -      | -   | Yes            | Yes* | Yes                  | Yes      | Supported by design |
| Note:       | M1113-E is compatible with M1113, M1114-E is compatible with M1114   |                    |          |                |       |        |     |                |      |                      |          |                     |
| M2014       | Refer to P1204(5.40.12)  | H.264 M-JPEG       | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| M1143-L     | 5.40beta19   | H.264 M-JPEG       | 1        | 800x600        | -     | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| M1144       | 5.40.10.4  | H.264 M-JPEG       | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| M3004       | 5.50.5.1   | H.264 M-JPEG       | 1        | 1280x800       | -     | -      | -   | *2             | *2   | Yes*                 | *2       | tested by link      |
| M3005       | 5.40.5.3   | H.264 M-JPEG       | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| M3006       | 5.40.13  | H.264 M-JPEG       | 1        | 2048x1536      | -     | -      | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| M3007       | 5.55.1.1   | H.264 M-JPEG       | 1        | 2592x1944      | -     | -      | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | fisheye camera   |                    |          |                |       |        |     |                |      |                      |          |                     |
| M3011       | 5.01   | H.264 MPEG4 M-JPEG | 1        | 640x480        | -     | -      | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| M3014       |  | H.264 M-JPEG       | 1        | 1280x800       | -     | -      | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| M3024-L     | 5.40.5   | H.264 M-JPEG       | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| M3025       | 5.50.5.1   | H.264 M-JPEG       | 1        | 1920x1080      | -     | -      | -   | *2             | *2   | Yes*                 | *2       | tested by link      |
| M3026       | Refer to M3024-L(5.40.5)   | H.264 M-JPEG       | 1        | 2048x1536      | -     | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| M3027       | refer to M3007(5.55.1.1)   | H.264 M-JPEG       | 1        | 2592x1944      | -     | -      | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| Note:       | fisheye camera   |                    |          |                |       |        |     |                |      |                      |          |                     |
| M3037       | 5.75.1   | H.264 MJPEG        | 1        | 2592x1944      | 2-way | -      | -   | -              | *2   | Yes*                 | -        |                     |
| Note:       | 1.Frame rate can not achieve to max fps. [Camera performance limitation]<br>2. Can not connect at Panorama Corner left, Panorama Corner right, Double Panorama Corner Modes. [Camera firmware issue] |                    |          |                |       |        |     |                |      |                      |          |                     |
| M3113-R     |  | H.264 M-JPEG       | 1        | 800x600        | -     | -      | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| M3113-VE    |  | H.264 M-JPEG       | 1        | 800x600        | -     | -      | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware                         | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch  | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|---------|-----|----------------|------|----------------------|----------|---------------------|
| M3114-R     | 5.11                                    | H.264<br>M-JPEG          | 1        | 1280x800       | -     | -       | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| M3114-VE    |   | H.264<br>M-JPEG          | 1        | 1280x800       | -     | -       | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| M3203       |   | H.264<br>M-JPEG          | 1        | 800x600        | -     | -       | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| Note:       | M3203-V is compatible with M3203        |                          |          |                |       |         |     |                |      |                      |          |                     |
| M3204       |   | H.264<br>M-JPEG          | 1        | 1280x800       | -     | -       | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| Note:       | M3204-V is compatible with M3204        |                          |          |                |       |         |     |                |      |                      |          |                     |
| M5013       |   | H.264<br>M-JPEG          | 1        | 800x600        | 2-way | -       | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| M5014       |   | H.264<br>MPEG4           | 1        | 1280x720       | 2-way | 2/2     | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| M7001       |   | H.264<br>M-JPEG          | 1        | 720x576        | -     | -       | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| M7010       | 5.40.6.1                                | H.264<br>M-JPEG          | 16*      | 720x576        | -     | -       | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:       | M7010 is 4 IP x 4 channels video server |                          |          |                |       |         |     |                |      |                      |          |                     |
| M7014       | 5.40.7.1                                | H.264<br>M-JPEG          | 4        | 720x576        | -     | -       | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| P1204       | 5.40.12                                 | H.264<br>M-JPEG          | 1        | 1280x720       | 1-way | 1/1     | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| P1214       | 5.40.12                                 | H.264<br>M-JPEG          | 1        | 1280x720       | 1-way | 1/1     | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| P1214-E     | 5.40.12                                 | H.264<br>M-JPEG          | 1        | 1280x720       | -     | *2(1/1) | -   | *2             | *2   | Yes*                 | *2       |                     |
| P1311       | 5.01                                    | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | 2-way | 1/1     | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| P1343       | 5.06                                    | H.264<br>M-JPEG          | 1        | 640*480        | 2-way | 1/1     | Yes | Yes            | Yes  | Yes                  | Yes      | *                   |
| P1343-E     |   | H.264<br>M-JPEG          | 1        | 800x600        | 2-way | 1/1     | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P1344       |   | H.264<br>M-JPEG          | 1        | 1280x800       | 2-way | 1/1     | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P1344-E     |   | H.264<br>M-JPEG          | 1        | 1280x800       | 2-way | 1/1     | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P1346       | 5.06                                    | H.264<br>M-JPEG          | 1        | 2048x1536      | 2-way | 1/1     | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| P1346-E     |   | H.264<br>M-JPEG          | 1        | 2048x1536      | 2-way | 1/1     | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P1347       | 5.11                                    | H.264<br>M-JPEG          | 1        | 2560x1920      | 2-way | 1/1     | Yes | Yes            | Yes* | Yes                  | Yes      |                     |





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| P1347-E     |  | H.264 M-JPEG | 1        | 2560x1920      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P1353-E     | refer to P1354 (5.40.14)   | H.264 M-JPEG | 1        | 800x600        | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P1354       | 5.60.1   | H.264 M-JPEG | 1        | 1280x960       | *2    | *2     | Yes | *2             | *2   | Yes*                 | *2       | tested by link      |
| Note:       | H264 AAC not support in Mini2v1.6 and above version  |              |          |                |       |        |     |                |      |                      |          |                     |
| P1355-E     | refer to P1354 (5.40.14)   | H.264 M-JPEG | 1        | 800x600        | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P1357       | 5.40.19.1  | H.264 M-JPEG | 1        | 2592x1944      | *2    | *2     | *2  | Yes            | *2   | Yes                  | Yes      |                     |
| P1405-LE    | 5.80.1   | H.264 MJPEG  | 1        | 1920x1080      | -     | -      | Yes | *2             | *2   | Yes*                 | *2       | Tested by link      |
| P1425-E     | Refer to P1425-LE(5.80.1)  | H.264 MJPEG  | 1        | 1920x1080      | -     | 1/1    | Yes | *2             | *2   | Yes*                 | *2       | Supported by design |
| P1425-LE    | 5.80.1   | H.264 MJPEG  | 1        | 1920x1080      | -     | 1/1    | Yes | *2             | *2   | Yes*                 | *2       |                     |
| Note:       | PTZ only support zoom & focus.   |              |          |                |       |        |     |                |      |                      |          |                     |
| P1427-LE    | 5.80.1   | H.264 MJPEG  | 1        | 2592x1944      | -     | *2     | Yes | *2             | *2   | Yes*                 | *2       |                     |
| Note:       | 1.Frame rate list does not sync with web. (Camera Firmware issue)<br>2.The connection is unstable, since camera connects via link. (Camera Firmware issue) |              |          |                |       |        |     |                |      |                      |          |                     |
| P1428-E     | 5.55.1   | H.264 M-JPEG | 1        | 3840x2160      | -     | *2     | Yes | *2             | *2   | Yes*                 | *2       |                     |
| P3214-V     | 5.55.3.2   | H.264 MJPEG  | 1        | 1280x960       | -     | *2     | Yes | *2             | *2   | Yes*                 | *2       |                     |
| Note:       | Zoom speed setting does not support.(Camera limitation)  |              |          |                |       |        |     |                |      |                      |          |                     |
| P3215-V     | 5.55.3.2   | H.264 MJPEG  | 1        | 1920x1080      | -     | *2     | Yes | *2             | *2   | Yes*                 | *2       |                     |
| P3224       | Refer to P3224-LV (5.75.3.1)   | H.264 MJPEG  | 1        | 1280x960       | -     | -      | Yes | *2             | *2   | Yes*                 | *2       | Supported by design |
| P3224-LV    | 5.75.3.1   | H.264 MJPEG  | 1        | 1280x960       | -     | -      | Yes | *2             | *2   | Yes*                 | *2       |                     |
| P3225       | Refer to P3225-LVE (5.75.3.1)  | H.264 MJPEG  | 1        | 1920x1080      | -     | -      | Yes | *2             | *2   | Yes*                 | *2       | Supported by design |
| P3225-LVE   | 5.75.3.1   | H.264 MJPEG  | 1        | 1920x1080      | -     | -      | Yes | *2             | *2   | Yes*                 | *2       |                     |
| P3301       | 5.11   | H.264 M-JPEG | 1        | 640x480        | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P3301-V     |  | H.264 M-JPEG | 1        | 640x480        | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| P3304       |  | H.264 M-JPEG | 1        | 1280x800       | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P3304-V     |  | H.264 M-JPEG | 1        | 1280x800       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P3343       | 5.06   | H.264 M-JPEG | 1        | 800x600        | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| Note:       | 1. P3343-V and P3343-VE are compatible with P3343<br>2. Support digital PTZ only |              |          |                |       |        |     |                |      |                      |          |                     |
| P3353       |  | H.264 M-JPEG | 1        | 800x600        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| P3344       | 5.06   | H.264 M-JPEG | 1        | 1280x800       | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:       | 1. P3344-V and P3344-VE are compatible with P3344<br>2. Support digital PTZ only |              |          |                |       |        |     |                |      |                      |          |                     |
| P3346       | 5.20   | H.264 M-JPEG | 1        | 2048x1536      | 2-way | 1/1    | Yes | Yes            | Yes* | Yes                  | Yes      |                     |
| Note:       | 1. P3346-V and P3346-VE are compatible with P3346<br>2. Support digital PTZ only |              |          |                |       |        |     |                |      |                      |          |                     |
| P3354       | 5.40.10.2  | H.264 M-JPEG | 1        | 1280x960       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | tested by link      |
| P3363       | 5.40.17.1  | H.264 MJPEG  | 1        | 800x600        | *2    | *2     | *2  | *2             | *2   | Yes*                 | *2       | tested by link      |
| P3364       | 5.40.10.2  | H.264 M-JPEG | 1        | 1280x960       | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | tested by link      |
| P3364-L     | 5.60.1.4   | H.264 MJPEG  | 1        | 1280x960       | 2-way | 1/1    | Yes | *2             | *2   | Yes*                 | *2       |                     |
| Note:       | PTZ only support zoom & focus.   |              |          |                |       |        |     |                |      |                      |          |                     |
| P3364-LV    | Refer to P3364-L(5.60.1.4)   | H.264 MJPEG  | 1        | 1280x960       | 2-way | 1/1    | Yes | *2             | *2   | Yes*                 | *2       | Supported by design |
| P3365       | 5.55.3.2   | H.264 M-JPEG | 1        | 1920x1080      | *2    | 1/1    | Yes | *2             | *2   | Yes*                 | *2       | tested by link      |
| P3365-V     | Refer to P3365(5.55.3.2)   | H.264 M-JPEG | 1        | 1920x1080      | *2    | 1/1    | Yes | *2             | *2   | Yes*                 | *2       | Supported by design |
| P3365-VE    | Refer to P3365(5.55.3.2)   | H.264 M-JPEG | 1        | 1920x1080      | *2    | 1/1    | Yes | *2             | *2   | Yes*                 | *2       | Supported by design |
| P3367       | 5.40.3   | H.264 M-JPEG | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:       | P3367-V, P3367-VE are compatible with P3367                                      |              |          |                |       |        |     |                |      |                      |          |                     |
| P3384       | 5.40.19  | H.264 MJPEG  | 1        | 1280x960       | *2    | *2     | -   | *2             | *2   | Yes*                 | *2       | tested by link      |
| P3905       | 5.55.3   | H.264 MJPEG  | 1        | 1920x1080      | -     | -      | -   | Yes            | *2   | Yes*                 | *2       | tested by link      |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch  | PTZ  | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------|----------|----------------|-------|---------|------|----------------|------|----------------------|----------|---------------------|
| P3905-R     | Refer to P3905(5.55.3)  | H.264 MJPEG  | 1        | 1920x1080      | -     | -       | -    | *2             | *2   | Yes*                 | *2       | Supported by design |
| P3905-RE    | Refer to P3905(5.55.3)  | H.264 MJPEG  | 1        | 1920x1080      | -     | -       | -    | *2             | *2   | Yes*                 | *2       | Supported by design |
| P3915       | 5.55.3  | H.264 MJPEG  | 1        | 1920x1080      | *2    | 1/1(*2) | -    | *2             | *2   | Yes*                 | *2       | tested by link      |
| P3915-R     | Refer to P3915(5.55.3)  | H.264 MJPEG  | 1        | 1920x1080      | *2    | 1/1(*2) | -    | *2             | *2   | Yes*                 | *2       | Supported by design |
| P5414       | 5.55.1  | H.264 M-JPEG | 1        | 1280x720       | 2-way | 4/4     | Yes  | Yes            | Yes  | Yes                  | Yes      | tested by link      |
| P5415       | Refer to P5414(5.55.1)  | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 4/4     | Yes  | Yes            | Yes  | Yes                  | Yes      |                     |
| P5512       |   | H.264 M-JPEG | 1        | 704x480        | 2-way | 4/4     | Yes  | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P5512-E     |   | H.264 M-JPEG | 1        | 704x480        | 2-way | 4/4     | Yes  | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P5514       | 5.85.1  | H.264 M-JPEG | 1        | 1280x720       | *2    | 4/4(*2) | Yes  | *2             | *2   | Yes*                 | *2       |                     |
| Note:       | 1.Bitrate list does not sync with web. (Camera Firmware issue)<br>2.Frame rate list does not sync with web. (Camera Firmware issue) |              |          |                |       |         |      |                |      |                      |          |                     |
| P5522       |   | H.264 M-JPEG | 1        | 720x480        | 2-way | 4/4     | Yes  | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P5522-E     |   | H.264 M-JPEG | 1        | 720x480        | 2-way | 4/4     | Yes  | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P5532       | 5.15  | H.264 M-JPEG | 1        | 720x480        | 2-way | 2/2     | Yes  | Yes            | Yes* | Yes                  | Yes      |                     |
| P5532-E     |   | H.264 M-JPEG | 1        | 720x480        | 2-way | 2/2     | Yes  | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P5534       | 5.15.1  | H.264 M-JPEG | 1        | 1280x720       | 2-way | 2/2     | Yes  | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P5534-E     |   | H.264 M-JPEG | 1        | 1280x720       | 2-way | 2/2     | Yes  | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P5544       | 5.41.2.2  | H.264 M-JPEG | 1        | 1280x720       | *2    | *2      | Yes  | *2             | *2   | Yes*                 | *2       | tested by link      |
| Note:       | P5544 is a two-len (fisheye and PTZ) camera   |              |          |                |       |         |      |                |      |                      |          |                     |
| P5624       | Refer to P5624-E(5.75.1)  | H.264 M-JPEG | 1        | 1280x720       | -     | -       | Yes* | *2             | *2   | Yes*                 | *2       | Supported by design |
| P5624-E     | 5.75.1  | H.264 M-JPEG | 1        | 1280x720       | -     | -       | Yes* | *2             | *2   | Yes*                 | *2       | tested by link      |
| P5635       | Refer to P5635-E(5.75.1)  | H.264 M-JPEG | 1        | 1920x1080      | *2    | 2       | Yes* | *2             | *2   | Yes*                 | *2       | Supported by design |
| P5635-E     | 5.75.1  | H.264 M-JPEG | 1        | 1920x1080      | *2    | 2/2(*2) | Yes* | *2             | *2   | Yes*                 | *2       | tested by link      |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| P7210       | 5.40.6.1   | H.264 M-JPEG | 20*      | 1536x1152      | 2-way | 16/16  | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:       | P7210 is 4IP x 5channels video server  |              |          |                |       |        |     |                |      |                      |          |                     |
| P7214       | Refer to P7210   | H.264 M-JPEG | 4        | 720x576        | 2-way | 4/4    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P7224       | 5.40.7   | H.264 M-JPEG | 4        | 720x576        | 2-way | 4/4    | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:       | P7224 can't use second audio input. First audio only support G.711   |              |          |                |       |        |     |                |      |                      |          |                     |
| P8221       | 5.10.2   | *2           | 1        | -              | *2    | *2     | -   | -              | *2   | -                    |          |                     |
| Note:       | Network I/O audio module   |              |          |                |       |        |     |                |      |                      |          |                     |
| P8513       | Refer to P8514   | H.264 M-JPEG | 1        | 800x600        | -     | 0/0    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| P8514       | 5.21   | H.264 M-JPEG | 1        | 1280x800       | -     | 0/0    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Q1602       | 5.40.3   | H.264 M-JPEG | 1        | 768x576        | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:       | 1. Q1602 camera not testing Audio, I/O, UPNP capability (by link)<br>2. Q1602-E is compatible with Q1602   |              |          |                |       |        |     |                |      |                      |          |                     |
| Q1604       | 5.40.3.2   | H.264 M-JPEG | 1        | 1280x960       | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:       | 1. Not support AAC when codec is MJPEG<br>2. Does not support H264 CBR mode  |              |          |                |       |        |     |                |      |                      |          |                     |
| Q1614       | 5.55.1   | H.264 MJPEG  | 1        | 1280x960       | *2    | *2     | -   | *2             | *2   | Yes*                 | *2       |                     |
| Q1615       | 5.55.3   | H.264 MJPEG  | 1        | 1920x1200      | *2    | *2     | -   | *2             | *2   | Yes*                 | *2       |                     |
| Note:       | Q1614 and Q1615: Max framerate show 60 regardless of Axis Capture mode.  |              |          |                |       |        |     |                |      |                      |          |                     |
| Q1635       | 5.80.1.2   | H.264 MJPEG  | 1        | 1920x1200      | *2    | *2     | Yes | *2             | *2   | Yes*                 | *2       |                     |
| Note:       | 1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)<br>2. Stream1 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation) |              |          |                |       |        |     |                |      |                      |          |                     |
| Q1755       | 5.02   | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:       | M-JPEG: Due to the HW constraints, the frame rate and audio will be impacted if resolution and quality are high.   |              |          |                |       |        |     |                |      |                      |          |                     |
| Q1755-E     |  | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Q1765-LE    | 5.55.1   | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Q1910       | 5.06   | H.264 M-JPEG | 1        | 720x576        | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| Q1910-E     |   | H.264 M-JPEG | 1        | 720x576        | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Q1931-E     | 5.55.1  | H.264 M-JPEG | 1        | 768x576        | 2-way | 2/2    | -   | Yes            | *2   | Yes                  | Yes      |                     |
| Note:       | 1.Thermal camera<br>2.Up to 30 fps within EU, Norway, Switzerland, Canada, USA, Japan, Australia, New ZealandUp to 8.3 fps in other countriesa                                |              |          |                |       |        |     |                |      |                      |          |                     |
| Q1921       | 5.11  | H.264 M-JPEG | 1        | 768x576        | 2-way | 2/0    | -   | Yes            | Yes* | Yes                  | Yes      | Supported by design |
| Q1921-E     |   | H.264 M-JPEG | 1        | 768x576        | 2-way | 2/0    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Q1922       | Refer to Q1921  | H.264 M-JPEG | 1        | 800x600        | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| Q2901-E     | 5.55.4.1  | H.264 M-JPEG | 1        | 720x576        | *2    | -      | -   | *2             | *2   | Yes*                 | *2       |                     |
| Q3505       | 5.80.1  | H.264 M-JPEG | 1        | 1920x1200      | *2    | -      | Yes | *2             | *2   | Yes*                 | *2       | tested by link      |
| Note:       | 1.PTZ only support zoom & focus.<br>2.Bitrate list range error.(Firmware Issue)<br>3.FPS cannot reach to 30 fps due to multi-connection of camera. (Camera Performance Issue) |              |          |                |       |        |     |                |      |                      |          |                     |
| Q3505-V     | Refer to Q3505(5.80.1)  | H.264 M-JPEG | 1        | 1920x1200      | *2    | -      | Yes | *2             | *2   | Yes*                 | *2       | Supported by design |
| Q6000       | Refer to Q6000-E(5.65.1)  | H.264 M-JPEG | 5        | 1920x1440      | -     | -      | -   | *2             | *2   | Yes*                 | *2       | Supported by design |
| Q6000-E     | 5.65.1  | H.264 M-JPEG | 5        | 1920x1440      | -     | -      | -   | *2             | *2   | Yes*                 | *2       | tested by link      |
| Note:       | 1.The range of 5th's frame rate is different from that on camera web. (Camera firmware issue).  |              |          |                |       |        |     |                |      |                      |          |                     |
| Q6032       |   | H.264 M-JPEG | 1        | 752x480        | 1-way | 4/4    | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Q6032-E     | 5.05  | H.264 M-JPEG | 1        | 704x576        | -     | -      | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Q6034       | 5.20.3  | H.264 M-JPEG | 1        | 1280x720       | 1-way | 2/2    | Yes | Yes            | Yes* | Yes                  | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution              | Audio | I/O Ch  | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------|----------|-----------------------------|-------|---------|-----|----------------|------|----------------------|----------|---------------------|
| Q6034-E     |   | H.264 M-JPEG | 1        | 1280x720                    | 1-way | 2/2     | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| Q6035       |   | H.264 M-JPEG | 1        | 1920x1080                   | 2-way | 4/4     | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| Q6035-E     |   | H.264 M-JPEG | 1        | 1920x1080                   | 1-way | -       | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| Q6042       | 5.55.1  | H.264 M-JPEG | 1        | 752x480                     | 2-way | 4/4     | Yes | Yes            | *2   | Yes                  | Yes      |                     |
| Q6044       | 5.55.1  | H.264 M-JPEG | 1        | 1920x1080                   | 2-way | 4/4     | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| Q6044-E     | 5.70.1.1  | H.264 MJPEG  | 1        | 1280x720                    | -     | -       | Yes | *2             | *2   | Yes*                 | *2       |                     |
| Q6045       | 5.55.1  | H.264 M-JPEG | 1        | 1920x1080                   | 2-way | 4/4     | Yes | Yes            | Yes  | Yes                  | Yes      | Tested by link      |
| Q6045-E     | 5.70.1.1  | H.264 M-JPEG | 1        | 1920x1080                   | -     | -       | Yes | *2             | *2   | Yes*                 | *2       |                     |
| Note        | 1. PTZ speed does not sync with web. (Camera Firmware issue)  |              |          |                             |       |         |     |                |      |                      |          |                     |
| Q6115-E     | 5.65.2  | H.264 M-JPEG | 1        | 1920x1080                   | -     | -       | Yes | *2             | *2   | Yes*                 | Yes      | Tested by link      |
| Q7401       |   | H.264 M-JPEG | 1        | 704x576                     | 2-way | 2/2     | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Q7404       | 5.02  | H.264 M-JPEG | 4        | 768x576                     | 2-way | 1/1     | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| Q7406       | 5.11.1  | H.264 M-JPEG | 6        | 704x576                     | 1-way | 1/1     | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Q7411       | 5.40.13.1   | H.264 M-JPEG | 1        | 720x576                     | 2-way | 4/4     | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Q7414       | 5.25  | H.264 M-JPEG | 4        | 720x576(PAL)<br>720x480(NT) | 2-way | 1/1     | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Q7424-R     | 5.40.10   | H.264 M-JPEG | 4        | 720x576                     | 2-way | 4/4     | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Note        | One of the cameras in the system must support I/O functions in order to enable the snapshot feature. This is a known issue and we are looking to fix it with the next product version update. |              |          |                             |       |         |     |                |      |                      |          |                     |
| V5915       | 5.75.1  | H.264 MJPEG  | 1        | 1920x1080                   | *2    | *2(4/4) | Yes | -              | *2   | Yes*                 | -        |                     |
| Note        | 1. Camera cannot achieve maximum FPS with high resolution and bitrate. (Camera performance limitation)<br>2. Framerate list can not sync with web. (Camera Firmware issue)                    |              |          |                             |       |         |     |                |      |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name    | Tested Firmware                   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks                |
|----------------|-----------------------------------|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|------------------------|
| BIP-640c       |                                   | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | -     | 1/1    | -   | -              | -    | -                    | Tested by manufacturer |
| BIP-640c-dn    |                                   | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | -     | 1/1    | -   | -              | -    | -                    | Tested by manufacturer |
| BIP-1000c      |                                   | H.264<br>MPEG4<br>M-JPEG | 1        | 1024x768       | -     | 1/1    | -   | -              | -    | -                    | Tested by manufacturer |
| BIP-1000c-dn   |                                   | H.264<br>MPEG4<br>M-JPEG | 1        | 1024x768       | -     | 1/1    | -   | -              | -    | -                    | Tested by manufacturer |
| BIP-1300c      |                                   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | -     | 1/1    | -   | -              | -    | -                    | Tested by manufacturer |
| BIP-1300c-dn   | BIP-1300c-dn-1.6-2                | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | -     | 1/1    | -   | Yes            | -    | -                    |                        |
| Note:          | On-Edge Motion: H.264 and M-JPEG. |                          |          |                |       |        |     |                |      |                      |                        |
| BIP-1600c      |                                   | H.264<br>MPEG4<br>M-JPEG | 1        | 1600x1200      | -     | 1/1    | -   | -              | -    | -                    | Tested by manufacturer |
| BIP-1600c-dn   |                                   | H.264<br>MPEG4<br>M-JPEG | 1        | 1600x1200      | -     | 1/1    | -   | -              | -    | -                    | Tested by manufacturer |
| BIP-D1000c-dn  |                                   | H.264<br>MPEG4<br>M-JPEG | 1        | 1024x768       | -     | 1/1    | -   | -              | -    | -                    | Tested by manufacturer |
| BIP-D1300c-dn  | BIP-D1300c-dn-1.6-1               | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | -     | 1/1    | -   | Yes            | -    | -                    |                        |
| Note:          | On-Edge Motion: H.264 and M-JPEG. |                          |          |                |       |        |     |                |      |                      |                        |
| BIP2-1600c-dn  |                                   |                          |          |                |       |        |     |                |      |                      |                        |
| BIP2-D1920c-DN | 3.8.0                             | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1440      | -     | 1/1    | -   | Yes            | Yes  | Yes                  |                        |
| Note:          | Not support Audio                 |                          |          |                |       |        |     |                |      |                      |                        |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name        | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|--------------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| <b>NBC-225-P</b>   | refer to NDC-225 (FW: 39500570)   | H.264        | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>NBC-255-P</b>   | refer to NDC-225 (FW: 39500570)   | H.264        | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>NBC-265-P</b>   | refer to NTC-265-PI (FW: 39500570)  | H.264        | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>NBC-274-P</b>   | refer to NTC-265-PI (FW: 15500552)  | H.264        | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>NBC-274-PM</b>  | refer to NTC-265-PI (FW: 15500552)  | H.264        | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>NBC-274-PT</b>  | refer to NTC-265-PI (FW: 15500552)  | H.264        | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>NBC-455</b>     | 5.72.0028(28500572)   | H.264        | 1        | 704x576        | *2    | *2     | -   | *2             | *2   | Yes                  | Yes      |                     |
| Note:              | 1. H.264 only support IP mode of GOP structure. (Camera→Encoder Profile→Profile N→Expert Settings→GOP structure→IP) i. (NUUO Server limitation)<br>2. Only support G.711 audio codec. i. (Camera performance limitation)<br>3. Can't set tream3 quality value. i. (Camera firmware issue) |              |          |                |       |        |     |                |      |                      |          |                     |
| <b>NBN-498</b>     | 5.72.0028(28500572)   | H.264        | 1        | 704x576        | *2    | *2     | -   | *2             | *2   | Yes                  | Yes      |                     |
| Note:              | 1. H.264 only support IP mode of GOP structure. (Camera→Encoder Profile→Profile N→Expert Settings→GOP structure→IP) i. (NUUO Server limitation)<br>2. Only support G.711 audio codec. i. (Camera performance limitation)<br>3. Can't set tream3 quality value. i. (Camera firmware issue) |              |          |                |       |        |     |                |      |                      |          |                     |
| <b>NBN-733</b>     | refer to NIN-733(5.90.0112)   | H.264        | 1        | 1280x720       | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>NBN-832</b>     | refer to NDN-832(5.90.0112)   | H.264        | 1        | 1920x1080      | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>NBN-40012</b>   | refer to NTI-40012(5.90.0126(26510590))   | H.264        | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| <b>NBN-50022</b>   | refer to NTI-50022(5.90.0126(26510590))   | H.264        | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| <b>NBN-71013-B</b> | 5.92.0090(90500592)   | H.264        | 1        | 1280x720       | 2-way | 2/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:              | 1. FPS can not achieve setting value. (Camera performance limitation)   |              |          |                |       |        |     |                |      |                      |          |                     |

- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name       | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| <b>NDC-225</b>    | 39500570  | H.264        | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:             | When H264 quality is set to '0', the camera will auto-adjust the quality setting. For minimum quality, the value should be '1'.<br>Audio Codec support g711, not support L1, AAC.   |              |          |                |       |        |     |                |      |                      |          |                     |
| <b>NDC-255-P</b>  | refer to NDC-225 (FW: 39500570)   | H.264        | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>NDC-225-PI</b> | refer to NDC-225 (FW: 39500570)   | H.264        | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>NDC-265-P</b>  | refer to NDC-265-PI (FW: 39500570)  | H.264        | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>NDC-274-P</b>  | 15500552  | H.264        | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:             | When H.264 quality is set to "0", the camera will Auto-adjust the quality setting. For minimum quality, the value should be "1".<br>Audio Codec support g711, not support L1, AAC.  |              |          |                |       |        |     |                |      |                      |          |                     |
| <b>NDC-274-PT</b> | refer to NDC-274-P (FW: 15500552)   | H.264        | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| <b>NDC-455</b>    | refer to NBC-455(5.72.0)  | H.264        | 1        | 704x576        | 1-way | 2/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| <b>NDN-498</b>    | refer to NBN-498(5.72.0)  | H.264        | 1        | 704x576        | 1-way | 2/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| <b>NDN-733</b>    | refer to NIN-733(5.90.0112)   | H.264        | 1        | 1280x720       | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>NDN-832</b>    | 5.90.0112   | H.264        | 1        | 1920x1080      | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:             | 1. H.264 only support IP mode of GOP structure. (Camera→Encoder Profile→Profile N→Expert Settings→GOP structure→IP)<br>2. Only support G.711 audio codec.<br>3. Changing resolution from 1920x1080 and 1280x720 to lower resolution need to set by web property to "H.264 MP SD". |              |          |                |       |        |     |                |      |                      |          |                     |
| <b>NDN-40012</b>  | refer to NTI-40012(5.90.0126 (26510590))  | H.264        | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| <b>NDN-50022</b>  | refer to NTI-50022(5.90.0126 (26510590))  | H.264        | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| <b>NDI-50022</b>  | refer to NTI-50022(5.90.0126 (26510590))  | H.264        | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |

- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name       | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| <b>NIN-733</b>    | 5.90.0112   | H.264        | 1        | 1280x720       | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:             | 1. H.264 only support IP mode of GOP structure. (Camera→Encoder Profile→Profile N→Expert Settings→GOP structure→IP)<br>2. Only support G.711 audio codec<br>3. Can't set framerate 1 under base frame rate 50/60 ips mode. (Camera firmware issue)  |              |          |                |       |        |     |                |      |                      |          |                     |
| <b>NIN-832</b>    | refer to NDN-832(5.90.0112)   | H.264        | 1        | 1920x1080      | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>NIN-40012</b>  | refer to NTI-40012(5.90.0126 (26510590))  | H.264        | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| <b>NTC-255-PI</b> | refer to NDC-225 (FW: 39500570)   | H.264        | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>NTC-265-PI</b> | refer to NDN-265-PIO (FW 39500570)  | H.264        | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>NTI-40012</b>  | 5.90.0126   | H.264        | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:             | 1. H.264 only support IP mode of GOP structure. (Camera→Encoder Profile→Profile N→Expert Settings→GOP structure→IP).i. (NUUO Server limitation)<br>2. Only support G.711 audio codec.i. (Camera performance limitation)<br>3. After changing MJPEG resolution on web and getting camera setting on NUUO, resolution will return to previous setting.i. (Camera firmware issue)<br>4. Snapshot resolution is not correspond to existing profile. (Camera firmware issue) |              |          |                |       |        |     |                |      |                      |          |                     |
| <b>NTI-50022</b>  | 5.90.0126   | H.264        | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:             | 1. H.264 only support IP mode of GOP structure. (Camera→Encoder Profile→Profile N→Expert Settings→GOP structure→IP).i. (NUUO Server limitation)<br>2. Only support G.711 audio codec.i. (Camera performance limitation)<br>3. After changing MJPEG resolution on web and getting camera setting on NUUO, resolution will return to previous setting.i. (Camera firmware issue)<br>4. Snapshot resolution is not correspond to existing profile. (Camera firmware issue) |              |          |                |       |        |     |                |      |                      |          |                     |
| <b>NUC-50022</b>  | refer to NTI-50022(5.90.0126 (26510590))  | H.264        | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| <b>NUC-51022</b>  | refer to NTI-50022(5.90.0126 (26510590))  | H.264        | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name        | Tested Firmware   | Video Format    | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|--------------------|---|-----------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| <b>NDN-265-PIO</b> | 39500570  | H.264           | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:              | <p>It can't set resolution below 1280x720 when stream2 property set to "Copy Stream 1".<br/>           When H.264 quality is set to "0", the camera will Auto-adjust the quality setting. For minimum quality, the value should be "100"<br/>           Audio AAC can't work due to NUUO platform issues.</p>   |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>NWC-455</b>     | 56500410  | H.264<br>M-JPEG | 1        | 704x576        | -     | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| Note:              | <p>Auto detect model unsupported.<br/>           H264 supports up to a maximum of 2CIF as this utilizes the Baseline Profile.<br/>           When H264 quality is set to '0', the camera will auto-adjust the quality setting. For minimum quality, the value should be '100'.<br/>           When MJPEG quality is set to '0', the camera will auto-adjust the quality setting. For minimum quality, the value should be '1'.<br/>           MJPEG frame rate depends on camera load. Value in settings dialog is not representative of actual frame rate.</p>   |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>NWC-495</b>     | 56500410  | H.264<br>M-JPEG | 1        | 704x576        | -     | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| Note:              | <p>Auto detect model unsupported.<br/>           H264 supports up to a maximum of 2CIF as this utilizes the Baseline Profile.<br/>           When H264 quality is set to '0', the camera will auto-adjust the quality setting. For minimum quality, the value should be '100'.<br/>           When MJPEG quality is set to '0', the camera will auto-adjust the quality setting. For minimum quality, the value should be '1'.<br/>           MJPEG frame rate depends on camera load. Value in settings dialog is not representative of actual frame rate.</p>   |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>NWD-455</b>     | 56500410  | H.264<br>M-JPEG | 1        | 704x576        | -     | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| Note:              | <p>Cannot auto detect model.<br/>           H264 supports up to a maximum of 2CIF as this utilizes the Baseline Profile.<br/>           When H264 quality is set to '0', the camera will auto-adjust the quality setting. For minimum quality, the value should be '100'.<br/>           When MJPEG quality is set to '0', the camera will auto-adjust the quality setting. For minimum quality, the value should be '1'.<br/>           Firmware Issue: MJPEG framerate on settings dialog is incorrect. The value is always 25.<br/>           MJPEG unstable issue. Frame rate of MJPEG stream is dependent on the camera load and can vary.</p> |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>NWD-495</b>     | 56500410  | H.264<br>M-JPEG | 1        | 704x576        | -     | -      | -   | Yes            | -    | Yes                  | -        |                     |
| Note:              | <p>Auto detect model unsupported.<br/>           H264 supports up to a maximum of 2CIF as this utilizes the Baseline Profile.<br/>           When H264 quality is set to '0', the camera will auto-adjust the quality setting. For minimum quality, the value should be '100'.<br/>           When MJPEG quality is set to '0', the camera will auto-adjust the quality setting. For minimum quality, the value should be '1'.<br/>           MJPEG frame rate depends on camera load. Value in settings dialog is not representative of actual frame rate.</p>   |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>VIP-X1XF-E</b>  | 39500570  | H.264           | 1        | 704x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:              | <p>When H264 quality is set to '0', the camera will auto-adjust the quality setting. For minimum quality, the value should be '1'.<br/>           Audio Codec support g711, not support L1, AAC.</p>  |                 |          |                |       |        |     |                |      |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name    | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|----------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| Generic        | 5.90.0112<br>(12510590)  | H.264        | 1        | 1920x1080      | 1-way | 2/2    | *2  | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:          | Support generic dewarp<br>1. H.264 only support IP mode of GOP structure. (Camera→Encoder Profile→Profile N→Expert Settings→GOP structure→IP) (NUUO Server limitation)<br>2. Only support G.711 audio codec. (Camera performance limitation)<br>3. After changing MJPEG resolution on web and getting camera setting on NUUO, resolution will return to previous setting. (Camera firmware issue)<br>4. Snapshot resolution is not correspond to existing profile. (Camera firmware issue)<br>5. Sometimes set multi-stream fail due to limitations of inter-streaming dependency.(NUUO Server limitation)<br>6. Can't set tream3 quality value. (Camera firmware issue)<br>7. Some resolution can't set framerate (NIN-733 Stream2 only support fps 7.5 under 1280x720 )(Camera performance limitation)<br>8. MJPEG framerate can't synchronize to web setting. (Camera performance limitation)<br>9. Can't set framerate 1 under base frame rate 50/60 ips mode. (Camera performance limitation)<br>10. NUUO not test ptz functions. |              |          |                |       |        |     |                |      |                      |          |                     |
| VG5-7028-C1PC4 | Refer to VG5-7130-CPT4 (6.11.0021)   | H.264        | 1        | 1280x720       | 2-way | 2/1    | Yes | Yes            | -    | Yes*                 | Yes      | Supported by design |
| VG5-7130-EPC4  | Refer to VG5-7130-CPT4 (6.11.0021)   | H.264        | 1        | 1280x720       | 2-way | 2/1    | Yes | Yes            | -    | Yes*                 | Yes      | Supported by design |
| VG5-7130-CPT4  | 6.11.0021  | H.264        | 1        | 1280x720       | 2-way | 2/1    | Yes | Yes            | -    | Yes*                 | Yes      |                     |
| Note:          | 1. Talk can't be used. (Camera Firmware issue)<br>2. The motion event we got only support when VCA of camera webpage has been open. (Camera Firmware issue)<br>3. Digital Output can be trigger by onvif command, but the status won't changed on hardware device. (Camera Firmware issue)<br>4. There are same resolution in resolution list of Low & Min. (Camera Firmware issue)  |              |          |                |       |        |     |                |      |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name          | Tested Firmware   | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks                |
|----------------------|---|--------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|------------------------|
| <b>OSD-200A 20xp</b> | gk20140422 NSA  | H.264 MJPEG        | 1        | 1920x1080      | *2    | *2     | Yes | Yes            | *2   | Yes*                 | Yes      |                        |
| Note:                | 1. Snapshot supported when one of stream choose MJPEG. (Camera firmware issue)<br>2. Error preset point. (Camera firmware issue)  |                    |          |                |       |        |     |                |      |                      |          |                        |
| <b>30xN</b>          | v3.2.2.8  | H.264 MJPEG MPEG4  | 1        | 2048x1536      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      |                        |
| Note:                | Fisheye camera<br>1. Cover model:<br>MD-300Np, FB-300Np, WFB-300Np, FD-302Np, VD-302Np, OB-302Np, OB-302Ne, WOB-302Ne, FB-200Np, OB-202Np. VD-300Np, FD-300Np, OB-300Np, WOB-300Np, GOB-300Np with zoom feature.<br>OB-300Np-AD, OB-200Np, VD-200Np with zoom and focus feature.<br>MD-300Np-360 is fisheye camera<br>2. MD-300Np and MD-300Np-360 are no support DI/DO and one way audio only.<br>3. MD-300Np-360 not support MD when format is MJPEG and MPEG4.<br>4.The RTSP stream has been disconnected in 5 minutes when the protocol is use under HTTP.<br>5.The Zoom , Focus or Auto Focus function has no response via camera web or CGI command.<br>6.The Motion Detection always triggered when the frame rate is 1.   |                    |          |                |       |        |     |                |      |                      |          |                        |
| <b>130N</b>          | v3.1.0.9  | H.264 MPEG4 M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                        |
| Note:                | OB-130Np, WOB-130Np, GOB-130Np, FD-130Np, VD-130Np. FB-130Np, WFB-130Np compare them with OB-130Np difference is w/o zoom control<br>Smart Zoom/Focus will spent 15s every time   |                    |          |                |       |        |     |                |      |                      |          |                        |
| <b>50xA series</b>   | V3.2.2.8  | H.264 MPEG4 M-JPEG | 1        | 2592x1944      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      |                        |
| Note:                | Fisheye camera<br>1. Covered model:FB-500Ap, FD-301Af, WFB-500Ap, CB-500Ap, WCB-500Ap, CB-502Ap, WCB-502Ap, FD-500Ap, FD-502Ap , VD-301Af, VD-500Ap, VD-502Ap , OB-500Af, MB-500Ap, WMB-500Ap, MD-500Ap-360, FD-301Af, VD-301Af, OB-200Ap, FB-202Ap, OB-202Ap.<br>OB-200Ap and VD-200Ap with zoom and focus function.<br>2. switch video resolution higher than 1920x1080 need waiting a period of time to reconnect stream<br>3. MD-500Ap-360 is no support DI/DO and one way audio only.<br>4. MD-500Ap-360 not support MD when format is MJPEG and MPEG4.<br>5. Support fisheye camera.<br>6.Max framerate can't sync with Wide and Ultra-Wide mode on camera web.<br>7.The RTSP stream has been disconnected in 5 minutes when the protocol is use under HTTP.<br>8.The image is broken when the format is MJPEG and resolution is 2592x1944 or 2304x1728.<br>9.The Zoom or Focus function has on response via camera web or CGI command. |                    |          |                |       |        |     |                |      |                      |          |                        |
| <b>CB-100Ae</b>      | v3.0.2.4  | MPEG4 M-JPEG       | 1        | 1280x800       | 1-way | -      | -   | -              | Yes  | Yes                  | -        | Tested by manufacturer |
| <b>CB-100A</b>       | v3.0.2.4  | H.264 MPEG4 M-JPEG | 1        | 1280x800       | 1-way | -      | -   | -              | Yes  | Yes                  |          | Tested by manufacturer |
| <b>FB-100Ae</b>      | v3.0.2.3  | MPEG4 M-JPEG       | 1        | 1280x800       | 1-way | 1/0    | -   | -              | Yes  | Yes                  | -        | Tested by manufacturer |
| <b>FB-100A</b>       | v3.0.2.3  | H.264 MPEG4 M-JPEG | 1        | 1280x800       | 1-way | 1/0    | -   | -              | Yes  | Yes                  | -        | Tested by manufacturer |
| <b>FD-100Ae</b>      | v3.0.2.3  | MPEG4 M-JPEG       | 1        | 1280x800       | 1-way | 1/0    | -   | -              | Yes  | Yes                  | -        | Tested by manufacturer |
| <b>FD-100A</b>       | v2.3.7.8  | H.264 MPEG4 M-JPEG | 1        | 1280x800       | 1-way | 1/0    | -   | -              | Yes  | Yes                  | -        |                        |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks                |
|-------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|------------------------|
| FD-130Ae    | Refer to VD-130Ap  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |          | Supported by design    |
| FD-130Ap    | Refer to VD-130Ap  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design    |
| Hydracam    | v3.2.3.4   | H.264                    | 3        | 1280x720       | 2-way | 2/2    | -   | -              | Yes  | Yes                  | -        |                        |
| Note:       | 1. Audio function is not supported.<br>2. Resolution and bitrate list is not synchronized with the camera webpage.<br>3. The video does not play smoothly when the frame rate set to 1.            |                          |          |                |       |        |     |                |      |                      |          |                        |
| OB-100Ap    | v3.1.0.8   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                        |
| OB-E200Nf   | v3.7.0.18.3u   | H.264<br>MJPEG           | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                        |
| VD-130Ae    | Refer to VD-130Ap  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design    |
| VD-130Ap    |  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |          |                        |
| VS-04A v2   | 3.5.2.15   | H.264<br>MJPEG           | 4        | 720x576        | 2-way | 4/4    | Yes | Yes            | Yes  | Yes                  | Yes      |                        |
| Note:       | 1. PTZ function doesn't work<br>2. Audio function doesn't work<br>3. The list of resolution and bitrate aren't synchronized with the camera's web  |                          |          |                |       |        |     |                |      |                      |          |                        |
| W/VS-01A    | v3.1.0.6   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                        |
| WCB-100Ae   | v3.0.2.4   | MPEG4<br>M-JPEG          | 1        | 1280x800       | 1-way | -      | -   | -              | Yes  | Yes                  |          | Tested by manufacturer |
| WCB-100A    | v2.3.7.8   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | -      | -   | -              | Yes  | Yes                  | -        |                        |
| WFB-100Ae   | v3.0.2.3   | MPEG4<br>M-JPEG          | 1        | 1280x800       | 1-way | 1/0    | -   | -              | Yes  | Yes                  | -        | Tested by manufacturer |
| WFB-100A    | v2.3.7.8   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | 1/0    | -   | -              | Yes  | Yes                  | -        |                        |
| Note:       | On-edge motion is only workable when stream 1 is MPEG4 with the bitrate under 1.5Mbps or quality under 3. We don't promise the performance of MD if the configuration isn't within the limitation. |                          |          |                |       |        |     |                |      |                      |          |                        |
| OSD/PZ-040D | v3.1.0.8   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                        |
| OSD/PZ-040E | v3.1.0.8   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                        |



Delighting You Always

- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name     | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Remarks             |
|-----------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|---------------------|
| <b>VB-S30D</b>  | Ver. 1.1.0   | MJPEG        | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 |                     |
| Note:           | Fisheye camera<br>1.The video parameters of the camera are not configurable with IP+.                    |              |          |                |       |        |     |                |      |                    |                      |                     |
| <b>VB-S31D</b>  | Refer to VB-S30D(Ver. 1.1.0)   | MJPEG        | 1        | 1920x1080      | 1-way | 1/1    | *2  | Yes            | -    | Yes                | Yes*                 | Supported by design |
| Note:           | Fisheye camera   |              |          |                |       |        |     |                |      |                    |                      |                     |
| <b>VB-S800D</b> | Ver. 1.1.0   | MJPEG        | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes*                 |                     |
| Note:           | Fisheye camera<br>1.The range of video parameters are difference between camera web and onvif responded. |              |          |                |       |        |     |                |      |                    |                      |                     |
| <b>VB-S900F</b> | Refer to VB-S800D(Ver. 1.1.0)  | MJPEG        | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes*                 | Supported by design |
| Note:           | Fisheye camera   |              |          |                |       |        |     |                |      |                    |                      |                     |
| <b>VB-S905F</b> | Ver. 1.0.0   | MJPEG        | 1        | 1280x960       | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes*                 |                     |
| Note:           | Fisheye camera<br>1.The range of video parameters are difference between camera web and onvif responded. |              |          |                |       |        |     |                |      |                    |                      |                     |
| <b>VB-S805D</b> | Refer to VB-S905F(Ver. 1.0.0)  | MJPEG        | 1        | 1280x960       | 1-way | 1/1    | -   | Yes            | -    | Yes                | Yes*                 | Supported by design |
| Note:           | Fisheye camera   |              |          |                |       |        |     |                |      |                    |                      |                     |





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name         | Tested Firmware  | Video Format   | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|---------------------|--|----------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| <b>DCS30HDIR30</b>  | v1.8.0601.10<br>01.93.0.65.1.0   | H.264<br>MJPEG | 1        | 2048x1536      | 2-way | 1/1    | Yes | Yes            | -    | Yes*                 |         |
| Note:               | 1.The bitrate type will be VBR under H.264 after set camera parameter.(Camera Firmware issue)<br>2.The Max bitrate was wrong under H.264.(Camera Firmware issue)<br>3.The ranges of bitrate and framerate may be different from camera web. (Camera Firmware issue)<br>4.Motion detection is not supported on MJPEG. (Camera Firmware issue) |                |          |                |       |        |     |                |      |                      |         |
| <b>DCS20HDIRE3V</b> | v1.8.0801.10<br>01.93.0.66.1.0   | H.264<br>MJPEG | 1        | 1920x1080      | 2-way | -      | -   | Yes            | -    | Yes*                 |         |
| Note:               | 1.The bitrate type will be VBR under H.264 after set camera parameter.(Camera Firmware issue)<br>2.The Max bitrate was wrong under H.264.(Camera Firmware issue)<br>3.The ranges of bitrate and framerate may be different from camera web. (Camera Firmware issue)<br>4.Motion detection is not supported on MJPEG. (Camera Firmware issue) |                |          |                |       |        |     |                |      |                      |         |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name    | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|----------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| <b>B13H</b>    | v1.1.0.0  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| <b>C10</b>     | refer to C10-W  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | Yes                  | Supported by design |
| <b>C10-W</b>   | v1.1.0.0(buil<br>d2)  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | Yes                  |                     |
| <b>D13HD</b>   | v1.1.0.0  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| <b>Generic</b> | cx20141008<br>NSA   | H.264<br>M-JPEG          | 1        | 1920x1080      | 2-way | 4/2    | Yes | Yes            | -    | Yes*                 | Supported by design |
| <b>Note:</b>   | Support generic dewarp<br>1. It can't stop pan & tilt sometimes. (Camera performance limitation)<br>2.It can't set zoom speed. (Camera Firmware issue)<br>3.It should set one stream in MJPEG, the snapshot will work. (Camera Firmware issue)<br>4.If set preset point too fast, it will set wrong point. (Camera performance limitation)<br>5.The resolution setting doesn't sync with web. (Camera Firmware issue) |                          |          |                |       |        |     |                |      |                      |                     |
| <b>W13H</b>    | v1.1.0.0(buil<br>d2)  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format            | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|-------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| BL3102      | 03_C002  | H.264<br>MJPEG          | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| Note:       | 1. Framerate is unable to achieve setting value in MJPEG 1920x1080. (Camera performance limitation)  |                         |          |                |       |        |     |                |      |                      |          |                     |
| DM3102      | 03_C002  | H.264<br>MJPEG          | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| Note:       | 1. Framerate is unable to achieve setting value in MJPEG 1920x1080. (Camera performance limitation)  |                         |          |                |       |        |     |                |      |                      |          |                     |
| BL5105      | 01_C018  | H.264<br>H.265<br>MJPEG | 1        | 2560x1920      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| Note:       | 1. Camera web does not have WDR setting. (Camera Firmware issue)<br>2. Quality list can not sync with web. (Camera Firmware issue)   |                         |          |                |       |        |     |                |      |                      |          |                     |
| DM5115      | 01_C017  | H.264<br>H.265<br>MJPEG | 1        | 2560x1920      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| BL5302      | 02   | H.264<br>MJPEG          | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| Note:       | 1. Framerate is unable to achieve to setting value in 1920x1080. (Camera performance limitation)   |                         |          |                |       |        |     |                |      |                      |          |                     |
| DM5302      | 02_C022  | H.264<br>MJPEG          | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| Note:       | 1. Audio has noise with AMR. (Camera Firmware issue)<br>2. Camera with highest resolution is unable to achieve maximum FPS. (Camera performance limitation)<br>3.PTZ only support zoom & focus.  |                         |          |                |       |        |     |                |      |                      |          |                     |
| BL7302      | 01_C013  | H.264<br>MJPEG          | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Audio has noise with AMR. (Camera Firmware issue)<br>2. Camera is unable to achieve maximum FPS. (Camera performance limitation)<br>3. Move can't not move to center. (Camera Firmware issue) |                         |          |                |       |        |     |                |      |                      |          |                     |
| BL7305      | 01_C013  | H.264<br>MJPEG          | 1        | 2560x1920      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| DM5113      | Refer to<br>Zavio<br>(01_C014)   | H.264<br>H.265<br>MJPEG | 1        | 2048x1536      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format            | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|-------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| DM7302      | 01_C013   | H.264<br>MJPEG          | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Audio has noise. (Camera Firmware issue)<br>2. G.726 does not supported. (NUUO server limitation)  |                         |          |                |       |        |     |                |      |                      |          |                     |
| DM7305      | 01_C010   | H.264<br>MJPEG          | 1        | 2560x1920      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| BL5103      | 01_C018   | H.264<br>H.265<br>MJPEG | 1        | 2048x1536      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| Note:       | 1. Display mosaic happen in 2304x1296 MJPEG. (Camera performance limitation)<br>2. Quality list can not sync with web. (Camera Firmware issue)<br>3. Bitrate list can not sync with web in MJPEG. (Camera Firmware issue) |                         |          |                |       |        |     |                |      |                      |          |                     |
| DM5103      | 01_C013   | H.264<br>H.265<br>MJPEG | 1        | 2048x1520      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| Note:       | 1. Display mosaic happen in 2304x1296 MJPEG. (Camera performance limitation)<br>2. Quality list can not sync with web. (Camera Firmware issue)<br>3. Bitrate list can not sync with web in MJPEG. (Camera Firmware issue) |                         |          |                |       |        |     |                |      |                      |          |                     |
| FE5403      | Refer to<br>Zavio<br>P4320<br>(01_C013)   | H.264<br>MJPEG          | 1        | 2048x1520      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| FE5405      | Refer to<br>Zavio<br>P4520(01_<br>C013)   | H.264<br>MJPEG          | 1        | 2560x1920      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name           | Tested Firmware                                  | Video Format    | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|-----------------------|--|-----------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| <b>CIVS-IPC-2500</b>  | V1.1.3R15  | MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 2/2    | -   | -              | Yes  | -                    |                     |
| <b>CIVS-IPC-2500W</b> | V1.1.3R03  | MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 2/2    | -   | -              | Yes  | -                    |                     |
| <b>PVC-300</b>        | 1.0.0  | MPEG4<br>M-JPEG | 1        | 640x480        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| Note:                 | PTZ is only supported by external RS-485 device. |                 |          |                |       |        |     |                |      |                      |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Remark              |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|---------------------|
| IBE3815 NVR |   | H.264<br>MPEG4<br>M-JPEG | 1        | 704x480        | 1-way | -      | Yes | -              | Yes  | -                  | Yes                  | Supported by design |
| IBE3815P VR |   | H.264<br>MPEG4<br>M-JPEG | 1        | 704x576        | 1-way | -      | Yes | -              | Yes  | -                  | Yes                  | Supported by design |
| IBE5810 NCR |   | H.264<br>MPEG4<br>M-JPEG | 1        | 704x480        | 1-way | -      | Yes | -              | Yes  | -                  | Yes                  | Supported by design |
| IBE5810P CR |   | H.264<br>MPEG4<br>M-JPEG | 1        | 704x576        | 1-way | -      | Yes | -              | Yes  | -                  | Yes                  | Supported by design |
| IBP5030C R  | XNET.A1-<br>2.01.13.02<br>04  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:       | In the MJPEG format, the fps is not enough when resolution is XGA or SXGA.  |                          |          |                |       |        |     |                |      |                    |                      |                     |
| IDC4000 T   | XNET.T1-<br>1.0.13.042<br>4   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  |                     |
| Note:       | IDC4000T: XNET.T1-1.0.13.0424<br>1. When setting Video MPEG with CBR in 4000 bitrate on camera web, the CGI will return incorrect video bitrate. It causes software show incorrect item "1M".<br>2. When trigger DI, DO will be triggered simultaneously.<br>3. 2nd stream format is MPEG4. |                          |          |                |       |        |     |                |      |                    |                      |                     |
| IDC4050F    | XNET.M1-<br>3.00.13.02<br>04  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:       | 1. Cannot set bitrate 128kbps when the resolution is D1 or VGA. It is firmware issue.<br>2. When it selects MJPEG, 1fps, the actually received fps is 6.  |                          |          |                |       |        |     |                |      |                    |                      |                     |
| IDC4050I R  | XNET.M1-<br>3.00.13.02<br>04  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:       | 1. Cannot set bitrate 128kbps when the resolution is D1 or VGA. It is firmware issue.<br>2. When it selects MJPEG, 1fps, the actually received fps is 6.  |                          |          |                |       |        |     |                |      |                    |                      |                     |
| IDC4050 VF  | XNET.M1-<br>3.00.13.11<br>25  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  |                     |
| Note:       | 1. Cannot set bitrate 128kbps when the resolution is D1 or VGA. It is firmware issue.<br>2. When it selects MJPEG, 1fps, the actually received fps is 6.  |                          |          |                |       |        |     |                |      |                    |                      |                     |
| IDC4050 VR  | Refer to<br>IDC4050VF<br>(XNET.M1-<br>3.00.13.11  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:       | 1. Cannot set bitrate 128kbps when the resolution is D1 or VGA. It is firmware issue.<br>2. When it selects MJPEG, 1fps, the actually received fps is 6.  |                          |          |                |       |        |     |                |      |                    |                      |                     |
| IDP4000 VD  | XNET.A1-<br>1.1.9.1104  | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | 1-way | -      | -   | -              | Yes  | -                  | Yes                  |                     |
| IDP4000 VR  | XNET.A1-<br>1.1.9.1104  | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | 1-way | -      | -   | -              | Yes  | -                  | Yes                  |                     |
| IDP4030 VR  | XNET.A1-<br>2.01.13.02<br>04  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:       | In the MJPEG format, the fps is not enough when resolution is XGA or SXGA.  |                          |          |                |       |        |     |                |      |                    |                      |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name         | Tested Firmware  | Video Format       | Video Ch | Max Resolution           | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Remark              |
|---------------------|--|--------------------|----------|--------------------------|-------|--------|-----|----------------|------|--------------------|----------------------|---------------------|
| <b>IDP5035 VR</b>   | XNET.M2-3.00.13.0204   | H.264              | 1        | 1280x1024                | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:               | Firmware issue, failed to set bitrate as 128k over VGA/D1.   |                    |          |                          |       |        |     |                |      |                    |                      |                     |
| <b>IGC2050F</b>     | XNET.M1-3.00.13.0204   | H.264 M-JPEG       | 1        | 1920x1080                | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  |                     |
| Note:               | 1. Cannot set bitrate 128kbps when the resolution is D1 or VGA. It is firmware issue.<br>2. When it selects MJPEG, 1fps, the actually received fps is 6. |                    |          |                          |       |        |     |                |      |                    |                      |                     |
| <b>IGP1000</b>      |  | H.264 MPEG4 M-JPEG | 1        | 640x480                  | 1-way | -      | Yes | -              | Yes  | -                  | -                    | Supported by design |
| <b>IGP1030</b>      | XNET.A1-2.01.13.0204   | H.264 MPEG4 M-JPEG | 1        | 1280x960                 | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  |                     |
| Note:               | In the MJPEG format, the fps is not enough when resolution is XGA or SXGA.   |                    |          |                          |       |        |     |                |      |                    |                      |                     |
| <b>IGP2035F</b>     | XNET.M2-3.00.13.0204   | H.264              | 1        | 1280x1024                | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  |                     |
| Note:               | Firmware issue, failed to set bitrate as 128k over VGA/D1.   |                    |          |                          |       |        |     |                |      |                    |                      |                     |
| <b>IJB2000</b>      |  | H.264 MPEG4 M-JPEG | 1        | 704x576                  | 1-way | -      | Yes | -              | Yes  | -                  | -                    | Supported by design |
| <b>INS2000</b>      | XNET.A1-2.01.13.0902   | H.264 MPEG4 M-JPEG | 1        | 704x576                  | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  |                     |
| Note:               | 1. Could not reach up to maximum FPS<br>2. Audio choppy with G.711   |                    |          |                          |       |        |     |                |      |                    |                      |                     |
| <b>IPM3063 N</b>    |  | H.264 MPEG4 M-JPEG | 1        | 704x480                  | 1-way | -      | Yes | -              | Yes  | -                  | -                    | Supported by design |
| <b>IPM3063 P</b>    |  | H.264 MPEG4 M-JPEG | 1        | 704x576                  | 1-way | -      | Yes | -              | Yes  | -                  | -                    | Supported by design |
| <b>IS1765x</b>      | Refer to ISMC1063x   | H.264 MPEG4 M-JPEG | 1        | 704x480(N)<br>704x576(P) | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | -                    | Supported by design |
| <b>ISMC1063N</b>    |  | H.264 MPEG4 M-JPEG | 1        | 704x480                  | 1-way | -      | Yes | Yes            | Yes  | -                  | -                    | Supported by design |
| <b>ISMC1063x</b>    | XNET.A1-2.01.13.0204   | H.264 MPEG4 M-JPEG | 1        | 704x480(N)<br>704x576(P) | 1-way | 4/0    | Yes | Yes            | Yes  | -                  | Yes                  |                     |
| Note:               | ISMC1063x includes ISMC1063P and ISMC1063N<br>1. Not support Audio codec G.726 when using TCP connection.  |                    |          |                          |       |        |     |                |      |                    |                      |                     |
| <b>ISS2765 NW</b>   |  | H.264 MPEG4 M-JPEG | 1        | 704x480                  | 1-way | -      | Yes | -              | Yes  | -                  | -                    | Supported by design |
| <b>ISS2765P W</b>   |  | H.264 MPEG4 M-JPEG | 1        | 704x576                  | 1-way | -      | Yes | -              | Yes  | -                  | -                    | Supported by design |
| <b>ISS2965x</b>     | Refer to ISMC1063x   | H.264 MPEG4 M-JPEG | 1        | 704x480(N)<br>704x576(P) | 1-way | 4/0    | Yes | Yes            | Yes  | -                  | -                    | Supported by design |
| <b>ISS4032Z 28W</b> | XNET.M2-3.00.13.0204   | H.264              | 1        | 1280x1024                | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:               | Firmware issue, failed to set bitrate as 128k over VGA/D1.   |                    |          |                          |       |        |     |                |      |                    |                      |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name       | Tested Firmware   | Video Format             | Video Ch | Max Resolution           | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Remark              |
|-------------------|---|--------------------------|----------|--------------------------|-------|--------|-----|----------------|------|--------------------|----------------------|---------------------|
| <b>ISSM206 3x</b> | Refer to ISMC1063x  | H.264<br>MPEG4<br>M-JPEG | 1        | 704x480(N)<br>704x576(P) | 1-way | 4/0    | Yes | Yes            | Yes  | -                  | -                    | Supported by design |
| <b>IVC5055 VF</b> | Refer to IDC4050IR  | H.264<br>M-JPEG          | 1        | 1920x1080                | 1-way | 1/1    | -   | Yes            | Yes  | -                  | -                    | Supported by design |
| <b>IVC5055 VR</b> | Refer to IDC4050VF (XNET.M1-3.00.13.1125)   | H.264<br>M-JPEG          | 1        | 1920x1080                | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:             | 1. Cannot set bitrate 128kbps when the resolution is D1 or VGA. It is firmware issue.<br>2. When it selects MJPEG, 1fps, the actually received fps is 6.  |                          |          |                          |       |        |     |                |      |                    |                      |                     |
| <b>IVP4000 VR</b> | XNET.A1-1.1.9.1028  | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480                  | 1-way | -      | -   | -              | Yes  | -                  | Yes                  |                     |
| <b>IVP4030 VR</b> |   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960                 | 1-way | -      | -   | -              | Yes  | -                  | Yes                  | Supported by design |
| <b>IVP4030 VR</b> | XNET.A1-2.01.13.0204  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960                 | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:             | In the MJPEG format, the fps is not enough when resolution is XGA or SXGA.  |                          |          |                          |       |        |     |                |      |                    |                      |                     |
| <b>IVP5035 VR</b> | Refer to IGP2035F (XNET.M2-2.00.12.1026)  | H.264                    | 1        | 1280x1024                | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| <b>IVP5035 VR</b> | XNET.M2-3.00.13.0204  | H.264                    | 1        | 1280x1024                | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:             | Firmware issue, failed to set bitrate as 128k over VGA/D1.  |                          |          |                          |       |        |     |                |      |                    |                      |                     |
| <b>IXC2050IR</b>  | XNET.M1-3.00.13.0204  | H.264<br>M-JPEG          | 1        | 1920x1080                | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:             | 1. Cannot set bitrate 128kbps when the resolution is D1 or VGA. It is firmware issue.<br>2. When it selects MJPEG, 1fps, the actually received fps is 6.  |                          |          |                          |       |        |     |                |      |                    |                      |                     |
| <b>IXP3035 VR</b> | XNET.M2-3.00.13.0204  | H.264                    | 1        | 1280x1024                | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:             | Firmware issue, failed to set bitrate as 128k over VGA/D1.  |                          |          |                          |       |        |     |                |      |                    |                      |                     |
| <b>MPC1070 PN</b> | 1.0.46  | H.264<br>MJPEG           | 1        | 2592x1944                | 2-way | -      | -   | Yes            | Yes  | -                  | Yes                  |                     |
| Note:             | 1. Fisheye camera<br>1. (Camera performance limitation) Camera is unable to achieve maximum FPS.<br>2. (Camera firmware issue) Audio stutter with G.711.<br>3. (Camera performance limitation) MJPEG bitrate setting is restricted by fps setting.<br>4. (Camera performance limitation) 2nd stream and 3rd stream are unable to achieve 500k/100k bps. |                          |          |                          |       |        |     |                |      |                    |                      |                     |
| <b>NDE5055 MF</b> | XNET.N1-1.02.13.0204  | H.264                    | 1        | 1920x1080                | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:             | 1. Video connection cannot establish when the setting of bitrate is 9M or 10M.  |                          |          |                          |       |        |     |                |      |                    |                      |                     |





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name       | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Remark              |
|-------------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|---------------------|
| <b>NDE5055 VR</b> | XNET.N1-1.02.13.0204   | H.264        | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:             | 1. Video connection cannot establish when the setting of bitrate is 9M or 10M.   |              |          |                |       |        |     |                |      |                    |                      |                     |
| <b>NGE2055 F</b>  | XNET.N1-1.02.13.0204   | H.264        | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  |                     |
| Note:             | 1. Video connection cannot establish when the setting of bitrate is 9M or 10M.   |              |          |                |       |        |     |                |      |                    |                      |                     |
| <b>NVE5055 MF</b> | XNET.N1-1.02.13.0204   | H.264        | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:             | 1. Video connection cannot establish when the setting of bitrate is 9M or 10M.   |              |          |                |       |        |     |                |      |                    |                      |                     |
| <b>NVE5055 VR</b> | XNET.N1-1.02.13.0204   | H.264        | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:             | 1. Video connection cannot establish when the setting of bitrate is 9M or 10M.   |              |          |                |       |        |     |                |      |                    |                      |                     |
| <b>NXE3055 MR</b> | XNET.N1-1.02.13.0204   | H.264        | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:             | 1. Video connection cannot establish when the setting of bitrate is 9M or 10M.   |              |          |                |       |        |     |                |      |                    |                      |                     |
| <b>NXE3055 VR</b> | XNET.N1-1.02.13.0204   | H.264        | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | Supported by design |
| Note:             | 1. Video connection cannot establish when the setting of bitrate is 9M or 10M.   |              |          |                |       |        |     |                |      |                    |                      |                     |
| <b>MVC2050 VR</b> | 3.4.2  | H.264        | 1        | 1920x1080      | -     | -      | -   | Yes            | -    | Yes                | Yes*                 |                     |
| Note:             | 1.Motion can't be used when the camera connected about 1 min. [Camera Firmware Issue]<br>2.Camera search fail if UPnP enable on camera web. [NUUO server limitation]<br>3.The audio function can't be used. [Camera Firmware Issue]<br>4.There has only support FPS up to 10 when the resolution is 1280x720. [Camera Firmware Issue]<br>5.The bitrate list was different from camera web. [Camera Firmware Issue] |              |          |                |       |        |     |                |      |                    |                      |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name  | Tested Firmware   | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|--------------|---|--------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| DCS-1100     | 1.00  | MPEG4 M-JPEG       | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | -                    | -        | Supported by design |
| DCS-1100L    | 1.03_4130   | MPEG4 M-JPEG       | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| DCS-1130     | 1.00  | MPEG4 M-JPEG       | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | -                    | -        | Supported by design |
| DCS-1130L    | 1.03_4130   | MPEG4 M-JPEG       | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| DCS-1201     | V0.00.01  | H.264 MPEG4 M-JPEG | 1        | 1280x720       | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| DCS-1301     | V0.01.00  | H.264 MPEG4 M-JPEG | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:        | The resolution and bitrate list may not be synchronized with camera web.(Camera Firmware issue)   |                    |          |                |       |        |     |                |      |                      |          |                     |
| DCS-2100     |   | H.263              | 1        | 720x576        | 1-way | -      | -   | Yes            | Yes  | -                    | -        | Supported by design |
| DCS-2100G    |   | H.263              | 1        | 720x576        | 1-way | -      | -   | Yes            | Yes  | -                    | -        | Supported by design |
| DCS-2102     |   | MPEG4 M-JPEG       | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| DCS-2103     | V1.20   | H.264 MPEG4 M-JPEG | 1        | 1280x800       | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:        | 1. Camera cannot achieve maximum fps. (Camera performnace limitation)   |                    |          |                |       |        |     |                |      |                      |          |                     |
| DCS-2103B1   | Refer to DCS-2132LB(V2.00.05)   | H.264 M-JPEG       | 1        | 1280x720       | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| DCS-2120     |   | MPEG4              | 1        | 720x576        | 1-way | -      | -   | Yes            | Yes  | -                    | -        | Supported by design |
| DCS-2120(TW) | 0201tw  | MPEG4              | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        |                     |
| DCS-2121     |   | MPEG4 M-JPEG       | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  |                      | -        | Supported by design |
| DCS-2130     | Refer to DCS-2103(1.20.00)  | H.264 MPEG4 M-JPEG | 1        | 1280x800       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| DCS-2132L    | 1.00.06   | H.264 MPEG4 M-JPEG | 1        | 1280x800       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| DCS-2132LB   | V2.00.05  | H.264 M-JPEG       | 1        | 1280x720       | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:        | 1. Audio-out will happen the loss of function when change the camera parameters. (Camera Firmware issue)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Sometimes motion can not be used. (Camera Firmware issue)<br>4.Resolution list does not synchronize with camera web, that cause all stream connection fail when a stream of the resolution sets to an out of boundary. (Camera Firmware issue) |                    |          |                |       |        |     |                |      |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| DCS-2132LB1 | v2.00.05   | H.264<br>M-JPEG          | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | Yes  | -                    | Yes      |                     |
| Note:       | 1. Not support TCP/UDP. (Camera Firmware issue)<br>2. Talk is not clear. (Camera performance limitation)<br>3. The probability of the audio out becomes invalid when changing a parameter of streams. (Camera performance limitation)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-2136L   | V1.03.00   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x720       | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| DCS-2210    | v1.22  | H.264<br>MPEG4<br>MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. In aspect 4:3 mode, the framerate list of CGI is not synchronized with the camera web when a stream sets to 1440x1080 resolution. (Camera Firmware issue)<br>2. When the stream 1 with highest resolution, the stream 2,3 are unable to achieve the setting framerate. (Camera performance issue)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-2210L   | Refer to DCS-2230L(v0.03.00)   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| DCS-2230    | Refer to DCS-2210(v1.22)   | H.264<br>MPEG4<br>MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| DCS-2230L   | v0.03.00   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:       | 1. The talk function can't be work. (Camera Firmware issue)<br>2. When the stream 1 with highest resolution, the stream 2,3 are unable to achieve the setting framerate. (Camera performance issue)<br>3. Stream 1 FPS will drop with the resolution large than 1024x768 when stream 2 or stream 3 connects in the same time. (Camera Performance issue) |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-2310L   | Refer to DCS-2332L(1.02.00)  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| DCS-2310LB1 | 0.03.00  | H.264<br>MJPEG           | 1        | 1280x720       | 1-way | -      | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:       | 1. Control mode of resolution, framerate, bitrate cannot be changed under H.264 format. (Camera firmware issue)<br>2. The name of this camera in search window will show as DCS-2310L. (Camera firmware issue)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-2330L   | V1.00.01   | H.264<br>M-JPEG          | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. not support TCP/UDP<br>2. not support talk<br>3. The list of resolution is not synchronized with camera web. (Camera Firmware issue)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-2332L   | 1.02.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 2-way | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Fps can not achieve to setting value. (Camera performance limitation)<br>2. Stream 3's settings would not syn. with camera web. (Camera firmware issue)<br>3. Resolution list may not sync with web. (Camera firmware issue)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-3010    | v1.12.07   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 2-way | -      | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:       | 1. Stream would disconnect and motion would not be triggered due to camera limited performance. (Camera firmware issue)  |                          |          |                |       |        |     |                |      |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| DCS-3110    |   | MPEG4<br>M-JPEG          | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| DCS-3112    | v1.11.01  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. DI can not work. (Camera Frimware issue)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-3130    | V0.2.99_12<br>1014  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | -                    | -        |                     |
| DCS-3220    |   | MPEG4                    | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| DCS-3220G   |   | MPEG4                    | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        |                     |
| DCS-3410    |   | MPEG4<br>M-JPEG          | 1        | 704x576        | 1-way | 2/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| DCS-3411    | 1.02_4125   | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | 1-way | 2/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DCS-3415    | 1.00  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | DCS-3415 PTZ Support: zoom only.  |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-3420    | 1.03  | MPEG4<br>M-JPEG          | 1        | 704x480        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        |                     |
| DCS-3430    | 1.02_4125   | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | 1-way | 2/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DCS-3511    | v1.10.13  | H.264<br>MPEG4<br>MJPEG  | 1        | 1280x800       | 2-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. When sending a RS-485 command, the live view will be disconnected in a few seconds. (Camera Firmware issue)<br>2. Audio out can not work. (Camera Firmware issue)<br>3. Audio stutter with AAC and G.711, and G.711 is not clear. (Camera performance issue)<br>4. The digital output(DO) connector follows digital input(DI) to change status when DI is triggered. (Camera Firmware issue) |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-3530    | Refer to<br>DCS-<br>3511(v1.00.<br>06)  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| DCS-3710    | 1.00  | MPEG4<br>M-JPEG          | 1        | 1280x960       | 1-way | 2/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DCS-3710B1  | V0.02.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Because the CGI content does not include qualitymode field, the bitrate control mode is not synchronized with camera web. (Camera Firmware issue)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-3713    |   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 2/1    | -   | Yes            |      | Yes                  | -        |                     |
| DCS-3714    | v1.00.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x720       | 2-way | 2/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Not support 8M bitrate. (Camera Firmware issue)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-3715    | v1.20   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | -                    | Yes      |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name  | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|--------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| DCS-3716     | V1.00.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:        | 1. The quality setting of M-JPEG is unavailable. (camera Firmware issue)<br>2. The main stream of resolution and frame rate list are different with camera web in MPEG4. (camera Firmware issue)<br>3. The camera with highest resolution is unable to achieve the setting framerate. (camera performance limitation)<br>4. The frame rate list is different with camera web when resolution set to 2048x1536. (camera Firmware issue)<br>5. The 2nd stream with any resolution is unable to achieve the setting bitrate in MPEG4. (camera performance limitation)<br>6. Talk function has stutter. (camrea Firmware issue)<br>7. The camera of all profiles with highest setting are unable to achieve the setting framerate.(camera performance limitation)<br>8. Bit rate can not achieve web setting in any setting.(camera performance limitation) |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-4201     | V1.00.02  | H.264<br>M-JPEG          | 1        | 1280x720       | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:        | 1. The 2nd stream can not set to resolution 1280x720, when stream1 resolution is 1280x720.(Camera Firmware issue)<br>2. The camera with highest resolution is unable to achieve the setting framerate.(Camera performance limitation)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-4602EV   | V1.00.01  | H.264<br>MJPEG           | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:        | 1. The camera with highest resolution is unable to achieve the setting framerate in MJPEG. (Camera performance limitation)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-4701E    | V1.00.02  | H.264<br>M-JPEG          | 1        | 1280x720       | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:        | 1. Stream 1 with MJPEG, resolution 1280*720 can not achieve maximum FPS. (Camera Firmware issue)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-4802E    | Refer to<br>DCS-4602EV(V1.00.01)  | H.264<br>MJPEG           | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| DCS-5010L    | Refer to<br>DCS-5020L(1.01)   | H264<br>MJPEG            | 1        | 640x480        | 1-way | -      | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| DCS-5020L    | 1.01  | H264<br>MJPEG            | 1        | 640x480        | 1-way | -      | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DCS-5211L    | 1.10  | H.264<br>MPEG4           | 1        | 1280x720       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| Note:        | 1. Only can patrol one times. (Camera firmware limitation)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-5220     | 0200  | MPEG4                    | 1        | 720x576        | 1-way | -      | Yes | Yes            | Yes  | -                    | -        |                     |
| DCS-5220 Bx  | 2.00  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DCS-5220(TW) |   | MPEG4                    | 1        | 720x576        | 1-way | -      | Yes | Yes            | Yes  | -                    | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| DCS-5222L   | 1.10  | H.264<br>MPEG4           | 1        | 1280x720       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | 1. Only can patrol one times. (Camera firmware limitation)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-5222LB  | Refer to DCS-5222LB1(v2.01.05)  | H.264<br>M-JPEG          | 1        | 1280x720       | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| DCS-5222LB1 | 2.01.05   | H.264<br>M-JPEG          | 1        | 1280x720       | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| DCS-5222LB2 | Refer to DCS-5222LB1(2.01.05)   | H.264<br>M-JPEG          | 1        | 1280x720       | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| DCS-5230    | 1.02_4317   | MPEG4<br>M-JPEG          | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DCS-5230L   | 1.02_4317   | MPEG4<br>M-JPEG          | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DCS-5300    | 1.05  | H.263                    | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        |                     |
| DCS-5300G   |   | H.263                    | 1        | 720x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design |
| DCS-5605    | 1.01, 4126  | H.264<br>MPEG4<br>M-JPEG | 1        | 740x480        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DCS-5610    |   | MPEG4<br>M-JPEG          | 1        | 720x576        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| DCS-5615    | 1.00.02   | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/0    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DCS-5635    | 1.01, 4126  | H.264<br>MPEG4<br>M-JPEG | 1        | 740x480        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DCS-6004L   | v0.00.01  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 2-way | -      | -   | Yes            | Yes  | -                    | Yes      |                     |
| Note:       | DCS-6004L:<br>1. Resolution 176x144 and bitrate 8M are not the same as camera web. (Camera firmware issue)                  |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-6005L   | Refer to DCS-6004L(0.00.01)   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| DCS-6010L   | v1.12.02  | H.264<br>MPEG4<br>MJPEG  | 1        | 1600x1200      | 2-way | -      | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. The resolution is changed to 1600x1200, that the display mode of fisheye is enforced to 4R mode. (Camera Firmware issue) |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-6045L   | V1.00b3   | H.264                    | 1        | 1280x720       | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| DCS-6110    | 1.00  | M-JPEG                   | 1        | 720x576        | -     | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks                |
|-------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|------------------------|
| DCS-6111    | 1.00   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                        |
| DCS-6112    | v2.10.02   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      |                        |
| Note:       | camera issue: 1.The camera with highest quality and MJPEG format is unable to achieve 30 fps<br>2.The audio talk is not supported  |                          |          |                |       |        |     |                |      |                      |          |                        |
| DCS-6112B1  | v3.00.00   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      |                        |
| Note:       | 1.The camera with highest quality and MJPEG format is unable to achieve 30 fps. (Camera performance issue)<br>2.The audio talk is not supported. (Camera Firmware issue)   |                          |          |                |       |        |     |                |      |                      |          |                        |
| DCS-6112V   |  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                        |
| DCS-6113    | refer to<br>DCS-<br>6112(v2.10.<br>02)   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by<br>design |
| DCS-6113B1  | v3.00.00   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                    | Yes      |                        |
| Note:       | 1. The camera with highest quality and MJPEG format is unable to achieve 30 fps. (Camera Firmware issue)<br>2. The audio talk is not supported.  |                          |          |                |       |        |     |                |      |                      |          |                        |
| DCS-6113V   |  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                        |
| DCS-6113VB1 | refer to<br>DCS-<br>6112B1(v3.<br>00.00)   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by<br>design |
| DCS-6115    | v0.09.00   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x720       | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                        |
| Note:       | 1.In highest parameter setting with MJPEG are unable to achieve sufficient FPS.(Camera performance limitation)<br>2. Multi-Stream Settings in auto mode bitrate will too high. (Camera Firmware issue)   |                          |          |                |       |        |     |                |      |                      |          |                        |
| DCS-6116    | v1.00.09   | H.264<br>MJPEG           | 1        | 2048x1536      | 2-way | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                        |
| Note:       | 1. When snapshot from camera, it will return a JPEG image with resolution 640x360(aspect ratio 16:9), or 640x480(aspect ratio 4:3). (Camera limitaion)<br>2. Frame rate lists are not sync with camera web on 50Hz. (Camera Firmware Issue)<br>3. Camera setting of speaker and mic switch doesn't synchronize with camera web. The status of them are in contrast. (Camera Firmware Issue)<br>4. Talk function with Alaw codec cannot work. (Camera Firmware Issue) |                          |          |                |       |        |     |                |      |                      |          |                        |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| DCS-6210    | v1.00.06  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Flip and Mirror of CGI are contrary the camera web. (Camera Firmware issue)<br>2. When move the camera, the camera is easily disconnect. (Camera performance limitation)<br>3. Audio has noise by using internal microphone. (Camera performance limitation)<br>4. In MJPEG, the live view displays 480x264 but the camera setting is 480x270. (Camera Firmware issue)<br>5. Each stream with any format and highest parameter setting are unable to achieve sufficient FPS. (Camera performance limitation)<br>6. The camera with highest setting is unable to achieve sufficient FPS in MJPEG. (Camera performance limitation)<br>7. The CGI's framerate and bitrate list is not same as camera web in the different resolution. (Camera Firmware issue)<br>8. Camera is unable achieve sufficient FPS with over 4M bitrate. (Camera Firmware issue)<br>9. In MPEG4 and MJPEG, the resolution list is not same as camera web.(Camera Firmware issue)<br>10. In MJPEG, the live view displays 800x448 but the camera setting is 800x450. (Camera Firmware issue)<br>11. When the format changes to MPEG4 before format is H.264 or MJPEG with the 176x144 resolution, the display will mosaic.(Camera performance limitation) |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-6212L   | 0.01.00   | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| DCS-6314    | v1.01   | H.264<br>MPEG4<br>MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1.Camera with highest resolution is unable to achieve maximum FPS in any format. (Camera performance issue)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-6315    | Refer to DCS-6115(V0.09.00)   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x720       | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| DCS-6410    | 1.00  | MPEG4<br>M-JPEG          | 1        | 704x576        | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| DCS-6510    | v1.02   | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | *2    | *2     | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. When snapshot from camera, it will return a JPEG image with resolution 640x360(aspect ratio 16:9), or 640x480(aspect ratio 4:3). (Camera limitaion)<br>2. Audio and I/O can not test without connector.  |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-6511    | V1.12.04  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. PTZ only support zoom and focus.<br>2. When changing format from others format to MPEG4, the resolution "176x144" is not synchronized with resolution list. (Camera Firmware issue)<br>3. Camera is unable to achieve maximum FPS. (Camera performance limitation)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-6513    | 1.02.00   | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. PTZ only supports focus.<br>2. In aspect ratio 4:3, the resolution of profile2 can't set 2048x1536 with H.264 and MJPEG.(Camera Firmware issue)<br>3. We can't integrate zoom function in our system, due to CGI request only has get operation by defining NIPCA 1.9.5.(Camera Firmware issue)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-6515    | Refer to DCS-7518(v1.00.00)   | H.264                    | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| DCS-6517    | Refer to DCS-7517(1.00.03)  | H.264 MJPEG        | 1        | 2560x1920      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| DCS-6616    | 0.01.00   | H.264 MPEG4 M-JPEG | 1        | 720x480        | 1-way | 8/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DCS-6620    | 1.05  | MPEG4 M-JPEG       | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        |                     |
| DCS-6620G   | 1.05  | MPEG4 M-JPEG       | 1        | 720x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        |                     |
| DCS-6815B1  | 0.01.00   | H.264 MPEG4 M-JPEG | 1        | 720x480        | 1-way | 8/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DCS-6817B1  | 0.01.00   | H.264 MPEG4 M-JPEG | 1        | 720x480        | 1-way | 8/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DCS-6818B1  | 0.01.00   | H.264 MPEG4 M-JPEG | 1        | 720x480        | 1-way | 8/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DCS-6915    | v1.00.10  | H.264              | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DCS-6915B1  | refer to DCS-6915(v1.00.10)   | H.264              | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| DCS-7000L   | v0.09.00  | H.264 M-JPEG       | 1        | 1280x720       | 1-way | -      | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:       | 1. The parameters of the camera are not configurable with H.264 format. (Camera Firmware issue)<br>2. The format of the camera is not configurable from MJPEG to H.264. (Camera Firmware issue)<br>3. The camera with highest quality/resolution and MJPEG format is unable to achieve 30 fps. (Camera Firmware issue)<br>4. Sever format list is not same as camera web format list. (Camera Firmware issue) |                    |          |                |       |        |     |                |      |                      |          |                     |
| DCS-7010L   | V1.05.03  | H.264 MPEG4 M-JPEG | 1        | 1280x800       | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. The camera with highest resolution is unable to achieve the setting framerate in H.264 and MPEG4. (Camera performance limitation)<br>2. When the format changes to MPEG4 before format is H.264 or MJPEG with the 176x144 resolution, the display will mosaic. (camera firmware issue)   |                    |          |                |       |        |     |                |      |                      |          |                     |
| DCS-7110    | v1.20_20120517  | H.264 MPEG4 M-JPEG | 1        | 1280x800       | -     | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DCS-7110A3  | V2.10.03  | H.264 MPEG4 M-JPEG | 1        | 1280x800       | -     | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:       | 1.The list of resolution 176x144 can't sync with web (Camera firmware issue)  |                    |          |                |       |        |     |                |      |                      |          |                     |
| DCS-7110B1  | V3.00.04  | H.264 MPEG4 MJPEG  | 1        | 1920x1080      | -     | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1.The camera with highest quality and resolution cannot achieve 30 fps. (Camera performance issue)<br>2.The framerate list will not change when resolution has been changed. (Camera Firmware issue)  |                    |          |                |       |        |     |                |      |                      |          |                     |
| DCS-7410    | 1.00_3710   | MPEG4 M-JPEG       | 1        | 720x480        | 1-way | 2/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| DCS-7413    | 1.00.02   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| DCS-7413 B1 | V2.11.08  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. The camera with highest bitrate and resolution are unable to achieve the setting framerate. (Camera performance issue)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-7510    | 1.00  | MPEG4<br>M-JPEG          | 1        | 704x576        | 1-way | 2/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| DCS-7513    | V1.11.06  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. The camera with highest bitrate and resolution are unable to achieve the setting framerate. (Camera performance issue)<br>2. When the format changes to MPEG4 before format is H.264 or MJPEG with the 176x144 resolution, the display will mosaic. (Camera Firmware issue)<br>3. The live view is not clear when the resolution changes to 320x176 or 480x270 in MPEG4. (Camera Firmware issue)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-7517    | V1.00.03  | H.264<br>MJPEG           | 1        | 2560x1920      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Audio out function could not work. (Camera Firmware issue)<br>2. Audio in function only support G.711 codec. (Camera Firmware issue)<br>3. OSD of live view is showed 960x536 when camera web is setting 960x540 resolution in MJPEG. (Camera Fireware issue)<br>4. Zoom and focs functions are not support. (Camera Fireware issue)<br>5. DI is triggered and DO status also opposites. (Camera Fireware issue)<br>6. Motion detection(MD) function is invalid when MD has activated for a long time. (Camera Fireware issue) |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-7518    | V1.00   | H.264                    | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:       | 1. Can not search the camera by UPnP. (Camera firmware issue)<br>2. Talk function will fail with G.711 a-law. (Camera firmware issue)<br>3. Camera video parameter of contrast will fail when set up to 9. (Camera firmware issue)<br>4. The list of resolution and framerate is not synchronized with camera web. (Camera firmware issue)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| DCS-900     | 1.00  | MPEG4                    | 1        | 640x480        | 1-way | -      | -   | -              | Yes  | -                    | -        | Supported by design |
| DCS-910     | 1.00  | MPEG4                    | 1        | 640x480        | -     | -      | -   | -              | Yes  | -                    | -        | Supported by design |
| DCS-920     |   | M-JPEG                   | 1        | 640x480        | -     | -      | -   | -              | Yes  | -                    | -        | Supported by design |
| DCS-930     | 1.00 build 2  | M-JPEG                   | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| DCS-930L    | 1.00 build 2  | M-JPEG                   | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| DCS-930LB   | Refer to DCS-930LB1(v2.00 b1)   | M-JPEG                   | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware                     | Video Format            | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|-------------------------------------|-------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| DCS-930LB1  | 2.00                                | M-JPEG                  | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:       | Camera issue: Auto detection faild. |                         |          |                |       |        |     |                |      |                      |          |                     |
| DCS-931L    | 1.00_b4                             | H.264<br>M-JPEG         | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| DCS-932     | 1.00                                | M-JPEG                  | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| DCS-932L    | 1.05_2012-10-26_2.0.16-b4           | M-JPEG                  | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| DCS-932LB   | Refer to DCS-932LB1(v2.00 b1)       | M-JPEG                  | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| DCS-932LB1  | refer to DCS-930LB1(v2.00 b1)       | M-JPEG                  | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| DCS-933L    | 1.00_b4                             | H.264<br>M-JPEG         | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| DCS-935L    | V1.00                               | H.264<br>M-JPEG         | 1        | 1280x720       | 1-way | -      | -   | Yes            | -    | Yes                  | Yes      |                     |
| DCS-940L    | 1                                   | H.264<br>M-JPEG         | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| DCS-942L    | 1.2                                 | H.264<br>M-JPEG         | 1        | 640x480        | 2-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| DCS-942LB   | Refer to DCS-942LB1(v2.00 b1)       | H.264<br>MJPEG<br>MPEG4 | 1        | 640x480        | 2-way | -      | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| DCS-942LB1  | V2.00_3815                          | H.264<br>MJPEG<br>MPEG4 | 1        | 640x480        | 2-way | -      | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| DCS-950     |                                     | MPEG4                   | 1        | 640x480        | 1-way | -      | -   | -              | Yes  | -                    | -        | Supported by design |
| DCS-950G    |                                     | MPEG4                   | 1        | 640x480        | 1-way | -      | -   | -              | Yes  | -                    | -        | Supported by design |
| DCS-G900    |                                     | M-JPEG                  | 1        | 640x480        | -     | -      | -   | -              | Yes  | -                    | -        | Supported by design |
| DCS-N2100   |                                     | MPEG4<br>M-JPEG         | 1        | 640x480        | -     | -      | -   | Yes            |      | Yes                  | -        |                     |
| DCS-N2104   |                                     | MPEG4<br>M-JPEG         | 1        | 640x480        | -     | -      | -   | Yes            |      | Yes                  | -        |                     |
| DCS-N2200   |                                     | MPEG4<br>M-JPEG         | 1        | 1280x1024      | -     | -      | -   | Yes            |      | Yes                  | -        |                     |
| DCS-N2204   |                                     | MPEG4<br>M-JPEG         | 1        | 1280x1024      | -     | -      | -   | Yes            |      | Yes                  | -        |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|-----------------|--------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| DCS-N3530   |                 | MPEG4 M-JPEG       | 1        | 720x576        | -     | 2/2    | -   | Yes            |      | Yes                  | -        |                     |
| DCS-N3531   |                 | MPEG4 M-JPEG       | 1        | 720x576        | -     | 2/2    | Yes | Yes            |      | Yes                  | -        |                     |
| DCS-N3534   |                 | MPEG4 M-JPEG       | 1        | 720x576        | -     | 2/2    | Yes | Yes            |      | Yes                  | -        |                     |
| DCS-N4141   |                 | MPEG4 M-JPEG       | 1        | 1280x1024      | -     | 1/1    | -   | Yes            |      | Yes                  | -        |                     |
| DCS-N4532   |                 | MPEG4 M-JPEG       | 1        | 720x576        | -     | 1/1    | -   | Yes            |      | Yes                  | -        |                     |
| DCS-N4533   |                 | MPEG4 M-JPEG       | 1        | 720x576        | -     | 1/1    | -   | Yes            |      | Yes                  | -        |                     |
| DCS-N5424   |                 | MPEG4 M-JPEG       | 1        | 720x576        | -     | 1/1    | Yes | Yes            |      | Yes                  | -        |                     |
| DCS-N5440   |                 | MPEG4 M-JPEG       | 1        | 720x576        | -     | 1/1    | Yes | Yes            |      | Yes                  | -        |                     |
| DCS-N5441   |                 | MPEG4 M-JPEG       | 1        | 720x576        | -     | 1/1    | Yes | Yes            |      | Yes                  | -        |                     |
| DCS-N5442   |                 | MPEG4 M-JPEG       | 1        | 720x576        | -     | 1/1    | Yes | Yes            |      | Yes                  | -        |                     |
| DCS-N5444   |                 | MPEG4 M-JPEG       | 1        | 720x576        | -     | 1/1    | Yes | Yes            |      | Yes                  | -        |                     |
| DCS-N6240   |                 | MPEG4 M-JPEG       | 1        | 720x576        | -     | 1/1    | Yes | Yes            |      | Yes                  | -        |                     |
| DCS-N6241   |                 | MPEG4 M-JPEG       | 1        | 720x576        | -     | 1/1    | Yes | Yes            |      | Yes                  | -        |                     |
| DCS-N6244   |                 | MPEG4 M-JPEG       | 1        | 720x576        | -     | 1/1    | Yes | Yes            |      | Yes                  | -        |                     |
| DVS-104     |                 | M-JPEG             | 4        | 720x576        | -     | 4/2    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| DVS-210-1   | 1.00.01         | MPEG4 M-JPEG       | 1        | 720x480        | 1-way | 2/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DVS-301     |                 | H.263              | 1        | 704x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| DVS-310-1   | 1.00.11         | H.264 MPEG4 M-JPEG | 1        | 720x480        | 1-way | 2/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| DVS-N1010   |                 | MPEG4 M-JPEG       | 4        | 720x576        | -     | 4/4    | Yes | Yes            |      | Yes                  | -        |                     |
| DVS-N3010   |                 | MPEG4 M-JPEG       | 1        | 720x576        | -     | 2/2    | Yes | Yes            |      | Yes                  | -        |                     |
| DVS-N3011   |                 | MPEG4 M-JPEG       | 1        | 720x576        | -     | 2/2    | Yes | Yes            |      | Yes                  | -        |                     |
| DVS-N3014   |                 | MPEG4 M-JPEG       | 1        | 720x576        | -     | 2/2    | Yes | Yes            |      | Yes                  | -        |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name     | Tested Firmware                | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks |
|-----------------|--------------------------------|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------|
| DVS-N3040       |                                | MPEG4<br>M-JPEG          | 4        | 700x576        | -     | 4/4    | Yes | Yes            |      | Yes                  | -        |         |
| DVS-N3041       |                                | MPEG4<br>M-JPEG          | 4        | 688x544        | -     | 4/4    | Yes | Yes            |      | Yes                  | -        |         |
| DVS-N3044       |                                | MPEG4<br>M-JPEG          | 4        | 688x544        | -     | 4/4    | Yes | Yes            |      | Yes                  | -        |         |
| Universal Model | Tested by DCS-2332L(V1.0 1.02) | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | -      | -   | Yes            | -    | Yes                  | -        |         |
| Note:           | Fisheye camera                 |                          |          |                |       |        |     |                |      |                      |          |         |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name        | Tested Firmware  | Video Format    | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|--------------------|--|-----------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| <b>HCVR5104H</b>   | 3.200.0005.1<br>.R, build :<br>2014-04-27  | H.264           | 4        | 1280x720       | 2-way | -      | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:              | 1.The bit-rate values in the combo box are not all valid, users have to choose a valid one (the range can be get from the web of the device) while setting. (NUUO Server limitation)<br>2.The auto detection and the UPnP searching are not supported. (Camera Firmware issue)<br>3.The audio-in is for Channel 1 only. (Camera Firmware issue)<br>4.The PCM audio format is not supported. (Camera Firmware issue)<br>5.The talk function is not supported. (Camera Firmware issue)<br>6.The move and auto-pan functions of PTZ are not supported. (Camera Firmware issue)<br>7.After doing focus-near or focus-far, it will do autofocus immediately. (Camera Firmware issue)<br>8.The auto-focus is not supported because it is not supported by the Dahua CGI API. (Camera Firmware issue)<br>9.The motion detection is not supported. (Camera Firmware issue)<br>10.In some cases (lower FPS), setting the video configuration will fail, even the bit-rate is fit. (Camera Firmware issue) |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>HDB3300</b>     |  | H.264<br>M-JPEG | 1        | 2048x1536      | 1-way | 2/1    | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| Note:              | HDB3300N and HDB3300P are compatible with HDB3300  |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>HDBW3300</b>    | V2.000 ,<br>Update<br>2011.10.22   | H.264<br>M-JPEG | 1        | 2048x1536      | 1-way | 2/1    | Yes | Yes            | -    | Yes                  | -        |                     |
| Note:              | HDBW3300N and HDBW3300P are compatible with HDBW3300   |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>HF3110</b>      | V2.000 ,<br>Update<br>2011.10.22   | H.264<br>M-JPEG | 1        | 1280x960       | 1-way | 1/1    | Yes | Yes            | -    | Yes                  | -        |                     |
| Note:              | HF3110N and HF3110P are compatible with HF3110   |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>HF3211</b>      | V2.000 ,<br>Update<br>2011.10.22   | H.264<br>M-JPEG | 1        | 1920x1080      | 1-way | 2/1    | Yes | Yes            | -    | Yes                  | -        |                     |
| Note:              | HF3211P is compatible with HF3211  |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>HF3300</b>      | V2.000 ,<br>Update<br>2011.10.22   | H.264<br>M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | -    | Yes                  | -        |                     |
| Note:              | 1. HF3300N, HF3300N-W, HF3300P and HF3300P-W are compatible with HF3300<br>2. HP3300 series: there may be image noise of dual stream, which can be observed from the camera web as well.<br>3. Setting preset point doesn't work properly<br>4. PTZ is only supported by external RS-485 device  |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>IPC-HFW5200</b> | 2.42   | H.264<br>MJPEG  | 1        | 1920x1080      | 2-way | 2/1    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Note               | 1. Sometime parameter dialog will fail to get codec parameter with high bitrate. (Camera performance limitation)<br>2. The range of parameter on camera will change by other parameter, our parameter dialog can't synchronize with camera. (Camera firmware issue)<br>3. Slow reaction when motion detection is triggered. (Camera performance limitation)<br>4. Polling the DI/Motion status will make the audio stutter (Camera performance limitation)   |                 |          |                |       |        |     |                |      |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name     | Tested Firmware   | Video Format   | Video Ch | Max Resolution | Audio | I/O Ch | PTZ  | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-----------------|---|----------------|----------|----------------|-------|--------|------|----------------|------|----------------------|----------|---------------------|
| IPC-HFW5302C    | 2.420.0005.0<br>.R, build :<br>2014-12-05   | H.264<br>MJPEG | 1        | 2048x1536      | 2-way | 2/1    | Yes  | Yes            | Yes  | Yes                  | Yes      |                     |
| Note            | 1. The range of parameter on camera will change by other parameter, our parameter dialog can't synchronize with camera. (Camera firmware issue)<br>2. When framerate set to 1 and record dynamic picture, the picture's framerate may rise to 30 immediately. (Camera firmware issue)<br>3. Sometime parameter dialog will fail to get parameters with high resolution, framerate, and bitrate. (Camera performance limitation)<br>4. Zoom in/out will not run step by step, it will zoom to limit directly. (Camera firmware issue)<br>5. DO can not trigger. (Camera firmware issue)<br>6. PTZ only support zoom & focus. |                |          |                |       |        |      |                |      |                      |          |                     |
| IPC-HF5100      | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05)  | H.264<br>MJPEG | 1        | 2048x1536      | 2-way | 2/1    | Yes  | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HF5200      | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05)  | H.264<br>MJPEG | 1        | 2048x1536      | 2-way | 2/1    | Yes  | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HF81200E    | 2.400.0000.7<br>.R  | H.264<br>MJPEG | 1        | 4000x3000      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:           | 1. The bitrate of stream 1 in camera with highest resolution via MJPEG is higher than settings bitrate. (Camera performance limitation)<br>2. Audio codec via G.726 and AAC can not be used. (NUUO server limitation)<br>3. The list of Frame Rate is not synchronized with the one on camera web. (Camera Firmware issue)  |                |          |                |       |        |      |                |      |                      |          |                     |
| IPC-HFW5100D    | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05)  | H.264<br>MJPEG | 1        | 2048x1536      | 2-way | 2/1    | Yes  | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HFW5200D    | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05)  | H.264<br>MJPEG | 1        | 2048x1536      | 2-way | 2/1    | Yes  | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HFW5100-IRA | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05)  | H.264<br>MJPEG | 1        | 2048x1536      | 2-way | 2/1    | Yes  | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HFW5200-IRA | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05)  | H.264<br>MJPEG | 1        | 2048x1536      | 2-way | 2/1    | Yes  | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HFW5100C    | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05)  | H.264<br>MJPEG | 1        | 2048x1536      | 2-way | 2/1    | Yes  | Yes            | Yes  | Yes                  | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name     | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-----------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| IPC-HFW5200C    | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HFW5300C    | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HFW5202C    | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HFW5100E-VF | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HFW5200E-VF | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HFW5300E-VF | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HFW5200E-Z  | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HFW5300E-Z  | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDBW5100    | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDBW5200    | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name     | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-----------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| IPC-HDBW5300    | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDBW5202    | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDBW5302    | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDBW5100-DI | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDBW5200-DI | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDBW5300-DI | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDBW5202-DI | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDBW5302-DI | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDB5100     | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDB5200     | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name    | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|----------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| IPC-HDB5202    | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDB5300    | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDB5302    | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDB5100-DI | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDB5200-DI | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDB5202-DI | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDB5300-DI | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HDB5302-DI | Refer to IPC-HFW5302C (FW 2.420.0005.0 .R, build : 2014-12-05) | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| IPC-HD2100     | 2.212.0000.1 .T, build : 2014-02-08                            | H.264 M-JPEG | 1        | 1280x960       | -     | -      | -   | Yes            | Yes  | Yes                  | -        |                     |

Note:

1. The range of bitrate and framerate does not synchronous with the camera's website which may result in failure of stream parameter setting.
2. If enable MD and used MJPEG as stream codec which could result in video freeze then start play after few seconds.
3. There is invalid mac address in UPnP search.
4. Bitrate combobox can't be setup on server web in NVRSolo/NVRMini2 version 2.0 with DevicePack version 3.1.0, but it can be set in local display.



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name  | Tested Firmware   | Video Format    | Video Ch | Max Resolution | Audio   | I/O Ch | PTZ  | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|--------------|---|-----------------|----------|----------------|---------|--------|------|----------------|------|----------------------|----------|---------------------|
| IPC-HFW3200C | 2.212.0000.1<br>.T, build :<br>2014-02-08   | H.264<br>M-JPEG | 1        | 1920x1080      | 1-way   | 2/1    | -    | Yes            | Yes  | Yes                  | -        |                     |
| Note:        | 1. The range of bitrate and framerate does not synchronous with the camera's website which may result in failure of stream parameter setting.<br>2. If enable MD and used MJPEG as stream codec which could result in video freeze then start play after few seconds.<br>3. There is big noise in audio with format PCM.<br>4. There is discontinuous audio with format G.711Mu and G.711A.<br>5. There is invalid mac address in UPnP search.<br>6. Bitrate combobox can't be setup on server web in NVRSolo/NVRMini2 version 2.0 with DevicePack version 3.1.0, but it can be set in local display.   |                 |          |                |         |        |      |                |      |                      |          |                     |
| IPC-HDB3101  | Refer to IPC-HFW3101C (FW V2.103)   | H264<br>MJPEG   | 1        | 1280x960       | 1-way*2 | 2/1    | -    | *2             | *2   | Yes                  | -        | Supported by design |
| IPC-HDBW3101 | Refer to IPC-HFW3101C (FW V2.103)   | H264<br>MJPEG   | 1        | 1280x960       | 1-way*2 | 2/1    | -    | *2             | *2   | Yes                  | -        | Supported by design |
| IPC-HFW3101C | V2.103  | H264<br>MJPEG   | 1        | 1280x960       | 1-way*2 | 2/1    | -    | *2             | *2   | Yes                  | -        |                     |
| Note         | FW issue:<br>bit rate range is different between camera web and response to cgi.  |                 |          |                |         |        |      |                |      |                      |          |                     |
| SD52C220S-HN | 2.210.0003.0<br>.R.A.2017,<br>build : 2014-11-12  | H.264<br>M-JPEG | 1        | 1920x1080      | 2-way   | 2/1    | Yes  | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:        | 1. The range of parameter on camera will change by other parameter, our parameter dialog can't synchronize with camera. (Camera firmware issue)<br>2. The camera can't be search by auto detection function and UPNP tool. (Camera firmware issue)<br>3. When framerate set to 1 and record dynamic picture, the picture's framerate may rise to 30 immediately. (Camera firmware issue)<br>4. Sometime parameter dialog will fail to get parameters with high resolution, framerate, and bitrate. (Camera performance limitation)<br>5. The setting may fail when setting format from MJPEG to H.264. (Camera firmware issue)<br>6. Audio and talk functions will fail with codec PCM. (Camera firmware issue) |                 |          |                |         |        |      |                |      |                      |          |                     |
| SD32203S-HN  | Refer to SD52C220S-HN(2.210.0003.0.R.A.2017, build : 2014-11-12)  | H.264<br>M-JPEG | 1        | 1920x1080      | 2-way   | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD50230S-HN  | Refer to SD52C220S-HN(2.210.0003.0.R.A.2017, build : 2014-11-12)  | H.264<br>M-JPEG | 1        | 1920x1080      | 2-way   | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD52C220S-HN | Refer to SD52C220S-HN(2.210.0003.0.R.A.2017, build : 2014-11-12)  | H.264<br>M-JPEG | 1        | 1920x1080      | 2-way   | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD52C230S-HN | Refer to SD52C220S-HN(2.210.0003.0.R.A.2017, build : 2014-11-12)  | H.264<br>M-JPEG | 1        | 1920x1080      | 2-way   | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name  | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ  | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|--------------|---|--------------|----------|----------------|-------|--------|------|----------------|------|----------------------|----------|---------------------|
| SD50120S-HN  | Refer to SD52C220S-HN(2.210.00 03.0.R.A.2017, build : 2014-11-12) | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD52C120S-HN | Refer to SD52C220S-HN(2.210.00 03.0.R.A.2017, build : 2014-11-12) | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD40212S-HN  | Refer to SD52C220S-HN(2.210.00 03.0.R.A.2017, build : 2014-11-12) | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD42212S-HN  | Refer to SD52C220S-HN(2.210.00 03.0.R.A.2017, build : 2014-11-12) | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD42C212S-HN | Refer to SD52C220S-HN(2.210.00 03.0.R.A.2017, build : 2014-11-12) | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD59212S-HN  | Refer to SD52C220S-HN(2.210.00 03.0.R.A.2017, build : 2014-11-12) | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD59220S-HN  | Refer to SD52C220S-HN(2.210.00 03.0.R.A.2017, build : 2014-11-12) | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD59230S-HN  | Refer to SD52C220S-HN(2.210.00 03.0.R.A.2017, build : 2014-11-12) | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD59120S-HN  | Refer to SD52C220S-HN(2.210.00 03.0.R.A.2017, build : 2014-11-12) | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD63220S-HN  | Refer to SD52C220S-HN(2.210.00 03.0.R.A.2017, build : 2014-11-12) | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name  | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ  | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|--------------|--|--------------|----------|----------------|-------|--------|------|----------------|------|----------------------|----------|---------------------|
| SD63230S-HN  | Refer to SD52C220S-HN(2.210.00 03.0.R.A.2017, build : 2014-11-12)  | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD63120S-HN  | Refer to SD52C220S-HN(2.210.00 03.0.R.A.2017, build : 2014-11-12)  | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD6C220S-HN  | Refer to SD52C220S-HN(2.210.00 03.0.R.A.2017, build : 2014-11-12)  | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD6C230S-HN  | Refer to SD52C220S-HN(2.210.00 03.0.R.A.2017, build : 2014-11-12)  | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD6C120S-HN  | Refer to SD52C220S-HN(2.210.00 03.0.R.A.2017, build : 2014-11-12)  | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SDZW2030S-HN | Refer to SD52C220S-HN(2.210.00 03.0.R.A.2017, build : 2014-11-12)  | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 2/1    | Yes* | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| SD6366E-HN   | 2.213.0000.1.R, build : 2013-12-27   | H.264 M-JPEG | 1        | 704x576        | 1-way | *2     | Yes  | Yes            | *2   | Yes                  | Yes      |                     |
| Note:        | 1. There is no guarantee that the bitrate values in the combo box is valid. User should apply a value in the valid C14 range (can be get from the web page of the camera) so that the setting can be applied successfully.<br>2. FW Issue: the Dahua CGI API dose not support the autofocus command though the camera has the function of autofocus. |              |          |                |       |        |      |                |      |                      |          |                     |
| SD65XX-HN    | 2.102.0001.0.D   | H.264 M-JPEG | 1        | 1920x1280      | 1-way | 7/2    | Yes  | Yes            | -    | Yes                  | -        |                     |
| Note:        | 1. MJPEG not support MD<br>2. FW issue, MJPEG bitrate can't not set over 8192.   |              |          |                |       |        |      |                |      |                      |          |                     |
| SD69XX-HN    | Refer to SD65XX-HN   | H.264 M-JPEG | 1        | 1920x1280      | 1-way | 7/2    | Yes  | Yes            | -    | Yes                  | -        |                     |
| Note:        | 1. MJPEG not support MD<br>2. FW issue, MJPEG bitrate can't not set over 8192.   |              |          |                |       |        |      |                |      |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks |
|-------------|-----------------|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------|
| SD6A230     | 2.212           | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 7/2    | Yes | Yes            | *2   | Yes                  | Yes      |         |

|       |  |
|-------|--|
| Note: | <ol style="list-style-type: none"> <li>1. The permitted parameter list on camera will be changed by other parameters, our parameter dialog can't synchronize with camera. (Camera firmware issue)</li> <li>2. The camera can't be searched by UPnP tools. (Camera firmware issue)</li> <li>3. Slow reaction when motion detection is triggered. (Camera performance limitation)</li> <li>4. Big audio noise with PCM. (Camera firmware issue)</li> <li>5. CGI response "support flip/mirror", but actually not. (Camera firmware issue)</li> <li>6. Polling the DI/Motion status will make the audio stutter. (Camera performance limitation)</li> </ol> |
|-------|--|



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name     | Tested Firmware   | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|-----------------|---|--------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| DCS-H_Series    |   | H.264 M-JPEG       | 1        | 2592x1944      | 1-way | 4/2    | Yes | Yes            | -    | Yes                  | Supported by design |
| Note:           | Fisheye camera  |                    |          |                |       |        |     |                |      |                      |                     |
| DCS-V_Series    |   | H.264 MPEG4 M-JPEG | 1        | -              | 2-way | 4/4    | Yes | Yes            | -    | Yes                  | Supported by design |
| Note:           | Fisheye camera  |                    |          |                |       |        |     |                |      |                      |                     |
| DCS-H30-51D/S   | Refer to DCS-H50-21D/S(1.0.0x0)   | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| DCS-H41-11D/SI  | Refer to DCS-H50-21D/S(1.0.0x0)   | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| DCS-H41-11D/SO  | Refer to DCS-H50-21D/S(1.0.0x0)   | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| DCS-H42-21D/SA  | Refer to DCS-H50-21D/S(1.0.0x0)   | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| DCS-H42-21D/SM  | Refer to DCS-H50-21D/S(1.0.0x0)   | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| DCS-H50-21D/S   | 1.0.0X0(20140307)   | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |
| DCS-H70-21D     | 2.0.9A5S2   | H264 MJPEG         | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| Note:           | covered DCS-H70-21D/A and DCS-H70-21D/M   |                    |          |                |       |        |     |                |      |                      |                     |
| Note:           | Firmware Issue: Not support Motion Detection;<br>Bitrate List on web shows 3Mkbps (the truly Bitrate value of camera could be 3Mkbps or 2.5Mkbps) |                    |          |                |       |        |     |                |      |                      |                     |
| DCS-H70-21D/M   | 2.0.9A5S2   | H264 MJPEG         | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| DCS-H70-21D/SA1 | Refer to DCS-H50-21D/S(1.0.0x0)   | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| DCS-H70-21D/SM1 | Refer to DCS-H50-21D/S(1.0.0x0)   | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| DCS-H70-22D     | 2.0.9A5S2   | H264 MJPEG         | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| DCS-N20M-10H2   | Refer to DCS-V70M-21H (v1.0.30)   | H264 MJPEG         | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-N30M-51H2   | Refer to DCS-V70M-21H (v1.0.30)   | H264 MJPEG         | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-N31M-21H3   | Refer to DCS-V70M-21H2 (VB1.0.29)   | H264 MPEG4 MJPEG   | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-N40M-22H3   | Refer to DCS-V70M-21H2 (VB1.0.29)   | H264 MPEG4 MJPEG   | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-N40M-32H2   | Refer to DCS-V70M-21H (v1.0.30)   | H264 MJPEG         | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name   | Tested Firmware                    | Video Format     | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|---------------|------------------------------------|------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| DCS-N40M-53H2 | Refer to DCS-V70M-21H (v1.0.30)    | H264 MJPEG       | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-N40M-81H3 | VC1.0.10                           | H264 MJPEG       | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| Note:         | DCS-N40M-81H3: Not support TCP/UDP |                  |          |                |       |        |     |                |      |                      |                     |
| DCS-N62-40H2  | V1.0.40                            | H264 MJPEG       | 1        | 720x480        | 1-way | 1/1    | Yes | -              | Yes  | Yes                  |                     |
| DCS-N70M-20H2 | Refer to DCS-V70M-21H (v1.0.30)    | H264 MJPEG       | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-N70M-21H3 | Refer to DCS-V70M-21H2 (VB1.0.29)  | H264 MPEG4 MJPEG | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-N70M-50H2 | Refer to DCS-V70M-21H (v1.0.30)    | H264 MJPEG       | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-V30M-50H  | Refer to DCS-V70M-21H (v1.0.30)    | H264 MJPEG       | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-V30M-51H  | Refer to DCS-V70M-21H (v1.0.30)    | H264 MJPEG       | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-V30M-51H2 | Refer to DCS-N70M-81H3 (VC1.0.10)  | H264 MPEG4 MJPEG | 1        | 1280x800       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-V40M-12H  | Refer to DCS-V70M-21H2 (VB1.0.29)  | H264 MPEG4 MJPEG | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-V40M-32H  | Refer to DCS-V70M-21H (v1.0.30)    | H264 MJPEG       | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-V40M-32H2 | Refer to DCS-V70M-21H2 (VB1.0.29)  | H264 MPEG4 MJPEG | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-V40M-33H  | Refer to DCS-V70M-21H (v1.0.30)    | H264 MJPEG       | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-V70M-11H  | Refer to DCS-V70M-21H2 (VB1.0.29)  | H264 MPEG4 MJPEG | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-V70M-20H  | Refer to DCS-V70M-21H (v1.0.30)    | H264 MJPEG       | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| DCS-V70M-21H  | v1.0.30                            | H264 MJPEG       | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| DCS-V70M-21H2 | VB1.0.29                           | H264 MPEG4 MJPEG | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| DCS-V70M-50H  | Refer to DCS-V70M-21H (v1.0.30)    | H264 MJPEG       | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|-------------|---|--------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| Generic     | z120141215 NSZ  | H.264 M-JPEG       | 1        | 2592x1944      | 2-way | 4/2    | Yes | Yes            | -    | Yes*                 |         |
| Note:       | Support generic dewarp<br>Generic support model: W1-BA100, W2-BAZ40, W5-CDWK0, NH073, NH063<br>Parameter setting will fail when mutistream is allow and resolution higher than 1080p.<br>PT function are not test on software.<br>The maximum resolution is depends on camera.<br>Camera (Z series) firmwawe must be z120141215NSZ or above then can use generic model.<br>Camera (W series) firmwawe must be z120130417NSA or above then can use generic model.<br>Camera (X series) firmwawe must be z120141027NSA or above then can use generic model. |                    |          |                |       |        |     |                |      |                      |         |
| na063       | z120120523 NSA  | H.264              | 1        | 2592x1944      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |         |
| Note:       | 1. Video parameter can't sync with camera web interface, need to refresh the browser<br>2. Talk quality is not clear<br>3. Camera doesn't tranport sufficient framerate when stream parameter set to high resolution & quality, and camera's resonse will become slowly.  |                    |          |                |       |        |     |                |      |                      |         |
| NA083       | z120131016 NSA  | H.264 M-JPEG       | 1        | 2592x1944      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |         |
| Note:       | Fisheye camera<br>1. M-JPEG on high resolution and quality may not get parameter.<br>2. Audio has some noise in high resolution.  |                    |          |                |       |        |     |                |      |                      |         |
| NH061-CCD   | CCD-cameraFw-100205P  | H.264 MPEG4 M-JPEG | 1        | 1280x960       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |         |
| Note:       | Camera FW is not stable enough, so camera is likely disconnected after modifying parameters. Current workaround is turning off and on to reboot camera.<br>Remove resolution 1280x720 in H.264 codec due to broken image problem.<br>Known FW issue: audio may be broken in certain operation.  |                    |          |                |       |        |     |                |      |                      |         |
| NH221-CCD   | CCD-cameraFw-100205P  | H.264 MPEG4 M-JPEG | 1        | 1280x960       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |         |
| Note:       | Remove resolution 1280x720 in H.264 codec due to broken image problem.<br>The image is broken badly when configuring to the highest resolution, fps, and quality under H.264/MPEG4 with UDP protocol.<br>Known FW issue: audio may be broken in certain operation.  |                    |          |                |       |        |     |                |      |                      |         |
| NH720-20N1  | pm20120222 NSA  | MJPEG/H 264        | 1        | 1920x1080      | 1-way | 4/2    | -   | Yes            | Yes  | Yes                  |         |
| NH720-20N8  | Refer to NH820-20N8 (z120131126)  | MJPEG/H 264        | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | Yes                  |         |
| NH820-20N1  | pm20120222 NSA  | MJPEG/H 264        | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | Yes                  |         |
| NH820-20N8  | z120131126 NSA  | MJPEG/H 264        | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | Yes                  |         |
| nv053       | pm20120222 NSA  | MJPEG/H 264        | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |         |
| nv063       | pm20120222 NSA  | MJPEG/H 264        | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |         |
| nv103       | pm20120222 NSA  | MJPEG/H 264        | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |         |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|-------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| nv223       | z120130417 NSA   | MJPEG/H264   | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |
| Note:       | nv223's PTZ only support Zoom.<br>nv223 support zoom or not is depends on spec.                                |              |          |                |       |        |     |                |      |                      |                     |
| V1-A        |  | H.264 M-JPEG | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes                  | Supported by design |
| V1-B        | d20100630NS  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes                  |                     |
| Note:       | There is high possibility to get broken image on the edge under H.264 codec with UDP protocol.                 |              |          |                |       |        |     |                |      |                      |                     |
| V2-A        |  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| V2-B        | d20100826NS  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| V6-A        |  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| V6-B        | d20100630NS  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| Note:       | The image is broken badly when configuring to the highest resolution, fps, quality, etc.                       |              |          |                |       |        |     |                |      |                      |                     |
| Note:       | Model A is referred to model B, promised by the manufacturer, so model A may encounter same issues of model B. |              |          |                |       |        |     |                |      |                      |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|-----------------|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| GLC-1401    | 1.42            | MPEG4 M-JPEG | 1        | 720x576        | 1-way | 1/0    | Yes | Yes            | Yes  | -                    | -        | Supported by design |
| GLC-1601    | 1.43            | MPEG4 M-JPEG | 1        | 720x576        | 1-way | 1/0    | Yes | Yes            | Yes  | -                    | -        |                     |
| GLC-1602H   | 1.43            | H.264 M-JPEG | 1        | 720x576        | 1-way | 1/0    | Yes | Yes            | Yes  | -                    | -        |                     |
| GLC-1610H   |                 | H.264 M-JPEG | 1        | 720x480        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| GLC-1701/IR | 1.45            | MPEG4 M-JPEG | 1        | 720x576        | -     | 1/0    | -   | Yes            | Yes  | Yes                  | -        |                     |
| GLD-1401    | 1.40            | MPEG4 M-JPEG | 1        | 720x576        | -     | 1/0    | -   | Yes            | Yes  | -                    | -        |                     |
| GLD-1501    | 1.43            | MPEG4 M-JPEG | 1        | 720x576        | 1-way | 1/0    | Yes | Yes            | Yes  | -                    | -        |                     |
| GLS-2101    | 1.45            | MPEG4 M-JPEG | 1        | 720x576        | 1-way | 1/0    | Yes | Yes            | Yes  | -                    | -        |                     |
| GLS-2104    | 1.78            | M-JPEG       | 4        | 704x272        | 1-way | -      | Yes | Yes            | Yes  | Yes                  | -        |                     |
| GLS-2301H   | 1.09            | H.264 M-JPEG | 1        | 720x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| NLC-1401    | v1.5.6          | H.264 MPEG4  | 1        | 704x576        | 1-way | 1/0    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| NLD-1401    | v1.5.6          | H.264 MPEG4  | 1        | 704x576        | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  | -        |                     |
| NLS-1401    | v1.5.6          | H.264 MPEG4  | 1        | 704x576        | 1-way | 2/0    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| NXC-1301M   | v2.1.2          | H.264        | 1        | 1280x720       | -     | 2/0    | -   | Yes            | Yes  | Yes                  | -        |                     |
| NXC-1302M   | v2.1.2          | H.264        | 1        | 1600x1200      | -     | 2/0    | -   | Yes            | Yes  | Yes                  | -        |                     |
| NXC-1401M   | v2.1.2          | H.264        | 1        | 1280x720       | -     | 2/0    | -   | Yes            | Yes  | Yes                  | -        |                     |
| NXC-1402M   | v2.1.2          | H.264        | 1        | 1600x1200      | -     | 2/0    | -   | Yes            | Yes  | Yes                  | -        |                     |
| NXD-1301M   | v2.1.2          | H.264        | 1        | 1280x720       | -     | 2/0    | -   | Yes            | Yes  | Yes                  | -        |                     |
| NXD-1302M   | v2.1.2          | H.264        | 1        | 1600x1200      | -     | 2/0    | -   | Yes            | Yes  | Yes                  | -        |                     |
| NXD-1401M   | v2.1.2          | H.264        | 1        | 1280x720       | -     | 2/0    | -   | Yes            | Yes  | Yes                  | -        |                     |
| NXD-1402M   | v2.1.2          | H.264        | 1        | 1600x1200      | -     | 2/0    | -   | Yes            | Yes  | Yes                  | -        |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name  | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|--------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| GXB-1710M-IR | refer to GXC-1710M(2.11)   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| GXB-1720M-IR | Refer to GXC-1720M(1.05_Beta)  | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| GXC-1605M    | Refer to GXC-1606M-IR(2.03)  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| GXC-1606M-IR | 2.03   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| GXC-1710M    | 2.11   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:        | Audio is disabled currently for camera FW bug: NXC-1301M, NXC-1302M, NXC-1401M, NXC-1402M, NXD-1301M, NXD-1302M, NXD-1401M and NXD-1402M |                          |          |                |       |        |     |                |      |                      |          |                     |
| Note:        | PTZ is only supported by external RS-485 device.   |                          |          |                |       |        |     |                |      |                      |          |                     |
| GXC-1720M    | 1.05_Beta  | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| GXD-1610M-IR | Refer to GXC-1606M-IR(2.03)  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| GXD-1710M-IR | refer to GXC-1710M(1.05_Beta)  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| GXD-1720M-IR | Refer to GXC-1720M(1.05_Beta)  | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| PXB-1080Z03  | Refer to PXD-2080Z03IR (FW: 4.19-20-ds)  | H264<br>MJPEG            | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes                  | -        | Supported by design |
| PXB-2080MIR  | Refer to PXD-2080Z03IR (FW: 4.19-20-ds)  | H264<br>MJPEG            | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes                  | -        | Supported by design |
| PXB-2080Z03  | Refer to PXD-2080Z03IR (FW: 4.19-20-ds)  | H264<br>MJPEG            | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes                  | -        | Supported by design |
| PXB-2180Z03  | Refer to PXD-2080Z03IR (FW: 4.19-20-ds)  | H264<br>MJPEG            | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes                  | -        | Supported by design |
| PXC-2080CS   | Refer to PXD-2080Z03IR (FW: 4.19-20-ds)  | H264<br>MJPEG            | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes                  | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name     | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-----------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| PXC-2080Z03     | Refer to PXD-2080Z031R (FW: 4.19-20-ds)   | H264 MJPEG   | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes                  | -        | Supported by design |
| PXD-1010F02     | vr20121016 NSA  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| PXD-1020F02     | refer to PXD-1010F02(vr20121016NSA)   | H.264 M-JPEG | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:           | Parameter setting will fail when Mjpeg quality bigger than 60   |              |          |                |       |        |     |                |      |                      |          |                     |
| PXD-2030PTZ1080 | vr20140416 NSA  | H.264 MJPEG  | 1        | 1920x1080      | *2    | *2     | Yes | *2             | *2   | Yes                  | Yes      |                     |
| Note:           | PXD-2030PTZ1080: High quality caused the fps lower.(Camera limitation issue)  |              |          |                |       |        |     |                |      |                      |          |                     |
| PXD-2080MIR     | Refer to PXD-2080Z031R (FW: 4.19-20-ds)   | H264 MJPEG   | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes                  | -        | Supported by design |
| PXD-2080Z03     | Refer to PXD-2080Z031R (FW: 4.19-   | H264 MJPEG   | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes                  | -        | Supported by design |
| PXD-2080Z031R   | 4.19-20-ds  | H264 MJPEG   | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        |                     |
| Note:           | 1. Only support rtsp port 554 by camera firmware issue.<br>2. Only integrate NTSC mode.<br>3. Audio will be discontinuous under fps 1.<br>4. Framerate may not enough under high resolution, framerate and quality settings. There will be missing record during the drop frame period. |              |          |                |       |        |     |                |      |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name  | Tested Firmware   | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|--------------|---|--------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| EV8180A      | 1.1.4 (build 003)   | MJPEG, H264        | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |
| EV8180Q - XD | 1.1.4 (build 003)   | MJPEG, H264        | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |
| <b>Note:</b> | EV8180Q-XD and EV8180A<br>1. Under four profile mode only support resolution 640x480. (camera limitation)<br>2. MotionDetection only works on H.264.<br>3. It needs to reboot after changing HTTP port. |                    |          |                |       |        |     |                |      |                      |                     |
| EV8580A      | Refer to EV8180A (1.1.4 (build 003))  | MJPEG, H264        | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| EV8581A      | Refer to EV8180A (1.1.4 (build 003))  | MJPEG, H264        | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| EV8582U-BL   | 1.1.6 (build 003)   | MJPEG, MPEG4, H264 | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes                  |                     |
| <b>Note</b>  | 1.Camera only support MD under H.264.   |                    |          |                |       |        |     |                |      |                      |                     |
| EV8780A      | Refer to EV8180A (1.1.4 (build 003))  | MJPEG, H264        | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| EV8781A      | Refer to EV8180A (1.1.4 (build 003))  | MJPEG, H264        | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| EV8782A      | Refer to EV8180A (1.1.4 (build 003))  | MJPEG, H264        | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| EV8782Q - BD | Refer to EV8180Q-(XD1.1.4 (build 003))  | MJPEG, H264        | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N51A-ML      | Refer to N71U-ML(FW1.1.6 (build 003))   | H264 MJPEG MPEG4   | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N50U-ML      | Refer to N71U-ML(FW1.1.6 (build 003))   | H264 MJPEG MPEG4   | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N51U-ML      | Refer to N71U-ML(FW1.1.6 (build 003))   | H264 MJPEG MPEG4   | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N71U-ML      | 1.1.6 (build 003)   | H264 MJPEG MPEG4   | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |
| <b>Note</b>  | 1.Camera only support Focus and Zoom .<br>2.Audio has noise.<br>3.Camera only support MD under H.264.<br>4.Dual stream will not connect if settings of main stream is MPEG4, 1080P and FPS over 20.     |                    |          |                |       |        |     |                |      |                      |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | ONVIF Search | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------|----------|----------------|-------|--------|-----|----------------|------|--------------|----------------------|----------|---------------------|
| EAN3200     | 1.0.14  | H.264 MJPEG        | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes          | -                    | -        |                     |
| EAN800A     | 1.2.5   | H.264 MPEG4 MJPEG  | 1        | 704x576        | 1-way | 1/1    | -   | Yes            | Yes  | -            | -                    | -        |                     |
| EAN800AW    | 1.2.5   | H.264 MPEG4 MJPEG  | 1        | 704x576        | 1-way | 1/1    | -   | Yes            | Yes  | -            | -                    | -        | Supported by design |
| EAN850A     | 1.2.5   | H.264 MPEG4 MJPEG  | 1        | 704x576        | 1-way | 1/1    | -   | Yes            | Yes  | -            | -                    | -        |                     |
| EAN900      | 1.2.5   | H.264 MPEG4 MJPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | -            | -                    | -        |                     |
| Note:       | Fix stream 1 as recording stream and fix stream 2 for mobile client used. |                    |          |                |       |        |     |                |      |              |                      |          |                     |
| EAN2150     | CCD-cameraFw-100811P  | MPEG4 M-JPEG H.264 | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -            | Yes                  | -        |                     |
| EAN2350     | ev20111116NSA   | H.264, MJPEG       | 1        | 2048x1536      | 1-way | 1/1    | -   | Yes            | Yes  | -            | Yes                  | -        |                     |
| EAN2218     | ev20111116NSA   | H.264, MJPEG       | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -            | Yes                  | -        |                     |
| EAN3120     | V1.0.5  | H.264, MJPEG       | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | -            | Yes                  | -        |                     |
| EAN3220     | V1.0.5  | H.264, MJPEG       | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -            | Yes                  | -        |                     |
| EAN3300     | refer to EHN3340(1.2.4)   | M-JPEG H.264       | 1        | 2048x1536      | 2-way | 1/1    | -   | Yes            | -    | Yes          | Yes                  | -        | Supported by design |
| EDN1220     | 1.0.8   | M-JPEG H.264       | 1        | 1920x1080      | 1-way | 0/0    | -   | Yes            | Yes  | Yes          | Yes                  | -        |                     |
| Note:       | 1. can't switch CBR/VBR.<br>2. only support VBR.<br>3. Not support Mpeg4  |                    |          |                |       |        |     |                |      |              |                      |          |                     |
| EDN1320     | 1.0.8   | M-JPEG H.264       | 1        | 2048x1536      | 1-way | 0/0    | -   | Yes            | Yes  | Yes          | Yes                  | -        |                     |
| Note:       | 1. can't switch CBR/VBR.<br>2. only support VBR.<br>3. Not support Mpeg4  |                    |          |                |       |        |     |                |      |              |                      |          |                     |
| EDN2210     | ev20121002NSA   | H.264, MJPEG       | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | -            | Yes                  | -        |                     |
| EDN2245     | ev20111028BNS   | M-JPEG H.264       | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -            | Yes                  | -        |                     |
| EDN2260     | 1.3.0.d   | H.264 MPEG4 MJPEG  | 1        | 1920x1080      | 1-way | -      | -   | -              | Yes  | Yes          | Yes                  | Yes      |                     |
| Note:       | 1. The value of H.264 quality isn't synchronized with camera's web        |                    |          |                |       |        |     |                |      |              |                      |          |                     |
| EDN3240     | 1.0.14  | H.264 MJPEG        | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes          | -                    | -        |                     |
| EDN3160     | 1.0.18  | M-JPEG H.264       | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes          | Yes                  | -        |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | ONVIF Search | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|--------------|----------------------|----------|---------------------|
| EDN3260     | 1.2.2   | M-JPEG<br>H.264          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes          | Yes                  | -        |                     |
| EDN3340     | refer to EHN3340(1.2.4)   | M-JPEG<br>H.264          | 1        | 2048x1536      | 2-way | 1/1    | -   | Yes            | -    | Yes          | Yes                  | -        | Supported by design |
| EPN2218     | ev20111116NSA   | M-JPEG<br>H.264          | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | -            | Yes                  | -        |                     |
| EDN800      | 1.2.5   | H.264<br>MPEG4<br>MJPEG  | 1        | 704x576        | 1-way | 1/1    | -   | Yes            | Yes  | -            | -                    | -        |                     |
| EDN850H     | 1.2.5   | H.264<br>MPEG4<br>MJPEG  | 1        | 704x576        | 1-way | 1/1    | -   | Yes            | Yes  | -            | -                    | -        |                     |
| EHN3160     | 1.0.18  | M-JPEG<br>H.264          | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes          | Yes                  | -        |                     |
| EHN3200     | 1.0.14  | H.264<br>MJPEG           | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes          | -                    | -        |                     |
| EHN3260     | 1.2.5B2   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes          | Yes*                 | *2       |                     |
| Note:       | 1. CBR mode is not supported.(Camera firmware limitation)<br>2. It will lose parameters of stream2 and stream3 if disable stream2 and stream3 on camera web.(Camera firmware limitation)  |                          |          |                |       |        |     |                |      |              |                      |          |                     |
| EHN3340     | 1.2.4   | M-JPEG<br>H.264          | 1        | 2048x1536      | 2-way | 1/1    | -   | Yes            | -    | Yes          | Yes                  | -        |                     |
| Note:       | 1. Onvif test tool get "No MPEG4 support" but actually it support. (Camera firmware issue)<br>2. The audio in status can't synchronize to web client. (ONVIF limitation)<br>3. Cannot change the rate control mode. (ONVIF limitation)<br>4. Cannot get snapshot by CGI(404). (Camera firmware issue)<br>5. The brightness only change when the value is 50 (Camera firmware issue) |                          |          |                |       |        |     |                |      |              |                      |          |                     |
| EHN3361     | refer to EZN3340(1.2.5-B2)  | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 2-way | 1/1    | -   | Yes            | -    | Yes          | Yes*                 | Yes      | Supported by design |
| EMN2220     | 0.8.7-B10   | M-JPEG<br>H.264          | 1        | 1920x1080      | 1-way | 0/0    | -   | Yes            | Yes  | Yes          | Yes                  | -        |                     |
| Note:       | 1. can't switch CBR/VBR.<br>2. only support VBR.  |                          |          |                |       |        |     |                |      |              |                      |          |                     |
| EMN2320     | 1.0.1   | M-JPEG<br>H.264          | 1        | 2048x1536      | 1-way | 0/0    | -   | Yes            | Yes  | Yes          | Yes                  | -        |                     |
| Note:       | EMN2320 no support 720x480, 704x480 and 640x480 resolution.   |                          |          |                |       |        |     |                |      |              |                      |          |                     |
| EPN3100     | 1.2.14  | H.264<br>MPEG4<br>MJPEG  | 1        | 704x576        | 1-way | 4/2    | Yes | Yes            | Yes  | -            | -                    | -        | Supported by design |
| EDN3260     | 1.0.18  | M-JPEG<br>H.264          | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -            | -                    | -        |                     |
| EPN3600     | 1.2.14  | H.264<br>MPEG4<br>MJPEG  | 1        | 704x576        | 1-way | 4/2    | Yes | Yes            | Yes  | -            | -                    | -        |                     |
| EPN4122     | 1.0.5   | M-JPEG<br>H.264          | 1        | 1280x960       | 1-way | 2/2    | Yes | Yes            | -    | Yes          | Yes                  | -        |                     |





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | ONVIF Search | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|--------------|----------------------|----------|---------------------|
| EPN4220     | 1.0.16  | M-JPEG<br>H.264          | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | -    | Yes          | Yes                  | -        |                     |
| Note:       | 1. The audio in status can't synchronize to web client. (ONVIF limitation)<br>2. Cannot change the rate control mode. (ONVIF limitation)<br>3. Cannot get snapshot by CGI(404). (Camera firmware issue)   |                          |          |                |       |        |     |                |      |              |                      |          |                     |
| EPN4220P    | refer to EPN4220(1.0.16)  | M-JPEG<br>H.264          | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | -    | Yes          | Yes                  | -        | Supported by design |
| EPN4230     | refer to EPN4220(1.0.16)  | M-JPEG<br>H.264          | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | -    | Yes          | Yes                  | -        | Supported by design |
| EQN2200     | 1.0.27  | H.264<br>MJPEG           | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes          | -                    | -        | Supported by design |
| EQN2201     | 1.0.27  | H.264<br>MJPEG           | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes          | -                    | -        | Supported by design |
| ETN2110     | v3.2.1.4  | M-JPEG<br>MPEG4<br>H.264 | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes                  | -        |                     |
| Note:       | ETN2110: Motion detection is not compatible with MPEG4 codec because of camera firmware issue.  |                          |          |                |       |        |     |                |      |              |                      |          |                     |
| ETN2260     | 1.0.1_F1  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | -      | Yes | Yes            | -    | Yes          | Yes*                 | Yes      |                     |
| Note:       | 1. Not support CBR mode. (Camera firmware issue)<br>2. The quality value can't be sync with camera web. (Camera firmware issue)<br>3. Not support zoom and focus. (Camera firmware issue)<br>4. The resolution of snapshot always be 640x480. (Camera firmware issue)<br>5. The quality value can't be setup to 0, and the quality value can't be setup to 10 under MJPEG. (Camera firmware issue)<br>6. If there are duplicate name of preset point, the function of GoTo preset point and Clear All preset point will fail. (Camera firmware issue) |                          |          |                |       |        |     |                |      |              |                      |          |                     |
| EVS200A     | 1.2.8   | H.264<br>MPEG4<br>MJPEG  | 2        | 704x576        | 1-way | 2/2    | Yes | Yes            | Yes  | -            | -                    | -        |                     |
| EVS200AW    | 1.2.8   | H.264<br>MPEG4<br>MJPEG  | 2        | 704x576        | 1-way | 2/2    | Yes | Yes            | Yes  | -            | -                    | -        | Supported by design |
| Note:       | EVS200A/EVS200AW: Fix stream 1 as recording stream and fix stream 2 for mobile client used. PTZ is only supported by external RS-485 device.  |                          |          |                |       |        |     |                |      |              |                      |          |                     |
| EVS410      | 1.0.21  | H.264<br>MJPEG           | 4        | 704x480        | 1-way | 4/1    | -   | Yes            | -    | Yes          | -                    | -        |                     |
| Note:       | 1. MJPEG high resolution only can up to 10 fps.<br>2. Not support RS-485 ptz.   |                          |          |                |       |        |     |                |      |              |                      |          |                     |
| EZN3240     | 1.0.14  | H.264<br>MJPEG           | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes          | -                    | -        |                     |
| EZN850      | 1.2.5   | H.264<br>MPEG4<br>MJPEG  | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -            | -                    | -        |                     |
| Note:       | PTZ: support focus only.  |                          |          |                |       |        |     |                |      |              |                      |          |                     |
| Note:       | Implement with ONVIF protocol v1.02: EAN3200, EDN3240, EHN3200, EQN2200, EQN2201, EVS410, EZN3240   |                          |          |                |       |        |     |                |      |              |                      |          |                     |
| Note:       | Due to the limitation of ONVIF protocol, ONVIF search works only as cameras keep default administrator name and password.   |                          |          |                |       |        |     |                |      |              |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | ONVIF Search | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|--------------|----------------------|----------|---------------------|
| EZN3160     | 1.0.7-B1   | M-JPEG<br>H.264          | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | -            | Yes                  | -        |                     |
| EZN3260     | 1.2.4  | M-JPEG<br>H.264          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -            | Yes                  | -        |                     |
| Note:       | 1. Third stream resolution can't set to 160x128<br>2. Stream2 and Stream3 are not sync with the value of onvif tool when close and open the stream2,stream3 check box in web site.<br>3. The quality value will correspond to website Bitrate/Quality depends on CBR/VBR.  |                          |          |                |       |        |     |                |      |              |                      |          |                     |
| EZN3340     | 1.2.5-B2   | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 2-way | 1/1    | *1  | Yes            | -    | Yes          | Yes*                 | Yes      |                     |
| Note:       | 1.The parameters of the camera are not configurable with MPEG4 format.(Camera firmware issue)<br>2.Not support CBR mode.(Camera firmware issue)<br>3.Not support zoom and focus.(Camera firmware issue)<br>4.It will lose parameters of stream2 and stream3 if you disable stream2 and stream3 on camera web.(Camera firmware issue) |                          |          |                |       |        |     |                |      |              |                      |          |                     |
| EZN3361     | refer to EZN3340(1.2.5-B2)   | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 2-way | 1/1    | -   | Yes            | -    | Yes          | Yes*                 | Yes      | Supported by design |
| Generic     | 1.2.5B11   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -            | Yes*                 | Yes      |                     |
| Note:       | Support generic dewarp<br>1.Not support CBR mode.(Camera Firmware issue)<br>2.It will lose parameters of stream2 and stream3 if you disable stream2 and stream3 on camera web.(Camera performance limitation)  |                          |          |                |       |        |     |                |      |              |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name   | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|---------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| ACM-B3000     | 1.02.09   | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 1-way | *2     | -   | Yes            | Yes  | -                  | Yes                  | -        |                     |
| ACM-PT500     | 2.03.16   | H.264<br>MPEG4           | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | -                  | Yes                  | Yes      |                     |
| Note:         | Camera is unable to achieve maximum FPS. (Camera performance limitation)  |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| ACM-R2001     | 1.02.09   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | -                  | Yes                  | -        |                     |
| Note:         | Framerate may not enough about 2~8 fps due to camera issue.   |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| ACM-R3002     | Refer to ACM-V3103(2.03.23A)  | H264<br>MPEG4            | 1        | 2048x1536      | Yes   | 2/1    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| Note:         | 1.Frame rate can't meet the requirements.(Camera performance limitation)<br>2.Not support zoom and focus.   |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| ACM-R3006     | 1.02.05T  | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 1-way | *2     | *2  | Yes            | Yes  | -                  | Yes                  | -        |                     |
| ACM-V3001     | 1.02.09   | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 1-way | *2     | -   | Yes            | Yes  | -                  | Yes                  | -        |                     |
| ACM-V3002     | Refer to ACM-V3103(2.03.23A)  | H264<br>MPEG4            | 1        | 2048x1536      | Yes   | 2/1    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| Note:         | 1.Frame rate can't meet the requirements.(Camera performance limitation)<br>2.Not support zoom and focus.   |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| ACM-V3103     | 2.03.23A  | H264<br>MPEG4            | 1        | 2048x1536      | Yes   | 2/1    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note:         | 1.Audio in can't be work.(Camera Firmware issue)<br>2.RS-485 can't be work.(Camera Firmware issue)<br>3.Alarm out can't be work.(Camera Firmware issue) |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| C3000/C3000-W | v3.2.2.3  | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        |                     |
| CDB-4KM552    | Refer to TCP-KM465(VK2.0.11.0_F)  | H.265<br>H.264<br>MJPEG  | 1        | 2592x1520      | 2-way | 1/1    | -   | *2             | Yes  | -                  | Yes*                 | *2       | Supported by design |
| CDB-5VM551    | Refer to TCP-VM559(VC2.0.26.6_F)  | H.264<br>M-JPEG          | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| CDB-5VM551G   | Refer to TCP-VM559G(VH2.0.0.6)  | H.264<br>M-JPEG          | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| CDB-720F      |   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | 1/1    | -   | Yes            | *1   | -                  | Yes                  | -        |                     |
| CDB-720F/1R   | V1.0.20_F   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | 1/1    | -   | Yes            | *1   | -                  | Yes                  | -        |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name  | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|--------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| CDB-720V     | VB1.0.26_F  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | 1-1    | -   | Yes            | Yes  | -                  | Yes                  | -        |                     |
| CDB-720VIR   | VB1.0.26_F  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | 1/1    | -   | Yes            | *1   | -                  | Yes                  | -        |                     |
| CDB-720VIR-H | VE2.0.14.2_F  | H.264<br>MJPEG           | 1        | 1280x800       | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      |                     |
| Note:        | 1. (Camera issue): FPS could not reach up to 20/30.<br>2. (Known issue): The info. of stream profile display failure  |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| CDB-HD280    | refer to TCP-HDVB800-H(VE2.0.16.8_F)  | H.264<br>MJPEG           | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| CDB-HFD720   | Refer to TCP-HDVB720-H(VE2.0.20.8)  | H264<br>MJPEG            | 1        | 1280x800       | -     | -      | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| CDB-HFD728   | refer to CDB-720VIR-H(VE2.0.14.2_F)   | H.264<br>MJPEG           | 1        | 1280x800       | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| CDB-HFD828   | refer to TCP-HDVB800-H(VE2.0.16.8_F)  | H.264<br>MJPEG           | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| CDB-HFD828W  | refer to TCP-HDVB800-H(VE2.0.16.8_F)  | H.264<br>MJPEG           | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| CDB-MD602    | refer to TCP-MZ602(VG1.0.14_F)  | H.264<br>M-JPEG          | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| CDB-MV1080F  | VB1.0.32_F  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | -     | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        |                     |
| CDB-MV720F   | VB1.0.28_F  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        |                     |
| Note         | Camera FW issue: framerate can not reach 30fps.   |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| CDB-MV720F-H | Refer to TCP-HDVB720-H(VE2.0.20.8)  | H264<br>MJPEG            | 1        | 1280x800       | -     | -      | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| CDB-T5       | A1D-500-V6.08.25-NB   | H.264<br>M-JPEG          | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note:        | Fisheye camera<br>Only audio can ben exported while selecting MOV format in playback system. (NUUO server limitation) |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| CDV-2M360    | VB1.0.32_F  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | -        |                     |
| Note         | Fisheye camera  |                          |          |                |       |        |     |                |      |                    |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name   | Tested Firmware  | Video Format      | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|---------------|--|-------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| CDV-3F828     | Refer to TCP-HDVB180(V E1.0.20.6_F)  | H.264 MJPEG       | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| CDV-3V930     |  | MPEG4 M-JPEG      | 1        | 720x480        | 1-way | 1/1    | -   | Yes            | -    | -                  | -                    | -        | Supported by design |
| CDV-3V930U    |  | MPEG4 M-JPEG      | 1        | 720x480        | 1-way | 1/1    | -   | Yes            | -    | -                  | -                    | -        | Supported by design |
| CDV-3VM301    |  | MPEG4 M-JPEG      | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | -                  | -                    | -        | Supported by design |
| CDV-3VM501    | refer to TCP-MH802(1.0.46)   | M-JPEG H.264      | 1        | 1600x1200      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| CDV-3VM800    | VC1.0.06_F   | H.264 M-JPEG      | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        |                     |
| CDV-3VM800-H  | refer to TCP-HDVB800-H(VE2.0.16.8_F)   | H.264 MJPEG       | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| CDV-3VM800-H1 | refer to TCP-HDVB800-H(VE2.0.16.8_F)   | H.264 MJPEG       | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| CDV-3VM800Z3  | refer to TCP-HDVB800Z3(VC2.0.24.2)   | H.264 MJPEG       | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| CDV-3VM800Z42 | VE1.0.20.2_F   | H.264 MJPEG       | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note:         | 1. The camera with highest resolution and MJPEG is unable to achieve highest fps. (Camera firmware issue)<br>2. If connect 2 or above streams, bitrate and frame rate will decrease. (Camera performance limitation) |                   |          |                |       |        |     |                |      |                    |                      |          |                     |
| CDV-3VWD960   | V1.0.16_F  | H.264 M-JPEG      | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | -    | -                  | -                    | -        |                     |
| CDV-3VWD960H  |  | H.264 M-JPEG      | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | -    | -                  | -                    | -        | Supported by design |
| CDV-4F936     | VH2.0.0.8_F  | H.264 MJPEG       | 1        | 2688x1520      | -     | -      | -   | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note:         | 1. Camera with highest resolution and MJPEG format is unable to use. (Camera performance limitation)   |                   |          |                |       |        |     |                |      |                    |                      |          |                     |
| CDV-4KM502    | Refer to TCP-KM465(VK2.0.11.0_F)   | H.265 H.264 MJPEG | 1        | 2592x1520      | 2-way | 1/1    | -   | *2             | Yes  | -                  | Yes*                 | *2       | Supported by design |
| CDV-4VM501    | Refer to TCP-VM469(VH1.0.0_F)  | H.264 MJPEG       | 1        | 2688x1520      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name   | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|---------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| CDV-4VM501Z42 | Refer to TCP-VM469Z42(VH2.0.0.2)  | H.264 MJPEG  | 1        | 2688x1520      | 2-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| CDB-4VM551    | Refer to TCP-VM469(VH1.0.0.F)   | H.264 MJPEG  | 1        | 2688x1520      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| CDV-5VM501    | Refer to TCP-VM559(VC2.0.26.6.F)  | H.264 M-JPEG | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| CDV-5VM501G   | Refer to TCP-VM559G(VH2.0.0.6)  | H.264 M-JPEG | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| CDV-5VM501Z3  | VC2.0.26.4_F  | H.264 M-JPEG | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note:         | 1. PTZ could only support zoom and autofocus.   |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| CDV-5VM501Z42 | Refer to TCP-VM559Z42(VC2.0.26.6)   | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| CDV-DT5       | V6.08.25-NB   | H.264 M-JPEG | 1        | 2592x1944      | 1-way | -      | -   | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note:         | Fisheye camera<br>1.Camera is unable to achieve maximum FPS. (Camera performance limitation)<br>2.Main console Flip/mirror checkbox not sync with Web interface. (NUUO server limitation) |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| CDV-DT951R    | Refer to CDV-DT5(V6.08.25-NB)   | H.264 M-JPEG | 1        | 2592x1944      | 1-way | -      | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| CDV-MD602     | refer to TCP-MZ602(VG1.0.14.F)  | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| CDV-MD605     | refer to TCP-MZ602(VG1.0.14.F)  | H.264 M-JPEG | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| CDV-MFB2000D  | 2.03.17   | H.264 MPEG4  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      |                     |
| Note:         | 1. Camera is unable to achieve maximum FPS. (Camera performance limitation)<br>2. The info. of stream profile display failure. (NUUO server limitation)                                   |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| CDV-MV1080F-H | refer to TCP-HDVB800-H(VE2.0.16.8.F)  | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes*     | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name   | Tested Firmware            | Video Format    | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|---------------|----------------------------|-----------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| CDV-P360      | refer to TCP-MH802(1.0.46) | M-JPEG<br>H.264 | 1        | 1600x1200      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| Note:         | Fisheye camera             |                 |          |                |       |        |     |                |      |                    |                      |          |                     |
| CDV-P360-5    | VC2.0.26.4_F               | H.264<br>M-JPEG | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note:         | Fisheye camera             |                 |          |                |       |        |     |                |      |                    |                      |          |                     |
| EDH-02H       | V1.0.20_F                  | H.264<br>M-JPEG | 1        | 720x480        | 1-way | 1/1    | Yes | Yes            | -    | -                  | -                    | -        |                     |
| EP-201        |                            | MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 0/0    | Yes | Yes            | -    | -                  | -                    | -        | Supported by design |
| EP-221        |                            | MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 1/0    | Yes | Yes            | -    | -                  | -                    | -        | Supported by design |
| EP-221DN      |                            | MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 0/0    | Yes | Yes            | -    | -                  | -                    | -        | Supported by design |
| EP-601        |                            | MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 0/0    | Yes | Yes            | -    | -                  | -                    | -        | Supported by design |
| EP-601HW      |                            | MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 0/0    | Yes | Yes            | -    | -                  | -                    | -        |                     |
| EP-908        |                            | MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 0/0    | Yes | Yes            | -    | -                  | -                    | -        | Supported by design |
| EP-908HW      |                            | MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 0/0    | Yes | Yes            | -    | -                  | -                    | -        | Supported by design |
| EP-936        |                            | MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 0/0    | Yes | Yes            | -    | -                  | -                    | -        | Supported by design |
| EP-936HW      |                            | MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 0/0    | Yes | Yes            | -    | -                  | -                    | -        | Supported by design |
| EP-HTQ935     | V3.2.56_F                  | MPEG4<br>M-JPEG | 1        | 720x480        | -     | 0/0    | Yes | Yes            | -    | -                  | -                    | -        |                     |
| EP-Q2018H-IP  |                            | H.264<br>M-JPEG | 1        | 720x480        | 1-way | 0/0    | Yes | Yes            | -    | -                  | -                    | -        | Supported by design |
| EP-Q2018HW-IP | V1.0.8_F                   | H.264<br>M-JPEG | 1        | 720x480        | 1-way | 0/0    | Yes | Yes            | -    | -                  | -                    | -        |                     |
| EP-Q2026H-IP  |                            | H.264<br>M-JPEG | 1        | 720x480        | 1-way | 0/0    | Yes | Yes            | -    | -                  | -                    | -        | Supported by design |
| EP-Q2026HW-IP |                            | H.264<br>M-JPEG | 1        | 720x480        | 1-way | 0/0    | Yes | Yes            | -    | -                  | -                    | -        | Supported by design |
| EP-Q2036H-IP  |                            | H.264<br>M-JPEG | 1        | 720x480        | 1-way | 0/0    | Yes | Yes            | -    | -                  | -                    | -        | Supported by design |
| EP-Q2036HW-IP | V1.0.46_F                  | H.264<br>M-JPEG | 1        | 720x576        | *2    | *2     | Yes | Yes            | *2   | -                  | Yes                  | Yes      |                     |
| MD-D1200      |                            | MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 1/1    | Yes | Yes            | -    | -                  | -                    | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name    | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|----------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| MD-D1322       | V1.0.23.09_F  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 2/1    | *1  | Yes            | Yes  | -                  | Yes                  | -        |                     |
| MD-D1612       | V1.0.16_F   | H.264<br>M-JPEG          | 1        | 720x576        | 1-way | 1/1    | Yes | Yes            | -    | -                  | -                    | -        |                     |
| MD-D3622Q-H    | VD1.0.12_04_F   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | -        |                     |
| SP-HP2013C-IP  | onvif_v2.4.2_20150327   | M-JPEG<br>H.264          | 1        | 1280x960       | 1-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| Note:          | 1. DI & DO can't be used. (Camera Firmware issue)<br>2. Bitrate list and quality list may not be synchronized with camera web. (Onvif limitation)<br>3. 704x288 is not shown in the resolution list of the second stream. (Camera Firmware issue)<br>4. Auto focus is not supported. (Camera performance limitation)<br>[IP+]5. Video parameter setting does not synchronize to camera web. (Camera Firmware issue)<br>[NAS]6. Focus and PTZ speed setting are not supported. (NUUO server limitation)<br>[NAS]7. The image of snapshot doesn't update via Snapshot to FTP function.(Camera Firmware issue)   |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| SP-HP2020C-IP  | onvif_v2.4.0_20141027   | M-JPEG<br>H.264          | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| Note:          | 1. DI does not function. (Camera Firmware issue)<br>2. DO is unable to turn off. (Camera Firmware issue)<br>3. Bitrate list and quality list may not be synchronized with camera web. (Onvif limitation)<br>4. 704x288 is not shown in the resolution list of the second stream. (Camera Firmware issue)<br>5. Flip and mirror are not supported. (Onvif limitation)<br>6. Auto pan is not supported. (Onvif limitation)<br>7. Auto focus is not supported. (Camera performance limitation)<br>8. Hue setting is not supported. (Onvif limitation)<br>9. Video parameter setting does not synchronize to camera web. (Camera Firmware issue)<br>[NAS] 10. Focus and PTZ speed setting are not supported. (NUUO server limitation) |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| SP-HP2020CM-IP | Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)   | M-JPEG<br>H.264          | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| SP-HP2020Q-IP  | Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)   | M-JPEG<br>H.264          | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| SP-HP2030CM-IP | Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)   | M-JPEG<br>H.264          | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name    | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|----------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| SP-HP2030Q-IP  | Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)   | M-JPEG H.264 | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| SP-HP2313C-IP  | Refer to SP-HP2013C-IP(onvif_v2.4.2_20150327)   | M-JPEG H.264 | 1        | 1280x960       | 1-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| SP-HP2320C-IP  | Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)   | M-JPEG H.264 | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| SP-HP2330C-IP  | Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)   | M-JPEG H.264 | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| SP-HP2330Q-IP  | Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)   | M-JPEG H.264 | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| SP-HP2336Q-IP  | Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)   | M-JPEG H.264 | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| SP-HP2620CP-IP | Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)   | M-JPEG H.264 | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      | Supported by design |
| SP-HP4833-IP   | A1D-500-V6.09.44-NB   | M-JPEG H.264 | 1        | 2688x1520      | 2-way | 4/2    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note:          | 1.The camera with resolution 1920x1080 is unable to achieve 30 fps. (Camera performance limitation) |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| SP-PTIR736A-IP | Refer to EP-Q2036HW-IP(V1.0.46_F)   | H.264 M-JPEG | 1        | 720x576        | *2    | *2     | Yes | Yes            | *2   | -                  | Yes                  | Yes      | Supported by design |
| SP-PTIR736B-IP | Refer to EP-Q2036HW-IP(V1.0.46_F)   | H.264 M-JPEG | 1        | 720x576        | *2    | *2     | Yes | Yes            | *2   | -                  | Yes                  | Yes      | Supported by design |
| SP-PTIR737-IP  | V1.0.16_F   | H.264 M-JPEG | 1        | 720x576        | 1-way | -      | Yes | Yes            | -    | -                  | -                    | -        |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name      | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|------------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| SP-PYIR737-LA-IP |  | H.264<br>M-JPEG          | 1        | 720x480        | 1-way | -      | Yes | Yes            | -    | -                  | -                    | -        | Supported by design |
| TCMA-99          |  | MPEG4<br>M-JPEG          | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | -                  | -                    | -        | Supported by design |
| TCMP-99          |  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | -    | -                  | -                    | -        | Supported by design |
| TCP-336AM        | VB1.0.40_F   | H.264<br>MPEG4<br>M-JPEG | 1        | 2032x1536      | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        |                     |
| Note:            | When format is set to MPEG4, resolution is 1920*180 and quality is excellent, the maximum FPS can only reach 20. |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| TCP-1200AV       | V1.0.26_F  | H.264<br>M-JPEG          | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | -                  | -                    | -        |                     |
| TCP-1300AM       | V1.0.26_F  | H.264<br>M-JPEG          | 1        | 1280x1024      | 1-way | -      | -   | Yes            | -    | -                  | -                    | -        |                     |
| TCP-2200AM       | V1.0.30_F  | H.264<br>MJPEG           | 1        | 1600x1200      | 1-way | -      | -   | -              | Yes  | -                  | Yes                  | -        |                     |
| TCP-2200AM-H     | refer to TCP-HDVB800-H(VE2.0.16.8_F)   | H.264<br>MJPEG           | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-2700AM       | refer to CDB-720VIR-H(VE1.0.12.2_F)  | H.264<br>MJPEG           | 1        | 1280x800       | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| TCP-2700AM-W     | refer to CDB-720VIR-H(VE2.0.14.4)  | H.264<br>MJPEG           | 1        | 1280x800       | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| TCP-2800AM       | refer to TCP-HDVB800-H(VE2.0.16.8_F)   | H.264<br>MJPEG           | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-670DNU       |  | MPEG4<br>M-JPEG          | 1        | 720x480        | 1-way | 2/2    | -   | Yes            | -    | -                  | -                    | -        | Supported by design |
| TCP-680DNU       |  | MPEG4<br>M-JPEG          | 1        | 720x480        | 1-way | 2/2    | -   | Yes            | -    | -                  | -                    | -        | Supported by design |
| TCP-690          |  | MPEG4<br>M-JPEG          | 1        | 720x480        | 1-way | 2/2    | -   | Yes            | -    | -                  | -                    | -        | Supported by design |
| TCP-690DN        |  | MPEG4<br>M-JPEG          | 1        | 720x480        | 1-way | 2/2    | -   | Yes            | -    | -                  | -                    | -        | Supported by design |
| TCP-690U         | V3.2.60_F  | MPEG4<br>M-JPEG          | 1        | 720x480        | 1-way | 2/2    | -   | Yes            | -    | -                  | -                    | -        |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name   | Tested Firmware   | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|---------------|---|--------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| TCP-B365K     | refer to TCP-HDVB800-H(VE2.0.16_8_F)  | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-BF128     | Refer to TCP-HDVB720-H(VE2.0.20.8)  | H264 MJPEG         | 1        | 1280x800       | -     | -      | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-BF108     | Refer to TCP-HDVB720-H(VE2.0.20.8)  | H264 MJPEG         | 1        | 1280x800       | -     | -      | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-BF1080    | refer to TCP-HDVB800-H(VE2.0.16_8_F)  | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| Note:         | 1. (Camera issue): FPS could not reach up to 20/30.<br>2. (Known issue): The info. of stream profile display failure  |                    |          |                |       |        |     |                |      |                    |                      |          |                     |
| TCP-BF208     | Refer to TCP-HDVB180(VE1.0.20.6_F)  | H.264 MJPEG        | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-BF428     | Refer to CDV-4F936(VH2.0.0.8_F)   | H.264 MJPEG        | 1        | 2688x1520      | -     | -      | -   | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| TCP-BF728IR   | refer to CDB-720VIR-  | H.264 MJPEG        | 1        | 1280x800       | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| TCP-BF828IR   | refer to TCP-HDVB800-H(VE2.0.16_8_F)  | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-HDVB110   | Refer to TCP-HDVB720-H(VE2.0.20.8)  | H264 MJPEG         | 1        | 1280x800       | -     | -      | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-HDVB180   | VE1.0.20.6_F  | H.264 MJPEG        | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| TCP-HDVB720P  | V1.0.20_F   | H.264 MPEG4 M-JPEG | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        |                     |
| TCP-HDVB720-H | VE2.0.20.8  | H264 MJPEG         | 1        | 1280x800       | -     | -      | -   | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note:         | 1.Setting FPS have problems(Camera Firmware issue), example:<br>(1)Stream1 & Stream2 format : JPEG, when stream1's resolution decrease, stream2's fps would increase a little<br>(2)Stream1 & Stream2 format : H264, stream2's fps can't reach our setting<br>(3)When this camera's users more than 1, fps would decrease |                    |          |                |       |        |     |                |      |                    |                      |          |                     |
| TCP-HDVB800   | VC1.0.18.2_F  | H.264 M-JPEG       | 1        | 1920x1080      | 1-way | 1/1    | -   | -              | Yes  | -                  | Yes                  | -        |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name    | Tested Firmware  | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|----------------|--|--------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| TCP-HDVB800-H  | VE2.0.16.8_F   | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note:          | 1. Camera is unable to achieve maximum FPS. (Camera performance limitation)<br>2. Audio has noise. (Camera firmware issue)<br>3. Parameter setting will lead camera can't connect. (Camera firmware issue) |                    |          |                |       |        |     |                |      |                    |                      |          |                     |
| TCP-HDVB800-H1 | refer to TCP-HDVB800-H(VE2.0.16.8_F)   | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-HDVB800Z3  | VC2.0.24.2_F   | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note:          | 1. PTZ only support zoom.  |                    |          |                |       |        |     |                |      |                    |                      |          |                     |
| TCP-HDVB800Z42 | Refer to CDV-3VM800Z42 (VE 1.0.20.2)   | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-HDVB801    |  | H.264 MPEG4 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | -              | Yes  | -                  | Yes                  | -        |                     |
| TCP-HFB720     | VB1.0.28_F   | H.264 MPEG4 M-JPEG | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        |                     |
| TCP-HFB720-H   | Refer to TCP-HDVB720-H(VE2.0.20.8)   | H264 MJPEG         | 1        | 1280x800       | -     | -      | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-HFB1080D   | 2.03.10  | H.264 MPEG4        | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | -                  | Yes                  | -        |                     |
| Note:          | 1.The response of camera setting is slow.  |                    |          |                |       |        |     |                |      |                    |                      |          |                     |
| TCP-HP1080     | VC1.0.06_F   | H.264 M-JPEG       | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        |                     |
| TCP-HP1080-H   | refer to TCP-HDVB800-H(VE2.0.16.8_F)   | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-HP1080WI   |  | H.264 MPEG4 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | -              | *1   | -                  | Yes                  | -        |                     |
| TCP-HP930      |  | MPEG4 M-JPEG       | 1        | 720x480        | 1-way | 2/2    | -   | Yes            | -    | -                  | -                    | -        | Supported by design |
| TCP-HP930U     |  | MPEG4 M-JPEG       | 1        | 720x480        | 1-way | 2/2    | -   | Yes            | -    | -                  | -                    | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name     | Tested Firmware   | Video Format      | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-----------------|---|-------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| TCP-HVB3100D    | Refer to ACM-V3103(2.03_23A)  | H264 MPEG4        | 1        | 2048x1536      | Yes   | 2/1    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| Note:           | 1.Frame rate can't meet the requirements.(Camera performance limitation)<br>2.Not support zoom and focus. |                   |          |                |       |        |     |                |      |                    |                      |          |                     |
| TCP-HVB3105D    | Refer to ACM-V3103(2.03_23A)  | H264 MPEG4        | 1        | 2048x1536      | Yes   | 2/1    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| Note:           | 1.Frame rate can't meet the requirements.(Camera performance limitation)                                  |                   |          |                |       |        |     |                |      |                    |                      |          |                     |
| TCP-IPWD690     |   | MPEG4 M-JPEG      | 1        | 720x480        | 1-way | 2/2    | -   | Yes            | -    | -                  | -                    | -        | Supported by design |
| TCP-IPWD700DN   | V1.0.16_F   | H.264 M-JPEG      | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | -    | -                  | -                    | -        |                     |
| TCP-IR590-WD30  | V1.0.20_F   | H.264 M-JPEG      | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | -    | -                  | -                    | -        |                     |
| TCP-IR590-WD50  |   | H.264 M-JPEG      | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | -    | -                  | -                    | -        | Supported by design |
| TCP-IRH5030C    | refer to TCP-MH802(1.0.46)  | M-JPEG H.264      | 1        | 1600x1200      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| TCP-IRH5040C    | refer to TCP-MH802(1.0.46)  | M-JPEG H.264      | 1        | 1600x1200      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| TCP-IRH5080-50  | Refer to IRH5080-70(VC2.0.26.4_F)   | H.264 M-JPEG      | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-IRH5080W-70 | Refer to TCP-IRH5080-70(VC2.0.26.4)   | H.264 M-JPEG      | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-IRH5080-70  | VC2.0.26.4_F  | H.264 M-JPEG      | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| TCP-IRH5080W-50 | Refer to TCP-IRH5080-70(VC2.0.26.4)   | H.264 M-JPEG      | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-IRV540      |   | MPEG4 M-JPEG      | 1        | 720x480        | 1-way | 0/0    | -   | Yes            | -    | -                  | -                    | -        | Supported by design |
| TCP-IRV560      |   | MPEG4 M-JPEG      | 1        | 720x480        | 1-way | 1/1    | -   | Yes            | -    | -                  | -                    | -        | Supported by design |
| TCP-KM465       | VK2.0.11.0_F  | H.265 H.264 MJPEG | 1        | 2592x1520      | 2-way | 1/1    | -   | *2             | Yes  | -                  | Yes*                 | *2       |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution               | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|------------------------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| TCP-KZ462   | Refer to TCP-KM465(VK2.0.11.0_F)   | H.265<br>H.264<br>MJPEG  | 1        | 2592x1520                    | 2-way | 1/1    | -   | *2             | Yes  | -                  | Yes*                 | *2       | Supported by design |
| TCP-M360K   | refer to TCP-HDVB800-H(VE2.0.16.8_F)   | H.264<br>MJPEG           | 1        | 1920x1080                    | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-M912DN  | V1.2.28_F  | MPEG4<br>M-JPEG          | 1        | MPEG4:<br>640x480<br>M-JPEG: | 1-way | 2/2    | -   | Yes            | -    | -                  | -                    | -        |                     |
| TCP-MB602   | refer to TCP-MZ602(VG1.0.14_F)   | H.264<br>M-JPEG          | 1        | 1920x1080                    | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| TCP-MB685   | refer to TCP-MZ602(VG1.0.14_F)   | H.264<br>M-JPEG          | 1        | 1920x1080                    | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| TCP-MH802   | 1.0.46   | M-JPEG<br>H.264          | 1        | 1600x1200                    | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      |                     |
| Note:       | 1. Framerate may be incorrect displayed with MJPEG format. (Camera firmware issue)<br>2. Camera is unable to achieve maximum FPS. (Camera performance limitation)  |                          |          |                              |       |        |     |                |      |                    |                      |          |                     |
| TCP-MH859   | Refer to TCP-VM559(VC2.0.26.6_F)   | H.264<br>M-JPEG          | 1        | 2592x1944                    | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| TCP-MZ602   | VG1.0.14_F   | H.264<br>M-JPEG          | 1        | 1920x1080                    | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      |                     |
| Note:       | Camera is unable to achieve maximum FPS. (Camera performance limitaion)  |                          |          |                              |       |        |     |                |      |                    |                      |          |                     |
| TCP-MB605   | refer to TCP-MZ602(VG1.0.14_F)   | H.264<br>M-JPEG          | 1        | 1920x1080                    | 2-way | 1/1    | -   | Yes            | Yes  | -                  | -                    | Yes      | Supported by design |
| TCP-MZ605   | refer to TCP-MZ602(VG1.0.14_F)   | H.264<br>M-JPEG          | 1        | 1920x1080                    | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| TCP-VM201   |  | MPEG4<br>M-JPEG          | 1        | 1280x1024                    | 1-way | 0/0    | -   | Yes            | -    | -                  | Yes                  | -        | Supported by design |
| TCP-VM2210  | 3.0.0.8  | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080                    | 2-way | 1/0    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note:       | 1. Talk does not implement. (Camera Firmware issue)<br>2. Bitrate list does not sync with web. (Camera Firmware issue)<br>3. Camera with highest resolution is unable to achieve maximum FPS in MJPEG or MPEG4. (Camera performance limitation)<br>4. The bitrate list of stream3 does not sync with web (Camera Firmware issue)<br>5. PTZ speed does not sync with web. (Camera Firmware issue) |                          |          |                              |       |        |     |                |      |                    |                      |          |                     |
| TCP-VM359   | VC1.0.16_F   | H.264<br>M-JPEG          | 1        | 2048x1536                    | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name  | Tested Firmware  | Video Format    | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|--------------|--|-----------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| TCP-VM469    | VH1.0.0_F  | H.264<br>M-JPEG | 1        | 2688x1520      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note:        | 1. Resolution list & frame rate list may not sync with web. (Camera Firmware issue)  |                 |          |                |       |        |     |                |      |                    |                      |          |                     |
| TCP-VM469Z42 | VH2.0.0.2  | H.264<br>MJPEG  | 1        | 2688x1520      | 2-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note:        | 1. Camera is unable to achieve high FPS. (Camera performance limitation)<br>2. Sever resolution list is not same as web resolution list. (Camera Firmware issue) |                 |          |                |       |        |     |                |      |                    |                      |          |                     |
| TCP-VM501    | refer to TCP-MH802(1.0.  | M-JPEG<br>H.264 | 1        | 1600x1200      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| TCP-VM559    | VC2.0.26.6_F   | H.264<br>M-JPEG | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| TCP-VM559G   | VH2.0.0.6_F  | H.264<br>M-JPEG | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note:        | 1. The camera with highest quality and MJPEG format is unable to use. (Camera performance limitation)  |                 |          |                |       |        |     |                |      |                    |                      |          |                     |
| TCP-VM559Z3  | refer to CDV-5VM501Z3(VC2.0.26.4_F)  | H.264<br>M-JPEG | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| TCP-VM559Z42 | VC2.0.26.6_F   | H.264<br>MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| WB-8211SD    |  | MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 2/4    | -   | Yes            | -    | -                  | Yes                  | -        | Supported by design |
| WB-8211SDU   |  | MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 2/4    | -   | Yes            | -    | -                  | Yes                  | -        | Supported by design |
| WB-8411      |  | MPEG4<br>M-JPEG | 4        | 720x480        | 1-way | 4/1    | -   | Yes            | -    | -                  | Yes                  | -        | Supported by design |
| WB-8412      | V2.2.26_F  | MPEG4<br>M-JPEG | 4        | 688x448        | 1-way | 4/4    | Yes | Yes            | -    | -                  | Yes                  | -        |                     |
| WB-H811      | V1.0.44_F  | M-JPEG<br>H.264 | 1        | 720x576        | 2-way | 2/2    | Yes | Yes            | Yes  | -                  | Yes                  | Yes      |                     |
| Note:        | Resolution can't set to 4CIF.  |                 |          |                |       |        |     |                |      |                    |                      |          |                     |
| WB-H814      | V1.0.82_F  | H.264<br>M-JPEG | 4        | 720x576        | 2-way | 4/4    | Yes | Yes            | Yes  | -                  | Yes                  | Yes      |                     |
| Note:        | 1. Support dual mode only. (Camera firmware issue)<br>2. Resolution can not be set correctly. (Camera firmware issue)  |                 |          |                |       |        |     |                |      |                    |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name          | Tested Firmware  | Video Format            | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|----------------------|--|-------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| <b>FC-348-NTSC</b>   | BU 1.2   | H.264<br>MJPEG<br>MPEG4 | 1        | 720x480        | -     | -      | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:                | 1. When bitrate set higher than 1Mbps, the RTSP connection is unstable.<br>2. Sometime we fail to change the encoding setting after the camera connected for a long time. The setting displays at web client and onvif interface will change but actually not.<br>3. Can't get the I/O status by Onvif interface<br>4. Can't use camera search function because of onvif command timeout.<br>5. Can't use auto detection because of Onvif command timeout. |                         |          |                |       |        |     |                |      |                      |          |                     |
| <b>FC-309</b>        | Refer to FC-348-NTSC(BU 1.2)   | H.264<br>MJPEG<br>MPEG4 | 1        | 720x480        | -     | -      | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| <b>FC-313</b>        | Refer to FC-348-NTSC(BU 1.2)   | H.264<br>MJPEG<br>MPEG4 | 1        | 720x480        | -     | -      | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| <b>FC-334</b>        | Refer to FC-348-NTSC(BU 1.2)   | H.264<br>MJPEG<br>MPEG4 | 1        | 720x480        | -     | -      | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| <b>FC-334S</b>       | Refer to FC-348-NTSC(BU 1.2)   | H.264<br>MJPEG<br>MPEG4 | 1        | 720x480        | -     | -      | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| <b>FC-324</b>        | Refer to FC-348-NTSC(BU 1.2)   | H.264<br>MJPEG<br>MPEG4 | 1        | 720x480        | -     | -      | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| <b>FC-324S</b>       | Refer to FC-348-NTSC(BU 1.2)   | H.264<br>MJPEG<br>MPEG4 | 1        | 720x480        | -     | -      | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| <b>FC-363</b>        | Refer to FC-348-NTSC(BU 1.2)   | H.264<br>MJPEG<br>MPEG4 | 1        | 720x480        | -     | -      | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| <b>FC-618-R-NTSC</b> | BU 1.2   | H.264<br>MJPEG<br>MPEG4 | 1        | 720x480        | -     | *2     | Yes | *2             | *2   | Yes*                 | Yes      |                     |
| Note:                | 1. When bitrate set higher than 1Mbps, the RTSP connection is unstable.<br>2. Sometime we fail to change the encoding setting after the camera connected for a long time. The setting displays at web client and onvif interface will change but actually not.<br>3. Can't get the I/O status by Onvif interface<br>4. Can't use camera search function because of onvif command timeout.<br>5. Can't use auto detection because of Onvif command timeout. |                         |          |                |       |        |     |                |      |                      |          |                     |
| <b>FC-690S</b>       | Refer to FC-618-NTSC(BU 1.2)   | H.264<br>MJPEG<br>MPEG4 | 1        | 720x480        | -     | -      | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| <b>FC-669S</b>       | Refer to FC-618-NTSC(BU 1.2)   | H.264<br>MJPEG<br>MPEG4 | 1        | 720x480        | -     | -      | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |





- : not available on camera  
\*1: not available on software  
\*2: not test on software

For multi stream support:  
Yes: multi stream fix to 500kbps/100kbps  
Yes\*: multi stream setting support

| Device Name | Tested Firmware              | Video Format      | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|------------------------------|-------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| FC-645S     | Refer to FC-618-NTSC(BU 1.2) | H.264 MJPEG MPEG4 | 1        | 720x480        | -     | -      | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| FC-632S     | Refer to FC-618-NTSC(BU 1.2) | H.264 MJPEG MPEG4 | 1        | 720x480        | -     | -      | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name       | Tested Firmware      | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------------|----------------------|--------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| ACD-3VM501        | refer to ACDV-3VM501 | H.264 M-JPEG       | 1        | 1600x1200      | -     | 1/1    | -   | Yes            | Yes  | -                  | -                    | -        | Supported by design |
| ACDV-3VM501       |                      | H.264 M-JPEG       | 1        | 1600x1200      | -     | 1/1    | -   | Yes            | Yes  | -                  | -                    | -        | Supported by design |
| AEP-Q2018HW-IP    |                      | H.264 M-JPEG       | 1        | 720x480        | -     | -      | Yes | Yes            | Yes  | -                  | -                    | -        | Supported by design |
| AEP-Q2026HW-IP    |                      | H.264 M-JPEG       | 1        | 720x480        | -     | -      | Yes | Yes            | Yes  | -                  | -                    | -        | Supported by design |
| AEP-Q2036HW-IP    |                      | H.264 M-JPEG       | 1        | 720x480        | -     | -      | Yes | Yes            | Yes  | -                  | -                    | -        | Supported by design |
| ASP-PTIR737-IP    |                      | H.264 M-JPEG       | 1        | 720x576        | -     | -      | Yes | Yes            | Yes  | -                  | -                    | -        | Supported by design |
| ASP-PTIR737-LA-IP |                      | H.264 M-JPEG       | 1        | 720x576        | -     | -      | Yes | Yes            | Yes  | -                  | -                    | -        | Supported by design |
| ATCP-IRH5030C     |                      | H.264 M-JPEG       | 1        | 1600x1200      | -     | 1/1    | -   | Yes            | Yes  | -                  | -                    | -        | Supported by design |
| ATCP-IRH5040C     |                      | H.264 M-JPEG       | 1        | 1600x1200      | -     | 1/1    | -   | Yes            | Yes  | -                  | -                    | -        | Supported by design |
| ATCP-MH802        |                      | H.264 M-JPEG       | 1        | 1600x1200      | -     | 1/1    | -   | Yes            | Yes  | -                  | -                    | -        | Supported by design |
| ATCP-MH802DN      |                      | H.264 M-JPEG       | 1        | 1600x1200      | -     | 1/1    | -   | Yes            | Yes  | -                  | -                    | -        | Supported by design |
| ATCP-MH802DN/WI   |                      | H.264 M-JPEG       | 1        | 1600x1200      | -     | 1/1    | -   | Yes            | Yes  | -                  | -                    | -        | Supported by design |
| ATCP-MH802WI      |                      | H.264 M-JPEG       | 1        | 1600x1200      | -     | 1/1    | -   | Yes            | Yes  | -                  | -                    | -        | Supported by design |
| ATCP-VM501        |                      | H.264 M-JPEG       | 1        | 1600x1200      | -     | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| AWB-H811          |                      | H.264 M-JPEG       | 1        | 720x480        | -     | 2/2    | Yes | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| AWB-H814          |                      | H.264 M-JPEG       | 1        | 720x576        | -     | 4/4    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| B0100             |                      | H.264 M-JPEG MPEG4 | 1        | 1280x800       | 1-way | 1/0    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| B0202             | V3.2.0.0             | H.264 M-JPEG MPEG4 | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        |                     |
| B1100             |                      | H.264 M-JPEG MPEG4 | 1        | 1280x800       | 1-way | 1/0    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| C1100             |                      | H.264 M-JPEG MPEG4 | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| C1100-W           |                      | H.264 M-JPEG MPEG4 | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| C2100             |                      | H.264 M-JPEG MPEG4 | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| C2200             | Refer to B0202       | H.264 M-JPEG MPEG4 | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmw<br>are   | Video<br>Format          | Video<br>Ch | Max<br>Resolution | Audio | I/O<br>Ch | PTZ | On-<br>Edge<br>Motion | UPn<br>P | Camera<br>Search<br>Tool | Multi<br>Stream<br>Support | Snapshot | Remarks             |
|-------------|---|--------------------------|-------------|-------------------|-------|-----------|-----|-----------------------|----------|--------------------------|----------------------------|----------|---------------------|
| C2200-W     | Refer to B0202  | H.264<br>M-JPEG<br>MPEG4 | 1           | 1920x1080         | 1-way | 1/1       | -   | Yes                   | Yes      | -                        | Yes                        | -        | Supported by design |
| D0100       |   | H.264<br>M-JPEG<br>MPEG4 | 1           | 1280x800          | 1-way | -         | -   | Yes                   | Yes      | -                        | Yes                        | -        | Supported by design |
| D1100       |   | H.264<br>M-JPEG<br>MPEG4 | 1           | 1280x800          | 1-way | 1/0       | -   | Yes                   | Yes      | -                        | Yes                        | -        | Supported by design |
| D2000-FD3   | Refer to M4202-DB03   | H.264<br>M-JPEG<br>MPEG4 | 1           | 1920x1080         | 1-way | 1/1       | -   | Yes                   | Yes      | -                        | Yes                        | -        | Supported by design |
| D2000-VD3   | Refer to M4202-DB02   | H.264<br>M-JPEG<br>MPEG4 | 1           | 1920x1080         | 1-way | 1/1       | -   | Yes                   | Yes      | -                        | Yes                        | -        | Supported by design |
| D2000-VP2   | Refer to M7202-DB03   | H.264<br>M-JPEG<br>MPEG4 | 1           | 1920x1080         | 1-way | 1/1       | -   | Yes                   | Yes      | -                        | Yes                        | -        | Supported by design |
| D2100       |   | H.264<br>M-JPEG<br>MPEG4 | 1           | 1280x800          | 1-way | 1/0       | -   | Yes                   | Yes      | -                        | Yes                        | -        | Supported by design |
| FBU-200LWD  | AgWT820<br>0122N06<br>V32<br>1401213F   | H.264                    | 1           | 1920x1080         | 1-way | 0/1       | Yes | Yes                   | Yes      | -                        | Yes                        | -        |                     |
| Note:       | (Camera FW issue): Camera not support DI.<br>(Camera FW issue): Camera snapshot function failed.<br>(Known issue): It is probable that bitrate per second of low/minumun stream is unable to achieve 500bps/100bps under D1, SXGA resolution. |                          |             |                   |       |           |     |                       |          |                          |                            |          |                     |
| FBU-201LWD  | Refer to FBU-200LWD (FW AgWT820 0122N06 V32 1401213F )  | H.264                    | 1           | 1920x1080         | 1-way | 0/1       | Yes | Yes                   | Yes      | -                        | Yes                        | -        | Supported by design |
| FBU-300LWD  | refer to FVD-300LWD( AgWT830 0036N06 V32 1401214F )   | H.264                    | 1           | 2048x1536         | 1-way | *2        | Yes | Yes                   | Yes      | -                        | Yes                        | -        | Supported by design |
| FBU-301LWD  | refer to FVD-300LWD( AgWT830 0036N06 V32 1401214F )   | H.264                    | 1           | 2048x1536         | 1-way | *2        | Yes | Yes                   | Yes      | -                        | Yes                        | -        |                     |
| FBS-1300 BX | AgWT813 0104N20_1405282B  | H.264                    | 1           | 1280x1024         | 2-way | 1/1       | Yes | Yes                   | Yes      | -                        | Yes                        | -        |                     |
| FBS-1300BL  | refer to FBS-1300BX(A gWT8130 104N20_1 405282B)   | H.264                    | 1           | 1280x1024         | 2-way | 1/1       | Yes | Yes                   | Yes      | -                        | Yes                        | -        | Supported by design |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name        | Tested Firmware                                    | Video Format            | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|--------------------|--|-------------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| <b>FBS-1300 ID</b> | refer to FBS-1300BX(AgWT8130104N20_1405282B)       | H.264                   | 1        | 1280x1024      | 2-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| <b>FBS-1300IDR</b> | refer to FBS-1300BX(AgWT8130104N20_1405282B)       | H.264                   | 1        | 1280x1024      | 2-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| <b>FBS-1300MID</b> | refer to FBS-1300BX(AgWT8130104N20_1405282B)       | H.264                   | 1        | 1280x1024      | 2-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| <b>FBS-1300MVD</b> | refer to FBS-1300BX(AgWT8130104N20_1405282B)       | H.264                   | 1        | 1280x1024      | 2-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| <b>FBS-1300VD</b>  | refer to FBS-1300BX(AgWT8130104N20_1405282B)       | H.264                   | 1        | 1280x1024      | 2-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| <b>FBS-1300VDR</b> | refer to FBS-1300BX(AgWT8130104N20_1405282B)       | H.264                   | 1        | 1280x1024      | 2-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| <b>FBX-200</b>     |  | H.264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -                  | Yes                  | -        | Supported by design |
| <b>FBX-200CL</b>   | Refer to FBU-200LWD (FW AgWT8200122N06V321401213F) | H.264                   | 1        | 1920x1080      | 1-way | 0/1    | Yes | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| <b>FBX-200LWD</b>  | Refer to FBU-200LWD (FW AgWT8200122N06V321401213F) | H.264                   | 1        | 1920x1080      | 1-way | 0/1    | Yes | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| <b>FBX-300LWD</b>  | refer to FVD-300LWD(AgWT8300036N06V321401214F)     | H.264                   | 1        | 2048x1536      | 1-way | *2     | Yes | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmwar e   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| FBX-300WD   |  | H.264<br>M-JPEG<br>MPEG4 | 1        | 2048x1536      | 1-way | 1/1    | Yes | -              | *1   | -                  | Yes                  | -        | Supported by design |
| FDM-200     |  | H.264<br>MPEG4<br>MJPEG  | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -                  | Yes                  | -        | Supported by design |
| FDM-200LWD  | Refer to FBU-200LWD (FW AgWT820 0122N06 V32 1401213F )   | H.264                    | 1        | 1920x1080      | 1-way | 0/1    | Yes | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| FDM-300LWD  | refer to FVD-300LWD( AgWT830 0036N06 V32 1401214F )  | H.264                    | 1        | 2048x1536      | 1-way | *2     | Yes | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| FDM-300WD   |  | H.264<br>MPEG4<br>MJPEG  | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | -    | -                  | Yes                  | -        | Supported by design |
| FVD-200     |  | H.264<br>MPEG4<br>MJPEG  | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -                  | Yes                  | -        | Supported by design |
| FVD-200LWD  | Refer to FBU-200LWD (FW AgWT820 0122N06 V32 1401213F )   | H.264                    | 1        | 1920x1080      | 1-way | 0/1    | Yes | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| FVD-200LWD  | Refer to FDM-200   | H.264<br>MPEG4<br>MJPEG  | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -                  | Yes                  | -        | Supported by design |
| FVD-300LWD  | AgWT830 0036N06 V32 1401214F   | H.264                    | 1        | 2048x1536      | 1-way | *2     | Yes | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| Note:       | (Camera FW issue) Camera replys no IO status.<br>(Camera FW issue): Camera snapshot function failed.<br>(Camera FW issue): FPS could not reach up to user setting by TCP protocol connection.<br>(Known issue): It is probable that bitrate per second of low/minimun stream is unable to achieve 500bps/100bps under D1, SXGA, 3M resolution. |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| FVD-300WD   |  | H.264<br>MPEG4<br>MJPEG  | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | -    | -                  | Yes                  | -        | Supported by design |
| GE-100-VS   |  | H.264<br>M-JPEG<br>MPEG4 | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| IPB-1080BL  | Refer to IPD-1080CD (VC1.0.22 .6_TG)   | H.264<br>MJPEG           | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name  | Tested Firmware                    | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|--|------------------------------------|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| IPB-1080BM   | Refer to IPD-1080CD                | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| IPB-1080E  | VE1.0.14.18_TG                     | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      |                     |
| Note: 1. Audio has noise. (Camera firmware issue)  |                                    |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| IPB-1080F  | refer to IPB-1080E(VE              | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| IPB-1080F28  | VE1.0.22.6_TG                      | H.264 MJPEG  | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note: 1. Streaming can not connect via RTSP over HTTP. (Camera firmware issue)<br>2. The second stream's frame rate list can not follow the adjusting rule to the main stream's resolution and FPS. (Camera firmware limitation)<br>3. Camera is unable to achieve maximum FPS. (Camera performance issue) |                                    |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| IPB-1080WDR  | Refer to IPD-1080WDR               | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| IPB-4065BM   | VK1.0.13.3_TG                      | H.265 MJPEG  | 1        | 2592x1520      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note: 1. Due to camera web restriction, some frame rate cannot be set. (Camera Firmware issue)   |                                    |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| IPB-8000BM   | VH1.0.0.11_TG                      | H.264 MJPEG  | 1        | 3840x2160      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note: 1. Camera cannot achieve maximum FPS with high resolution and bitrate. (Camera performance limitation)<br>2. Audio has noise. (Camera Firmware issue)  |                                    |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| IPD-1080CD   | VC1.0.22.6_TG                      | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      |                     |
| IPD-1080E  | refer to IPB-1080E(VE              | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| IPD-1080MF   | refer to IPB-1080E(VE              | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| IPD-1080KF   | refer to IPB-1080E(VE              | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |
| IPD-1080WDR  | Forenix_rootfs_VG1.0.20_TG         | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      |                     |
| Note: 1. Stream1 and stream2 framerate list is not as same as web. (Camera Firmware issue)<br>2. in 1080p HD 12bits 60fps(True WDR) mode, stream2 and stream3 can not connect, and can not get parameters(Camera Firmware issue)   |                                    |              |          |                |       |        |     |                |      |                    |                      |          |                     |
| IPD-4065CD   | Refer to IPB-4065BM(VK1.0.13.3_TG) | H.265 MJPEG  | 1        | 2592x1520      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| IPD-8000CD   | Refer to IPB-8000BM(VH1.0.0.11_TG) | H.264 MJPEG  | 1        | 3840x2160      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |
| IPM-1080F  | refer to IPB-1080E(VE1.0.14.18_TG) | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      | Supported by design |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmwar e   | Video Format               | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPn P | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|----------------------------|----------|----------------|-------|--------|-----|----------------|-------|--------------------|----------------------|----------|---------------------|
| IPM-1080RF  | refer to IPB-1080E(VE 1.0.14.18_TG)                                | H.264 MJPEG                | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes   | -                  | Yes                  | Yes      | Supported by design |
| IPT-1080F   | refer to IPB-1080E(VE 1.0.14.18_TG)                                | H.264 MJPEG                | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes   | -                  | Yes                  | Yes      | Supported by design |
| IPV-1080CD  | Refer to IPD-1080CD (VC1.0.22.6_TG)                                | H.264 MJPEG                | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes   | -                  | Yes                  | Yes      | Supported by design |
| IPV-1080E   | refer to IPB-1080E(VE 1.0.14.18_TG)                                | H.264 MJPEG                | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes   | -                  | Yes                  | Yes      | Supported by design |
| IPV-1080F   | refer to IPB-1080E(VE 1.0.14.18_TG)                                | H.264 MJPEG                | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes   | -                  | Yes                  | Yes      | Supported by design |
| IPV-1080WDR | Refer to IPD-1080WDR   | H.264 MJPEG                | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes   | -                  | Yes*                 | Yes      | Supported by design |
| IPV-4065CD  | Refer to IPB-4065BM(V K1.0.13.3_TG)                                | H.264 MJPEG<br>H.265 MJPEG | 1        | 2592x1520      | 2-way | 1/1    | -   | Yes            | Yes   | -                  | Yes*                 | Yes      | Supported by design |
| IPV-8000CD  | Refer to IPB-8000BM(V H1.0.0.11_TG)                                | H.264 MJPEG                | 1        | 3840x2160      | 2-way | 1/1    | -   | Yes            | Yes   | -                  | Yes*                 | Yes      | Supported by design |
| IPX-1080E   | refer to IPB-1080E(VE 1.0.14.18_TG)                                | H.264 MJPEG                | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes   | -                  | Yes                  | Yes      | Supported by design |
| IPX-1080DN  | Refer to IPD-1080CD (VC1.0.22.6_TG)                                | H.264 MJPEG                | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes   | -                  | Yes                  | Yes      | Supported by design |
| IPX-1080WDR | Refer to IPD-1080WDR (Forenix_r ootfs_VG1.0.20_TG_20150129_101057) | H.264 MJPEG                | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes   | -                  | Yes*                 | Yes      | Supported by design |
| IPX-4065DN  | Refer to IPB-4065BM(V K1.0.13.3_TG)                                | H.264 MJPEG<br>H.265 MJPEG | 1        | 2592x1520      | 2-way | 1/1    | -   | Yes            | Yes   | -                  | Yes*                 | Yes      | Supported by design |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmware                    | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|------------------------------------|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| IPX-8000DN  | Refer to IPB-8000BM(VH1.0.0.11_TG) | H.264 MJPEG  | 1        | 3840x2160      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes*                 | Yes      | Supported by design |





- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name    | Tested Firmwar e   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPn P | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|----------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|-------|--------------------|----------------------|----------|---------------------|
| IPZB-1000R     | 3.0.0.4  | H.264<br>MJPEG<br>MPEG4  | 1        | 1920x1080      | 2-way | 1/0    | Yes | Yes            | Yes   | Yes                | Yes*                 | Yes      |                     |
| Note:          | 1. Talk function can't be used. (Camera Firmware issue)<br>2. DI can't be trigger. (Camera Firmware issue)<br>3. Motion can't be trigger. (Camera Firmware issue)<br>4. Frame rate, quality, and bitrate can't not sync with web. (Camera Firmware issue)<br>5. MJPEG quality can't be set. (Camera Firmware issue)<br>6. Quality range can not sync with web. (Camera Firmware issue)<br>7. Bitrate list can not sync with web. (Camera Firmware issue)<br>8. In H.264 & MPEG-4, bitrate can not achieve setting value. (Camera performance limitation)<br>9. In MJPEG & MPEG-4, framerate can not achieve setting value. (Camera performance limitation) |                          |          |                |       |        |     |                |       |                    |                      |          |                     |
| ISPD-2018      | Refer to ISPD-2020(VC1.0.301204_TG)  | H.264<br>MJPEG           | 1        | 1920x1080      | 2-way | 4/1    | Yes | Yes            | *1    | *1                 | Yes*                 | Yes      | Supported by design |
| ISPD-2020      | VC1.0.301204_TG  | H.264<br>MJPEG           | 1        | 1920x1080      | 2-way | 4/1    | Yes | Yes            | *1    | *1                 | Yes*                 | Yes      |                     |
| Note:          | 1. Not support Talk. (Camera Firmware issue)<br>2. Always trigger input-0 if alarm 1-4 has been trigged. (Camera Firmware issue)<br>3. Audio was broken with G.726. (Camera Firmware issue)<br>4. [NAS]Focus can't be used. (NUUO server limitation)<br>5. Not support camera search. (NUUO server limitation)<br>6. Not support auto detection. (NUUO server limitation)  |                          |          |                |       |        |     |                |       |                    |                      |          |                     |
| ISPDIII-3010   | 0.1.4960M  | H.264<br>MJPEG           | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | Yes   | -                  | Yes*                 | Yes      |                     |
| Note:          | Fisheye camera<br>ISPDIII-3010:<br>1. Fps and resolution list is not synchronized with the camera web due to onvif protocol mechanism. (Camera limitation issue)<br>2. Talk(audio out) are not supported due to there is no implementation mechanism from sdk document. (Camera issue)   |                          |          |                |       |        |     |                |       |                    |                      |          |                     |
| ISPD II-1312WD | AgWT8131312N20_1404185F  | H.264                    | 1        | 1280x1024      | -     | -      | Yes | Yes            | Yes   | -                  | Yes                  | -        |                     |
| Note:          | 1. Dual stream with main stream resolution SXGA, SXVGA, D1 is unable to achieve 500k/100k bps. (Camera performance limitation)<br>2. Camera with quality over 8192 is unable to achieve maximum FPS ( Camera performance limitation)<br>3. Camera pan/tilt periodic moves per 30 seconds/2 minutes. After periodic moving, camera can't tilt for 1 minute.   |                          |          |                |       |        |     |                |       |                    |                      |          |                     |
| ISPD II-3018WD | AgWT8303018N20_1404185F  | H.264                    | 1        | 2048x1536      | -     | -      | Yes | Yes            | Yes   | -                  | Yes                  | -        |                     |
| Note:          | 1. Dual stream with main stream resolution 3M, SXGA, D1 is unable to achieve 500k/100k bps. (Camera performance limitation)<br>2. Camera with quality over 8192 is unable to achieve maximum FPS. ( Camera firmware issue)   |                          |          |                |       |        |     |                |       |                    |                      |          |                     |
| M0202-BH01     | Refer to B0202   | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes   | -                  | Yes                  | -        | Supported by design |
| M0202-BH02     | Refer to B0202   | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes   | -                  | Yes                  | -        | Supported by design |
| M0202-BH03     | Refer to B0202   | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes   | -                  | Yes                  | -        | Supported by design |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| M4202-DB02  | Refer to B0202   | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| M4202-DB03  | Refer to B0202   | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| M7202-DB03  | Refer to B0202   | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| NPB-720     | refer to NPB-720BM                                     | H.264<br>M-JPEG<br>MPEG4 | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| NPB-720A    | refer to NPB-720BM                                     | H.264<br>M-JPEG<br>MPEG4 | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| NPB-720BM   | VB1.0.26_TG  | H.264<br>M-JPEG<br>MPEG4 | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        |                     |
| Note:       | NPB-720BM FW issue cannot support UPnP and autodetect. |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| NPB-720U    | refer to NPB-720BM                                     | H.264<br>M-JPEG<br>MPEG4 | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| NPD-720K    | refer to NPB-720BM                                     | H.264<br>M-JPEG<br>MPEG4 | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| NPD-720R    | refer to NPB-720BM                                     | H.264<br>M-JPEG<br>MPEG4 | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| T2000-FB1   | Refer to M0202-BH01                                    | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| T2000-FB2   | Refer to M0202-BH02                                    | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| T2000-VB3   | Refer to M0202-BH03                                    | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| VQ2100      |  | MJPEG<br>MPEG4<br>H.264  | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| VQ2200      |  | MJPEG<br>MPEG4<br>H.264  | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| VQ2210C     |  | MJPEG<br>MPEG4<br>H.264  | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| VQ2300      |  | MJPEG<br>MPEG4<br>H.264  | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |
| VQ2310      |  | MJPEG<br>MPEG4<br>H.264  | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | -                  | Yes                  | -        | Supported by design |



- : not available on camera  
\*1: not available on software  
\*2: not test on software

For multi stream support:  
Yes: multi stream fix to 500kbps/100kbps  
Yes\*: multi stream setting support

| Device Name     | Tested Firmware  | Video Format   | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|-----------------|------------------|----------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| TVC-M1245E-2M-P | V4.0.g           | H264<br>MPEG4  | 1        | 1280x690       | -     | -      | -   | Yes            | Yes  | Yes                  |         |
| TVC-MP2B-S      | e20120223B<br>NS | H264<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |         |



GLOBAL NETWORK SECURITY

- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name    | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|----------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|--------------------|----------------------|----------|---------------------|
| GNS            |  | H264<br>MPEG4<br>M-JPEG  | 1        |                | 2-way | 4/4    | Yes | Yes            | -    | Yes                | Yes                  |          | Supported by design |
| Note:          | Fisheye camera   |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| A3101LE /A4101 | 4.0.30.51  | H.264<br>MJPEG           | 1        | 1280x720       | -     | -      | -   | Yes            | -    | -                  | Yes*                 | Yes      |                     |
| Note:          | 1. Video format cannot be switched. (Camera Firmware issue)<br>2. Resolution 704x480 cannot be set. (Camera Firmware issue)<br>3. Resolution via MJPEG will show 800x592 when set to 800x600. (Camera Firmware issue)<br>4. The camera does not support functions including audio and talk. (Camera Firmware issue)<br>5. The video parameters may not be synchronized with actual streaming. (Camera Firmware issue)<br>6. Hue setting is not supported. (ONVIF limitation) |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| A3253LE /A3263 | 4.8.26.51  | H.264<br>MJPEG           | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| Note:          | 1. Video format cannot be switched. (Camera Firmware issue)<br>2. The camera does not support functions including audio and talk. (Camera Firmware issue)<br>3. Resolution via MJPEG will show 640x352 when set to 640x360. (Camera Firmware issue)<br>4. Stream via UDP will disconnect in 20 seconds. (Camera Firmware issue)<br>5. Camera is unable to achieve maximum FPS and bit rate. (Camera Performance issue)   |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| A3102LE /4102  | 4.11.23.51   | H.264<br>MJPEG           | 1        | 1280x960       | 1-way | -      | -   | Yes            | -    | Yes                | Yes*                 | Yes      |                     |
| Note:          | 1. Video format cannot be switched. (Camera Firmware issue)<br>2. Resolution 704x480 cannot be set. (Camera Firmware issue)<br>3. Resolution via MJPEG will show 800x592 when set to 800x600. (Camera Firmware issue)<br>4. The camera does not support functions including audio and talk. (Camera Firmware issue)<br>5. The video parameters may not be synchronized with actual streaming. (Camera Firmware issue)<br>6. Hue setting is not supported. (ONVIF limitation) |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| GNS-B3202LE    | v1.8.0801.1<br>001.101.0.6<br>6.1.0  | H.264<br>M-JPEG          | 1        | 1920x1080      | *2    | -      | -   | *2             | -    | *2                 | Yes*                 | Yes      |                     |
| Note:          | 1. Some bitrate can't be set. (Onvif limitation)   |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| GNS-C1201L     | V1.0.40  | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      |                     |
| Note:          | 1. Audio only support G7.11. (Camera firmware issue)   |                          |          |                |       |        |     |                |      |                    |                      |          |                     |
| GNS-C3203LE    | 2.3.3073.74  | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | -                  | Yes                  | Yes      |                     |
| Note:          | 1. DO cannot be triggered. (Camera firmware issue)<br>2. Motion cannot be triggered when video format is MJPEG. (Camera firmware issue)<br>3. If change mode to corridor 90 or 270, the information of stream 3 is incorrect and stream 3 can not connect. (Camera firmware issue)<br>4. Camera is unable to achieve FPS when 3 streams are connecting. (Camera performance limitation)  |                          |          |                |       |        |     |                |      |                    |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name   | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|---------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| GCI-0735P     |  | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576        | 1-way | 4/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| GCI-C0745P    | 720110412NS  | H.264<br>M-JPEG          | 1        | 720x576        | 1-way | 4/1    | Yes | Yes            | Yes  | Yes                  |                     |
| GCI-G1536F    | gr20140530NSA  | H.264,<br>MJPEG          | 1        | 2592x1944      | 2-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| Note:         | Fisheye camera   |                          |          |                |       |        |     |                |      |                      |                     |
| GCI-H0503B    | 720110422NS  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| GCI-H0522V    |  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| GCI-H0602B    |  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| GCI-H2505B    | Refer to GCI-K2505B(gr20130417NSX)   | H.264,<br>MJPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| GCI-K0322V    | 720110413NS  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| GCI-K0503B    |  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| GCI-K0512W    |  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | -     | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| GCI-K0523T    |  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| Note:         | With HW restrictions, the video @ H.264 with TCP protocol is not smooth in the conditions of high resolution, fps and bitrate. We recommend to lower bitrate to 4000.  |                          |          |                |       |        |     |                |      |                      |                     |
| GCI-K0589T(H) | Refer to GCI-K1586V(gr20130621NSA)   | H.264,<br>MJPEG          | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| GCI-K0779P    | gr20130621NSA  | H.264,<br>MJPEG          | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | Yes                  |                     |
| GCI-K1523VS   | Refer to GCI-K2505B(gr20130417NSX)   | H.264,<br>MJPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| GCI-K1526V    | gr20120522NSA  | MJPEG,<br>H.264          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| Note:         | When we set the resolution, compression and frame rate in maximal value, the camera would not respond if we want to get camera parameter, and the audio we get is also unstable.<br>Camera may not connect to if the frame rate is 1. We suggest to change the GOV length to lower value on camera web page.<br>I1080P not support 2nd stream. |                          |          |                |       |        |     |                |      |                      |                     |
| GCI-K1526VS   | Refer to GCI-K2505B(gr20130417NSX)   | H.264,<br>MJPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name       | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|-------------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| <b>GCI-K1585V</b> | Refer to GCI-K1586V(gr20130621NSA)  | H.264, MJPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| <b>GCI-K1586V</b> | gr20130621NSA   | H.264, MJPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |
| Note:             | FW: gr20130621NAS, gr20130417NSX<br>1. Audio has noise when camera setting is high.<br>2. Get parameter will ailed when camera setting is high.<br>3. GCI-K1586V, GCI-K0589T(H), GCI-K1585V PTZ only support zoom and focus.  |              |          |                |       |        |     |                |      |                      |                     |
| <b>GCI-K1812W</b> | gr20120522NSA   | H.264        | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes                  |                     |
| Note:             | When we set the resolution, compression and frame rate in maximal value, the camera would not respond if we want to get camera parameter, and the audio we get is also unstable.<br>Camera may not connect to if the frame rate is 1. We suggest to change the GOV length to lower value on camera web page.<br>1080P not support 2nd stream. |              |          |                |       |        |     |                |      |                      |                     |
| <b>GCI-K2505B</b> | gr20130417NSX   | H.264, MJPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| Note:             | Framerate setting will failed when choosing TV system Autoiris WDR25fps, WDR 25fps and WDR 30fps.   |              |          |                |       |        |     |                |      |                      |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name   | Tested Firmware                           | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|---|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| <b>GDN-D1300V</b>   | Refer to Generic(AS6 5_ALL001_V 1.00.07 ) | H.264        | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| Note: 1. Not support 16 KHz sampling rate audio in.   |   |              |          |                |       |        |     |                |      |                      |          |                     |
| <b>GDN-DV1300IR</b>   | Refer to Generic(AS6 5_ALL001_V 1.00.07 ) | H.264        | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| <b>GDN-D1300IR</b>  | Refer to Generic(AS6 5_ALL001_V 1.00.07 ) | H.264        | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| <b>GND-D2300V</b>   | Refer to Generic(AS6 5_ALL001_V 1.00.07 ) | H.264        | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| <b>GDN-D3200V</b>   | Refer to Generic(AS6 5_ALL001_V 1.00.07 ) | H.264        | 1        | 2048x1536      | 1-way | 1/1    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| <b>GDN-D3200IR</b>  | Refer to Generic(AS6 5_ALL001_V 1.00.07 ) | H.264        | 1        | 2048x1536      | 1-way | 1/1    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| <b>GDN-F1300V</b>   | Refer to Generic(AS6 5_ALL001_V 1.00.07 ) | H.264        | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| <b>GND-F2300</b>  | Refer to Generic(AS6 5_ALL001_V 1.00.07 ) | H.264        | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| <b>GDN-H1300IR</b>  | Refer to Generic(AS6 5_ALL001_V 1.00.07 ) | H.264        | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| <b>GND-H2300IR</b>  | Refer to Generic(AS6 5_ALL001_V 1.00.07 ) | H.264        | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| Note: 1. Camera will be rebooted (60 seconds) after parameter configuration. (Camera performance limitation)<br>2. 16 KHz sampling rate audio in are not supported.<br>3. Camera search is not supported. (Camera firmware issue)<br>4. The camera setting will be failed if choose the value "BOTH".(Camera firmware issue)<br>5. Camera cannot be connected when 2nd resolution set to 854*480. (Camera firmware issue)<br>6. The default value of brightness should be 50. (Camera firmware issue) |   |              |          |                |       |        |     |                |      |                      |          |                     |



- : not available on camera  
\*1: not available on software  
\*2: not test on software  
For multi stream support:  
Yes: multi stream fix to 500kbps/100kbps  
Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format            | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|-------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| Generic     | AS65_ALL001_V1.00.07   | H.264<br>MJPEG<br>MPEG4 | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes*                 | Yes      |                     |
| Note:       | Support generic dewarp<br>1.Camera reboot (60 seconds) after parameter configuration.<br>2.Not support 16 KHz sampling rate audio in.<br>3.No support Camera search.<br>4.Camera can not connect when 2nd resolution set to 854*480. |                         |          |                |       |        |     |                |      |                      |          |                     |
| GDN-H3200IR | Refer to Generic(AS65_ALL001_V1.00.07 )  | H.264                   | 1        | 2048x1536      | 1-way | 1/1    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |



Digital Video Security System

**HDPRO**

- : not available on camera  
\*1: not available on software  
\*2: not test on software

For multi stream support:  
Yes: multi stream fix to 500kbps/100kbps  
Yes\*: multi stream setting support

| Device Name     | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks |
|-----------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------|
| HD-IC221STH211P | 1.3.0   | H.264 MJPEG  | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      |         |
| Note:           | 1. The dual stream type is affected by the enabled streaming number on camera remote setup.<br>2. Audio only support G.711 codec. |              |          |                |       |        |     |                |      |                      |          |         |

New-platform models: FW 20100628 is compatible  
 Old-platform models: only FW 20100320 is acceptable

- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support



| Device Name      | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch  | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|------------------|--|--------------|----------|----------------|-------|---------|-----|----------------|------|----------------------|----------|---------------------|
| DS-2CD2012-I     | v5.0.2 build130805   | H.264        | 1        | 1280x960       | -     | -       | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:            | 1. DS-2CD2012-I FW issue: not support PTZ function but web setting can enable this option.<br>2. Sub stream resolution can't bigger than Main stream resolution. |              |          |                |       |         |     |                |      |                      |          |                     |
| DS-2CD2012F-I    | v5.3.0   | H.264        | 1        | 1280x960       | -     | -       | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| DS-2CD2032-I     | V5.3.0 build 150513  | H.264        | 1        | 2048x1536      | -     | -       | -   | *2             | *2   | Yes*                 | *2       |                     |
| Note:            | 1.Frame rate will display too high. (NUUO server limitation)   |              |          |                |       |         |     |                |      |                      |          |                     |
| DS-2CS2132F      | Refer to DS-2CD2032-I(V5.3.0 build 150513)   | H.264        | 1        | 2048x1536      | -     | -       | -   | *2             | *2   | Yes*                 | *2       | Supported by design |
| DS-2CD2112-(I)   | Refer to DS-2CD2012-I(v5.0.2 build130805)  | H.264        | 1        | 1280x960       | -     | -       | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| DS-2CD2212-I3    | Refer to DS-2CD2012-I(v5.0.2)  | H.264        | 1        | 1280x960       | -     | -       | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| DS-2CD2212-I5    | Refer to DS-2CD2012-I(v5.0.2 build130805)  | H.264        | 1        | 1280x960       | -     | -       | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| DS-2CD2312-I     | Refer to DS-2CD2012-I(v5.0.2 build130805)  | H.264        | 1        | 1280x960       | -     | -       | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| DS-2CD2612F-I    | Refer to DS-2CD2012-I(v5.0.2)  | H.264        | 1        | 1280x960       | -     | -       | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| DS-2CD2612F-IS   | v5.0.2 build130805   | H264         | 1        | 1280x960       | 1-way | 1/1     | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| DS-2CD2632F-IS   | Refer to DS-2CD2732F-IS(v5.0.2 build130805)  | H264         | 1        | 2048x1536      | 1-way | 1/1     | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| DS-2CD2712F-I    | Refer to DS-2CD2012-I(v5.0.2)  | H.264        | 1        | 1280x960       | -     | -       | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| DS-2CD2712F-IS   | Refer to DS-2CD2612F-IS(v5.0.2 build130805)  | H264         | 1        | 1280x960       | 1-way | 1/1     | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| DS-2CD2732F-IS   | v5.0.2 build130805   | H264         | 1        | 2048x1536      | 1-way | 1/1     | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| DS-2CD4124F-IZ   | Refer to DS-2CD4224F-IZH(V5.3.5 build 151218)  | H.264 MPEG4  | 1        | 1920x1080      | -     | -       | -   | *2             | *2   | Yes*                 | *2       | Support by design   |
| DS-2CD4132FWD-IZ | Refer to DS-2CD4332FWD (V5.3.0)  | H.264 MPEG4  | 1        | 2048x1536      | *2    | 2/2(*2) | *2  | *2             | *2   | Yes*                 | *2       |                     |

New-platform models: FW 20100628 is compatible  
 Old-platform models: only FW 20100320 is acceptable

- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support



| Device Name        | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch  | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|--------------------|---|--------------|----------|----------------|-------|---------|-----|----------------|------|----------------------|----------|---------------------|
| DS-2CD4224F-IZH    | V5.3.5 build 151218   | H.264 MPEG4  | 1        | 1920x1080      | -     | -       | -   | *2             | *2   | Yes*                 | *2       |                     |
| Note:              | 1. Bitrate list can not synchronized with camera web. (Camera Firmware issue)<br>2. The stream 2 or 3 in camera with higher resolution via MJPEG is unable to achieve settings fps. (Camera performance limitation)<br>3. The bitrate of stream 2 or 3 in camera with highest resolution via MJPEG is higher than settings bitrate. (Camera performance limitation) |              |          |                |       |         |     |                |      |                      |          |                     |
| DS-2CD4332FWD      | V5.3.0  | H.264 MPEG4  | 1        | 2048x1536      | *2    | 2/2(*2) | *2  | *2             | *2   | Yes*                 | *2       |                     |
| Note:              | 1. Bitrate list is not synchronized with web. (Camera Firmware issue)   |              |          |                |       |         |     |                |      |                      |          |                     |
| DS-2CD4625FWD-IZS  | V5.3.4  | H.264        | 1        | 1920x1080      | *2    | *2      | *2  | *2             | *2   | Yes*                 | *2       |                     |
| Note:              | 1. Bitrate list can not sync with web. (Camera Firmware issue)  |              |          |                |       |         |     |                |      |                      |          |                     |
| DS-2CD4A25FWD-IZ   | V5.3.0 build 150617   | H.264        | 1        | 1920x1080      | -     | -       | Yes | *2             | *2   | Yes*                 | Yes      |                     |
| Note:              | PTZ only support zoom & focus.<br>1. Bitrate lists can not sync with web. (Camera Firmware Issue)   |              |          |                |       |         |     |                |      |                      |          |                     |
| DS-2CD4A25FWD-IZHS | V5.3.5 build 151218   | H.264        | 1        | 1920x1080      | *2    | *2      | *2  | *2             | *2   | Yes*                 | *2       |                     |
| Note:              | 1. Bitrate list can not sync with web. (Camera Firmware issue)<br>2. Bitrate is unable to achieve setting value. (Camera performance limitation)  |              |          |                |       |         |     |                |      |                      |          |                     |
| DS-2CD6026FHWD-A   | V5.1.0 build 131202   | H.264 MPEG4  | 1        | 1920x1080      | *2    | *2      | *2  | *2             | *2   | Yes*                 | *2       |                     |
| Note:              | 1. Framerate and bitrate can not achieve to maximum. (Camera performance limitation)<br>2. OSD will display 1920x1088 in MPEG4 1920x1080. (Camera Firmware issue)<br>3. Can't set frame rate to 50 fps. (Camera Firmware issue)   |              |          |                |       |         |     |                |      |                      |          |                     |
| DS-2CD702NF-E      |   | H.264        | 1        | 704x576        | 1-way | 1/1     | Yes | Yes            | Yes  | -                    | -        | Supported by design |
| DS-2CD702PF-E      |   | H.264        | 1        | 704x576        | 1-way | 1/1     | Yes | Yes            | Yes  | -                    | -        | Supported by design |
| DS-2CD712NF-E      |   | H.264        | 1        | 704x576        | 1-way | 1/1     | Yes | Yes            | Yes  | -                    | -        | Supported by design |
| DS-2CD712PF-E      |   | H.264        | 1        | 704x576        | 1-way | 1/1     | Yes | Yes            | Yes  | -                    | -        | Supported by design |
| DS-2CD7133-E       | V2.0 100628   | H.264        | 1        | 640x480        | -     | -       | -   | Yes            | -    | -                    | -        |                     |
| DS-2CD7153-E       | v5.0.8 build 130930   | H.264 MPEG4  | 1        | 1600x1200      | -     | -       | -   | Yes            | *2   | Yes                  | -        |                     |
| Note:              | The range of framerate is not sync. with web when resolution is 1600x1200   |              |          |                |       |         |     |                |      |                      |          |                     |

New-platform models: FW 20100628 is compatible  
 Old-platform models: only FW 20100320 is acceptable

- : not available on camera  
 \*1: not available on software  
 \*2: not test on software



For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name     | Tested Firmware  | Video Format      | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks                |
|-----------------|--|-------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|------------------------|
| DS-2CD7253F-EIZ | V5.0.2 Build 130709  | H.264 MPEG4       | 1        | 1600x1200      | -     | -      | Yes | Yes            | Yes  | Yes                  | Yes      |                        |
| Note:           | 1. Only support zoom in/out in the PTZ-control.<br>2. The range of framerate is not sync. with web when resolution is 1600x1200 and 1600x912.<br>3. Sub stream's format must be the same as main stream's except MJPEG.<br>4. UPnP Search can not get a valid mac address. |                   |          |                |       |        |     |                |      |                      |          |                        |
| DS-2CD732F-E    | 20100320   | H.264             | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Tested by manufacturer |
| DS-2CD733F-E    | V2.0 100716  | H.264             | 1        | 640x480        | 1-way | 2/2    | Yes | Yes            | -    | -                    | -        | Supported by design    |
| DS-2CD752MF-E   |  | H.264             | 1        | 1600x1200      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                        |
| DS-2CD752MF-FB  | V2.0 110426  | H.264             | 1        | 1600x1200      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                        |
| Note:           | DS-2CD752MF-FB PTZ can't test on RS-485  |                   |          |                |       |        |     |                |      |                      |          |                        |
| DS-2CD753F-E    | V2.0 100628  | H.264             | 1        | 1600x1200      | 1-way | 2/2    | Yes | Yes            | -    | -                    | -        | Supported by design    |
| DS-2CD754F-E    | Refer to 2CD754FWD-EI  | H.264 MPEG4       | 1        | 1920x1080      | 1-way | 2/2    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design    |
| DS-2CD754F-EI   | Refer to 2CD754FWD-EI  | H.264 MPEG4       | 1        | 1920x1080      | 1-way | 2/2    | Yes | Yes            | Yes  | Yes                  | -        |                        |
| DS-2CD754FWD-EI | V3.2 120105  | H.264 MPEG4 MJPEG | 1        | 1920x1080      | 1-way | 2/2    | Yes | Yes            | YES  | Yes                  | -        |                        |
| DS-2CD762MF-FB  | 20100320   | H.264             | 1        | 1280x960       | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD792NF-E   |  | H.264             | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD792PF-E   |  | H.264             | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Tested by manufacturer |
| DS-2CD793PFWD-E | V2.0 100628  | H.264             | 1        | 704x576        | 1-way | 2/2    | Yes | Yes            | No   | -                    | -        | Supported by design    |
| DS-2CD802NF     |  | H.264             | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD802NF-E   |  | H.264             | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD802NF-W   |  | H.264             | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD802PF     |  | H.264             | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD802PF-E   |  | H.264             | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD802PF-W   |  | H.264             | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |

New-platform models: FW 20100628 is compatible  
 Old-platform models: only FW 20100320 is acceptable

- : not available on camera  
 \*1: not available on software  
 \*2: not test on software



For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name    | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks                |
|----------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|------------------------|
| DS-2CD802N-IR1 |   | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD802N-IR3 |   | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD802N-IR5 |   | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD802P-IR1 |   | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD802P-IR3 |   | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD802P-IR5 |   | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD812NF    |   | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD812NF-E  |   | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD812NF-W  |   | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD812PF    | v2.0 build 090522                                       | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Tested by manufacturer |
| DS-2CD812PF-E  | Refer to DS-2CD812PF (FW v2.0 build 090522)             | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD812PF-W  | Refer to DS-2CD812PF (FW v2.0 build 090522)             | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD812N-IR1 |   | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD812N-IR3 |   | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD812N-IR5 |   | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD812P-IR1 |   | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD812P-IR3 |   | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD812P-IR5 |   | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        |                        |
| DS-2CD8253F-EI | v4.0.3 build121123                                      | H.264 MPEG4  | 1        | 1600x1200      | -     | -      | -   | Yes            | Yes  | -                    | Yes      |                        |
| Note:          | Not support audio but the clickbox is opened(cgi issue) |              |          |                |       |        |     |                |      |                      |          |                        |

New-platform models: FW 20100628 is compatible  
 Old-platform models: only FW 20100320 is acceptable

- : not available on camera  
 \*1: not available on software  
 \*2: not test on software



For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name         | Tested Firmware   | Video Format   | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks                |
|---------------------|---|----------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|------------------------|
| DS-2CD8254F-EIS     | V3.2 120105   | H.264<br>MPEG4 | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design    |
| DS-2CD8264FWD-(EIS) | v4.0.3<br>build121123   | H.264<br>MPEG4 | 1        | 1280x960       | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | Yes      |                        |
| Note:               | PTZ can't work, MD will delay   |                |          |                |       |        |     |                |      |                      |          |                        |
| DS-2CD832F          |   | H.264          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD832F-E        |   | H.264          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        |                        |
| DS-2CD852MF-E       | 20100320  | H.264          | 1        | 1600x1200      | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        |                        |
| DS-2CD853F-E        | V3.2 120105   | H.264<br>MPEG4 | 1        | 1600x1200      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                        |
| DS-2CD854F-E        | V3.2 120105   | H.264<br>MPEG4 | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design    |
| DS-2CD862MF-E       |   | H.264          | 1        | 1280x960       | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Tested by manufacturer |
| DS-2CD863PF-E       | V2.0 100628   | H.264          | 1        | 1280x960       | 1-way | 1/1    | Yes | Yes            | -    | -                    | -        |                        |
| DS-2CD864FWD-E      | v4.0.3<br>build121123   | H.264<br>MPEG4 | 1        | 1280x960       | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | Yes      |                        |
| Note:               | DI can't work, MD will delay, G726 talk can't work, zoom in/out can't work  |                |          |                |       |        |     |                |      |                      |          |                        |
| DS-2CD883F-E        | V3.2 120105   | H.264<br>MPEG4 | 1        | 2560x1920      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design    |
| Note:               | 1.DS-2CD8254F-EIS、DS-2CD853F-E、DS-2CD854F-E、DS-2CD883F-E can't set framerate 15~22 in Max resolution<br>2.DS-2CD8254F-EIS、DS-2CD854F-E、DS-2CD883F-E image broken when resolution over 1600x1200 |                |          |                |       |        |     |                |      |                      |          |                        |
| DS-2CD892NF         |   | H.264          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD892NF-E       |   | H.264          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD892NF-W       |   | H.264          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD892PF         |   | H.264          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD892PF-E       |   | H.264          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD892PF-W       |   | H.264          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD892N-IR1      |   | H.264          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |
| DS-2CD892N-IR3      |   | H.264          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design    |

New-platform models: FW 20100628 is compatible  
 Old-platform models: only FW 20100320 is acceptable

- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support



| Device Name     | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-----------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| DS-2CD892N-IR5  |  | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design |
| DS-2CD892P-IR1  |  | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design |
| DS-2CD892P-IR3  |  | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design |
| DS-2CD892P-IR5  |  | H.264        | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        |                     |
| DS-2CD4065F-P   | V5.3.4 build 150812  | H.264        | 1        | 3072x2048      | *2    | *2     | *2  | *2             | *2   | Yes*                 | *2       |                     |
| Note:           | 1.Bitrate list does not sync with camera web. (Camera Firmware issue)<br>2.When we name the preset point, preset point label will change to arabic number. (Camera Firmware issue)<br>3.Camera can't change to 1920x1080 with 3072x1728. (Camera Firmware issue) |              |          |                |       |        |     |                |      |                      |          |                     |
| DS-2CD4565F-IZH | Refer to DS-2CD4065F-P(V5.3.4 build 150812)  | H.264        | 1        | 3072x2048      | *2    | *2     | *2  | *2             | *2   | Yes*                 | *2       | Supported by design |
| DS-2CD6362F-IVS | V5.0.9 build 141009  | H.264        | 1        | 3072x2048      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:           | Fisheye camera<br>1. Not support MP2L2. (NUUO server limitation)   |              |          |                |       |        |     |                |      |                      |          |                     |
| DS-2CD6362F-I   | Refer to DS-2CD6362F-IVS(V5.0.9 build 141009)  | H.264 MJPEG  | 5        | 2048x2048      | 2-way | 1/1    | -   | Yes            | *2   | Yes*                 | Yes      | Supported by design |
| Note:           | Fisheye Camera   |              |          |                |       |        |     |                |      |                      |          |                     |
| DS-2CD6362F-IV  | Refer to DS-2CD6362F-IVS(V5.0.9 build 141009)  | H.264 MJPEG  | 5        | 2048x2048      | 2-way | 1/1    | -   | Yes            | *2   | Yes*                 | Yes      | Supported by design |
| Note:           | Fisheye Camera   |              |          |                |       |        |     |                |      |                      |          |                     |
| DS-2CD6362F-IS  | Refer to DS-2CD6362F-IVS(V5.0.9 build 141009)  | H.264 MJPEG  | 5        | 2048x2048      | 2-way | 1/1    | -   | Yes            | *2   | Yes*                 | Yes      | Supported by design |
| Note:           | Fisheye Camera   |              |          |                |       |        |     |                |      |                      |          |                     |
| DS-2CD6332FWD-I | Refer to DS-2CD6362F-IVS(V5.0.9 build 141009)  | H.264 MJPEG  | 5        | 2048x2048      | 2-way | 1/1    | -   | Yes            | *2   | Yes*                 | Yes      | Supported by design |
| Note:           | Fisheye Camera   |              |          |                |       |        |     |                |      |                      |          |                     |

New-platform models: FW 20100628 is compatible  
 Old-platform models: only FW 20100320 is acceptable

- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support



| Device Name       | Tested Firmware  | Video Format      | Video Ch | Max Resolution | Audio | I/O Ch | PTZ  | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------------|--|-------------------|----------|----------------|-------|--------|------|----------------|------|----------------------|----------|---------------------|
| DS-2CD6332FWD-IV  | Refer to DS-2CD6362F-IVS(V5.0.9 build 141009)  | H.264 MJPEG       | 5        | 2048x2048      | 2-way | 1/1    | -    | Yes            | *2   | Yes*                 | Yes      | Supported by design |
| Note:             | Fisheye Camera   |                   |          |                |       |        |      |                |      |                      |          |                     |
| DS-2CD6332FWD-IS  | Refer to DS-2CD6362F-IVS(V5.0.9 build 141009)  | H.264 MJPEG       | 5        | 2048x2048      | 2-way | 1/1    | -    | Yes            | *2   | Yes*                 | Yes      | Supported by design |
| Note:             | Fisheye Camera   |                   |          |                |       |        |      |                |      |                      |          |                     |
| DS-2CD6332FWD-IVS | Refer to DS-2CD6362F-IVS(V5.0.9 build 141009)  | H.264 MJPEG       | 5        | 2048x2048      | 2-way | 1/1    | -    | Yes            | *2   | Yes*                 | Yes      | Supported by design |
| Note:             | Fisheye Camera   |                   |          |                |       |        |      |                |      |                      |          |                     |
| DS-2DE7174-AE     | Refer to DS-2DE7184-A(V5.3.9 build 150910)   | H.264             | 1        | 1920x1080      | *2    | -      | Yes* | Yes            | *2   | Yes*                 | Yes      | Supported by design |
| DS-2DE7184-A      | V5.3.9 build 150910  | H.264             | 1        | 1920x1080      | *2    | -      | Yes* | Yes            | *2   | Yes*                 | Yes      |                     |
| Note:             | 1. Auto focus can't be used. (NUUO server limitation)<br>2. Audio codec via AAC can't be used. (NUUO server limitation)                |                   |          |                |       |        |      |                |      |                      |          |                     |
| DS-2DF1-572       | V4.1.2 build 121205  | H.264             | 1        | 1280*720       | 1-way | 1/1    | Yes  | Yes            | -    | Yes                  | Yes      |                     |
| DS-2DF8223I-AEL   | V5.2.8 build 150124  | H.264 MPEG4       | 1        | 1920x1080      | *2    | *2     | Yes* | *2             | *2   | Yes*                 | *2       |                     |
| Note:             | 1. Bitrate list is not sync with web. (Camera Firmware issue)<br>2. Some default preset points can't be used. (NUUO server limitation) |                   |          |                |       |        |      |                |      |                      |          |                     |
| DS-6101HFI-IP     | V2.0 101112  | H.264             | 1        | 704x576        | -     | 1/1    | -    | Yes            | -    | -                    | Yes      |                     |
| Note:             | PTZ is only supported by external RS-485 device.   |                   |          |                |       |        |      |                |      |                      |          |                     |
| DS-6716HWI        | V1.2.5 build 150522  | H.264 MJPEG MPEG4 | 16       | 960x480        | 2-way | 16/4   | Yes* | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:             | 1. Can't get snapshot. (NUUO server limitation)  |                   |          |                |       |        |      |                |      |                      |          |                     |



New-platform models: FW 20100628 is compatible  
 Old-platform models: only FW 20100320 is acceptable

- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support



| Device Name    | Tested Firmware  | Video Format            | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks |
|----------------|--|-------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------|
| DS-8116HQHI-SH | V3.1.2 build 141219 /Encoding Version: V5.0 build 141218   | H.264                   | 16       | 960x576        | 2-way | 16/4   | Yes | Yes            | Yes  | Yes*                 | Yes      |         |
| Note:          | 1. The resolution of streaming was not stable. (Camera firmware issue)<br>2. Motion detection can't be used. (Camera firmware issue)<br>3. The video parameter (brightness, contrast..) can't be used. (Camera firmware issue)<br>4. UPnP search can't be used. (Camera firmware issue)<br>5. The number of DI and DO was wrong. (Camera firmware issue)<br>6. DO can't be used. (Camera firmware issue)<br>7. Can't get RTSP port, default value 554. (Camera firmware issue)<br>8. PTZ function only works in channel 1. (Camera firmware issue)<br>9. Unable to achieve setting frame rate, due to duplicate P frame. (Camera firmware issue) |                         |          |                |       |        |     |                |      |                      |          |         |
| Generic        | V3.1.2 build 141219  | H.264<br>MPEG4<br>MJPEG | 16       | 2560x1920      | 2-way | 2/2    | Yes | Yes            | *1   | Yes                  | Yes      |         |
| Note:          | 1. V3.1.2 build 141219 is the version of firmware of video server.<br>2. Talk not support in the model support ISAPI protocol. (Camera firmware issue)<br>3. Can't get RTSP port, default value 554. (Camera firmware issue)   |                         |          |                |       |        |     |                |      |                      |          |         |
| Generic Camera | V5.3.0 build 150616<br>V5.0.9 build 141009   | H.264<br>MPEG4<br>MJPEG | 1        | 2560x1920      | 2-way | 2/2    | Yes | Yes            | *1   | Yes                  | Yes      |         |
| Note:          | 1. V5.3.0 build 150616 is the version of firmware of IPCam.<br>2. V5.0.9 build 141009 is the version of firmware of fisheye.<br>3. Talk not support in the model support ISAPI protocol. (Camera firmware issue)<br><br>Fisheye model:<br>1. Support generic dewarp<br>2. When audio codec is changed in webpage, audio in IP Camera 2, 3, 4, 5 can't use correct codec. (Camera Firmware issue)<br>3. If stream mode is " Mode 2: Fisheye / 4 PTZ", the total number of connections is limited. ex: If someone preview "Fisheye view", you are not permitted to preview " 4 PTZ view". (Camera performance limitation)                          |                         |          |                |       |        |     |                |      |                      |          |         |
| Note           | One of the cameras in the system must support I/O functions in order to enable the snapshot feature. This is a known issue and we are looking to fix it with the next product version update.  |                         |          |                |       |        |     |                |      |                      |          |         |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| ACUIX       | 1.5.6   | MPEG4        | 1        | 4CIF           | -     | -      | Yes | -              | -    | Yes                  | -        |                     |
| Note:       | Sometimes the PTZ function doesn't work properly due to camera FW; users have to restart to make it work. The speed of PTZ is not correspondent with camera web, which might be due to camera FW.   |              |          |                |       |        |     |                |      |                      |          |                     |
| H3D1F       | 40.0.6  | H.264        | 1        | 1280x720       | 1-way | 1/0    | -   | Yes            | -    | Yes                  | -        |                     |
| Note:       | To ensure compatibility with H3D1F1, H3D1F2, H3D1F3, H4D1F1, HCD1F, HCV1F, H3W1F1, H4W1F1, H3D1F2X, H3D1F3X, H4D1F1X, HCD1FX, HCV1FX, H3W1F1X or H4W1F1X, H3D1F must be selected to work with either model.   |              |          |                |       |        |     |                |      |                      |          |                     |
| H3D2F       | 40.0.6  | H.264        | 1        | 1920x1080      | 1-way | 1/0    | Yes | Yes            | -    | Yes                  | -        |                     |
| Note:       | 1. H3D2F: Only support Zoom, not support Pan and Tilt.<br>2. To ensure compatibility with H3D2F1X, H3D2F1, H4D2F1 or H4D2F1X, H3D2F must be selected to work with either model.   |              |          |                |       |        |     |                |      |                      |          |                     |
| HCD5541P    | 5.4.5   | MPEG4        | 1        | 4CIF           | 1-way | 0/1    | -   | -              | -    | Yes                  | -        |                     |
| Note:       | Disable input function due to camera FW.  |              |          |                |       |        |     |                |      |                      |          |                     |
| HCD5MIH     | 13.1.2  | H.264        | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | -    | -                    | -        |                     |
| Note:       | For integration issue not support TCP connection.   |              |          |                |       |        |     |                |      |                      |          |                     |
| HD3MDIH     | 11.0.3  | H.264        | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | -    | -                    | -        |                     |
| Note:       | For integration issue not support TCP connection.   |              |          |                |       |        |     |                |      |                      |          |                     |
| HD3MDIP     | 7.07  | MPEG4        | 1        | 1280x720       | 1-way | -      | -   | Yes            | -    | Yes                  | -        |                     |
| HD4MDIP     | 8.04  | MPEG4        | 1        | 1280x720       | 1-way | -      | -   | Yes            | -    | Yes                  | -        |                     |
| HD4MDIH     | 12.0.3  | H.264        | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | -    | -                    | -        |                     |
| Note:       | For integration issue not support TCP connection.   |              |          |                |       |        |     |                |      |                      |          |                     |
| HNVE1       | 6.3.4   | MPEG4        | 1        | 4CIF           | 1-way | -      | -   | -              | -    | Yes                  | -        |                     |
| Note:       | Disable I/O function due to camera FW.  |              |          |                |       |        |     |                |      |                      |          |                     |
| HDZ20HDX    | H20120808N SA   | H.264 MJPEG  | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| HDZ20HDE X  | Refer to HDZ20HDX(H20120808NS)  | H.264 MJPEG  | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| HDZ20HD     | Refer to HDZ20HDX(H20120809NS)  | H.264 MJPEG  | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| HDZ20HDE    | Refer to HDZ20HDX(H20120810NS A)  | H.264 MJPEG  | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| Note:       | Parameter setting will fail when Mjpeg quality bigger than 60   |              |          |                |       |        |     |                |      |                      |          |                     |
| Note:       | HD3MDIP, HD4MDIP: Not support I/O currently.<br>All models: Users may be confused because the username on login page of camera web is "administrator", but it's "admin" actually. If you type in "administrator", you are no longer to connect the cameras. |              |          |                |       |        |     |                |      |                      |          |                     |
| Note        | One of the cameras in the system must support I/O functions in order to enable the snapshot feature. This is a known issue and we are looking to fix it with the next product version update.   |              |          |                |       |        |     |                |      |                      |          |                     |

# Innotech

- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name   | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | ONVIF Search | Multi Stream Support | Snapshot | Remarks |
|---------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------|----------------------|----------|---------|
| EXCA1001P2    | v1.8.1001.3.5.25  | H.264 MJPEG  | 1        | 1920x1080      | 2-way | -      | -   | Yes            | -    | *2           | Yes*                 | Yes      |         |
| Note:         | 1. Due to Onvif restriction, some frame rate and bit rates cannot be set. (Camera firmware issue)<br>2. motion event is not supported under MJPEG format. (Camera firmware issue) |              |          |                |       |        |     |                |      |              |                      |          |         |
| EXCA2151P2    |   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | -      | -   | Yes            | -    | *2           | Yes*                 | Yes      |         |
| EXCA3361P2    |   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | -      | -   | Yes            | -    | *2           | Yes*                 | Yes      |         |
| EXCA2341P2    |   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | -      | -   | Yes            | -    | *2           | Yes*                 | Yes      |         |
| EXCA2341P2WDR |   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | -      | -   | Yes            | -    | *2           | Yes*                 | Yes      |         |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | ONVIF Search | Multi Stream Support | Remarks             |
|-------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------|----------------------|---------------------|
| Generic     |   | H.264 M-JPEG | 1        | 2592x1920      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | Supported by design |
| Note:       | Support generic dewarp<br>1.Focus function is not test on software.<br>2.The maximum resolution is depends on camera.<br>3.Some framerate and bitrate can't be set due to Onvif restriction.  |              |          |                |       |        |     |                |      |              |                      |                     |
| NCOA22F     | refer to NCOA52F(v1.8.1001.85.0.8317)   | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes*                 | Supported by design |
| NCOA32FD    | refer to NCOA52F(v1.8.1001.85.0.8317)   | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes*                 | Supported by design |
| NCOA52F     | v1.8.1001.85.0.8317   | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes*                 |                     |
| Note:       | 1. Camera with high resolution and quality is unable to achieve max fps. (Camera performance limitation)<br>2. The range of bitrate isn't synchronized with the one on camera's web due to Onvif restriction. (Camera performance limitation)<br>3. The list of framerate isn't synchronized with the one on camera's web due to Onvif restriction. (Camera performance limitation) |              |          |                |       |        |     |                |      |              |                      |                     |
| NDOA22F-W   | refer to NCOA52F(v1.8.1001.85.0.8317)   | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes*                 | Supported by design |
| NDOA32FD-W  | refer to NCOA52F(v1.8.1001.85.0.8317)   | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes*                 | Supported by design |
| NIAA202F    | refer to NCOA52F(v1.8.1001.85.0.8317)   | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes*                 | Supported by design |
| NIDA212F-W  | refer to NCOA52F(v1.8.1001.85.0.8317)   | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes*                 | Supported by design |
| NIDA312FD-W | refer to NCOA52F(v1.8.1001.85.0.8317)   | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes*                 | Supported by design |
| NIDA512F-W  | refer to NCOA52F(v1.8.1001.85.0.8317)   | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes*                 | Supported by design |
| NIPA2H22-C  | refer to NCOA52F(v1.8.1001.85.0.8317)   | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes*                 | Supported by design |
| NIPA2H22-W  | refer to NCOA52F(v1.8.1001.85.0.8317)   | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes*                 | Supported by design |
| NIRA222F    | refer to NCOA52F(v1.8.1001.85.0.8317)   | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes*                 | Supported by design |

# IP Power



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name      | Tested Firmware                       | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | ONVIF Search | Multi Stream Support | Remarks             |
|------------------|---------------------------------------|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------|----------------------|---------------------|
| <b>NIRA232F</b>  | refer to NCOA52F(v1.8.1001.85.0.8317) | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes*                 | Supported by design |
| <b>NIRA332FD</b> | refer to NCOA52F(v1.8.1001.85.0.8317) | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes*                 | Supported by design |
| <b>NITA212F</b>  | refer to NCOA52F(v1.8.1001.85.0.8317) | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes*                 | Supported by design |
| <b>NITA312FD</b> | refer to NCOA52F(v1.8.1001.85.0.8317) | H.264 MJPEG  | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes          | Yes*                 | Supported by design |

# IPcam

- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ  | On-Edge Motion | UPnP | ONVIF Search | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------|----------|----------------|-------|--------|------|----------------|------|--------------|----------------------|----------|---------------------|
| NBL3102     | 03_C002   | H.264 MJPEG  | 1        | 1920x1080      | -     | -      | -    | Yes            | Yes  | -            | Yes*                 | Yes      |                     |
| Note:       | 1. Framerate is unable to achieve setting value in MJPEG 1920x1080. (Camera performance limitation)   |              |          |                |       |        |      |                |      |              |                      |          |                     |
| NBL5302     | Refer to Zavio B8210(02_C022)   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 2/2    | Yes  | Yes            | Yes  | -            | Yes*                 | Yes      | Supported by design |
| Note:       | 1. Audio has noise with AMR. (Camera Firmware issue)<br>2. Camera with highest resolution is unable to achieve maximum FPS. (Camera performance limitation)<br>3. Move can't not move to center. (Camera Firmware issue)<br>4. Speed range is not synchronize with web. (Camera Firmware issue) |              |          |                |       |        |      |                |      |              |                      |          |                     |
| NBL7302     | 01_C013   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 2/2    | Yes  | Yes            | Yes  | -            | Yes*                 | Yes      |                     |
| Note:       | 1. Audio has noise with AMR. (Camera Firmware issue)<br>2. Camera is unable to achieve maximum FPS. (Camera performance limitation)<br>3. Move can't not move to center. (Camera Firmware issue)  |              |          |                |       |        |      |                |      |              |                      |          |                     |
| NBL7305     | Refer to Zavio B8520(01_C013)   | H.264 MJPEG  | 1        | 2560x1920      | 2-way | 2/2    | Yes* | Yes            | Yes  | -            | Yes*                 | Yes      | Supported by design |
| NDM3102     | 03_C002   | H.264 MJPEG  | 1        | 1920x1080      | -     | -      | -    | Yes            | Yes  | -            | Yes*                 | Yes      | Supported by design |
| Note:       | 1. Framerate is unable to achieve setting value in MJPEG 1920x1080. (Camera performance limitation)   |              |          |                |       |        |      |                |      |              |                      |          |                     |
| NDM5302     | Refer to Zavio D8210(02_C022)   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 2/2    | Yes  | Yes            | Yes  | -            | Yes*                 | Yes      | Supported by design |
| Note:       | 1. Audio has noise with AMR. (Camera Firmware issue)<br>2. Camera with highest resolution is unable to achieve maximum FPS. (Camera performance limitation)<br>3.PTZ only support zoom & focus.   |              |          |                |       |        |      |                |      |              |                      |          |                     |
| NBL5103     | Refer to Zavio B6320(01_C006)   | H.264 MJPEG  | 1        | 2048x1520      | -     | -      | -    | Yes            | Yes  | -            | Yes*                 | Yes      | Supported by design |
| NDM5103     | 01_C013   | H.264 MJPEG  | 1        | 2048x1520      | -     | -      | -    | Yes            | Yes  | -            | Yes*                 | Yes      | Supported by design |
| Note:       | 1. Display mosaic happen in 2304x1296 MJPEG. (Camera performance limitation)<br>2. Quality list can not sync with web. (Camera Firmware issue)<br>3. Bitrate list can not sync with web in MJPEG. (Camera Firmware issue)   |              |          |                |       |        |      |                |      |              |                      |          |                     |
| NDM7302     | 01_C013   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 2/2    | Yes  | Yes            | Yes  | -            | Yes*                 | Yes      |                     |
| Note:       | 1. Audio has noise. (Camera Firmware issue)<br>2. G.726 does not supported. (NUUO server limitation)  |              |          |                |       |        |      |                |      |              |                      |          |                     |
| NDM7305     | Refer to Zavio B8520(01_C013)   | H.264 MJPEG  | 1        | 2560x1920      | 2-way | 2/2    | Yes* | Yes            | Yes  | -            | Yes*                 | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name       | Tested Firmware | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|-------------------|-----------------|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| JS-C1100          |                 | H.264<br>M-JPEG<br>MPEG4 | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | Yes                  | Supported by design |
| JS-C2100          |                 | H.264<br>M-JPEG<br>MPEG4 | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | Yes                  | Supported by design |
| JS-WGP-100-CB     |                 | H.264<br>M-JPEG<br>MPEG4 | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | Yes                  | Supported by design |
| JS-B0100          |                 | H.264<br>M-JPEG<br>MPEG4 | 1        | 1280x800       | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  | Supported by design |
| JS-B0100-W        |                 | H.264<br>M-JPEG<br>MPEG4 | 1        | 1280x800       | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  | Supported by design |
| JS-B0131          |                 | M-JPEG<br>MPEG4          | 1        | 1280x800       | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  | Supported by design |
| JS-B1100-R30      |                 | H.264<br>M-JPEG<br>MPEG4 | 1        | 1280x800       | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  | Supported by design |
| JS-B1100          |                 | H.264<br>M-JPEG<br>MPEG4 | 1        | 1280x800       | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  | Supported by design |
| JB-B1204-R25      |                 | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| JS-D0100          |                 | H.264<br>M-JPEG<br>MPEG4 | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | Yes                  | Supported by design |
| JS-D1100          |                 | H.264<br>M-JPEG<br>MPEG4 | 1        | 1280x800       | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  | Supported by design |
| JS-D1130          |                 | M-JPEG<br>MPEG4          | 1        | 1280x800       | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  | Supported by design |
| JS-D1204          |                 | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| JS-<br>ISD0200x18 |                 | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| JS-<br>OSD0200x20 |                 | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | Yes                  | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format           | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|-------------|---|------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| VN-H37      | refer VN-H137   | H.264                  | 1        | 1920x1080      | -     | -      | -   | Yes            | -    | Yes                  |         |
| VN-H237     | refer VN-H137   | H.264                  | 1        | 1920x1080      | -     | -      | -   | Yes            | -    | Yes                  |         |
| VN-H137     | 4.02.378  | H.264                  | 1        | 1920x1080      | -     | -      | -   |                | -    | Yes                  |         |
| Note:       | 1. H264 support Baseline Profile only<br>2. When 30fps or 25fps is set, 3DDNR, motion detection and analog video output are not available.<br>3. Encoder settings can not be changed during multicast.<br>4. Firmware Issue: H264 video stream is unstable over low framerate.  |                        |          |                |       |        |     |                |      |                      |         |
| VN-H157     | refer VN-H57  | H.264                  | 1        | 1920x1080      | 1-way | 2/2    | -   | Yes            | -    | Yes                  |         |
| VN-H257     | refer VN-H57  | H.264                  | 1        | 1920x1080      | 1-way | 2/2    | -   | Yes            | -    | Yes                  |         |
| VN-H57      | 4.00.575  | H.264                  | 1        | 1920x1080      | 1-way | 2/2    | -   | Yes            | -    | Yes                  |         |
| Note:       | 1. H264 support Baseline Profile only<br>2. When 30fps or 25fps is set, 3DDNR, motion detection and analog video output are not available.<br>3. Encoder settings can not be changed during multicast.<br>4. Firmware Issue: MJPEG video stream is unstable over high resolutions.  |                        |          |                |       |        |     |                |      |                      |         |
| VN-H657     | 2.01.827<br>SPL2841   | H264<br>MJPEG          | 1        | 1920x1080      | -     | 2/2    | Yes | Yes            | -    | Yes                  |         |
| Note:       | Motion Detection is available at Home Position.<br>Firmware Issue: Mjpeg video stream is unstable over high resolutions such as 1920X1080, 1280x720.  |                        |          |                |       |        |     |                |      |                      |         |
| VN-T16      | j.2.2.2232  | H264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | -      | -   | Yes            | -    | Yes                  |         |
| Note:       | 1. There are lower frame rate limitations for H264 and MPEG4. When choosing CBR, some conditions will be disabled based on different resolution setting. When choosing VBR, some conditions will be disabled based on different resolution setting.<br>2. Firmware Issue: Mjpeg video stream is unstable over high resolutions such as 1920X1080, 1280x720.<br>3. Firmware Issue: The Encoder parameters may not sync camera web. |                        |          |                |       |        |     |                |      |                      |         |
| VN-T216     | refer VN-T16  | H264<br>MPEG4<br>MJPEG | 1        | 1920x1080      | 1-way | -      | -   | Yes            | -    | Yes                  |         |
| Note:       | 1. There are lower frame rate limitations for H264 and MPEG4. When choosing CBR, some conditions will be disabled based on different resolution setting. When choosing VBR, some conditions will be disabled based on different resolution setting.<br>2. Firmware Issue: Mjpeg video stream is unstable over high resolutions such as 1920X1080, 1280x720.<br>3. Firmware Issue: The Encoder parameters may not sync camera web. |                        |          |                |       |        |     |                |      |                      |         |
| VN-V686     | refer VN-V685   | MPEG4                  | 1        | VGA            | -     | 2/2    | Yes | Yes            | -    | Yes                  |         |
| VN-V685     | 3.04  | MPEG4                  | 1        | VGA            | -     | 2/2    | Yes | Yes            | -    | Yes                  |         |
| Note:       | Motion Detection is available at Home Position.   |                        |          |                |       |        |     |                |      |                      |         |



# LevelOne



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name  | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|--------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| FCS-0010     |  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | -   | -              | Yes  | -                    | Supported by design |
| FCS-0020     |  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | -   | -              | Yes  | -                    | Supported by design |
| FCS-0030     | Refer to<br>WCS-0030   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | -                    | Supported by design |
| FCS-0031     | 1.0.0.35   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | -                    |                     |
| Note:        | Not support on-edge motion with MJPEG format, which is camera limitation.  |                          |          |                |       |        |     |                |      |                      |                     |
| FCS-0040     | Refer to<br>WCS-0040   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | -      | -   | -              | Yes  | -                    | Supported by design |
| Note:        | Not support on-edge motion currently due to camera issue.  |                          |          |                |       |        |     |                |      |                      |                     |
| FCS-1010     | 0102d  | H.263                    | 1        | 720x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    |                     |
| FCS-1030V1.0 |  | H.263                    | 1        | 720x576        | 1-way | -      | -   | Yes            | Yes  | -                    | Supported by design |
| FCS-1030V2.0 |  | MPEG4                    | 1        | 720x576        | 1-way | -      | -   | Yes            | Yes  | -                    | Supported by design |
| FCS-1040     | 0102a  | MPEG4<br>M-JPEG          | 1        | 720x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    |                     |
| FCS-1050     |  | H.263                    | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | Supported by design |
| FCS-1060     | 0202a  | MPEG4                    | 1        | 720x576        | 1-way | -      | Yes | Yes            | Yes  | -                    |                     |
| FCS-1070     |  | MPEG4<br>M-JPEG          | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | Supported by design |
| FCS-1081     |  | MPEG4<br>M-JPEG          | 1        | 640x480        | -     | -      | -   | Yes            | Yes  | -                    | Supported by design |
| FCS-1081A    |  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | -                    |                     |
| FCS-1091     |  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 2/2    | -   | -              | Yes  | -                    | Supported by design |
| FCS-1101     |  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | -                    | Supported by design |
| FCS-1131     | L20101222N<br>S  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                    |                     |
| FCS-1132     | v1.0.0.2   | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| Note:        | Motion Detection of MPEG4 is error.  |                          |          |                |       |        |     |                |      |                      |                     |
| FCS-1141     | L20100623N<br>S  | H.264<br>M-JPEG          | 1        | 1280x960       | 1-way | 1/1    | -   | Yes            | Yes  | -                    |                     |
| Note:        | UPnP search doesn't work properly sometimes, which happens on camera's own UPnP tool. We are clarifying with vendor. |                          |          |                |       |        |     |                |      |                      |                     |

# LevelOne



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|-------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| FCS-1151    | 0100c  | H.264<br>MPEG4<br>M-JPEG | 1        | 1600x1200      | 1-way | 1/1    | Yes | Yes            | Yes  | -                    |                     |
| Note:       | UPnP search doesn't work properly sometimes, which happens on camera's own search tool. We are clarifying with vendor.   |                          |          |                |       |        |     |                |      |                      |                     |
| FCS-3000    | 0101a  | MPEG4<br>M-JPEG          | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    |                     |
| FCS-3021    |  | MPEG4<br>M-JPEG          | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| FCS-3031    | V1.0.04  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | -              | Yes  | -                    |                     |
| Note:       | The frame rate is 15 even configuring frame rate 1 under 320x240 and 160x120 resolution, which belongs to camera issue.<br>Not support on-edge motion currently due to camera issue. |                          |          |                |       |        |     |                |      |                      |                     |
| FCS-3052    | v1.0.0.2   | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| Note:       | Motion Detection of MPEG4 is error.  |                          |          |                |       |        |     |                |      |                      |                     |
| FCS-3061    | 1.0.0.34   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | 1/1    | -   | Yes            | Yes  | -                    |                     |
| FCS-3062    | v1.0.0.6   | MPEG4<br>M-JPEG<br>H.264 | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| FCS-3071    | L20101222N<br>S  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | -                    |                     |
| FCS-3071-V2 | le20120905N<br>SA  | H.264<br>M-JPEG          | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes                  |                     |
| FCS-3081    | L20101222N<br>S  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                    |                     |
| FCS-3091    | 2.0.0629   | MPEG4<br>M-JPEG          | 1        | 1600x1200      | 1-way | 4/1    | -   | -              | Yes  | -                    |                     |
| Note:       | Not support on-edge motion & dual stream in this camera FW due to its limitation.  |                          |          |                |       |        |     |                |      |                      |                     |
| FCS-3101    | FCS-3101-<br>ANC3211M-<br>1.0.1.3-08-  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes                  |                     |
| FCS-4010    |  | MPEG4<br>M-JPEG          | 1        | 720x576        | 1-way | 4/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| FCS-4041    | le20130117N<br>SA  | M-JPEG<br>H.264          | 1        | 1920x1080      | 2-way | 4/2    | Yes | Yes            | Yes  | Yes                  |                     |
| Note:       | LevelOne FCS-4041: High video parameter causes slow CGI command response.  |                          |          |                |       |        |     |                |      |                      |                     |
| FCS-4042    | Le20140113<br>NSA  | M-JPEG<br>H.264          | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | Yes                  |                     |
| Note:       | 1. FPS could not reach up to 30 while high quality.<br>2. Preset name use special symbol failed ex: #<br>3. High video parameter causes slow CGI command response                    |                          |          |                |       |        |     |                |      |                      |                     |
| FCS-4101    | FCS-4101-<br>ANC3210M-<br>1.0.1.3-08-  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | -      | Yes | Yes            | Yes  | Yes                  |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|-------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| FCS-4x00    |  | MPEG4<br>M-JPEG          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | Supported by design |
| FCS-5011    | 0100c  | MPEG4<br>M-JPEG          | 1        | 720x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| FCS-5030    | 0100a2   | MPEG4<br>M-JPEG          | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| Note:       | No audio support in M-JPEG.  |                          |          |                |       |        |     |                |      |                      |                     |
| FCS-5041    | 1.0.0.46   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | 1/1    | -   | Yes            | Yes  | -                    |                     |
| FCS-5042    | 2.0.0.1  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/0    | Yes | Yes            | Yes  | Yes                  |                     |
| FCS-5051    | L20101222N<br>S  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                    |                     |
| FCS-5052    | v1.0.0.2   | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| Note:       | Motion Detection of MPEG4 is error.  |                          |          |                |       |        |     |                |      |                      |                     |
| FCS-5061    | le20130117N<br>SA  | H264<br>MJPEG            | 1        | 2592x1944      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| FCS-5062    | v1.0.0.2   | H.264<br>MPEG4<br>M-JPEG | 1        | 2592x1944      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| Note:       | Motion Detection of MPEG4 is error.  |                          |          |                |       |        |     |                |      |                      |                     |
| FCS-6010    | 1.0.0.11   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | 1/0    | Yes | Yes            | Yes  | -                    |                     |
| Note:       | Not support DO in this camera FW.<br>Cannot get video stream through TCP/UDP sometimes, which belongs to camera issue.<br>Camera may reboot itself when changing video format to MPEG4, which belongs to camera issue. |                          |          |                |       |        |     |                |      |                      |                     |
| FCS-7011    |  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | Supported by design |
| SDK8        | CFA-<br>V6.07.23-L1  | H264<br>MJPEG            | 1        | 3648x2736      | 2-way | 1/1    | Yes | Yes            | -    | Yes*                 | Supported by design |
| WCS-0010    |  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | -   | -              | Yes  | -                    | Supported by design |
| WCS-0020    |  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | Yes | -              | Yes  | -                    | Supported by design |
| WCS-0030    | 1.0.0.35   | H.264<br>MPEG4           | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | -                    |                     |
| WCS-0040    | 1.0.0.3  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | -      | -   | -              | Yes  | -                    |                     |
| Note:       | Not support on-edge motion currently due to camera issue.  |                          |          |                |       |        |     |                |      |                      |                     |
| WCS-0050    | v1.0.0.36  | MPEG4<br>MJPEG<br>H264   | 1        | 1280x800       | 1-way | -      | -   | Yes            | Yes  | Yes                  |                     |

# LevelOne



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name  | Tested Firmware | Video Format            | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|--------------|-----------------|-------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| WCS-1090     |                 | MPEG4<br>M-JPEG         | 1        | 640x480        | 1-way | 2/2    | -   | -              | Yes  | -                    | Supported by design |
| WCS-2010V1.0 |                 | H.263                   | 1        | 720x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | Supported by design |
| WCS-2010V2.0 |                 | H.263                   | 1        | 720x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | Supported by design |
| WCS-2030V1.0 | 0200d           | H.263                   | 1        | 720x576        | 1-way | -      | -   | Yes            | Yes  | -                    |                     |
| WCS-2030V2.0 |                 | H.263                   | 1        | 720x576        | 1-way | -      | -   | Yes            | Yes  | -                    | Supported by design |
| WCS-2030V3.0 |                 | MPEG4                   | 1        | 720x576        | 1-way | -      | -   | Yes            | Yes  | -                    | Supported by design |
| WCS-2040     | 0101b           | MPEG4<br>M-JPEG         | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    |                     |
| WCS-2060     |                 | MPEG4                   | 1        | 720x576        | 1-way | -      | -   | Yes            | Yes  | -                    | Supported by design |
| WCS-2070     | 0100b           | MPEG4<br>M-JPEG         | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    |                     |
| WCS-6020     | 1.1.4.1         | MJPEG<br>MPEG4<br>H.264 | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |
| WCS-6050     | 1.0.4.2         | MJPEG<br>H.264          | 1        | 2560x1920      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ  | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|-------------|--|--------------|----------|----------------|-------|--------|------|----------------|------|----------------------|---------------------|
| LDW2010     | 260.0.0.1208100  | H.264 MJPEG  | 1        | 2040x1536      | 1-way | 1/1    | -    | Yes            | -    | Yes                  |                     |
| LNB3100     | Refer to LND5100   | H.264 MJPEG  | 1        | 1280x1024      | 1-way | 1/1    | -    | Yes            | -    | Yes                  |                     |
| LNB5100     | Refer to LND5100   | H.264 MJPEG  | 1        | 1280x1024      | 1-way | 1/1    | -    | Yes            | -    | Yes                  |                     |
| LND3100     | Refer to LND5100   | H.264 MJPEG  | 1        | 1280x1024      | 1-way | 1/1    | -    | Yes            | -    | Yes                  |                     |
| LND5100     | 1796.0.0.1208060   | H.264 MJPEG  | 1        | 1280x1024      | 1-way | 1/1    | -    | Yes            | -    | Yes                  |                     |
| LND7210     | Refer to LNV7210R(xx.xx.0.0.1405190)   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | *2     | -    | Yes            | *2   | Yes                  | Supported by design |
| LND7210R    | Refer to LNV7210R(xx.xx.0.0.1405190)   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | *2     | -    | Yes            | *2   | Yes                  | Supported by design |
| LND7300     | 1801.0.0.1303220   | H.264 MJPEG  | 1        | 2048x1536      | *2    | *2     | -    | Yes            | -    | Yes                  |                     |
| LNP2800     | Refer to LNP3700T  | H.264 MJPEG  | 1        | D1             | 1-way | 4/2    | Yes  | Yes            | -    | Yes                  |                     |
| LNP2800I    | Refer to LNP3700T  | H.264 MJPEG  | 1        | D1             | 1-way | 4/2    | Yes  | Yes            | -    | Yes                  |                     |
| LNP2810T    | 1890.0.0.1302150   | H.264 MJPEG  | 1        | 1280x720       | *2    | *2     | Yes  | Yes            | -    | Yes                  |                     |
| LNP3020     | 1891.0.0.1411270   | H.264 MJPEG  | 1        | 1920x1080      | *2    | *2     | Yes* | Yes            | *2   | Yes                  |                     |
| Note:       | 1.The 2nd stream's frame rate will exceed the setting value (Camera limitation). |              |          |                |       |        |      |                |      |                      |                     |
| LNP3700     | Refer to LNP3700T  | H.264 MJPEG  | 1        | D1             | 1-way | 4/2    | Yes  | Yes            | -    | Yes                  |                     |
| LNP3700T    | 1286.0.0.1205140   | H.264 MJPEG  | 1        | D1             | 1-way | 4/2    | Yes  | Yes            | -    | Yes                  |                     |
| LNU5100R    | 1954.0.0.1303120   | H.264 MJPEG  | 1        | 1280x1024      | *2    | *2     | -    | Yes            | -    | Yes                  |                     |
| LNU7210R    | Refer to LNV7210R(xx.xx.0.0.1405190)   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | *2     | -    | Yes            | *2   | Yes                  | Supported by design |
| LNV5100     | Refer to LND5100   | H.264 MJPEG  | 1        | 1280x1024      | 1-way | 1/1    | -    | Yes            | -    | Yes                  |                     |
| LNV5100R    | 1972.0.0.1303110   | H.264 MJPEG  | 1        | 1280x1024      | *2    | *2     | -    | Yes            | -    | Yes                  |                     |
| LNV5110     | Refer to LND5100   | H.264 MJPEG  | 1        | 1280x1024      | 1-way | 1/1    | -    | Yes            | -    | Yes                  |                     |
| LNV7210     | Refer to LNV7210R(xx.xx.0.0.1405190)   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | *2     | -    | Yes            | *2   | Yes                  | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|-------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| LNV7210R    | 2237.0.0.1405190  | H.264 MJPEG  | 1        | 1920x1080      | 2-way | *2     | -   | Yes            | *2   | Yes                  |                     |
| Note:       | Unable to set video parameter (brightness...etc)                      |              |          |                |       |        |     |                |      |                      |                     |
| LNV7300     | Refer to LND7300(FW 1801.0.0.130)                                     | H.264 MJPEG  | 1        | 2048x1536      | *2    | *2     | -   | Yes            | -    | Yes                  |                     |
| LSW2010     | Refer to LDW2010  | H.264 MJPEG  | 1        | 2040x1536      | 1-way | 1/1    | -   | Yes            | -    | Yes                  | Supported by design |
| LSW900      | Refer to LVW701   | H.264 MJPEG  | 1        | D1             | 1-way | 1/1    | -   | Yes            | -    | Yes                  | Supported by design |
| LSW901      | Refer to LVW701   | H.264 MJPEG  | 1        | D1             | 1-way | 1/1    | -   | Yes            | -    | Yes                  | Supported by design |
| LVS201      | 385.0.0.1208200   | H.264 MJPEG  | 1        | D1             | -     | -      | Yes | Yes            | -    | Yes                  |                     |
| LVS301      | Refer to LVS311   | H.264 MJPEG  | 1        | D1             | 1-way | 1/1    | Yes | Yes            | -    | Yes                  | Supported by design |
| LVS311      | 129.1.0.1110260   | H.264 MJPEG  | 1        | D1             | 1-way | 1/1    | Yes | Yes            | -    | Yes                  |                     |
| LVW700      | Refer to LVW701   | H.264 MJPEG  | 1        | D1             | 1-way | 1/1    | -   | Yes            | -    | Yes                  | Supported by design |
| LVW701      | 4.1.1.1110260   | H.264 MJPEG  | 1        | D1             | 1-way | 1/1    | -   | Yes            | -    | Yes                  |                     |
| LVW900      | Refer to LVW701   | H.264 MJPEG  | 1        | D1             | 1-way | 1/1    | -   | Yes            | -    | Yes                  | Supported by design |
| LVW901      | Refer to LVW701   | H.264 MJPEG  | 1        | D1             | 1-way | 1/1    | -   | Yes            | -    | Yes                  | Supported by design |
| LW130W      | 4097.0.0.1203131  | H.264 MJPEG  | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | -    | Yes                  |                     |
| LW332       | 1026.0.0.1110260  | H.264 MJPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes                  |                     |
| LW335       | Refer to LW332  | H.264 MJPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes                  |                     |
| LW342       | Refer to LW345  | H.264 MJPEG  | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes                  |                     |
| LW345       | 515.0.0.1110260   | H.264 MJPEG  | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes                  |                     |
| Note:       | 1. Can't support dual-stream at H264,1920x1080 (or above), over 20fps |              |          |                |       |        |     |                |      |                      |                     |
| LW352       | 1030.0.0.1111160  | H.264 MJPEG  | 1        | 2040x1536      | 1-way | 1/1    | -   | Yes            | -    | Yes                  |                     |
| LW355       | Refer to LW352  | H.264 MJPEG  | 1        | 2040x1536      | 1-way | 1/1    | -   | Yes            | -    | Yes                  | Supported by design |
| LW6324      | Refer to LW332  | H.264 MJPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes                  |                     |
| LW6354      | Refer to LW332  | H.264 MJPEG  | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | -    | Yes                  |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware      | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|-------------|----------------------|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| LW6424      | Refer to LW345       | H.264 MJPEG  | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes                  |                     |
| LW6454      | Refer to LW345       | H.264 MJPEG  | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes                  |                     |
| LW9226      | 774.0.0.1211<br>289  | H.264 MJPEG  | 1        | D1             | 1-way | 4/2    | Yes | Yes            | -    | Yes                  |                     |
| LW92261     | Refer to LW9226      | H.264 MJPEG  | 1        | D1             | 1-way | 4/2    | Yes | Yes            | -    | Yes                  | Supported by design |
| LW9228      | Refer to LW9226      | H.264 MJPEG  | 1        | D1             | 1-way | 4/2    | Yes | Yes            | -    | Yes                  | Supported by design |
| LW92281     | Refer to LW9226      | H.264 MJPEG  | 1        | D1             | 1-way | 4/2    | Yes | Yes            | -    | Yes                  | Supported by design |
| LW9422      | 1632.0.0.120<br>5030 | H.264 MJPEG  | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | -    | Yes                  |                     |

Note:

For LW9422:  
 1. PTZ will stop automatically when press button over 10sec.  
 2. Focus Near / Far need setup the Focus mode in camera's OSD  
 3. Adjust zoom speed is useless  
 4. Can't support dual-stream at H264,1920x1080 (or above), over 20fps

For LW9226 :  
 1. PTZ will stop automatically when press button over 10sec.  
 2. Focus Near / Far need setup the Focus mode in camera's OSD  
 2. Audio out impedance is too large.

For LVS201:  
 1. QCIF has image noise at the bottom line.

# MegaIP



- : not available on camera  
\*1: not available on software  
\*2: not test on software  
For multi stream support:  
Yes: multi stream fix to 500kbps/100kbps  
Yes\*: multi stream setting support

| Device Name       | Tested Firmware   | Video Format    | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|-------------------|---|-----------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| <b>NCD-2003PR</b> | 51110.2.126<br>2.100  | H.264<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |         |
| Note:             | 1. When set Anti-Flicker Mode to 50Hz, Mainconsole would get wrong Max of FPS(30). (Firmware issue)<br>2. PTZ only support Zoom/Focus   |                 |          |                |       |        |     |                |      |                      |         |
| <b>NMX-2003P</b>  | 51110.2.126<br>2.100  | H.264<br>M-JPEG | 1        | 1920x1080      | -     | -      | Yes | Yes            | Yes  | Yes                  |         |
| Note:             | 1. Getting bitrate value would not sync with camera's web. (Camera onvif issue)<br>2. Setting quality value would not sync with camera's web. (Camera onvif issue)<br>3. After setting parameter on camera, camera would restart for a while. After camera restart completed, then parameter can be got.<br>4. MD and I/O works only when http is 80. |                 |          |                |       |        |     |                |      |                      |         |





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name      | Tested Firmware  | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|------------------|--|--------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| <b>NCB855PRO</b> | AP_01-00-60-25A_MS03   | H264, MJPEG, MPEG4 | 1        | 1920x1080      | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| Note             | 1.Set parameter will take 10 sec or more to setup<br>2.Get parameter may wrong after set parameter<br>3.Broken textures on connected in 1~4sec at MPEG4<br>4.Not support auto detection<br>5.Setup bit rate of MPEG4 will response wrong parameter |                    |          |                |       |        |     |                |      |                      |                     |
| <b>NCC800</b>    | AP_01-00-60-25B_MS03   | H264, MJPEG, MPEG4 | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| Note             | 1.Set parameter will take 10 sec or more to setup<br>2.Get parameter may wrong after set parameter<br>3.Broken textures on connected in 1~4sec at MPEG4<br>4.Not support auto detection  |                    |          |                |       |        |     |                |      |                      |                     |
| <b>NDF821</b>    | Refer to NDR891 (AP_01-00-60-25A_MS02)   | H.264 MJPEG MPEG4  | 1        | 1920x1080      | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| <b>NDF821PRO</b> | Refer to NCR875PRO (AP_01-00-60-25A_MS03)  | H.264 MJPEG MPEG4  | 1        | 1920x1080      | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| <b>NDF831</b>    | Refer to NDR891 (AP_01-00-60-25A_MS02)   | H.264 MJPEG MPEG4  | 1        | 1920x1080      | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| <b>NDF831PRO</b> | Refer to NCR875PRO (AP_01-00-60-25A_MS03)  | H.264 MJPEG MPEG4  | 1        | 1920x1080      | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| <b>NCB858</b>    | Refer to NCR878 (AP_01-00-62-18_MS05)  | H.264 MJPEG MPEG4  | 1        | 2592x1944      | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| <b>NCR870</b>    | AP_01-00-62-18_MS00-01N  | H.264 MJPEG MPEG4  | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes                  |                     |
| Note:            | 1.Set parameter will take 10 sec or more to setup.<br>2.Get parameter may wrong after set parameter.<br>3.The setting of framerate is 30, but actual receiving framerate is only 15.   |                    |          |                |       |        |     |                |      |                      |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name       | Tested Firmware  | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|-------------------|--|--------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| <b>NCR875PRO</b>  | AP_01-00-60-25A_MS03   | H264, MJPEG, MPEG4 | 1        | 1920x1080      | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  |                     |
| Note              | 1.Set parameter will take 10 sec or more to setup<br>2.Get parameter may wrong after set parameter<br>3.Broken textures on connected in 1~4sec at MPEG4<br>4.Not support auto detection<br>5.Setup bit rate of MPEG4 will response wrong parameter |                    |          |                |       |        |     |                |      |                      |                     |
| <b>NCR878</b>     | AP_01-00-62-18_MS05  | H.264 MJPEG MPEG4  | 1        | 2592x1944      | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  |                     |
| Note:             | 1.Set parameter will take 10 sec or more to setup.<br>2.Get parameter may wrong after set parameter.<br>3.Auto detection can't be use.   |                    |          |                |       |        |     |                |      |                      |                     |
| <b>NDF820</b>     | Refer to NCR870(AP_01-00-62-18_MS00-01N)   | H.264 MJPEG MPEG4  | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes                  | Supported by design |
| Note:             | 1.Set parameter will take 10 sec or more to setup.<br>2.Get parameter may wrong after set parameter.<br>3.The setting of framerate is 30, but actual recieving framerate is only 15.   |                    |          |                |       |        |     |                |      |                      |                     |
| <b>NDR891</b>     | AP_01-00-60-25A_MS02   | H264, MJPEG, MPEG4 | 1        | 1920x1080      | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  |                     |
| Note              | 1.Set parameter will take 10 sec or more to setup<br>2.Get parameter may wrong after set parameter<br>3.Broken textures on connected in 1~4sec at MPEG4<br>4.Not support auto detection<br>5.Setup bit rate of MPEG4 will response wrong parameter |                    |          |                |       |        |     |                |      |                      |                     |
| <b>NDR891PRO</b>  | Refer to NCR875PRO(AP_01-00-60-25A_MS03)   | H.264 MJPEG MPEG4  | 1        | 1920x1080      | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| <b>NIC950HPRO</b> | A1D-310-V4.12.09-NB  | MPEG4 M-JPEG H.264 | 1        | 720x480        | 1-way | -      | Yes | Yes            | -    | Yes                  |                     |
| Note              | 1.Not support UPnP<br>2.Not support auto detection<br>3.Not support motion detection on MJPEG<br>4.Not support DI and DO   |                    |          |                |       |        |     |                |      |                      |                     |

# Messoa



- : not available on camera  
\*1: not available on software  
\*2: not test on software

For multi stream support:  
Yes: multi stream fix to 500kbps/100kbps  
Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|-------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| NIC990      | M.O.2.9   | H.264        | 1        | 1920x1080      | 1-way | 6/1    | Yes | Yes            | Yes  | Yes                  |         |
| Note        | 1.Can't set framerate<br>2.Not support dual stream on 1080P |              |          |                |       |        |     |                |      |                      |         |

# MIWI-URMET



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name         | Tested Firmware | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|---------------------|-----------------|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| HD-PRO302DN         | DC Standard     | H.264 MJPEG  | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | -                    | Supported by design |
| HD-PRO310DNW        | mw2014070 3NSA  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| HD-PRO332DNW        | mw2014070 3NSA  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| HD-PRO350DNW        | mw2014070 3NSA  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| HD-PRO350DNW /H     | mw2014070 3NSA  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| HD-PRO350DNW /IR    | mw2014070 3NSA  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| HD-PRO350DNW /IR/H  | mw2014070 3NSA  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| HD-PRO351DNW /H     | mw2014070 3NSA  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| HD-PRO351DNW /IR/H  | mw2014070 3NSA  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| HD-PRO352DNW        | mw2014070 3NSA  | H.264 M-JPEG | 1        | 2592x1944      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| HD-PRO352DNW /IR    | mw2014070 3NSA  | H.264 M-JPEG | 1        | 2592x1944      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| HD-PRO370W          | mw2014070 3NSA  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes                  | Supported by design |
| HD-PRO370WOUT       | mw2014070 3NSA  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes                  | Supported by design |
| HD-PRO392DNW /V     | mw2014070 3NSA  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| HD-PRO410DNW /H     | mw2014070 3NSA  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| HD-PRO410DNW /H-POE | mw2014070 3NSA  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| HD-PRO518DN         | mw2014070 3NSA  | H.264 MJPEG  | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | -                    | Supported by design |
| HD-PRO610DNW        | mw2014070 3NSA  | H.264 M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| HD-PRO692DNW /V/IR  | mw2014070 3NSA  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |

|                              |                   |                 |   |           |       |     |     |     |     |     |                        |
|------------------------------|-------------------|-----------------|---|-----------|-------|-----|-----|-----|-----|-----|------------------------|
| <b>HD-PRO710DNW</b>          | mw2014070<br>3NSA | H.264<br>M-JPEG | 1 | 2592x1944 | 1-way | 1/1 | -   | Yes | Yes | Yes | Supported<br>by design |
| <b>HD-PRO750DNW</b>          | mw2014070<br>3NSA | H.264<br>M-JPEG | 1 | 2592x1944 | 1-way | 1/1 | Yes | Yes | Yes | Yes | Supported<br>by design |
| <b>HD-PRO750DNW<br/>/IR</b>  | mw2014070<br>3NSA | H.264<br>M-JPEG | 1 | 2592x1944 | 1-way | 1/1 | Yes | Yes | Yes | Yes | Supported<br>by design |
| <b>HD-PRO810DNW<br/>/H</b>   | mw2014070<br>3NSA | H.264<br>M-JPEG | 1 | 2592x1944 | 1-way | 1/1 | Yes | Yes | Yes | Yes | Supported<br>by design |
| <b>HD-PRO810DNW<br/>/H/M</b> | mw2014070<br>3NSA | H.264<br>M-JPEG | 1 | 2592x1944 | 1-way | 1/1 | Yes | Yes | Yes | Yes | Supported<br>by design |
| <b>HD-PRO890</b>             | mw2014070<br>3NSA | H.264,<br>MJPEG | 1 | 2592x1944 | 1-way | 1/1 | -   | Yes | Yes | Yes | Supported<br>by design |
| Note:                        | Fisheye camera    |                 |   |           |       |     |     |     |     |     |                        |
| <b>HD-PRO890/OUT</b>         | mw2014070<br>3NSA | H.264,<br>MJPEG | 1 | 2592x1944 | 1-way | 1/1 | -   | Yes | Yes | Yes | Supported<br>by design |
| Note:                        | Fisheye camera    |                 |   |           |       |     |     |     |     |     |                        |

# Robotix



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name                | Tested Firmware                        | Video Format    | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|----------------------------|--|-----------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| <b>C25</b>                 | Refer to i25(4.3.2.77)                 | MJPEG<br>MxPEG  | 1        | 2592x1944      | 1-way | -      | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| <b>D12D-IT</b>             |  | MxPEG<br>M-JPEG | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| <b>D12D-Sec</b>            |  | MxPEG<br>M-JPEG | 1        | 2048x1536      | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| <b>D14D-Sec</b>            | MX-V4.1.0.2                            | MxPEG<br>M-JPEG | 1        | 2048x1536      | 1-way | -      | -   | -              | -    | Yes                  | -        |                     |
| <b>D15D-Sec</b>            | Refer to D15D-Sec-Dnight(MX-V4.1.9.29) | MxPEG<br>M-JPEG | 1        | 2048x1536      | 2-way | 2/2    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| Note:                      | Fisheye camera                         |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>D15D-Sec-Dnight</b>     | MX-V4.1.9.29                           | MxPEG<br>M-JPEG | 1        | 2048x1536      | 2-way | 2/2    | -   | Yes            | -    | Yes*                 | Yes      |                     |
| Note:                      | Fisheye camera                         |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>D15D-Sec-Night-Pano</b> | Refer to D15D-Sec-Dnight(MX-V4.1.9.29) | MxPEG<br>M-JPEG | 1        | 2048x1536      | 2-way | 2/2    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| Note:                      | Fisheye camera                         |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>D15D-Sec-Pano</b>       | Refer to D15D-Sec-Dnight(MX-V4.1.9.29) | MxPEG<br>M-JPEG | 1        | 2048x1536      | 2-way | 2/2    | -   | Yes            | -    | Yes                  | Yes      | Supported by design |
| Note:                      | Fisheye camera                         |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>D22M-Basic</b>          |  | MxPEG<br>M-JPEG | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| <b>D22M-IT</b>             | MX-V3.4.0.9                            | MxPEG<br>M-JPEG | 1        | 640x480        | 1-way | 2/2    | -   | Yes            | -    | Yes                  | -        | Supported by design |
| <b>D22M-Sec</b>            |  | MxPEG<br>M-JPEG | 1        | 2048x1536      | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| <b>D24M-Basic</b>          |  | MxPEG<br>M-JPEG | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| <b>D24M-IT</b>             |  | MxPEG<br>M-JPEG | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |

# Robotix



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name     | Tested Firmware  | Video Format    | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-----------------|--|-----------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| D24M-Sec        | MX-V4.0.1.15<br>(2009-07-20)   | MxPEG<br>M-JPEG | 1        | 2048x1536      | 1-way | 2/2    | -   | Yes            | -    | Yes                  | -        |                     |
| D25             | Refer to<br>i25(4.3.2.77)  | MJPEG<br>MxPEG  | 1        | 2592x1944      | 1-way | -      | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| i25             | 4.3.2.77   | MJPEG<br>MxPEG  | 1        | 2592x1944      | 1-way | -      | -   | Yes            | -    | Yes*                 | Yes      |                     |
| Note:           | 1.Audio only support under MxPEG.(Camera Firmware Issue)<br>2.The max framerate we get only 12 frame per second.(Camera Firmware Issue)  |                 |          |                |       |        |     |                |      |                      |          |                     |
| Generic         | MX-V4.1.9.29   | MxPEG<br>M-JPEG | 1        | 2048x1536      | 2-way | 2/2    | -   | Yes            | -    | Yes                  | -        |                     |
| Note:           | Support generic dewarp   |                 |          |                |       |        |     |                |      |                      |          |                     |
| M10D            | M10-V2.2.2.17  | M-JPEG          | 1        | 2048x1536      | 1-way | -      | -   | Yes            | -    | Yes                  | -        |                     |
| M12D-IT         |  | MxPEG<br>M-JPEG | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| M12D-Sec        | MX-V3.4.0.9  | MxPEG<br>M-JPEG | 1        | 2048x1536      | 1-way | -      | -   | Yes            | -    | Yes                  | -        |                     |
| M12D-Web        |  | MxPEG<br>M-JPEG | 1        | 2048x1536      | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| M15D-Sec        | 4.3.4.5  | MxPEG<br>M-JPEG | 1        | 3072x2048      | 1-way | 2/2    | -   | *2             | *2   | Yes*                 | Yes      |                     |
| Note:           | 1. Does not support rotate. (NUUO server limitation)<br>2. The camera with higher quality and resolution is unable to achieve the fps which users set for all streams. (Camera Firmware issue)<br>3. The 2nd and 3rd stream resolution will depends on 1st stream resolution setting. For example, if users set the resolution of 1st stream to 2048*1536(the ratio of height and width is 4:3) and 2nd stream resolution is 1920*1080, the 2nd stream resolution will become 1440*1080(4:3) instead of 1920*1080(16:9). (Camera performance limitation) |                 |          |                |       |        |     |                |      |                      |          |                     |
| M15D-Sec-Dnight | Refer to<br>M15D-Sec(MX-V4.1.9.29)   | MxPEG<br>M-JPEG | 1        | 2048x1536      | 2-way | 2/2    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| Note:           | Fisheye camera   |                 |          |                |       |        |     |                |      |                      |          |                     |
| M15M-Sec        | Refer to<br>M15D-Sec(MX-V4.1.9.29)   | MxPEG<br>M-JPEG | 1        | 2048x1536      | 2-way | 2/2    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| Note:           | Fisheye camera   |                 |          |                |       |        |     |                |      |                      |          |                     |

# Robotix



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name    | Tested Firmware  | Video Format    | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|----------------|--|-----------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| M22M-IT        |  | MxPEG<br>M-JPEG | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| M22M-Sec       |  | MxPEG<br>M-JPEG | 1        | 2048x1536      | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| M24M-Sec       | MX-V4.0.4.28   | MxPEG<br>M-JPEG | 1        | 2048x1536      | 1-way | -      | -   | Yes            | -    | Yes                  | -        |                     |
| Note:          | 1.Motion event works abnormal until first time trigger.<br>2.Resolution of dual-stream can't bigger then main-stream |                 |          |                |       |        |     |                |      |                      |          |                     |
| M25M           | Refer to i25(4.3.2.77)   | MJPEG<br>MxPEG  | 1        | 2592x1944      | 1-way | -      | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| P25            | Refer to i25(4.3.2.77)   | MJPEG<br>MxPEG  | 1        | 2592x1944      | 1-way | -      | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| Q22M-Basic     |  | MxPEG<br>M-JPEG | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| Note:          | Fisheye camera   |                 |          |                |       |        |     |                |      |                      |          |                     |
| Q22M-Sec       | MX-V3.4.5.10   | MxPEG<br>M-JPEG | 1        | 2048x1536      | 1-way | 2/2    | -   | Yes            | -    | Yes                  | -        | Supported by design |
| Note:          | Fisheye camera   |                 |          |                |       |        |     |                |      |                      |          |                     |
| Q24M-Basic     |  | MxPEG<br>M-JPEG | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| Note:          | Fisheye camera   |                 |          |                |       |        |     |                |      |                      |          |                     |
| Q24M-Sec       | MX-V4.0.1.7  | MxPEG<br>M-JPEG | 1        | 2048x1536      | 1-way | -      | -   | Yes            | -    | Yes                  | -        |                     |
| Note:          | Fisheye camera   |                 |          |                |       |        |     |                |      |                      |          |                     |
| Q25            | Refer to i25(4.3.2.77)   | MJPEG<br>MxPEG  | 1        | 2592x1944      | 1-way | -      | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| Q25M-Secure    | MX-V4.1.10.35  | MxPEG<br>M-JPEG | 1        | 2048X1536      | 2-way | 2/2    | Yes | Yes            | -    | Yes*                 | Yes      |                     |
| Note:          | 1. Fisheye camera<br>2. When display mode is panorama, move will become vague.                                       |                 |          |                |       |        |     |                |      |                      |          |                     |
| S14D-Sec       | Refer to S15D-Sec(MX-V4.1.9.29)  | MxPEG<br>M-JPEG | 1        | 2048x1536      | 2-way | 2/2    | -   | Yes            | -    | Yes                  | -        | Supported by design |
| Note:          | Fisheye camera   |                 |          |                |       |        |     |                |      |                      |          |                     |
| S14D-Sec-Night | Refer to S15D-Sec(MX-V4.1.9.29)  | MxPEG<br>M-JPEG | 1        | 2048x1536      | 2-way | 2/2    | -   | Yes            | -    | Yes                  | -        | Supported by design |
| Note:          | Fisheye camera   |                 |          |                |       |        |     |                |      |                      |          |                     |



# Robotix



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name           | Tested Firmware  | Video Format    | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-----------------------|--|-----------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| <b>S14M-Sec</b>       | Refer to S15D-Sec(MX-V4.1.9.29)  | MxPEG<br>M-JPEG | 1        | 2048x1536      | 2-way | 2/2    | -   | Yes            | -    | Yes                  | -        | Supported by design |
| Note:                 | Fisheye camera   |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>S15D-Sec</b>       | MX-V4.1.9.29   | MxPEG<br>M-JPEG | 1        | 2048x1536      | 2-way | 2/2    | -   | Yes            | -    | Yes*                 | Yes      |                     |
| Note:                 | Fisheye camera   |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>S15M-Sec</b>       | Refer to S15D-Sec(MX-V4.1.9.29)  | MxPEG<br>M-JPEG | 1        | 2048x1536      | 2-way | 2/2    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| Note:                 | Fisheye camera   |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>S15M-Sec-Night</b> | Refer to S15D-Sec(MX-V4.1.9.29)  | MxPEG<br>M-JPEG | 1        | 2048x1536      | 2-way | 2/2    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| Note:                 | Fisheye camera<br>For M15D-Sec, S15D-Sec, D15D-Sec:<br>1. (Camera issue): The camera with higher quality and resolution is unable to achieve the fps which users set for all streams<br>2. (Known issue): The actual sub-stream resolution depend on 1st stream resolution value . For example, if users set the resolution of 1st stream to 2048*1536(the ratio of height and width is 4:3) and 2nd stream resolution is 1920*1080, the 2nd stream resolution will become 1440*1080(4:3) instead of 1920*1080(16:9) |                 |          |                |       |        |     |                |      |                      |          |                     |
| <b>T24M-Sec</b>       | MX-V4.0.4.19   | MxPEG<br>M-JPEG | 1        | 2048x1536      | 1-way | 7/3    | -   | Yes            | -    | Yes                  | -        |                     |
| <b>T25M-Secure</b>    | MX-V4.1.10.35  | MxPEG<br>M-JPEG | 1        | 2048x1536      | 2-way | 2/2    | Yes | Yes            | -    | Yes*                 | Yes      |                     |
| Note:                 | 1. Fisheye camera<br>2. When display mode is panorama, move will become vague.   |                 |          |                |       |        |     |                |      |                      |          |                     |
| Note:                 | For All Model:<br>1. For display mode, please set on the Robotix web setting page first.<br>2. No Support Audio from Camera when video format is MJPEG.<br>3. Using ExtIO, please set on the Robotix web setting page first.   |                 |          |                |       |        |     |                |      |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|-------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| HMNC100     | 00910   | H.264        | 1        | 1280x720       | -     | -      | -   | -              | Yes  | Yes                  |         |
| Note:       | 1. When setting FPS to 6~9, Camera will achieve maximum FPS. (Camera firmware issue)<br>2. Bitrate setting is not work. (Camera firmware issue)<br>3. Camera UPnP search failure. (Camera firmware issue)<br>4. No quality options in VBR mode. (Camera firmware issue)<br>5. Motion are not supported. (Camera firmware issue) |              |          |                |       |        |     |                |      |                      |         |
| HMNC500     | 00910   | H.264        | 1        | 1280x720       | 1-way | -      | -   | -              | Yes  | Yes                  |         |
| Note:       | 1: When setting FPS to 6~9, Camera will achieve maximum FPS.(Camera firmware issue)<br>2. Quality options for CBR mode is not work. (Camera firmware issue)<br>3. Not support motion. (Camera firmware issue)<br>4. Camera UPnP search failure. (Camera firmware issue)   |              |          |                |       |        |     |                |      |                      |         |



# ONVIF



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Brand    | Device Name  | Tested Firmware         | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|----------|--|-------------------------|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| Histream | HH9803C-L16  | v2.3.1.4.0.22           | M-JPEG<br>H.264<br>MPEG4 | 1        | 704x480        | -     | -      | Yes | -              | -    | Yes*                 |         |
| Note:    | 1. Due to Onvif restriction, some frame rate and bit rates cannot be set.<br>2. MPEG-4 cannot use due to camera firmware issue.<br>3. The value of MJPEG quality isn't synchronized with camera's web  |                         |                          |          |                |       |        |     |                |      |                      |         |
| Jetstor  | JV-B1201R  | V6.03.05-CGBO24200-1210 | M-JPEG<br>H.264          | 1        | 1920x1080      | -     | -      | -   | -              | -    | Yes*                 |         |
| Note:    | 1. Due to Onvif restriction, some frame rate and bit rates cannot be set.<br>2. 2nd and 3rd cannot set to different resolution.  |                         |                          |          |                |       |        |     |                |      |                      |         |
| Jetstor  | JV-OSD0200-X20   | V6.03.05-CGBO24200-1228 | H.264<br>MJPEG           | 1        | 1920x1080      | -     | -      | -   | -              | -    | Yes*                 |         |
| LILIN    | LD2222   | 1.1.16                  | H.264<br>MJPEG           | 1        | 1920x1080      | 1-way | *2     | -   | Yes            | -    | Yes*                 |         |
| Note:    | 1. Due to Onvif restriction, some frame rate and bit rates cannot be set. (ONVIF limitation)<br>2. Due to Onvif restriction, dependency between framerate and bitrate cannot be showed. (ONVIF limitation)<br>3. Motion detection may always trigger continuously. (Camera firmware issue)   |                         |                          |          |                |       |        |     |                |      |                      |         |
| LILIN    | IPD2322ESX   | 1.0.60                  | H.264<br>MJPEG           | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes*                 |         |
| Note:    | 1. Due to Onvif restriction, some frame rate and bit rates cannot be set. (ONVIF limitation)<br>2. Due to Onvif restriction, dependency between framerate and bitrate cannot be showed. (ONVIF limitation)   |                         |                          |          |                |       |        |     |                |      |                      |         |
| LILIN    | IPS518   | 1.2.02                  | H.264<br>MJPEG           | 1        | 1920x1080      | *2    | *2     | *2  | *2             | -    | Yes*                 |         |
| Note:    | 1. The range of bitrate and frame rate may be different from what camera web shows. (Camera Firmware issue)<br>2. Image setting, digital input, talk and motion detection do not function. (Camera Firmware issue)<br>3. Zoom and focus do not function normally. (Camera Firmware issue)<br>4. Video settings may not be synchronized to camera web. (Camera Firmware issue)<br>5. Audio is not available under TCP and UDP. (Camera performance limitation)<br>6. Autodetection and camera search do not function. (Generic model)<br>7. The camera supports 4 streams, while only 3 streams could be displayed. (NUUO server limitation)<br>8. Some frame rates and bit rates cannot be set. (ONVIF limitation)<br>9. Dependency between frame rate and bitrate is not shown. (ONVIF limitation)<br>10. Flip and mirror are not supported. (ONVIF limitation) |                         |                          |          |                |       |        |     |                |      |                      |         |

# ONVIF



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Brand   | Device Name   | Tested Firmware          | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|---------|---|--------------------------|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| ONVIF   | ONVIF   | -                        | -            | -        | -              | -     | -      | -   | -              | -    | -                    |         |
| Note:   | Fisheye camera<br>ONVIF specification must be fully implemented by camera vendors in order to be supported by NUUO software. To confirm the compatibility, it is recommended to execute testing prior to any further usage.<br>1. Some frame rates and bit rates cannot be set. (ONVIF limitation)<br>2. Dependency between frame rate and bit rate cannot be shown. (ONVIF limitation)<br>3. The bit rate mode cannot be switched among constant bit rate (CBR), variable bit rate (VBR) and average bit rate (AVR). (ONVIF limitation)<br>4. The pin index of DI and DO may be different from camera spec since the indexing rule is unknown. (ONVIF limitation)<br>5. The maximum numbers of DI and DO are 4. (NUUO software limitation)<br>6. Talk function is not supported if the camera does not support backchannel. (ONVIF limitation)<br>7. May not support http but software shows the http option at protocol setting. (NUUO software limitation) |                          |              |          |                |       |        |     |                |      |                      |         |
| Qihan   | QH-NV431  | v2.3.8.1                 | H.264        | 1        | 1920x1080      | -     | -      | -   | -              | -    | Yes*                 |         |
| Note:   | 1. Due to Onvif restriction, some bit rates cannot be set.<br>2. 2nd or 3rd stream cannot be connected when 1st stream under high bitrate.  |                          |              |          |                |       |        |     |                |      |                      |         |
| Stanley | 1310-F  | NSD-1.0.9.58             | H.264        | 1        | 1280x720       | -     | -      | -   | -              | -    | Yes*                 |         |
| TVT     | TD9412M   | 3.4.0Beta6               | H.264        | 1        | 1280x720       | 1-way | -      | -   | -              | -    | Yes*                 |         |
| TVT     | TD9422M   | 3.4.0Beta6               | H.264        | 1        | 1920x1080      | 1-way | -      | -   | -              | -    | Yes*                 |         |
| Tyco    | ADVEIPSD37AH  | V1.04_STD-1              | H.264        | 1        | 704x480        | 1-way | 1/1    | Yes | Yes            | -    | Yes*                 |         |
| Note:   | 1. Due to Onvif restriction, some frame rate and bit rates cannot be set.<br>2. Camera web MJPEG has no quality options.  |                          |              |          |                |       |        |     |                |      |                      |         |
| Wapa    | HH9803BL-C7HA1080I L-T18C-L16   | V6.03.05-CGBO2420 0-1210 | M-JPEG H.264 | 1        | 1920x1080      | -     | -      | -   | -              | -    | Yes*                 |         |
| Note:   | 1. Due to Onvif restriction, some bit rates cannot be set.<br>2. Framerate setting has no effect on streaming.  |                          |              |          |                |       |        |     |                |      |                      |         |

# Panasonic



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| BB-HCE481   |  | M-JPEG                   | 1        | 640x480        | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| BB-HCM100   | 1.3  | M-JPEG                   | 1        | 640x480        | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| BB-HCM110   | 1.3  | M-JPEG                   | 1        | 640x480        | 1-way | 2/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| BB-HCM311   |  | M-JPEG                   | 1        | 640x480        | 1-way | 2/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| BB-HCM331   | 1.3  | M-JPEG                   | 1        | 640x480        | 1-way | 2/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| BB-HCM371   |  | M-JPEG                   | 1        | 640x480        | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| BB-HCM381   | 1.3  | M-JPEG                   | 1        | 640x480        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| BB-HCM403   |  | M-JPEG                   | 1        | 640x480        | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| BB-HCM511   | 1.3  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 2/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| BB-HCM515   | 3.11R01  | MPEG4<br>M-JPEG          | 1        | 1280x1024      | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | No audio support in M-JPEG @ 1280x1024.                            |                          |          |                |       |        |     |                |      |                      |          |                     |
| BB-HCM527   |  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| BB-HCM531   | 3.51R00  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| BB-HCM547   | 3.60R00  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 2/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | The camera is tested by link, so some functions can't be verified. |                          |          |                |       |        |     |                |      |                      |          |                     |
| BB-HCM580   |  | MPEG4<br>M-JPEG          | 1        | 640x480        | -     | 2/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| BB-HCM581   | 1.3  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 2/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| BB-HCM701   | 4.30R00  | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  | -        |                     |
| BB-HCM705   | 4.11R01  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  | -        |                     |
| BB-HCM715   |  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | 2/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| BB-HCM735   | 1.05-03<br>(100303-02)   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | 2/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| BB-HCS301   |  | M-JPEG                   | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |

# Panasonic



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| BB-ST162    | refer to WV-ST162 (1 Application: 1.81<br>2 Image data: 1.04) | H264 MJPEG         | 1        | 800x600        | -     | 3/1    | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| BB-SW172    | refer to WV-ST162 (1 Application: 1.81<br>2 Image data: 1.04) | H264 MJPEG         | 1        | 800x600        | -     | 3/1    | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| BL-C1       |   | M-JPEG             | 1        | 640x480        | -     | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| BL-C10      |   | M-JPEG             | 1        | 640x480        | -     | -      | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| BL-C101     | 3.52R00   | MPEG4 M-JPEG       | 1        | 640x480        | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  | -        |                     |
| BL-C111     | 3.10R01   | MPEG4 M-JPEG       | 1        | 640x480        | 1-way | -      | Yes | Yes            | Yes  | Yes                  | -        |                     |
| BL-C121     | 3.52R00   | MPEG4 M-JPEG       | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| BL-C131     |   | MPEG4 M-JPEG       | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| BL-C140     | 3.51R01   | MPEG4 M-JPEG       | 1        | 640x480        | -     | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| BL-C160     | 3.51R01   | MPEG4 M-JPEG       | 1        | 640x480        | -     | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| BL-C20      |   | M-JPEG             | 1        | 640x480        | -     | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| BL-C210     | 4.31R00   | H.264 MPEG4 M-JPEG | 1        | 640x480        | 1-way | -      | Yes | Yes            | Yes  | Yes                  | -        |                     |
| BL-C230     |   | H.264 MPEG4 M-JPEG | 1        | 640x480        | 1-way | -      | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| BL-C30      |   | M-JPEG             | 1        | 640x480        | -     | -      | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| BL-VP101    | Application: 1.67   | H264 MJPEG         | 1        | 640x480        | -     | -      | -   | Yes            | -    | Yes                  | -        |                     |
| BL-VP104    | Application: 1.67   | H264 MJPEG         | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                  | -        |                     |
| BL-VP104W   | refer BL-VP104 (Application: 1.67)                            | H264 MJPEG         | 1        | 1280x720       | -     | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| BL-VT164    | Application: 1.81   | H264 MJPEG         | 1        | 1280x720       | 1-way | -      | Yes | Yes            | -    | Yes                  | -        |                     |
| BL-VT164W   | refer BL-VT164 (Application: 1.81)                            | H264 MJPEG         | 1        | 1280x720       | 1-way | -      | Yes | Yes            | -    | Yes                  | -        | Supported by design |

# Panasonic



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| KX-HCM110   |  | M-JPEG                   | 1        | 640x480        | 1-way | 2/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| KX-HCM280A  |  | M-JPEG                   | 1        | 640x480        | -     | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| DG-GXE100   | 2.02   | H.264                    | 1        | 720x480        | -     | -      | *2  | Yes            | *2   | Yes*                 | Yes      |                     |
| DG-NF282    |  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | -                    | -        | Supported by design |
| DG-NF302    | 1.5  | MPEG4<br>M-JPEG          | 1        | 1280x960       | 1-way | -      | -   | Yes            | -    | -                    | -        | Supported by design |
| DG-NP240    |  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | -                    | -        | Supported by design |
| DG-NP244    |  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| DG-NP304    | 1.5  | MPEG4<br>M-JPEG          | 1        | 1280x960       | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| DG-NS202    |  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| DG-NS202A   | 2.6  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | Yes | Yes            | -    | Yes                  | -        |                     |
| DG-NS950    | 1.5  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| DG-NS954    | 1.5  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| DG-NW960    | 1.5  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| DG-NW964    | 1.5  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| DG-SC385    | Refer to WV-SC385<br>1 Application: 1.66<br>2 Driver: 1.39<br>3 Image data: 1.09 | M-JPEG<br>MPEG4<br>H.264 | 1        | 1280x960       | *2    | *2     | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| DG-SF132    | Refer to WV-SP102(1<br>Application: 1.81<br>2 Image data: 1.03)                  | H.264<br>M-JPEG          | 1        | 640x480        | -     | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| DG-SF334    | 1.03<br>1.05   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | -      | -   | Yes            | -    | Yes                  | -        |                     |
| Note:       | Disable H.264 and MPEG4 will get MJPEG stream playing more smoothly.             |                          |          |                |       |        |     |                |      |                      |          |                     |



# Panasonic



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| DG-SP102    | Refer to WV-SP102(1 Application: 1.81 2 Image data: 1.03)   | H.264 M-JPEG       | 1        | 640x480        | -     | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| DG-SW155    | Refer to WV-SW155/M   | H.264 M-JPEG       | 1        | 1280x960       | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| K-EF134L    | V2.42   | H.264 M-JPEG       | 1        | 1280x960       | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. The bit-rate values in the combo box are not all valid, users have to choose a valid one (the range can be get from the web of the device) while setting. (NUUO Server limitation)<br>2. Video parameter setting and rotate function may result in failure by Day/Night profile. (Camera Firmware issue)<br>3. When format is MJPEG, and resource is too much, the image is not complete. (Camera performance limitation)<br>4. UPNP search fail.(Camera firmware issue)   |                    |          |                |       |        |     |                |      |                      |          |                     |
| K-EW114L    | 2.420.PS00.0.T , build: 2014-09-19  | H.264 M-JPEG       | 1        | 1280x960       | -     | -      | -   | Yes            | *2   | Yes*                 | Yes      |                     |
| Note:       | 1. The bit-rate values in the combo box are not all valid, users have to choose a valid one (the range can be get from the web of the device) while setting. (NUUO Server limitation)<br>2. Video parameter setting and rotate function may result in failure by Day/Night profile. (Camera Firmware issue)<br>3. When format is MJPEG, and resource is too much, the image is not complete. (Camera performance limitation)<br>4. The bitrate ranges of server are different from camera web while image format is MJPEG.(Camera Firmware issue) |                    |          |                |       |        |     |                |      |                      |          |                     |
| WJ-GXE500   | 1.03  | H.264 MPEG4 M-JPEG | 4        | 720x480        | 1-way | -      | -   | Yes            | -    | Yes                  | -        |                     |
| Note:       | Motion detection works abnormally when "face detection" function is enabled. Not support PTZ currently.   |                    |          |                |       |        |     |                |      |                      |          |                     |
| WJ-NT304    | 1.04  | M-JPEG             | 4        | 640x480        | -     | -      | Yes | -              | -    | Yes                  | -        |                     |
| WJ-NT314    |   | M-JPEG             | 4        | 640x480        | 1-way | -      | Yes | -              | -    | Yes                  | -        | Supported by design |
| WV-NF284    |   | MPEG4 M-JPEG       | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| WV-NF302    | 1.40E4_1.06   | MPEG4 M-JPEG       | 1        | 1280x960       | 1-way | -      | -   | Yes            | -    | Yes                  | -        |                     |
| WV-NM100    |   | MPEG4 M-JPEG       | 1        | 640x480        | -     | -      | Yes | -              | -    | Yes                  | -        | Supported by design |
| WV-NP1000   |   | M-JPEG             | 1        | 1280x960       | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| WV-NP1004   | 1.21  | M-JPEG             | 1        | 1280x960       | 1-way | -      | -   | Yes            | -    | Yes                  | -        |                     |
| WV-NP240    |   | MPEG4 M-JPEG       | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |
| WV-NP244    |   | MPEG4 M-JPEG       | 1        | 640x480        | 1-way | -      | -   | Yes            | -    | Yes                  | -        | Supported by design |

# Panasonic



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch      | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|-------------|-----|----------------|------|----------------------|----------|---------------------|
| WV-NP304    | 1.50E5_1.06   | MPEG4<br>M-JPEG          | 1        | 1280x960       | 1-way | -           | -   | Yes            | -    | Yes                  | -        |                     |
| WV-NP472    |   | M-JPEG                   | 1        | 640x480        | -     | -           | -   | Yes            | -    | Yes                  | -        | Supported by design |
| WV-NP502    | 1.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 1-way | -           | -   | Yes            | -    | Yes                  | -        |                     |
| WV-NS202    |   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -           | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| WV-NS202A   | 2.6   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -           | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| WV-NS324    |   | M-JPEG                   | 1        | 640x480        | -     | -           | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| WV-NS950    | 1.5   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -           | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| WV-NS954    | 1.06E0  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -           | Yes | Yes            | -    | Yes                  | -        |                     |
| Note:       | Audio is abnormal in MPEG4 format.  |                          |          |                |       |             |     |                |      |                      |          |                     |
| WV-SC384    | 1.46  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | 0~3/<br>0~1 | Yes | Yes            | -    | Yes                  |          | Supported by design |
| WV-SC385    | Application: 2.1<br>0 Driver: 1.54  | H.264                    | 1        | 1280x960       | 2-way | 3/1         | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Brightness value may not sync with web.(Camera Firmware issue)<br>2. Bit Rate Control (Transmission priority) only support Constant bit rate & Frame rate.(NUUO server limitation)<br>3. The flip status on camera web is opposite to server.(Camera Firmware issue) |                          |          |                |       |             |     |                |      |                      |          |                     |
| WV-SC386    | 1 Application:<br>1.44<br>2 Driver: 1.12<br>3 Image data:<br>1.05   | M-JPEG<br>MPEG4<br>H.264 | 1        | 1280x960       | 1-way | 0~3/<br>0~1 | Yes | Yes            | -    | Yes                  | -        |                     |
| WV-SF132    | Refer to WV-SP102(1<br>Application:<br>1.81<br>2 Image data:<br>1.03)   | H.264<br>M-JPEG          | 1        | 640x480        | -     | -           | -   | Yes            | -    | Yes                  | -        | Supported by design |
| WV-SF135    | Refer to WV-SW155/M   | H.264<br>M-JPEG          | 1        | 1280x960       | 1-way | -           | -   | Yes            | -    | Yes                  | -        | Supported by design |
| WV-SF332    |   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | 0~1/<br>0~1 | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| WV-SF335    |   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | 0~1/<br>0~1 | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| Note:       | WV-SF355 include WV-SF335E  |                          |          |                |       |             |     |                |      |                      |          |                     |

# Panasonic



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name       | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| <b>WV-SF336</b>   | 1.05   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | -      | Yes | Yes            | -    | Yes                  | -        |                     |
| Note:             | Motion detection works abnormally when "face detection" function is enabled.   |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>WV-SF342</b>   | Refer to WV-SF332  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | -      | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| <b>WV-SF346</b>   | Refer to WV-SF336  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | -      | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| <b>WV-SF438</b>   | 1 Application:<br>1.04<br>2 Image data:<br>1.12  | H264<br>MJPEG            | 1        | 2048x1536      | 1-way | 3/1    | -   | Yes            | -    | Yes                  | -        |                     |
| Note:             | Fisheye camera   |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>WV-SF539</b>   | 1 Application:<br>1.60<br>2 Image data:<br>2.34  | H.264                    | 1        | 1920x1080      | *2    | *2     | -   | Yes            | *2   | Yes*                 | Yes      |                     |
| Note:             | 1. Brightness value may not sync with web. (Camera Firmware issue)<br>2. We tested on camera web with the following parameters, and found camera will disconnect or image will delay. The following link lists some issues:<br><a href="https://docs.google.com/spreadsheets/d/1Ri44tFID29DKYhf-s6VQhDImfYycbLV8nuhpASViksw/edit#gid=0">https://docs.google.com/spreadsheets/d/1Ri44tFID29DKYhf-s6VQhDImfYycbLV8nuhpASViksw/edit#gid=0</a><br>3. The 2nd stream cannot be set and connect while the image mode is 3mega pixel. (Camera Firmware issue)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>WV-SFN310</b>  | 1.71   | H.264                    | 1        | 1280x960       | 1-way | 3/1    | -   | Yes            | -    | Yes*                 | Yes      |                     |
| Note:             | 1. Setting higher bitrate may be fail (Camera firmware issue)<br>2. When 60fps mode, H.264(1) bitrate cannot be set less than 1024 (Camera firmware issue)<br>3. No Audio when audio codec is AAC (NUUO server limitation)<br>4. Bitrate list range is not synchronize with web (Camera firmware issue)<br>5. MJPEG framerate is affected by h264 stream. If h264 stream(1 or 2) open, MJPEG support 5 fps the most. (Camera performance limitation)<br>6. Brightness value may not sync with web. (Camera firmware issue)<br>7. Motion event snapshot resolution sync with stream3 instead of stream1. (Camera firmware issue)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>WV-SFN310J</b> | Refer to WV-SFN310(1.71)   | H.264<br>MJPEG           | 1        | 1280x960       | 1-way | 3/1    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| <b>WV-SFN311</b>  | Refer to WV-SFN310(1.71)   | H.264<br>MJPEG           | 1        | 1280x960       | 1-way | 3/1    | -   | Yes            | -    | Yes*                 | Yes      | Supported by design |
| <b>WV-SFV481</b>  | 1.12   | H.264                    | 1        | 2992x2992      | 2-way | 3/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:             | Fisheye camera<br>1. Brightness Value may not sync with Camera Web Interface. (Camera Firmware issue)<br>2. Audio out 16Kbps was not supported. (NUUO server limitation)<br>3. Digital in and Digital out can not trigger continuously. (Camera Firmware issue)<br>4. Camera may not achieve maximum FPS. (Camera performance limitation)<br>5. The range of bitrate may not sync with camera web. (Camera Firmware issue)<br>6. The bit-rate & FPS values in the combo box are not all valid, users have to choose a valid one (the range can be get from the web of the device) while setting. (NUUO server limitation)<br>7. Snapshot resolution may not sync with display resolution. (NUUO server limitation) |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>WV-SFV611L</b> | Refer to WV-SFV631L(V1.83)   | H.264                    | 1        | 2048x1536      | *2    | *2     | -   | Yes            | *2   | Yes*                 | *2       | Supported by design |

# Panasonic



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch      | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|----------------|-------|-------------|-----|----------------|------|----------------------|----------|---------------------|
| WV-SFV631L  | 1.83   | H.264                    | 1        | 2048x1536      | *2    | *2          | -   | Yes            | *2   | Yes*                 | *2       |                     |
| Note:       | 1. The bitrate list doesn't match the camera web.(Camera Firmware issue)<br>2. Zoom & focus can't be used.(Camera Firmware issue)<br>3. Brightness value may not sync with web.(Camera Firmware issue)<br>4. Bit Rate Control (Transmission priority) only support Constant bit rate & Frame rate.(NUUO server limitation) |                          |          |                |       |             |     |                |      |                      |          |                     |
| WV-SFV631LT | Refer to WV-SFV631L(V1.83)   | H.264                    | 1        | 2048x1536      | *2    | *2          | -   | Yes            | *2   | Yes*                 | *2       | Supported by design |
| WV-SP102    | 1 Application: 1.81<br>2 Image data: 1.03  | H.264<br>M-JPEG          | 1        | 640x480        | -     | -           | -   | Yes            | -    | Yes                  | -        | Tested by link      |
| WV-SP105    | 1 Application: 1.61<br>2 Image data: 2.01  | H.264<br>M-JPEG          | 1        | 1280x960       | -     | -           | -   | Yes            | -    | Yes                  | -        |                     |
| WV-SP302    |  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | -           | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| WV-SP305    |  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | -           | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| WV-SP306    | 1.04   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | -           | Yes | Yes            | -    | Yes                  | -        |                     |
| Note:       | Motion detection works abnormally when "face detection" function is enabled.   |                          |          |                |       |             |     |                |      |                      |          |                     |
| WV-SP508    | 1Application: 1.05<br>2 Image data: 2.05   | MJPEG<br>H264            | 1        | 2048x1536      | -     | 0~1/<br>0~1 | -   | Yes            | -    | Yes                  | -        | Tested by link      |
| WV-SP509    | 1Application: 1.07<br>2 Image data: 2.11   | MJPEG<br>H264            | 1        | 2048x1536      | 1-way | 0~3/<br>0~1 | -   | Yes            | -    | Yes                  | -        |                     |
| WV-SPN311   | V1.71  | H.264                    | 1        | 1280x720       | 2-way | 3/1         | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| WV-SPN631   | Refer to WV-SFV631L(V1.83)   | H.264                    | 1        | 2048x1536      | *2    | *2          | -   | Yes            | *2   | Yes*                 | *2       | Supported by design |
| WV-SPW631L  | Refer to WV-SFV631L(V1.83)   | H.264                    | 1        | 2048x1536      | *2    | *2          | -   | Yes            | *2   | Yes*                 | *2       | Supported by design |
| WV-ST162    | 1 Application: 1.81<br>2 Image data: 1.04  | H264<br>MJPEG            | 1        | 800x600        | -     | 3/1         | Yes | Yes            | -    | Yes                  | -        | Tested by link      |
| WV-ST165    | 1Application: 1.44<br>2 Image data: 1.03   | MJPEG<br>H264            | 1        | 1280x960       | 1-way | 0~3/<br>0~1 | Yes | Yes            | -    | Yes                  | -        | Tested by link      |
| Note:       | Enable "VMD addition information" on camera web and reboot to obtain Motion Detection Info   |                          |          |                |       |             |     |                |      |                      |          |                     |
| WV-SW152    | Refer to WV-SW155  | H.264<br>M-JPEG          | 1        | 1280x960       | 1-way | -           | -   | Yes            | -    | Yes                  | -        | Supported by design |

# Panasonic



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch      | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|-------------|-----|----------------|------|----------------------|----------|---------------------|
| WV-SW155    | 2.02  | H.264                    | 1        | 1280x720       | -     | *2          | -   | Yes            | *2   | Yes*                 | Yes      |                     |
| Note:       | Brightness value may not sync with web. (Camera Firmware issue)   |                          |          |                |       |             |     |                |      |                      |          |                     |
| WV-SW155/M  | 1.03  | H.264<br>M-JPEG          | 1        | 1280x960       | 1-way | -           | -   | Yes            | -    | Yes                  | -        |                     |
| WV-SW158    | 1.07  | M-JPEG                   | 1        | 2048x1536      | 1-way | -           | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Mirror is not supported (Camera firmware issue)<br>2. It may have chance to fail to set higher bitrate (Camera firmware issue)   |                          |          |                |       |             |     |                |      |                      |          |                     |
| WV-SW172    | refer to WV-ST162(1)<br>Application: 1.81<br>2 Image data: 1.04)  | H264<br>MJPEG            | 1        | 800x600        | -     | 3/1         | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| WV-SW174W   | 1.81  | MJPEG<br>H264            | 1        | 1280x960       | 1-way | 3/1         | Yes | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | WV-SW174W Camera constraint:<br>MJPEG framerate is affected by h264 stream. If h264 stream(1 or 2) open, MJPEG support 5 fps the most.  |                          |          |                |       |             |     |                |      |                      |          |                     |
| WV-SW175    | Refer to ST165  | MJPEG<br>H264            | 1        | 1280x960       | 1-way | 0~3/<br>0~1 | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| WV-SW314    | Refer to SW316/L  | MJPEG<br>H264            | 1        | 1280x960       | -     | -           | -   | Yes            | -    | Yes                  | -        | Supported by design |
| WV-SW316/L  | 1 Application: 1.46<br>2 Image data: 1.04   | MJPEG<br>H264            | 1        | 1280x960       | 1-way | 0~1/<br>0~1 | -   | Yes            | -    | Yes                  | -        | Tested by link      |
| Note:       | WV-SW316/L is compatible with WV-SW316  |                          |          |                |       |             |     |                |      |                      |          |                     |
| WV-SW352    | Refer to WV-SW352   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | -           | -   | Yes            | -    | Yes                  | -        | Supported by design |
| WV-SW355    | 1.41  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | 0~1/<br>0~1 | -   | Yes            | -    | Yes                  | -        |                     |
| WV-SW395    | Refer to WV-SC385 (Application: 1.01,   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | 1-way | -           | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| WV-SW396    | 1.44  | M-JPEG<br>MPEG4<br>H.264 | 1        | 1280x960       | 1-way | 0~3/<br>0~1 | Yes | Yes            | -    | Yes                  | -        |                     |
| Note:       | WV-SW396 support continuous PTZ   |                          |          |                |       |             |     |                |      |                      |          |                     |
| WV-SW458    | V1.60   | H.264                    | 1        | 1920x1080      | 2-way | 3/1         | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | Fisheye camera<br>1. G726/16Kbps has noise. (NUUO server limitation)<br>2. Brightness value may not sync with web. (Camera Firmware issue)<br>3. MountType and DisplayMode UI only support English. (NUUO server limitation)<br>4. Camera is unable to achieve maximum FPS. (Camera performance limitation)<br>5. Setting higher bitrate may be fail (Camera Firmware issue)<br>6. Motion event snapshot resolution may not sync with current stream (NUUO server limitation) |                          |          |                |       |             |     |                |      |                      |          |                     |

# Panasonic



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name      | Tested Firmware   | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch      | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|------------------|---|--------------------|----------|----------------|-------|-------------|-----|----------------|------|----------------------|----------|---------------------|
| <b>WV-SW558</b>  | Refer to SP509  | MJPEG H264         | 1        | 2048x1536      | -     | 0~3/<br>0~1 | -   | Yes            | -    | Yes                  | -        | Supported by design |
| <b>WV-SW559</b>  | Refer to SP509  | MJPEG H264         | 1        | 2048x1536      | 1-way | 0~3/<br>0~1 | -   | Yes            | -    | Yes                  | -        | Supported by design |
| <b>WV-SW598</b>  | 2.07  | H.264              | 1        | 1920x1080      | *2    | *2          | Yes | Yes            | *2   | Yes*                 | Yes      |                     |
| Note:            | 1. Brightness value may not sync with web. (Camera Firmware issue)<br>2. The flip status on camera web is opposite to server. (Camera Firmware issue)<br>3. The move function can not make live view to center. (Camera Firmware issue) |                    |          |                |       |             |     |                |      |                      |          |                     |
| <b>WV-NW484</b>  | 1.10ED  | MPEG4 M-JPEG       | 1        | 640x480        | -     | -           | -   | Yes            | -    | Yes                  | -        |                     |
| <b>WV-NW502S</b> | 1.00  | H.264 MPEG4 M-JPEG | 1        | 2048x1536      | 1-way | -           | -   | Yes            | -    | Yes                  | -        |                     |
| <b>WV-NW960</b>  | 1.5   | MPEG4 M-JPEG       | 1        | 640x480        | 1-way | -           | Yes | Yes            | -    | Yes                  | -        | Supported by design |
| <b>WV-NW964</b>  |   | MPEG4 M-JPEG       | 1        | 640x480        | 1-way | -           | Yes | Yes            | -    | Yes                  | -        | Supported by design |



by Schneider Electric

- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|-------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| D5118       | Software Version : 1.6.13.9310-A1.4657<br>Hardware Version : 9310-A1.1-10345   | H264 JPEG    | 1        | 1280x960       | -     | -      | Yes | -              | -    | Yes                  |         |
| Note:       | Do not support to "clear all" preset points.   |              |          |                |       |        |     |                |      |                      |         |
| D5220       | 1.8.3.8-20121119.9320-A1.8614  | H264 JPEG    | 1        | 1920x1080      | *1    | *1     | Yes | *1             | -    | Yes                  |         |
| Note:       | 1. D5220 preset point name can't be changed, and would not sync with camera's web.<br>2. fps would not reach its setting when resolution or quality is high.<br>3. Need turn off second profile on web then parameter setting can be changed normally.<br>4. D5220 would cause Mainconsole unstable when changing protocol. (UDP->HTTP, HTTP->UDP) |              |          |                |       |        |     |                |      |                      |         |
| IBPS110-ER  | 3N19-A1.1-40123  | H.264 MJPEG  | 1        | 800x600        | *2    | *2     | Yes | *2             | -    | Yes*                 |         |
| Note:       | 1. Talk can't be used. (Camera Firmware issue)<br>2. Due to onvif restriction, some bitrate and quality cannot be set. (Camera Firmware issue)   |              |          |                |       |        |     |                |      |                      |         |
| IL10        | 1.8.2.4.8310-O3.9119   | H264 JPEG    | 1        | 1280x720       | -     | -      | -   | *1             | -    | Yes                  |         |
| Note:       | 1. fps would not reach its setting when resolution or quality is high.   |              |          |                |       |        |     |                |      |                      |         |
| IM10        | 1.8.2.18-20121109-1.8272-O1.8503   | H264 JPEG    | 1        | 1280x960       | *1    | -      | Yes | *1             | -    | Yes                  |         |
| Note:       | 1. fps would not reach its setting when resolution or quality is high.<br>2. IM10 need turn off second profile on web then parameter setting can be changed normally.  |              |          |                |       |        |     |                |      |                      |         |
| IMPS110-1   | 03.29.37   | H.264 MJPEG  | 1        | 800x600        | 2-way | 1/1    | Yes | *2             | *2   | Yse*                 |         |
| Note:       | 1. Due to onvif restriction, some bitrate and quality cannot be set. (Camera Firmware issue)<br>2. Talk can't be used. (Camera Ffirmware issue)  |              |          |                |       |        |     |                |      |                      |         |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks           |
|-------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|-------------------|
| PBY-Hi82    | VH1.0.0.3_Y  | H.264 MJPEG  | 1        | 2688x1520      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| Note:       | 1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)<br>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)<br>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)<br>4. Audio has noise. (Camera Firmware issue) |              |          |                |       |        |     |                |      |                      |          |                   |
| PBY-H7982   | VH1.0.0.3_Y  | H.264 MJPEG  | 1        | 2688x1520      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| Note:       | 1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)<br>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)<br>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)<br>4. Audio has noise. (Camera Firmware issue) |              |          |                |       |        |     |                |      |                      |          |                   |
| PBY-H7A82   | VH1.0.0.3_Y  | H.264 MJPEG  | 1        | 2688x1520      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| Note:       | 1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)<br>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)<br>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)<br>4. Audio has noise. (Camera Firmware issue) |              |          |                |       |        |     |                |      |                      |          |                   |
| PBY-H7B82   | VH1.0.0.3_Y  | H.264 MJPEG  | 1        | 2688x1520      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| Note:       | 1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)<br>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)<br>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)<br>4. Audio has noise. (Camera Firmware issue) |              |          |                |       |        |     |                |      |                      |          |                   |
| PBY-H7B82M  | VH1.0.0.3_Y  | H.264 MJPEG  | 1        | 2688x1520      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| Note:       | 1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)<br>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)<br>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)<br>4. Audio has noise. (Camera Firmware issue) |              |          |                |       |        |     |                |      |                      |          |                   |
| PBY-H79882  | VH1.0.0.3_Y  | H.264 MJPEG  | 1        | 2688x1520      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| Note:       | 1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)<br>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)<br>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)<br>4. Audio has noise. (Camera Firmware issue) |              |          |                |       |        |     |                |      |                      |          |                   |



|                   |   |             |   |           |       |     |   |     |     |      |     |                   |
|-------------------|---|-------------|---|-----------|-------|-----|---|-----|-----|------|-----|-------------------|
| <b>PBY-H7B882</b> | VH1.0.0.3_Y   | H.264 MJPEG | 1 | 2688x1520 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | <p>1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)</p> <p>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)</p> <p>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)</p> <p>4. Audio has noise. (Camera Firmware issue)</p> |             |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-HL882</b>  | VH1.0.0.3_Y   | H.264 MJPEG | 1 | 2688x1520 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | <p>1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)</p> <p>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)</p> <p>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)</p> <p>4. Audio has noise. (Camera Firmware issue)</p> |             |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-H7982M</b> | VH1.0.0.3_Y   | H.264 MJPEG | 1 | 2688x1520 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | <p>1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)</p> <p>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)</p> <p>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)</p> <p>4. Audio has noise. (Camera Firmware issue)</p> |             |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-HB26A</b>  | VE1.0.20.10_Y   | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | <p>1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)</p> <p>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)</p> <p>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)</p> <p>4. Audio has noise. (Camera Firmware issue)</p> |             |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-HH26A</b>  | VE1.0.20.10_Y   | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | <p>1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)</p> <p>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)</p> <p>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)</p> <p>4. Audio has noise. (Camera Firmware issue)</p> |             |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-H7A26A</b> | VE1.0.20.10_Y   | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | <p>1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)</p> <p>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)</p> <p>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)</p> <p>4. Audio has noise. (Camera Firmware issue)</p> |             |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-Hi82M</b>  | VH1.0.0.3_Y   | H.264 MJPEG | 1 | 2688x1520 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | <p>1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)</p> <p>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)</p> <p>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)</p> <p>4. Audio has noise. (Camera Firmware issue)</p> |             |   |           |       |     |   |     |     |      |     |                   |



|                    |   |             |   |           |       |     |   |     |     |      |     |                   |
|--------------------|---|-------------|---|-----------|-------|-----|---|-----|-----|------|-----|-------------------|
| <b>PBY-HP82</b>    | VH1.0.0.3_Y   | H.264 MJPEG | 1 | 2688x1520 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:              | <p>1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)</p> <p>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)</p> <p>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)</p> <p>4. Audio has noise. (Camera Firmware issue)</p> |             |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-HQ26A</b>   | VE1.0.20.10_Y   | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:              | <p>1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)</p> <p>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)</p> <p>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)</p> <p>4. Audio has noise. (Camera Firmware issue)</p> |             |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-HQ855</b>   | VE1.0.20.10_Y   | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:              | <p>1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)</p> <p>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)</p> <p>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)</p> <p>4. Audio has noise. (Camera Firmware issue)</p> |             |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-HS26A</b>   | VE1.0.20.10_Y   | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:              | <p>1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)</p> <p>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)</p> <p>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)</p> <p>4. Audio has noise. (Camera Firmware issue)</p> |             |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-HS855</b>   | VE1.0.20.10_Y   | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:              | <p>1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)</p> <p>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)</p> <p>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)</p> <p>4. Audio has noise. (Camera Firmware issue)</p> |             |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-HV26A</b>   | VE1.0.20.10_Y   | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:              | <p>1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)</p> <p>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)</p> <p>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)</p> <p>4. Audio has noise. (Camera Firmware issue)</p> |             |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-H626A</b>   | VE1.0.20.10_Y   | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:              | <p>1. Stream2 cannot achieve mimum FPS with connecting two streams simultaneously. (Camera performance limitation)</p> <p>2. Audio codec only can choose G711. (Camera Firmware issue)</p> <p>3. Upnp will find wrong model. (Camera Firmware issue)</p>  |             |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-H7926AM</b> | VE1.0.20.10_Y   | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:              | <p>1. Stream2 cannot achieve mimum FPS with connecting two streams simultaneously. (Camera performance limitation)</p> <p>2. Audio codec only can choose G711. (Camera Firmware issue)</p> <p>3. Upnp will find wrong model. (Camera Firmware issue)</p>  |             |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-H7A855</b>  | VE1.0.20.10_Y   | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:              | <p>1. Stream2 cannot achieve mimum FPS with connecting two streams simultaneously. (Camera performance limitation)</p> <p>2. Audio codec only can choose G711. (Camera Firmware issue)</p> <p>3. Upnp will find wrong model. (Camera Firmware issue)</p>  |             |   |           |       |     |   |     |     |      |     |                   |

|                   |  |                |   |           |       |     |   |     |     |      |     |                   |
|-------------------|--|----------------|---|-----------|-------|-----|---|-----|-----|------|-----|-------------------|
| <b>PBY-HB855</b>  | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-HC26A</b>  | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-HC855</b>  | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-HD26A</b>  | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-HD855</b>  | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-HH855</b>  | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-Hi26A</b>  | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-Hi26AM</b> | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-HK26A</b>  | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                   |
| <b>PBY-HK855</b>  | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| Note:             | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                   |

|                        |  |                |   |           |       |     |   |     |     |      |     |                      |
|------------------------|--|----------------|---|-----------|-------|-----|---|-----|-----|------|-----|----------------------|
| <b>PBY-<br/>HL26A</b>  | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by<br>design |
| Note:                  | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                      |
| <b>PBY-<br/>HL26AM</b> | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by<br>design |
| Note:                  | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                      |
| <b>PBY-<br/>HMi855</b> | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by<br>design |
| Note:                  | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                      |
| <b>PBY-<br/>HNI855</b> | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by<br>design |
| Note:                  | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                      |
| <b>PBY-<br/>HQ26A</b>  | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by<br>design |
| Note:                  | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                      |
| <b>PBY-<br/>HQ855</b>  | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by<br>design |
| Note:                  | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                      |
| <b>PBY-<br/>HS26A</b>  | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by<br>design |
| Note:                  | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                      |
| <b>PBY-<br/>HS855</b>  | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by<br>design |
| Note:                  | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                      |
| <b>PBY-<br/>HV26A</b>  | VE1.0.20.10_Y  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by<br>design |
| Note:                  | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)<br>3. Upnp will find wrong model. (Camera Firmware issue) |                |   |           |       |     |   |     |     |      |     |                      |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name   | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks           |
|---------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|-------------------|
| DAI-310IPEH04 | 3.4.2  | H.264        | 1        | 2048x1536      | -     | -      | -   | *2             | *2   | Yes*                 | Yes      |                   |
| Note:         | 1. Auto detect fail. (Camera Firmware issue)<br>2. Can not change CBR/VBR. (Camera Firmware issue)<br>3. Bitrate & firmware list can not sync with web. (Camera Firmware issue)<br>4. Quality name can not sync with web. (Camera Firmware issue)<br>5. Auto detect & upnp search can not be used. (Camera Firmware issue) |              |          |                |       |        |     |                |      |                      |          |                   |
| DAI-310IPEHVF | Refer to DAI-310IPEH04(3.4.2)  | H.264        | 1        | 2048x1536      | -     | -      | -   | *2             | *2   | Yes*                 | Yes      | Support by design |
| D1-310IPEHVF  | Refer to DAI-310IPEH04(3.4.2)  | H.264        | 1        | 2048x1536      | -     | -      | -   | *2             | *2   | Yes*                 | Yes      | Support by design |
| I3-310IPEH04  | Refer to DAI-310IPEH04(3.4.2)  | H.264        | 1        | 2048x1536      | -     | -      | -   | *2             | *2   | Yes*                 | Yes      | Support by design |
| I4-310IPEHVF  | Refer to DAI-310IPEH04(3.4.2)  | H.264        | 1        | 2048x1536      | -     | -      | -   | *2             | *2   | Yes*                 | Yes      | Support by design |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format   | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks |
|-------------|---|----------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------|
| Generic     | v1.8.0601.10<br>01.110.0.36.<br>1.0   | H.264<br>MJPEG | 1        | 2592x1944      | 2-way | 1/1    | Yes | Yes            | -    | Yes*                 | Yes      |         |
| Note:       | Support generic dewarp<br>1. Audio in with Raw PCM codec are not supported.(Camera firmware issue)<br>2. Home function are not supported. (Camera firmware issue)<br>3. The streaming has broken under MJPEG format.(Camera firmware issue)<br>4. Due to Onvif restriction, some frame rate and bit rates cannot be set.(Camera performance limitation) |                |          |                |       |        |     |                |      |                      |          |         |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution                | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|-------------------------------|-------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| SNB-1000    | v1.07_110407   | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480                       | 1-way | 1/1    | -   | Yes            | -                  | Yes                  | -        |                     |
| Note:       | This is POE camera, but the device is unstable without AC power connection. We suggest connecting with AC power.   |                          |          |                               |       |        |     |                |                    |                      |          |                     |
| Note:       | I/O and MD is unstable, which is a known issue reported by Samsung. They won't do any change since the camera is discontinued.   |                          |          |                               |       |        |     |                |                    |                      |          |                     |
| SNB-1001    | 1.00_111226  | H.264<br>M-JPEG          | 1        | 640x480                       | 1-way | 1/0    | -   | Yes            | -                  | Yes                  | -        | Test by link        |
| SNB-2000    |  | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576                       | -     | 2/2    | -   | -              | -                  | -                    | -        | Supported by design |
| SNB-3000    |  | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576                       | 1-way | 2/2    | -   | -              | -                  | -                    | -        | Supported by design |
| SNB-3002    | refer to SND-3082/F (FW 2.10_130416)   | H.264<br>MPEG4<br>M-JPEG | 1        | PAL: 704x576<br>NTSC: 704x480 | 1-way | 1/1    | -   | Yes            | Yes                | Yes                  | -        | Supported by design |
| SNB-5000    | v1.33_110218   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024                     | 1-way | 1/1    | -   | Yes            | -                  | Yes                  | -        |                     |
| SNB-5000A   | refer to SND5080/F (FW 3.10_130416)  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024                     | 1-way | 1/1    | -   | Yes            | Yes                | -                    | -        | Supported by design |
| SNB-5001    | 1.00_120521  | H.264<br>M-JPEG          | 1        | 1280x1024                     | -     | 1/0    | -   | Yes            | -                  | Yes                  | -        |                     |
| SNB-5003    | 1.12_131031  | H.264<br>M-JPEG          | 1        | 1280x1024                     | *2    | *2     | *2  | Yes            | -                  | Yes                  | -        | Test by link        |
| SNB-5004    | 1.12_131031  | H.264<br>M-JPEG          | 1        | 1280x1024                     | 1-way | 1/1    | Yes | Yes            | -                  | Yes                  | -        |                     |
| Note:       | For SNB-5003, SNB-5004, SND-5083, SND-5084 and SNV-5084:<br>1. Camera can support 128 preset points, but we are only support 64 preset points.<br>2. Before starting "talk", we do check that the talk's gain is greater than zero. If it is 0, we are going to adjust gain to default value 5.<br>3. If user do change audio setting in the website, then the previous connection will be interrupted and re-connect. |                          |          |                               |       |        |     |                |                    |                      |          |                     |
| SNB-6003    | refer to SND-6083(FW 1.00_130412)  | H264<br>MJPEG            | 1        | 1920x1080                     | 1-way | 1/1    | -   | Yes            | Yes                | Yes                  | -        | Supported by design |
| SNB-6004    | Refer to SND-6084(SNV-6084R-V3.01_140804)  | H264<br>MJPEG            | 1        | 1920x1080                     | *2    | *2     | Yes | Yes            | -                  | Yes*                 | Yes      | Supported by design |
| SNB-7000    | Refer to SND-7080  | H.264<br>M-JPEG          | 1        | 2048x1536                     | 1-way | 1/1    | -   | Yes            | -                  | Yes                  | -        | Supported by design |
| SNB-7001    | Refer to SND-7011 (FW 1.00_120601)   | H.264<br>M-JPEG          | 1        | 2048x1536                     | -     | 1/0    | -   | Yes            | -                  | Yes                  | -        | Supported by design |





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name       | Tested Firmware  | Video Format             | Video Ch | Max Resolution                | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------------|--|--------------------------|----------|-------------------------------|-------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| <b>SNB-7002</b>   | 1.06_130402  | H.264<br>M-JPEG          | 1        | 2048x1536                     | 1-way | 1/1    | -   | Yes            | Yes                | Yes                  | -        |                     |
| Note:             | Sometimes can't get correct UI setting because camera response time too long.  |                          |          |                               |       |        |     |                |                    |                      |          |                     |
| <b>SNC-B2315</b>  | 2.01   | MPEG4<br>M-JPEG          | 1        | 720x576                       | 1-way | 2/2    | -   | Yes            | -                  | -                    | -        |                     |
| <b>SNC-B2331</b>  | v1.00_090810   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576                       | -     | 2/2    | -   | Yes            | -                  | -                    | -        |                     |
| <b>SNC-B2335</b>  | v1.10_100129   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576                       | 1-way | 2/2    | -   | Yes            | -                  | -                    | -        |                     |
| <b>SNC-B5368</b>  | v1.00_091001   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576                       | -     | 2/2    | -   | Yes            | -                  | -                    | -        |                     |
| <b>SNC-B5395</b>  | 2.10   | MPEG4<br>M-JPEG          | 1        | 720x576                       | 1-way | 2/2    | -   | Yes            | -                  | -                    | -        |                     |
| <b>SNC-B5399</b>  | v1.10_091120   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576                       | 1-way | 2/2    | -   | Yes            | -                  | -                    | -        |                     |
| <b>SNC-C6225</b>  | 1.01   | MPEG4<br>M-JPEG          | 1        | 720x576                       | 1-way | 2/1    | Yes | Yes            | -                  | -                    | -        |                     |
| <b>SNC-C7225</b>  | 1.01   | MPEG4<br>M-JPEG          | 1        | 720x576                       | 1-way | 2/1    | Yes | Yes            | -                  | -                    | -        | Supported by design |
| <b>SNC-C7478</b>  | v1.01_090625   | MPEG4<br>M-JPEG          | 1        | 720x576                       | 1-way | 8/4    | Yes | Yes            | -                  | -                    | -        |                     |
| <b>SNC-M300</b>   | v2.11_090729   | MPEG4<br>M-JPEG          | 1        | 2048x1536                     | 1-way | 2/2    | -   | Yes            | -                  | -                    | -        |                     |
| <b>SND-1010</b>   | v1.07_110407   | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480                       | -     | 1/1    | -   | Yes            | -                  | Yes                  | -        |                     |
| Note:             | This is POE camera, but the device is unstable without AC power connection. We suggest connecting with AC power.               |                          |          |                               |       |        |     |                |                    |                      |          |                     |
| Note:             | I/O and MD is unstable, which is a known issue reported by Samsung. They won't do any change since the camera is discontinued. |                          |          |                               |       |        |     |                |                    |                      |          |                     |
| <b>SND-1011</b>   | 1.00_111226  | H.264<br>M-JPEG          | 1        | 640x480                       | -     | 1/0    | -   | Yes            | -                  | Yes                  | -        | Test by link        |
| <b>SND-1080</b>   | 1.00_111226  | H.264<br>M-JPEG          | 1        | 640x480                       | 1-way | 1/0    | -   | Yes            | -                  | Yes                  | -        | Test by link        |
| <b>SND-3080</b>   |  | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576                       | -     | 2/2    | -   | -              | -                  | -                    | -        | Supported by design |
| <b>SND-3082</b>   | Refer to SND-3082/F(2.10_130416)   | H.264<br>MPEG4<br>M-JPEG | 1        | 704x576(PAL)<br>704x480(NTSC) | 1-way | 1/1    | -   | Yes            | Yes                | Yes                  | -        | Supported by design |
| <b>SND-3082/F</b> | 2.10_130416  | H.264<br>MPEG4<br>M-JPEG | 1        | 704x576(PAL)<br>704x480(NTSC) | 1-way | 1/1    | -   | Yes            | Yes                | Yes                  | -        |                     |
| <b>SND-5010</b>   | 1.00_120626  | H.264<br>M-JPEG          | 1        | 1280*1024                     | -     | 0/0    | -   | Yes            | -                  | Yes                  | -        |                     |
| <b>SND-5011</b>   | 1.00_120521  | H.264<br>M-JPEG          | 1        | 1280x1024                     | -     | 1/0    | -   | Yes            | -                  | Yes                  | -        |                     |
| <b>SND-5061</b>   | 1.00_120521  | H.264<br>M-JPEG          | 1        | 1280x1024                     | -     | 1/0    | -   | Yes            | -                  | Yes                  | -        |                     |
| <b>SND-5080</b>   | 3.10_130416  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024                     | 1-way | 1/1    | -   | Yes            | Yes                | Yes                  | -        |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio     | I/O Ch  | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------|----------|----------------|-----------|---------|-----|----------------|--------------------|----------------------|----------|---------------------|
| SND-5083    | 1.12_131031 refer to SNB-5003  | H.264 M-JPEG | 1        | 1280x1024      | 1-way     | 1/1     | Yes | Yes            | -                  | Yes                  | -        | Supported by design |
| SND-5084    | 1.12_131031 refer to SNB-5004  | H.264 M-JPEG | 1        | 1280x1024      | 1-way     | 1/1     | Yes | Yes            | -                  | Yes                  | -        | Supported by design |
| SND-6011R   | 1.11_131011  | H.264 M-JPEG | 1        | 1920x1080      | -         | *2      | -   | Yes            | -                  | Yes*                 | -        |                     |
| SND-6083    | 1.00_130412  | H264 MJPEG   | 1        | 1920x1080      | 1-way     | 1/1     | -   | Yes            | Yes                | Yes                  | -        |                     |
| SND-6084    | SNV-6084R-V3.01_140804   | H264 MJPEG   | 1        | 1920x1080      | *2        | *2      | Yes | *2             | *2                 | Yes*                 | Yes      |                     |
| Note:       | 1. The camera with higher quality and resolution is unable to achieve 30 fps (Camera performance issue)  |              |          |                |           |         |     |                |                    |                      |          |                     |
| SND-6084R   | 1.00_130316 refer to SNB-6004  | H264 MJPEG   | 1        | 1920x1080      | *2        | *2      | Yes | *2             | -                  | Yes                  | -        | Supported by design |
| SND-7011    | 1.00_120601  | H.264 M-JPEG | 1        | 2048x1536      | -         | 1/0     | -   | Yes            | -                  | Yes                  | -        |                     |
| Note:       | Sometimes can't get correct UI setting because camera response time too long.  |              |          |                |           |         |     |                |                    |                      |          |                     |
| SND-7061    | Refer to SND-7011 (FW1.00_120601)  | H.264 M-JPEG | 1        | 2048x1536      | -         | 1/1     | -   | Yes            | -                  | Yes                  | -        | Supported by design |
| SND-7080    | v1.10_110819   | H.264 M-JPEG | 1        | 2048x1536      | 1-way     | 1/1     | -   | Yes            | -                  | Yes                  | -        |                     |
| SND-7082    | 1.00_120824  | H.264 M-JPEG | 1        | 2048x1536      | 1-way     | 1/1     | -   | Yes            | Yes                | Yes                  | -        |                     |
| SND-7082/F  | refer to SNB-7002 (1.06_130402)  | H.264 M-JPEG | 1        | 2048x1536      | 1-way     | 1/1     | -   | Yes            | -                  | Yes                  | -        |                     |
| Note:       | Sometimes can't get correct UI setting because camera response time too long.  |              |          |                |           |         |     |                |                    |                      |          |                     |
| SND-7084    | Refer to SND-7084R(0.51_140116)  | H.264        | 1        | 2048x1536      | 2-way     | 1/1     | -   | Yes            | -                  | Yes*                 | Yes      | Supported by design |
| SND-7084R   | 0.51_140116  | H.264        | 1        | 2048x1536      | 2-way     | 1/1     | -   | Yes            | -                  | Yes*                 | Yes      |                     |
| Note:       | 1.Snapshot's resolution will follow MJPEG stream. (Camera Firmware issue)  |              |          |                |           |         |     |                |                    |                      |          |                     |
| SND-L6013R  | Refer to SNO-L6083R (1.00_150403)  | H.264 M-JPEG | 1        | 1920x1080      | *2(1-way) | -       | -   | *2(Yes)        | -                  | Yes*                 | *2(Yes)  | Supported by design |
| SNF-7010    | 1.00_130806  | H264 MJPEG   | 1        | 2048x1536      | 2-way     | -       | -   | Yes            | -                  | Yes                  | -        |                     |
| Note:       |  |              |          |                |           |         |     |                |                    |                      |          |                     |
| SNF-8010    | 1.00_140719  | H.264 M-JPEG | 1        | 2560x2048      | *2(2-way) | *2(1/1) | -   | *2(Yes)        | -                  | Yes*                 | *2(Yes)  |                     |
| Note:       | 1. The list of camera's stream 2 and stream 3 frame rate is not synchronized with the one on camera's web.(Camera Firmware issue)<br>2.To get OSD correct value need to reconnect by manual to connect the correct stream after parameters setting.(Camera Firmware issue) |              |          |                |           |         |     |                |                    |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name   | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio     | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|---------------|--|--------------------------|----------|----------------|-----------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| SNO-1080R     | 1.00_120125  | H.264<br>M-JPEG          | 1        | 640x480        | -         | 1/0    | -   | Yes            | -                  | Yes                  | -        | Test by link        |
| SNO-5080R     | 3.10_130416  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way     | 1/1    | -   | Yes            | -                  | Yes                  | -        |                     |
| SNO-6011R     | refer to SND-6011R(1.11_131011)  | H.264<br>M-JPEG          | 1        | 1920x1080      | -         | *2     | -   | Yes            | *2                 | Yes*                 | -        | Supported by design |
| SNO-6084      | refer to SND-6083(1.00_130412)   | H264<br>MJPEG            | 1        | 1920x1080      | 1-way     | 1/1    | -   | Yes            | Yes                | Yes                  | -        | Supported by design |
| SNO-6084R     | 1.00_130316<br>refer to SNB-6004   | H264<br>MJPEG            | 1        | 1920x1080      | *2        | *2     | Yes | *2             | -                  | Yes                  | -        | Supported by design |
| SNO-7080R     | 2.00_121004  | H.264<br>MJPEG           | 1        | 2048x1536      | *2        | *2     | Yes | Yes            | -                  | Yes*                 | -        |                     |
| SNO-7082R     | refer to SNB-7002 (1.06_130402)  | H.264<br>M-JPEG          | 1        | 2048x1536      | 1-way     | 1/1    | -   | Yes            | Yes                | Yes                  | -        | Supported by design |
| SNO-7084R     | 3.00_140915  | H.264                    | 1        | 2048x1536      | *2        | 1/1    | Yes | *2             | -                  | Yes*                 | Yes      |                     |
| Note:         | <p>1. There is dual streaming rule problem in NAS's AUTO mode. (NUUO server limitation)<br/>           Ex: stream 2 only supports MJPEG codec and stream 3 supports H.264 and MJPEG codec, but the program's logic is 3 stealing 2 in this situation.</p> <p>2. The actual FPS is not enough to the setting value. (Camera firmware issue)</p> <p>3. We can not connect by TCP or UDP. (Camera firmware issue)</p> <p>4. After the stream 2 and 3 are set the resolution to 320x180, the actual resolution is 320x176. (Camera firmware issue)</p> <p>5. This camera only support Zoom, Focus, AutoFocus with PTZ.</p> |                          |          |                |           |        |     |                |                    |                      |          |                     |
| SNO-L6013R    | Refer to SNO-L6083R (1.00_150403)  | H.264<br>M-JPEG          | 1        | 1920x1080      | *2(1-way) | -      | -   | *2(Yes)        | -                  | Yes*                 | *2(Yes)  | Supported by design |
| SNO-L6083R    | 1.00_150403  | H.264<br>M-JPEG          | 1        | 1920x1080      | *2(1-way) | -      | -   | *2(Yes)        | -                  | Yes*                 | *2(Yes)  |                     |
| Note:         | <p>1. Frame rate list does not sync with web. (Camera Firmware issue)</p> <p>2.NVRsolo integrated camera second stream as our first stream</p>   |                          |          |                |           |        |     |                |                    |                      |          |                     |
| SNP-3120/V    | v1.24_110816   | H.264<br>MPEG4<br>M-JPEG | 1        | 704x480        | 1-way     | 2/2    | Yes | Yes            | -                  | Yes                  | -        |                     |
| Note:         | It takes a while to stop after users click stop patrol button.   |                          |          |                |           |        |     |                |                    |                      |          |                     |
| SNP-3301      | v1.21_110310   | H.264<br>MPEG4<br>M-JPEG | 1        | 704x480        | 1-way     | 4/2    | Yes | Yes            | -                  | Yes                  | -        |                     |
| SNP-3302/H    | Refer to SNP-3371/H/TH   | H.264<br>MPEG4<br>M-JPEG | 1        | 704x480        | 1-way     | 4/2    | Yes | Yes            | -                  | Yes                  | -        | Supported by design |
| SNP-3370      | v1.21_110310   | H.264<br>MPEG4<br>M-JPEG | 1        | 704x480        | 1-way     | 4/2    | Yes | Yes            | -                  | Yes                  | -        |                     |
| Note:         | SNP-3301/SNP-3370: not support QCIF resolution with H.264 through TCP.   |                          |          |                |           |        |     |                |                    |                      |          |                     |
| SNP-3371/H/TH | S/W :<br>1.01_111104<br>ISP : 1.28   | H.264<br>MPEG4<br>M-JPEG | 1        | 704x480        | 1-way     | 4/2    | Yes | Yes            | -                  | Yes                  | -        | Test by link        |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name       | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| <b>SNP-3430H</b>  | v1.10_110818  | H.264<br>MPEG4<br>M-JPEG | 1        | 704x480        | 1-way | 8/4    | Yes | Yes            | -                  | Yes                  | -        |                     |
| Note:             | This is POE camera, but the device is unstable without AC power connection. We suggest connecting with AC power.  |                          |          |                |       |        |     |                |                    |                      |          |                     |
| Note:             | There is a camera FW issue that we cannot get VBR/CBR info to show quality or bit rate correctly. Please upgrade to FW 1.11_111103 to fix it.   |                          |          |                |       |        |     |                |                    |                      |          |                     |
| Note:             | Voice cracks in the video exported with ASF format, while the audio of video file is correctly recorded actually. Please choose to export with AVI format.  |                          |          |                |       |        |     |                |                    |                      |          |                     |
| Note:             | Not support Area Zoom due to protocol limitation.   |                          |          |                |       |        |     |                |                    |                      |          |                     |
| Note:             | The speed selections of PTZ and focus in LiveView is not synchronized with camera web due to protocol limitation.   |                          |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNP-5200H</b>  | v1.02_110603  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 4/2    | -   | Yes            | -                  | Yes                  | -        |                     |
| Note:             | 1. SNP-5200 is compatible with SNP-5200H<br>2. Voice cracks in the video exported with ASF format, while the audio of video file is correctly recorded actually. Please choose to export with AVI format.<br>3. Not support Area Zoom due to protocol limitation.<br>4. The speed selections of PTZ and focus in LiveView is not synchronized with camera web due to protocol limitation. |                          |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNP-5300</b>   | 1.10_130523   | H.264<br>M-JPEG          | 1        | 1280x1024      | *2    | *2     | Yes | Yes            | Yes                | Yes                  | -        |                     |
| <b>SNP-6200</b>   | V1.00_120302  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | -                  | Yes                  | -        |                     |
| <b>SNP-6200H</b>  | refer to SNP-6200(FW V1.00_120302)  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | -                  | Yes                  | -        | Supported by design |
| <b>SNP-6200HP</b> | refer to SNP-6200(FW V1.00_120302)  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | -                  | Yes                  | -        | Supported by design |
| <b>SNP-6200P</b>  | refer to SNP-6200(FW V1.00_120302)  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | -                  | Yes                  | -        | Supported by design |
| <b>SNP-6200RH</b> | 3.02_140722   | H.264<br>M-JPEG          | 1        | 1920x1080      | 2-way | 4/2    | Yes | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:             | Camera is unable to achieve maximum FPS with high quality / bitrate. (Camera performance limitation)  |                          |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNP-6320H</b>  | 1.01_141007   | H.264<br>MJPEG           | 1        | 1920x1080      | 2-way | 4/2    | Yes | Yes            | *2                 | Yes*                 | Yes      |                     |
| <b>SNV-1080</b>   | Refer to SNO-1080R(FW 1.00_120125)  | H.264<br>M-JPEG          | 1        | 640x480        | 1-way | 1/0    | -   | Yes            | -                  | Yes                  | -        | Test by link        |
| <b>SNV-1080R</b>  | Refer to SNO-1080R(FW 1.00_120125)  | H.264<br>M-JPEG          | 1        | 640x480        | 1-way | 1/0    | -   | Yes            | -                  | Yes                  | -        | Test by link        |
| <b>SNV-3080</b>   |   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576        | 1-way | 2/2    | -   | -              | -                  | Yes                  | -        | Supported by design |
| Note:             | Please uncheck the "RTSP time out" first.   |                          |          |                |       |        |     |                |                    |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution                | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|-------------------------------|-------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| SNV-3082    | refer to SND-3082 (FW 2.10_130416)  | H.264<br>MPEG4<br>M-JPEG | 1        | 704x576(PAL)<br>704x480(NTSC) | 1-way | 1/1    | -   | Yes            | Yes                | Yes                  | -        |                     |
| SNV-3120    | v1.24_110816  | H.264<br>MPEG4<br>M-JPEG | 1        | 704x480                       | 1-way | 1/1    | Yes | -              | -                  | Yes                  | -        |                     |
| Note:       | PTZ: support zoom and focus.  |                          |          |                               |       |        |     |                |                    |                      |          |                     |
| SNV-5010    | v2.00_110727  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024                     | 1-way | -      | -   | Yes            | -                  | Yes                  | -        |                     |
| Note:       | The frame rate of main stream decrease to the half if watching dual stream video. Camera vendor fix this issue in FW 2.10_111227.                                   |                          |          |                               |       |        |     |                |                    |                      |          |                     |
| SNV-5080    | refer to SND-5080(FW3.10_130416)  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024                     | 1-way | 1/1    | -   | Yes            | Yes                | Yes                  | -        | Supported by design |
| SNV-5080R   | 3.10_130416   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024                     | 1-way | 1/1    | -   | Yes            | Yes                | Yes                  | -        |                     |
| Note:       | It's likely failed to query camera parameter in high resolution configuration. It happens on SNO-5080R most. When encountering this issue, please go to camera web. |                          |          |                               |       |        |     |                |                    |                      |          |                     |
| SNV-5084    | 1.12_131031 refer to SNB-5004   | H.264<br>M-JPEG          | 1        | 1280x1024                     | 1-way | 1/1    | Yes | Yes            | -                  | Yes                  | -        | Supported by design |
| SNV-6012M   | 1.00_130704   | H264<br>MJPEG            | 1        | 1920x1080                     | -     | *2     | -   | *2             | -                  | Yes                  | -        |                     |
| SNV-6084    | refere to SND-6083 (FW 1.00_130412)   | H264<br>MJPEG            | 1        | 1920x1080                     | 1-way | 1/1    | -   | Yes            | Yes                | Yes                  | -        | Supported by design |
| SNV-6084R   | 1.00_130316 refer to SNB-6004   | H264<br>MJPEG            | 1        | 1920x1080                     | *2    | *2     | Yes | *2             | -                  | Yes                  | -        | Supported by design |
| SNV-7080    | Refer to SND-7080(FWv1.10_110819)   | H.264<br>M-JPEG          | 1        | 2048x1536                     | 1-way | 1/1    | -   | Yes            | -                  | Yes                  | -        | Supported by design |
| SNV-7080R   | 2.00_121004   | H.264<br>MJPEG           | 1        | 2048x1536                     | *2    | *2     | Yes | Yes            | -                  | Yes*                 | -        |                     |
| SNV-7082    | refer to SNB-7002(1.06_130402)  | H.264<br>M-JPEG          | 1        | 2048x1536                     | 1-way | 1/1    | -   | Yes            | Yes                | Yes                  | -        | Supported by design |
| Note:       | Sometimes can't get correct UI setting because camera response time too long.   |                          |          |                               |       |        |     |                |                    |                      |          |                     |
| SNV-7084    | Refer to SND-7084R(0.51_140116)   | H.264                    | 1        | 2048x1536                     | 2-way | 1/1    | -   | Yes            | -                  | Yes*                 | Yes      | Supported by design |
| SNV-7084R   | Refer to SND-7084R(0.51_140116)   | H.264                    | 1        | 2048x1536                     | 2-way | 1/1    | -   | Yes            | -                  | Yes*                 | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks      |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|--------------------|----------------------|----------|--------------|
| SNV-L6083R  | 1.00_150403   | H.264                    | 1        | 1920x1080      | *2    | -      | -   | *2             | -                  | Yes*                 | *2       |              |
| Note:       | 1. Frame rate list with stream 2 is not synchronized with web. (Camera Firmware issue)  |                          |          |                |       |        |     |                |                    |                      |          |              |
| SNZ-5200    | v1.05_111216  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | -                  | Yes                  | -        |              |
| SPE-100     | v1.19_110317  | H.264<br>MPEG4<br>M-JPEG | 1        | 704x480        | 1-way | 1/1    | Yes | Yes            | -                  | Yes                  | -        |              |
| Note:       | SPE-100 PTZ is abnormal, which PTZ may not be stopped after operating. This is camera FW bug, we can observe the same phenomenon on camera web.                                 |                          |          |                |       |        |     |                |                    |                      |          |              |
| SPE-400     | S/W :<br>1.40_120201  | H.264<br>MPEG4<br>M-JPEG | 4        | 704x480        | 1-way | 4/4    | Yes | Yes            | -                  | Yes                  | -        | Test by link |
| Note:       | SPE-400 is 4IP x 4channels video server   |                          |          |                |       |        |     |                |                    |                      |          |              |
| Note:       | All cameras: it's likely failed to query camera parameter in high resolution configuration. It happens on SNO-5080R most. When encountering this issue, please go to camera web |                          |          |                |       |        |     |                |                    |                      |          |              |
| Note:       | All cameras: if configuring fixed frame rate on camera web, parameter selection on NVR web page won't be synchronized   |                          |          |                |       |        |     |                |                    |                      |          |              |



**SANTEC**

- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ  | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks |
|-------------|--|--------------|----------|----------------|-------|--------|------|----------------|------|----------------------|----------|---------|
| SNC-100PBIA | BurgWaechter_IPC-HX5X2X-Themis_GerEng_PN_Stream3_P2P_IVS_V2.400.BW00.O.T.20151022.bin  | H.264 MJPEG  | 1        | 1280x960       | 2-way | -      | -    | Yes            | Yes  | Yes*                 | Yes      |         |
| Note:       | 1. Video parameter only works on normal profile due to camera response without profile information from cgi. (Camera Firmware issue)<br>2. UPnP search can not be used. (Camera Firmware issue)<br>3. Stream parameter setting may fail if the ranges of bitrate is not synchronized with the camera web. (Camera Firmware issue)<br>4. Can not support H.264H and H.264B for format. (NUUO server limitation)<br>5. G.711mu 8k has noise. (Camera Firmware issue)<br>6. G.711mu 16k and AAC can not be used. (NUUO server limitation)                                     |              |          |                |       |        |      |                |      |                      |          |         |
| SNC-200PDIA | BurgWaechter_IPC-HFW2(4)X01_GerEng_PN_V2.210.BW00.8.R.20151124.bin   | H.264 MJPEG  | 1        | 1920x1080      | -     | -      | Yes  | Yes            | Yes  | Yes*                 | Yes      |         |
| Note:       | 1. Image rotation may not sync with web. (Camera Firmware Issue)<br>2. When motion trigger or in low-light situation, camera will disconnect. (Camera performance limitation)<br>3. UPnP search can not be used. (Camera Firmware Issue)<br>4. Framerate & Bitrate list can not sync with web. (Camera Firmware Issue)   |              |          |                |       |        |      |                |      |                      |          |         |
| SNC-211RSIA | V2.210.BW01.O.R.20150409   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 2/1    | Yes  | Yes            | Yes  | Yes*                 | Yes      |         |
| Note:       | 1. Audio in with 16 KHz sampling rate does not supported. (NUUO server limitation)<br>2. Camera UPnP Search does not supported (Camera Firmware issue)<br>3. Auto Focus function does not supported (Camera Firmware issue)<br>4. Stream parameter setting may fail if the ranges of bitrate and framerate are not synchronized with the camera web. (Camera Firmware issue)<br>5. Server Bitrate Value may not sync with web interface. (Camera Firmware issue)<br>6. Mirror function integrated with flip function, mirror button does not work. (Camera Firmware issue) |              |          |                |       |        |      |                |      |                      |          |         |
| SNC-231RZNA | V2.400.BW06.O.R.T1.484, build : 2016-01-13   | H.264 MJPEG  | 1        | 1920x1080      | -     | -      | Yes* | Yes            | *2   | Yes*                 | Yes      |         |
| SNC-331DLNN | v2.400.BW00.O.R  | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes  | Yes            | Yes  | Yes*                 | Yes      |         |
| Note:       | 1. PTZ can not be used. (Camera Firmware issue)<br>2. Flip/Mirror could not work. (Camera Firmware issue)<br>3. Stream parameter setting may fail if the ranges of bitrate and framerate are not synchronized with the camera web. (Camera Firmware issue)<br>4. UPnP can not be used (Camera Firmware issue)  |              |          |                |       |        |      |                |      |                      |          |         |



**SANTEC**

- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| SNC-311FEIF | V2.420.BW00.O.T.20150213   | H.264 MJPEG  | 1        | 2048x1536      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Camera search is not supported. (Camera Firmware issue)<br>2. Stream parameter setting may fail if the ranges of bitrate and framerate are not synchronized with the camera web. (Camera performance limitation)<br>3. HTTP and RTSP port cannot be changed on the camera web. (Camera Firmware issue)  |              |          |                |       |        |     |                |      |                      |          |                     |
| SNC-311FBIF | Refer to SNC-311FEIF (V2.420.BW00.O.T.20150213)  | H.264 MJPEG  | 1        | 2048x1536      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| SNC-311RBIA | 2.420.BW00.O.T   | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Camera search is not supported. (Camrea Firmware issue)<br>2. Autodetection will detect the wrong model. (Camera Firmware issue)<br>3. Stream parameter setting may fail if the ranges of bitrate and framerate are not synchronized with the camera web. (Camera performance limitation)<br>4. Pan and tilt are not supported. (Camera performance limitation)<br>5. Camera does not stop zooming until it reaches the end. (Camrea Firmware issue)<br>6. Some frame rates are not supported if the video format is H.264H. (Camera performance limitation)<br>7. Video parameter setting, flip and mirror are supported under normal mode. (NUUO server limitation) |              |          |                |       |        |     |                |      |                      |          |                     |
| SNC-311RDIA | Refer to SNC-311RBIA(2.420.BW00.O.T)   | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| SNC-311RINA | Refer to SNC-311RBIA(2.420.BW00.O.T)   | H.264 MJPEG  | 1        | 2048x1536      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| SNC-3302    | v1.0.3.447   | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes*                 | -        |                     |
| SNC-3303    | v1.0.3.454   | H.264 M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Audio stutter with the setting MJPEG 1920x1080 25fps quality: 70 in TCP protocol.<br>2. The snapshot will failed when there are no MJPEG stream.<br>3 Camera with MJPEG resolution 1920x1080 is unable to achieve 20 fps  |              |          |                |       |        |     |                |      |                      |          |                     |
| SNC-3305    | v1.0.2.386   | H.264 M-JPEG | 1        | 2592x1944      | 1-way | 1/1    | -   | Yes            | Yes  | Yes*                 | -        |                     |
| Note:       | M-JPEG on high resolution and quality may not get parameter.<br>Audio has some noise in high resolution.<br>The range of framerate is not sync. with web when resolution is 2048x1536 and PAL mode.  |              |          |                |       |        |     |                |      |                      |          |                     |





**SANTEC**

- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| SNC-3322    | v1.0.3.447  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | -        |                     |
| Note:       | 1. M-JPEG on high resolution and quality may not get parameter.<br>2. Audio has some noise in high resolution.<br>3. SNC-3322 PTZ not support preset.<br>4. The frame interval will be unstable under high stream setting, it will cause video and audio not smoothly and image broken.<br>5. Snapshot resolution is always the same as MJPEG resolution.(Camera limitation issue)<br>6. Snapshot not support when none of stream format is MJPEG.(Camera limitation issue) |                          |          |                |       |        |     |                |      |                      |          |                     |
| SNC-3342    | 1.0.0.11  | H.264<br>M-JPEG          | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| SNC-3901MDN | 5.2.3   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| SNC-3903M   | 9.6.1   | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | PTZ is only supported by external RS-485 device.  |                          |          |                |       |        |     |                |      |                      |          |                     |
| SNC-390DN/W | 1.5   | MPEG4<br>M-JPEG          | 1        | 720x576        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | PTZ is only supported by external RS-485 device.  |                          |          |                |       |        |     |                |      |                      |          |                     |
| SNC-4302    | v1.0.3.447  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes*                 | -        |                     |
| SNC-4323IR  | refer to SNC-6323IRH(1.0.3.454)   | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| SNC-5211MIR | 5.2.2   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| SNC-5211R/W | 1.5   | MPEG4<br>M-JPEG          | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| SNC-5312IR  | Refer to SNC-6312IRH(v1.0.2.386)  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | -        | Supported by design |
| SNC-5312MIR |   | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| SNC-5315IR  | Refer to SNC-6315IRH(v1.0.2.386)  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | -        | Supported by design |
| SNC-5323IRH | refer to SNC-6323IRH(1.0.3.454)   | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| SNC-5651R/W | 1.5   | MPEG4<br>M-JPEG          | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| SNC-6163ID  |   | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |



**SANTEC**

- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks                |
|-------------|---|--------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|------------------------|
| SNC-620/W   | 1.0.1.5   | MPEG4 M-JPEG       | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | -    | Yes                  | -        | Tested by manufacturer |
| SNC-6201M   | 5.2.2   | H.264 MPEG4 M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design    |
| SNC-6202    | Refer to SNC-3302(v1.0.3.447)   | H.264 M-JPEG       | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes*                 | -        | Supported by design    |
| SNC-6212IR  | Refer to SNC-6312IRH(v1.0.2.386)  | H.264 M-JPEG       | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | -        | Supported by design    |
| SNC-6221MIR | 5.2.2   | H.264 MPEG4 M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design    |
| SNC-6223MIR |   | H.264 MPEG4 M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design    |
| SNC-6301M   | 5.2.2   | H.264 MPEG4 M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design    |
| SNC-6302    | Refer to SNC-3302(v1.0.3.447)   | H.264 M-JPEG       | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes*                 | -        | Supported by design    |
| Note:       | M-JPEG on high resolution and quality may not get parameter.<br>Audio has some noise in high resolution.  |                    |          |                |       |        |     |                |      |                      |          |                        |
| SNC_6303    | refer to SNC-3303(1.0.3.454)  | H.264 M-JPEG       | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design    |
| SNC-6303M   |   | H.264 MPEG4 M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design    |
| SNC-6312IRH | v1.0.2.386  | H.264 M-JPEG       | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | -        |                        |
| SNC-6315IRH | v1.0.2.386  | H.264 M-JPEG       | 1        | 2592x1944      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | -        |                        |
| Note:       | M-JPEG on high resolution and quality may not get parameter.<br>Audio has some noise in high resolution.<br>The range of framerate is not sync. with web when resolution is 2048x1536 and PAL mode.<br>SNC-6312IRH and SNC-6315IRH PTZ only support zoom and focus. |                    |          |                |       |        |     |                |      |                      |          |                        |
| SNC-6323IRH | v1.0.3.454  | H.264 M-JPEG       | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                        |
| Note:       | 1. Audio stutter with the setting MJPEG 1920x1080 25fps quality: 70 in TCP protocol.<br>2. The snapshot will failed when there are no MJPEG stream.<br>3 Camera with MJPEG resolution 1920x1080 is unable to achieve 20 fps   |                    |          |                |       |        |     |                |      |                      |          |                        |
| SNC-6332    | 1.0.0.10  | H.264 M-JPEG       | 1        | 1600x1200      | 1-way | 4/1    | -   | -              | Yes  | Yes                  | -        |                        |



**SANTEC**

- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name         | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks                |
|---------------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|------------------------|
| <b>SNC-6701D/W</b>  | 1.0.1.5  | MPEG4<br>M-JPEG          | 1        | 720x576        | 1-way | 1/1    | Yes | Yes            | -    | Yes                  | -        | Tested by manufacturer |
| <b>SNC-83221/HO</b> | v1.0.3.447   | H264<br>M-JPEG           | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | Yes*                 | -        | Supported by design    |
| <b>SNC-P3601M</b>   | 5.2.2  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design    |
| <b>SNC-P3603M</b>   |  | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design    |
| Note:               | On-edge motion: H.264 and MPEG4 (3 megapixel cameras)  |                          |          |                |       |        |     |                |      |                      |          |                        |
| <b>SVS-1100</b>     | 1.1.8  | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576        | 1-way | 2/2    | Yes | Yes            | Yes  | Yes                  | -        |                        |
| <b>SVS-3001</b>     |  | H264<br>M-JPEG           | 1        | 720x480        | 1-way | 1/1    | Yes | -              | Yes  | Yes                  | -        | Supported by design    |
| Note:               | 1.3 megapixel cameras: frame rate of MJPEG format is not synchronized as camera actually sends, for example, we set fps to 5 fps, but the video is 3 fps. This issue is fixed in camera FW v5.2.6. |                          |          |                |       |        |     |                |      |                      |          |                        |
| Note:               | 1.3 megapixel and 3 megapixel cameras: with HW restrictions, the video @ H.264 with TCP protocol is not smooth in the conditions of high resolution, fps and bitrate.                              |                          |          |                |       |        |     |                |      |                      |          |                        |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name       | Tested Firmware | Video Format    | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|-------------------|-----------------|-----------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| <b>FBN-D101N</b>  | v1.0.1_20121005 | M-JPEG<br>H.264 | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | -    | Yes                  | Supported by design |
| <b>FBN-D101P</b>  | v1.0.1_20121005 | M-JPEG<br>H.264 | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | -    | Yes                  | Supported by design |
| <b>PSN-1012N</b>  | v1.0.4_20121029 | M-JPEG<br>H.264 | 1        | 1920x1080      | 1-way | 2/1    | Yes | Yes            | -    | Yes                  | Supported by design |
| <b>PSN-1012P</b>  | v1.0.4_20121029 | M-JPEG<br>H.264 | 1        | 1920x1080      | 1-way | 2/1    | Yes | Yes            | -    | Yes                  | Supported by design |
| <b>PSSN-1012N</b> | v1.0.4_20121029 | M-JPEG<br>H.264 | 1        | 1920x1080      | 1-way | 2/1    | Yes | Yes            | -    | Yes                  | Supported by design |
| <b>PSSN-1012P</b> | v1.0.4_20121029 | M-JPEG<br>H.264 | 1        | 1920x1080      | 1-way | 2/1    | Yes | Yes            | -    | Yes                  | Supported by design |
| <b>RIN-0012N</b>  | v1.0.4_20121029 | H.264           | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes                  | Supported by design |
| <b>RIN-0012P</b>  | v1.0.4_20121029 | H.264           | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | -    | Yes                  | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name     | Tested Firmware  | Video Format            | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|-----------------|--|-------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| <b>SNC-21XX</b> | BgWT813003<br>5N03 V23<br>1208152A   | H.264<br>MPEG4<br>MJPEG | 1        | 720P           | 1-way | 1/1    | Yes | Yes            | -    | Yes                  |         |
| Note            | SNC-21XX contains SNC-WD2112MDN, SNC-WD2122DN, SNC-WDL2132DN, SNC-WDL2142DN. |                         |          |                |       |        |     |                |      |                      |         |
| <b>SNC-22XX</b> | BgWT820271<br>5N03 V23<br>1208153A   | H.264<br>MPEG4<br>MJPEG | 1        | 1080P          | 1-way | 1/1    | Yes | Yes            | -    | Yes                  |         |
| Note            | SNC-22XX contains SNC-2212MDN, SNC-2222DN, SNC-L2232DN.                      |                         |          |                |       |        |     |                |      |                      |         |
| <b>SNC-23XX</b> | BgWT830003<br>6N03 V23<br>1208154A   | H.264<br>MPEG4<br>MJPEG | 1        | 3M             | 1-way | 1/1    | Yes | Yes            | -    | Yes                  |         |
| Note            | SNC-23XX contains SNC-WD2312MDN, SNC-WD2322DN, SNC-WDL2132DN, SNC-WDL2332DN. |                         |          |                |       |        |     |                |      |                      |         |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| Generic     | 1.7.0   | H.264<br>M-JPEG          | 1        | All            | 1-way | 2/2    | -   | Yes            | Yes                | Yes                  | Yes      |                     |
| Note:       | Support generic dewarp<br>For G6 model only.<br>In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a> |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-CH110   | 1.27.00   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | -     | -      | -   | Yes            | Yes                | Yes*                 | -        |                     |
| Note:       | SNC-CH110/B and SNC-CH110/S are compatible with SNC-CH110   |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-CH120   | 1.80  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | -     | 1/0    | -   | Yes            | Yes                | Yes                  | -        |                     |
| Note:       | SNC-CH120 not support SolidPTZ mode.  |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-CH140   | 1.07.00   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-CH160   | 1.82.01   | H.264<br>M-JPEG          | 1        | 1280x1024      | -     | 1/1    | Yes | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:       | Camera with resolution 1280x1024 is unable to achieve 30 fps  |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-CH180   | 1.26.01   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-CH210   | 1.78.00   | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | -     | -      | -   | Yes            | Yes                | Yes*                 | -        |                     |
| Note:       | 1. SNC-CH210/B and SNC-CH210/S are compatible with SNC-CH210<br>2. Dualstream can not be enabled when H.264, 1280 x 720, 30 fps is selected for Image 1.<br>3. The number of connection is 1 for JPEG and 2 for H264 and MPEG4 at the same time.  |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-CH220   | 1.21.02   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1440      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-CH240   | 1.10.01   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1440      | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-CH260   | 1.78.00   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1440      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| Note:       | 1. PTZ function only support zoom tele/wide, focus near/far and auto function.<br>2. DualStream can not be enabled when the H264, 1920x1080, 30 FPS is selected for Image1.<br>3. The number of connection is 1 for JPEG and 2 for H264 and MPEG4 at the same time.   |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-CH280   | 1.26.01   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1440      | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-CM120   | 1.00  | MPEG4<br>M-JPEG          | 1        | 1280x960       | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-CS10    |   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes                | Yes*                 | -        | Supported by design |
| SNC-CS11    | 1.05  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-CS20    |   | MPEG4<br>M-JPEG          | 1        | 768x576        | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        | Supported by design |
| SNC-CS3     |   | M-JPEG                   | 1        | 736x480        | -     | 1/2    | -   | -              | Yes                | Yes*                 | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| SNC-CS50    | 2.21   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 2/2    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-CX600W  | 1.7.0  | H.264<br>M-JPEG          | 1        | 1280x1024      | 2-way | -      | -   | Yes            | Yes                | Yes                  | Yes      |                     |
| Note:       | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a>  |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-DF50    | 1.11   | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-DF70    | 1.17   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-DF80    | 1.11   | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-DF85    |  | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        | Supported by design |
| SNC-DH110   | 1.82.01  | H.264<br>M-JPEG          | 1        | 1280x960       | -     | -      | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:       | 1. SNC-DH110/B and SNC-DH110/W are compatible with SNC-DH110<br>2. Change Format will take 30~50 second to reconnect.  |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-DH110T  | Refer to SNC-DH110   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x960       | -     | -      | -   | Yes            | Yes                | Yes*                 | -        | Supported by design |
| Note:       | SNC-DH110T/B and SNC-DH110T/W are compatible with SNC-DH110T   |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-DH120   | 1.78.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | -     | -      | -   | Yes            | Yes                | Yes*                 | -        |                     |
| Note:       | 1. PTZ function only support zoom tele/wide, focus near/far and auto function.<br>2. Dualstream can not be enabled when H.264, 1280 x 720, 30 fps is selected for Image 1.<br>3. The connection cannot established with high probability when selected JPEG, high resolution and high quality.<br>4. The number of connection is 1 for JPEG and 2 for H264 and MPEG4 at the same time. |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-DH140   | 1.07.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| Note:       | Motion detection will be turned off upon changing to maximum resolution. Remember to enable it in camera web.  |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-DH160   | 1.13.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-DH180   | 1.10.02  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-DH210   |  | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | -     | -      | -   | Yes            | Yes                | Yes*                 | -        | Supported by design |
| Note:       | SNC-DH210/B and SNC-DH210/W are compatible with SNC-DH210  |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-DH210T  | 1.27.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | -     | -      | -   | Yes            | Yes                | Yes*                 | -        |                     |
| Note:       | SNC-DH210T/B and SNC-DH210T/W are compatible with SNC-DH210T   |                          |          |                |       |        |     |                |                    |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| SNC-DH220   | 1.82.01   | H.264<br>M-JPEG          | 1        | 1920x1440      | -     | -      | Yes | Yes            | Yes                | Yes*                 | Yes      |                     |
| SNC-DH220T  | Refer to SNC-DH220  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1440      | 1-way | 1/1    | Yes | Yes            | Yes                | Yes*                 | -        | Supported by design |
| SNC-DH240   | 1.11.00   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1440      | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-DH260   | 1.30.00   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1440      | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-DH280   | 1.26.01   | H.264<br>MPEG4<br>M-JPEG | 1        | 1921x1440      | 1-Way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-DM110   |   | MPEG4<br>M-JPEG          | 1        | 1280x960       | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        | Supported by design |
| SNC-DM160   | 1.01  | MPEG4<br>M-JPEG          | 1        | 1280x960       | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-DS10    | 1.01  | H.264<br>MPEG4<br>M-JPEG | 1        | 768x576        | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-DS60    | 1.00  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/2    | -   | Yes            | Yes                | Yes*                 | -        |                     |
| SNC-EB600   | Refer to SNC-EB600B(1.9.2)  | H264<br>MJPEG            | 1        | 1280x1024      | -     | -      | -   | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| Note:       | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a> |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-EB602R  | Refer to SNC-EB632R(2.1.2)  | H.264<br>M-JPEG          | 1        | 1920x1080      | -     | -      | Yes | Yes            | Yes                | Yes*                 | Yes      | Supported by design |
| SNC-EB600B  | 1.9.2   | H264<br>MJPEG            | 1        | 1280x1024      | -     | -      | -   | Yes            | Yes                | Yes                  | Yes      |                     |
| Note:       | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a> |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-EB630   | 1.9.2   | H.264<br>M-JPEG          | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes                | Yes                  | Yes      |                     |
| Note:       | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a> |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-EB630B  | Refer to SNC-EB630(1.9.2)   | H.264<br>M-JPEG          | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| Note:       | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a> |                          |          |                |       |        |     |                |                    |                      |          |                     |





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name       | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| <b>SNC-EB632R</b> | 2.2.1  | H.264<br>M-JPEG          | 1        | 1920x1080      | -     | -      | Yes | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:             | PTZ only support zoom and focus.   |                          |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-EM600</b>  | Refer to SNC-EB600B(1.9.2)   | H264<br>MJPEG            | 1        | 1280x1024      | -     | -      | -   | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a>                |                          |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-EM601</b>  | Refer to SNC-EB600B(1.9.2)   | H264<br>MJPEG            | 1        | 1280x1024      | -     | -      | -   | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a>                |                          |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-EM602R</b> | Refer to SNC-EB600B(1.9.2)   | H264<br>MJPEG            | 1        | 1280x1024      | -     | -      | -   | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a>                |                          |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-EM630</b>  | Refer to SNC-EB630(1.9.2)  | H.264<br>M-JPEG          | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a>                |                          |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-EM631</b>  | Refer to SNC-EB630(1.9.2)  | H.264<br>M-JPEG          | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a>                |                          |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-EM632R</b> | 1.9.2  | H.264<br>M-JPEG          | 1        | 1920x1080      | -     | -      | Yes | Yes            | Yes                | Yes                  | Yes      |                     |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a><br>Easy Focus. |                          |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-EP520</b>  | 1.40.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 2/1    | Yes | Yes            | Yes                | Yes                  | -        |                     |
| <b>SNC-EP521</b>  | 1.42.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576        | 1-way | 2/1    | Yes | Yes            | Yes                | Yes                  | -        |                     |
| <b>SNC-EP550</b>  | Refer to SNC-ER550   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x720       | 1-way | 2/1    | Yes | Yes            | Yes                | Yes                  | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| SNC-EP580   | 1.42.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 2/1    | Yes | Yes            | Yes                | Yes                  | -        |                     |
| Note:       | For performance consideration, users are unable to watch live videos on both NVR side and camera side.   |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-ER520   | 1.42.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 2/1    | Yes | Yes            | Yes                | Yes                  | -        |                     |
| SNC-ER521   | 1.42.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576        | 1-way | 2/1    | Yes | Yes            | Yes                | Yes                  | -        |                     |
| SNC-ER550   | 1.78.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x720       | 1-way | 2/1    | Yes | Yes            | Yes                | Yes                  | -        |                     |
| Note:       | 1. Dualstream can not be enabled when H264, 1280x720, 30fps is selected for image 1.<br>2. The number of connection is 1 for JPEG and 2 for H264 and MPEG4 at the same time.<br>3. The connection cannot established with high probability when selected JPEG, high resolution and high quality.   |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-ER580   | 1.82.01  | H.264<br>M-JPEG          | 1        | 1920x1080      | 2-way | 2/1    | Yes | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:       | For performance consideration, users are unable to watch live videos on both NVR side and camera side.   |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-ER585   | 1.78.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | *2    | *2     | Yes | Yes            | *2                 | Yes                  | -        | Tested by link      |
| SNC-HM662   | 1.1.1  | H.264<br>MJPEG           | 1        | 2560x1920      | 1-way | 1/1    | -   | Yes            | -                  | Yes                  | Yes      |                     |
| Note:       | 1. fisheye camera<br>2. In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a><br>3. The images of JPEG with resolution 2560x1920 does not support audio.<br>4. Only default RTSP path of all streams are supported.<br>5. Camera is unable to achieve maximum FPS. |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-P1      | 1.28   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes                | Yes                  | -        |                     |
| SNC-P5      | 1.11   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 2/1    | Yes | Yes            | Yes                | Yes                  | -        |                     |
| SNC-RH124   | 1.84.00  | H.264<br>M-JPEG          | 1        | 1280x720       | 2-way | 4/2    | Yes | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:       | 1. The camera with MJPEG format and resolution is larger than 640x480 may disconnect.<br>2. The camera with MJPEG format is unable to achieve 30fps<br>3. Camera must reconnect when change the audio codec in web site.   |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-RH164   | 1.10.01  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x720       | 1-way | 4/2    | Yes | Yes            | Yes                | Yes                  | -        |                     |
| SNC-RS44N   |  | H.264<br>MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 4/2    | Yes | Yes            | Yes                | Yes                  | -        | Supported by design |
| SNC-RS44P   |  | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576        | 1-way | 4/2    | Yes | Yes            | Yes                | Yes                  | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| SNC-RS46N   |   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 4/2    | Yes | Yes            | Yes                | Yes                  | -        | Supported by design |
| SNC-RS46P   | 1.10.02   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576        | 1-way | 4/2    | Yes | Yes            | Yes                | Yes                  | -        |                     |
| SNC-RS84N   |   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 4/2    | Yes | Yes            | Yes                | Yes                  | -        | Supported by design |
| SNC-RS84P   |   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576        | 1-way | 4/2    | Yes | Yes            | Yes                | Yes                  | -        | Supported by design |
| SNC-RS86N   |   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x480        | 1-way | 4/2    | Yes | Yes            | Yes                | Yes                  | -        | Supported by design |
| SNC-RS86P   |   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576        | 1-way | 4/2    | Yes | Yes            | Yes                | Yes                  | -        | Supported by design |
| SNC-RX530   | 3.00  | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | 1-way | 2/2    | Yes | Yes            | Yes                | Yes                  | -        |                     |
| SNC-RX550   |   | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | 1-way | 2/2    | Yes | Yes            | Yes                | Yes                  | -        | Supported by design |
| SNC-RX570   | 3.01  | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | 1-way | 2/2    | Yes | Yes            | Yes                | Yes                  | -        |                     |
| SNC-RZ25    | 1.29  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 2/2    | Yes | Yes            | Yes                | Yes                  | -        |                     |
| SNC-RZ30    | 3.14  | M-JPEG                   | 1        | 736x480        | -     | 3/2    | Yes | -              | Yes                | Yes                  | -        |                     |
| SNC-RZ50    | 2.21  | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | 1-way | 2/2    | Yes | Yes            | Yes                | Yes                  | -        |                     |
| SNC-VB600   | 1.9.2   | H.264<br>M-JPEG          | 1        | 1280x1024      | 2-way | 2/2    | -   | Yes            | Yes                | Yes                  | Yes      |                     |
| Note:       | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a> |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-VB600B  | 1.7.0   | H.264<br>M-JPEG          | 1        | 1280x1024      | 2-way | 2/2    | -   | Yes            | Yes                | Yes                  | Yes      |                     |
| Note:       | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a> |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-VB630   | 2.2.1   | H264<br>MJPEG            | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | Yes                | Yes*                 | Yes      |                     |
| Note:       | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a> |                          |          |                |       |        |     |                |                    |                      |          |                     |
| SNC-VB635   | 1.11.0  | H264<br>MJPEG            | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | Yes                | Yes                  | Yes      |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name       | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------------|--|--------------|----------|----------------|-------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a><br>Easy Focus. |              |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-VM600</b>  | Refer to SNC-VB600(1.9.2)  | H.264 M-JPEG | 1        | 1280x1024      | 2-way | 2/2    | -   | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a>                |              |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-VM600B</b> | Refer to SNC-VB600B(FW 1.7.0)  | H.264 M-JPEG | 1        | 1280x1024      | 2-way | 2/2    | -   | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a>                |              |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-VM601</b>  | Refer to SNC-VB600(1.9.2)  | H.264 M-JPEG | 1        | 1280x1024      | 2-way | 2/2    | -   | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a>                |              |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-VM601B</b> | Refer to SNC-VB600(1.9.2)  | H.264 M-JPEG | 1        | 1280x1024      | 2-way | 2/2    | -   | Yes            | -                  | -                    | -        | Supported by design |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a>                |              |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-VM602R</b> | Refer to SNC-VB600(1.9.2)  | H.264 M-JPEG | 1        | 1280x1024      | 2-way | 2/2    | -   | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a>                |              |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-VM630</b>  | Refer to SNC-VM632R(1.9.2)   | H264 MJPEG   | 1        | 1920x1080      | 2-way | 2/2    | -   | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a>                |              |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-VM631</b>  | Refer to SNC-VM632R(1.9.2)   | H264 MJPEG   | 1        | 1920x1080      | 2-way | 2/2    | -   | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a>                |              |          |                |       |        |     |                |                    |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name       | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------------|---|--------------|----------|----------------|-------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| <b>SNC-VM632R</b> | 1.9.2   | H264 MJPEG   | 1        | 1920x1080      | 2-way | 2/2    | -   | Yes            | Yes                | Yes                  | Yes      |                     |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a> |              |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-WR600</b>  | 1.11.0  | H264 MJPEG   | 1        | 1280x1024      | 2-way | 4/2    | Yes | Yes            | Yes                | Yes                  | Yes      |                     |
| <b>SNC-WR602</b>  | Refer to SNC-WR600(1.11.0)  | H264 MJPEG   | 1        | 1280x1024      | 2-way | 4/2    | Yes | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| <b>SNC-WR630</b>  | 1.11.0  | H264 MJPEG   | 1        | 1920x1080      | 2-way | 4/2    | Yes | Yes            | Yes                | Yes                  | Yes      |                     |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a> |              |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-WR632</b>  | Refer to SNC-WR630 (1.11.0)   | H264 MJPEG   | 1        | 1920x1080      | 2-way | 4/2    | Yes | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a> |              |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-XM631</b>  | 2.2.1   | H.264 MJPEG  | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| <b>SNC-XM632</b>  | 1.12.0  | H.264 MJPEG  | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes                | Yes                  | Yes      |                     |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a> |              |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-XM636</b>  | Refer to SNC-XM632(1.12.0)  | H.264 MJPEG  | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a> |              |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-XM637</b>  | Refer to SNC-XM632(1.12.0)  | H.264 MJPEG  | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes                | Yes                  | Yes      | Supported by design |
| Note:             | In certain scenarios i.e. under high frame rate and resolution with multiple stream condition, camera might have limitation by bandwidth specification.<br>For further information, please visit Sony A&E Portal: <a href="https://www.security.sony.biz/ssp/ae/homeDisplay.do">https://www.security.sony.biz/ssp/ae/homeDisplay.do</a> |              |          |                |       |        |     |                |                    |                      |          |                     |
| <b>SNC-Z20</b>    | 1.06  | M-JPEG       | 1        | 736x480        | -     | 1/2    | Yes | -              | Yes                | Yes                  | -        |                     |
| Note:             | PTZ Support: zoom only.   |              |          |                |       |        |     |                |                    |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format       | Video Ch | Max Resolution                | Audio | I/O Ch | PTZ | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------|----------|-------------------------------|-------|--------|-----|----------------|--------------------|----------------------|----------|---------------------|
| SNC-ZB550   | 1.82.01   | H.264 MJPEG        | 1        | 1280x1024                     | -     | 1/1    | -   | Yes            | Yes                | Yes*                 | Yes      |                     |
| SNT-EP104   |   | H.264 MPEG4 M-JPEG | 4        | 720x480                       | -     | -      | -   | Yes            | Yes                | Yes                  | -        | Supported by design |
| SNT-EP154   | 1.10.01   | H.264 MPEG4 M-JPEG | 4        | 720x480                       | -     | -      | -   | Yes            | Yes                | Yes                  | -        |                     |
| SNT-EX101   |   | H.264 MPEG4 M-JPEG | 1        | 720x480                       | 1-way | 2/2    | Yes | Yes            | Yes                | Yes                  | -        | Supported by design |
| SNT-EX101E  | 1.10.01   | H.264 MPEG4 M-JPEG | 1        | PAL: 720x576<br>NTSC: 720x480 | 1-way | 2/2    | Yes | Yes            | Yes                | Yes                  | -        |                     |
| SNT-EX104   | 1.10.01   | H.264 MPEG4 M-JPEG | 4        | PAL: 720x576<br>NTSC: 720x480 | 1-way | 4/4    | Yes | Yes            | Yes                | Yes                  | -        |                     |
| SNT-EX154   | 1.10.01   | H.264 MPEG4 M-JPEG | 4        | 720x480                       | 1-way | 4/4    | Yes | Yes            | Yes                | Yes                  | -        |                     |
| SNT-V704    | 2.15  | MPEG4 M-JPEG       | 4        | 720x480                       | 1-way | 1/4    | -   | -              | Yes                | Yes                  | -        |                     |
| Note:       | When use 2nd stream on "E" and "X" series, IP-cameras motion detection will not able to use. Please refer to Sony user's guide. The 1.7 and above version of FW slove this problem.           |                    |          |                               |       |        |     |                |                    |                      |          |                     |
| Note        | One of the cameras in the system must support I/O functions in order to enable the snapshot feature. This is a known issue and we are looking to fix it with the next product version update. |                    |          |                               |       |        |     |                |                    |                      |          |                     |



spark

UltraHD technology

- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name    | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ  | On-Edge Motion | Camera Search Tool | Multi Stream Support | Snapshot | Remarks |
|----------------|---|--------------|----------|----------------|-------|--------|------|----------------|--------------------|----------------------|----------|---------|
| SR-C-F21100    | 2.420.0005.0.R  | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | Yes  | Yes            | -                  | Yes*                 | Yes      |         |
| Note:          | 1. Camera Search and Auto Detect was not supported. (Camera firmware issue)<br>2. Bitrate Range in camera web was not sync with NUUO server. (Camera firmware issue)<br>3. G711A 16K was not supported. (NUUO server limitation)<br>4. Because of bitrate range was not sync between server and camera web, camera setting probably fail. (Camera firmware issue) |              |          |                |       |        |      |                |                    |                      |          |         |
| SR-C-F25100-V  | 2.210.0004.0.T.A.3013.3N.R  | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 2/1    | Yes  | Yes            | -                  | Yes*                 | Yes      |         |
| Note:          | 1. Camera Search and Auto Detect was not supported. (Camera firmware issue)<br>2. Bitrate Range in camera web was not sync with NUUO server. (Camera firmware issue)<br>3. G711A 16K was not supported. (NUUO server limitation)<br>4. Because of bitrate range was not sync between server and camera web, camera setting probably fail. (Camera firmware issue) |              |          |                |       |        |      |                |                    |                      |          |         |
| SR-C-F24110-FV | 2.420.0005.0.R  | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | Yes  | Yes            | -                  | Yes*                 | Yes      |         |
| Note:          | 1. Camera Search and Auto Detect was not supported. (Camera firmware issue)<br>2. Bitrate Range in camera web was not sync with NUUO server. (Camera firmware issue)<br>3. In G.711 sound will distort. (Camera firmware issue)<br>4. Zoom can't use successfully. (Camera performance limitation)  |              |          |                |       |        |      |                |                    |                      |          |         |
| SR-C-F26110    | 2.420.0005.0.R  | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 2/1    | Yes  | Yes            | -                  | Yes*                 | Yes      |         |
| Note:          | 1. Camera Search and Auto Detect was not supported. (Camera firmware issue)<br>2. Bitrate Range in camera web was not sync with NUUO server. (Camera firmware issue)<br>3. G711A 16K was not supported. (NUUO server limitation)<br>4. Because of bitrate range was not sync between server and camera web, camera setting probably fail. (Camera firmware issue) |              |          |                |       |        |      |                |                    |                      |          |         |
| SR-C-F22100-V  | 2.420.0005.0.R  | H.264 MJPEG  | 1        | 1920x1080      | -     | -      | -    | Yes            | -                  | Yes*                 | Yes      |         |
| Note:          | 1. Camera Search and Auto Detect was not supported. (Camera firmware issue)<br>2. Bitrate Range in camera web was not sync with NUUO server. (Camera firmware issue)<br>3. Because of bitrate range was not sync between server and camera web, camera setting probably fail. (Camera firmware issue)   |              |          |                |       |        |      |                |                    |                      |          |         |
| SR-C-F23120-V  | 2.420.0005.0.R  | H.264 MJPEG  | 1        | 1920x1080      | 1-way | -      | Yes* | Yes            | -                  | Yes*                 | Yes      |         |
| Note:          | 1. Camera Search and Auto Detect was not supported. (Camera firmware issue)<br>2. Bitrate Range in camera web was not sync with NUUO server. (Camera firmware issue)<br>3. G711A 16K was not supported. (NUUO server limitation)<br>4. Because of bitrate range was not sync between server and camera web, camera setting probably fail. (Camera firmware issue) |              |          |                |       |        |      |                |                    |                      |          |         |
| Nitida 12000   | 01.10:01.08:01.13:01.11:01.05:00.04   | H.264        | 1        | 1920x1080      | -     | -      | -    | -              | -                  | Yes*                 | -        |         |
| Note:          | Second stream is unable to achieve setting bit rate.(Camera performance limitation)   |              |          |                |       |        |      |                |                    |                      |          |         |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name         | Tested Firmware  | Video Format    | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | ONVIF Search | Multi Stream Support | Snapshot | Remarks             |
|---------------------|--|-----------------|----------|----------------|-------|--------|-----|----------------|------|--------------|----------------------|----------|---------------------|
| Generic             | v1.9.0601.10<br>01.3.0.36.0.0  | H.264<br>M-JPEG | 1        | 2592x1944      | 2-way | 2/2    | Yes | Yes            | -    | -            | Yes*                 | Yes      |                     |
| Note:               | Support generic dewarp<br>Test by IPC54-40EDN in DP v3.13.(FW : v1.9.0601.1001.3.0.36.0.0) (I/O ch : 1/1)<br>1. The ranges of bitrate and framerate may be different from camera web. (Camera Firmware issue)<br>2. Motion detection is not supported on MJPEG. (Camera performance limitation)<br>3. Bitrate of actual streaming may be different from the setting. (Camera Firmware issue)<br>4. Frame rate of actual streaming may be different from the setting. (Camera Firmware issue) |                 |          |                |       |        |     |                |      |              |                      |          |                     |
| IPS54/70DN/<br>Z18  | refer to<br>IPS54/70DN/<br>ZR18  | H.264<br>M-JPEG | 1        | 1280x720       | 1-way | 1/0    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| IPS54/70DN/<br>ZR18 | v1.6_build044<br>014_027   | H.264<br>M-JPEG | 1        | 1280x720       | 1-way | 1/0    | Yes | Yes            | -    | -            | Yes                  | -        |                     |
| IPS54/70DR/<br>Z18  | refer to<br>IPS54/70DN/<br>ZR18  | H.264<br>M-JPEG | 1        | 1280x720       | 1-way | 1/0    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| IPS54/70DR/<br>ZR18 | refer to<br>IPS54/70DN/<br>ZR18  | H.264<br>M-JPEG | 1        | 1280x720       | 1-way | 1/0    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| IPS54/71DN/<br>Z18  | refer to<br>IPS54/70DN/<br>ZR18  | H.264<br>M-JPEG | 1        | 1280x720       | 1-way | 1/0    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| IPS54/80DR          | refer to<br>IPS54/70DN/<br>ZR18  | H.264<br>M-JPEG | 1        | 1280x720       | 1-way | 1/0    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-<br>IPC54/11DN   | refer to SN-<br>IPC54/11FDN  | H.264<br>M-JPEG | 1        | 1280x720       | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-<br>IPC54/11EDN  | refer to SN-<br>IPC54/11FDN  | H.264<br>M-JPEG | 1        | 1280x720       | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-<br>IPC54/11FDN  | v1.6_build044<br>014_027   | H.264<br>M-JPEG | 1        | 1280x720       | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        |                     |
| SN-<br>IPC54/12DN   | refer to SN-<br>IPD54/12VDN  | H.264<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-<br>IPC54/12EDN  | refer to SN-<br>IPD54/12VDN  | H.264<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-<br>IPC54/12FDN  | refer to SN-<br>IPD54/12VDN  | H.264<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-<br>IPC54/14EDN  | refer to<br>IPD54/12VDN<br>(v1.6_build04<br>4014_106)  | H.264<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-<br>IPC54/20DN   | 1.6_build0440<br>11_061  | H.264<br>M-JPEG | 1        | 704x576        | 1-way | -      | -   | Yes            | -    | Yes          | -                    | -        |                     |
| SN-<br>IPC54/31EDN  | refer to SN-<br>IPV54/31UDR<br>(v1.6_build04<br>4014_137)  | H.264<br>M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-<br>IPC54/40EDN  | v1.6_build044<br>014_137   | H.264<br>M-JPEG | 1        | 2592x1920      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        |                     |
| SN-<br>IPC54/50DN   |  | H.264<br>M-JPEG | 1        | 1280x720       | 1-way | -      | -   | Yes            | -    | Yes          | -                    | -        | Supported by design |
| SN-<br>IPD54/11DN   |  | H.264<br>M-JPEG | 1        | 1280x720       | 1-way | -      | -   | Yes            | -    | Yes          | -                    | -        | Supported by design |





- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name     | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | ONVIF Search | Multi Stream Support | Snapshot | Remarks             |
|-----------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------|----------------------|----------|---------------------|
| SN-IPD54/11VDN  | refer to SN-IPC54/11FDN  | H.264 M-JPEG | 1        | 1280x720       | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPD54/11VDR  | refer to SN-IPC54/11FDN  | H.264 M-JPEG | 1        | 1280x720       | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes*                 | -        | Supported by design |
| SN-IPD54/12DN   |  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | -      | -   | Yes            | -    | Yes          | -                    | -        | Supported by design |
| SN-IPD54/12VDR  | refer to SN-IPD54/12VDN  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPD54/12VDN  | v1.9.0601.10<br>01.3.0.22.0.0  | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | -    | Yes          | Yes*                 | Yes      |                     |
| Note:           | 1.The snapshot function can't be used.(Camera firmware issue)<br>2.The PTZ function can't be use on camera web.(Camera firmware issue)<br>3.Some framerate and bitrate can't be set due to Onvif restriction.(Camera firmware issue)<br>4.Due to Onvif restriction, some frame rate and bit rates cannot be set .(Camera firmware issue)<br>5.Audio only support G.711 mu-law.(NUUO server limitation) |              |          |                |       |        |     |                |      |              |                      |          |                     |
| SN-IPC55/20EDN  | v1.8.1001.10<br>01.3.0.46.0.0  | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | -    | Yes          | Yes*                 | Yes      |                     |
| Note:           | 1.The snapshot function can't be used.(Camera firmware issue)<br>2.The PTZ function can't be use on camera web.(Camera firmware issue)<br>3.Some framerate and bitrate can't be set due to Onvif restriction.(Camera firmware issue)<br>4.Due to Onvif restriction, some frame rate and bit rates cannot be set .(Camera firmware issue)<br>5.Audio only support G.711 mu-law.(NUUO server limitation) |              |          |                |       |        |     |                |      |              |                      |          |                     |
| SN-IPD54/14VDN  | refer to IPD54/12VDN (v1.6_build04_4014_106)   | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPD54/14VDR  | refer to IPD54/12VDN (v1.6_build04_4014_106)   | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPD54/31VDN  | refer to SN-IPV54/31UDR (v1.6_build04_4014_137)  | H.264 M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPD54/31VDR  | refer to SN-IPV54/31UDR (v1.6_build04_4014_137)  | H.264 M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPD54/40VDN  | refer to SN-IPC54/40EDN (v1.6_build04_4014_137)  | H.264 M-JPEG | 1        | 2592x1920      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPR54/11AKDN | refer to SN-IPC54/11FDN  | H.264 M-JPEG | 1        | 1280x720       | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPR54/11ALDN | refer to SN-IPC54/11FDN  | H.264 M-JPEG | 1        | 1280x720       | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name          | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | ONVIF Search | Multi Stream Support | Snapshot | Remarks             |
|----------------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------|----------------------|----------|---------------------|
| SN-IPR54/11ANDN      | refer to SN-IPC54/11FDN   | H.264 M-JPEG | 1        | 1280x720       | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPR54/11DN        | refer to SN-IPC54/11FDN   | H.264 M-JPEG | 1        | 1280x720       | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPR54/12AKDN      | refer to SN-IPD54/12VDN   | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPR54/12ALDN      | refer to SN-IPD54/12VDN   | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPR54/12ANDN      | refer to SN-IPD54/12VDN   | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPR54/12DN        | refer to SN-IPD54/12VDN   | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPR54/14AKDN      | refer to IPD54/12VDN (v1.6_build04 4014_106)                      | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPR54/14APDN      | refer to IPD54/12VDN (v1.6_build04 4014_106)                      | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPR54/31AKDN      | refer to SN-IPV54/31UDR (v1.6_build04 4014_137)                   | H.264 M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPR54/31APDN      | refer to SN-IPV54/31UDR (v1.6_build04 4014_137)                   | H.264 M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPR54/31UDN       | v1.7.1001.3.0.13  | H.264 M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | -   | Yes            | -    | Yes          | Yes                  | -        |                     |
| Note:                | Some framerate and bitrate can't be set due to Onvif restriction. |              |          |                |       |        |     |                |      |              |                      |          |                     |
| SN-IPR54/40AKDN      | refer to SN-IPC54/40EDN (v1.6_build04 4014_137)                   | H.264 M-JPEG | 1        | 2592x1920      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPR54/40APDN      | refer to SN-IPC54/40EDN (v1.6_build04 4014_137)                   | H.264 M-JPEG | 1        | 2592x1920      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPR54/50DN        |   | H.264 M-JPEG | 1        | 1280x720       | 1-way | -      | -   | Yes            | -    | Yes          | -                    | -        | Supported by design |
| SN-IPS54/60DN/Z18    |   | H.264 M-JPEG | 1        | 704x576        | 1-way | -      | Yes | Yes            | -    | Yes          | -                    | -        | Supported by design |
| SN-IPS54/60DN/Z18/WI | v1.6_build044 013_040   | H.264 MJPEG  | 1        | 704x480        | 1-way | -      | Yes | Yes            | -    | Yes          | Yes                  | -        |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name       | Tested Firmware         | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | ONVIF Search | Multi Stream Support | Snapshot | Remarks             |
|-------------------|-------------------------|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------|----------------------|----------|---------------------|
| SN-IPS54/60DN/Z36 |                         | H.264 M-JPEG | 1        | 704x576        | 1-way | -      | Yes | Yes            | -    | Yes          | -                    | -        | Supported by design |
| SN-IPV54/11DN     | refer to SN-IPC54/11FDN | H.264 M-JPEG | 1        | 1280x720       | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPV54/11DR     | refer to SN-IPC54/11FDN | H.264 M-JPEG | 1        | 1280x720       | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPV54/11UDN    | refer to SN-IPC54/11FDN | H.264 M-JPEG | 1        | 1280x720       | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPV54/11UDR    | refer to SN-IPC54/11FDN | H.264 M-JPEG | 1        | 1280x720       | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPV54/11ZDR    | refer to SN-IPC54/11FDN | H.264 M-JPEG | 1        | 1280x720       | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPV54/12DN     | refer to SN-IPD54/12VDN | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPV54/12DR     | refer to SN-IPD54/12VDN | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPV54/12UDN    | refer to SN-IPD54/12VDN | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name    | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | ONVIF Search | Multi Stream Support | Snapshot | Remarks             |
|----------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------|----------------------|----------|---------------------|
| SN-IPV54/12UDR | refer to SN-IPD54/12VDN  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPV54/12ZDR | refer to IPD54/12VDN (v1.6_build04 4014_106)   | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPV54/14UDR | refer to IPD54/12VDN (v1.6_build04 4014_106)   | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPV54/14ZDR | refer to IPD54/12VDN (v1.6_build04 4014_106)   | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPV54/31UDN | v1.6_build044 014_137  | H.264 M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        |                     |
| Note:          | SN-IPV54/31UDN FW issue: Camera will reboot when MJPEG 2048x1536, 1920x1080 and quality 9.   |              |          |                |       |        |     |                |      |              |                      |          |                     |
| SN-IPV54/31UDR | refer to SN-IPV54/31UDR (v1.6_build04 4014_137)  | H.264 M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPV54/31ZDR | refer to SN-IPV54/31UDR (v1.6_build04 4014_137)  | H.264 M-JPEG | 1        | 2048x1536      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPV54/40UDN | refer to SN-IPC54/40EDN (v1.6_build04 4014_137)  | H.264 M-JPEG | 1        | 2592x1920      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPV54/40UDR | refer to SN-IPC54/40EDN (v1.6_build04 4014_137)  | H.264 M-JPEG | 1        | 2592x1920      | 1-way | 1/1    | Yes | Yes            | -    | -            | Yes                  | -        | Supported by design |
| SN-IPV54/50DN  |  | H.264 M-JPEG | 1        | 1280x720       | 1-way | -      | -   | Yes            | -    | Yes          | -                    | -        | Supported by design |
| SN-IPV54/50DR  |  | H.264 M-JPEG | 1        | 1280x720       | 1-way | -      | -   | Yes            | -    | Yes          | -                    | -        | Supported by design |
| SN-VSR54/04    | build044014_136_1  | H.264        | 4        | 704x576        | 1-way | 2/1    | Yes | Yes            | -    | -            | Yes                  | -        |                     |
| Note:          | 1. Audio only available on channel 1 and channel 2.<br>2. DI2 can't work correctly.  |              |          |                |       |        |     |                |      |              |                      |          |                     |
| VSR54/01       | v1.6_build044 014_026  | H.264 M-JPEG | 1        | D1             | 1-way | 2-1    | Yes | Yes            | -    | -            | Yes                  | -        |                     |
| Note:          | IPS54/70DN/ZR18: Changing MJPEG resolution may get Fail message due to camera FW issue.  |              |          |                |       |        |     |                |      |              |                      |          |                     |
| Note:          | SN-IPD54/12VDN: Can't test DI due to HW broken.  |              |          |                |       |        |     |                |      |              |                      |          |                     |
| Note:          | SN-IPC54/40EDN<br>1. MJPEG 2592x1920 by camera FW issue.<br>2. Camera will reboot when MJPEG 2048x1536 and quality 9 by camera FW issue.   |              |          |                |       |        |     |                |      |              |                      |          |                     |
| Note:          | SN-IPS54/60DN/Z18/WI:<br>1. Audio, MD, PTZ function only test by SN-IPS54/60DN/Z18/WI and v1.6_build044013_040 firmware.<br>2. Dualstream may not connect sometimes when accessing camera too frequency. |              |          |                |       |        |     |                |      |              |                      |          |                     |
| Note:          | SN-IPV54/50DR: Implement with ONVIF protocol v1.02.  |              |          |                |       |        |     |                |      |              |                      |          |                     |
| Note:          | Due to the limitation of ONVIF protocol, ONVIF search works only as cameras keep default administrator name and password.  |              |          |                |       |        |     |                |      |              |                      |          |                     |
| Note:          | Do not support I/O due to camera FW limitation.  |              |          |                |       |        |     |                |      |              |                      |          |                     |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | ONVIF Search | Multi Stream Support | Snapshot | Remarks |
|-------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|--------------|----------------------|----------|---------|
| Note:       | VSR54/01:<br>1. Autodetect fail due to camera FW issue.<br>2. Changing MJPEG resolution may get Fail message due to camera FW issue.<br>3. DI can't work correctly due to camera FW issue. |              |          |                |       |        |     |                |      |              |                      |          |         |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format      | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Auto Pan | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|-------------------|----------|----------------|-------|--------|-----|----------------|------|----------|----------------------|----------|---------------------|
| TV-IP262P   | 1.0.3   | H.264 MJPEG       | 1        | 1280x1024      | 2-way | -      | -   | Yes            | Yes  | -        | Yes                  | Yes      |                     |
| Note:       | 1. Fps cannot be set to over 15 fps by cgi when it is 720P, but it can be set on web.(Camera Firmware Issue)<br>2. Sometimes setting by server is different with camera web. In fact, it sure has been set successfully.(Camera Firmware Issue)   |                   |          |                |       |        |     |                |      |          |                      |          |                     |
| TV-IP262PI  | refer to TV-IP262P(1.0.3)   | H.264 MJPEG       | 1        | 1280x1024      | 2-way | -      | -   | Yes            | Yes  | -        | Yes                  | Yes      | Supported by design |
| TV-IP310PI  | V5.0.1 140303   | H.264             | 1        | 2048x1536      | -     | -      | -   | Yes            | Yes  | -        | Yes                  | Yes      |                     |
| Note:       | 1. Second stream is unable to change bitrate. (Camera firmware issue)<br>2. Frame rate list over the corret range when the resolution is 2048x1536. (Camera fimware issue)<br>3. Second stream is unable to achieve maximun FPS, when resolution of main stream is 2048x1536. (Camera performance limitation) |                   |          |                |       |        |     |                |      |          |                      |          |                     |
| TV-IP311PI  | refer to TV-IP310PI(V5.0.1 140303)  | H.264             | 1        | 2048x1536      | -     | -      | -   | Yes            | Yes  | -        | Yes                  | Yes      | Supported by design |
| TV-IP572P   | refer to TV-IP672W(1.1.2)   | H.264 MJPEG MPEG4 | 1        | 1280x800       | 2-way | -      | Yes | Yes            | Yes  | -        | Yes                  | Yes      | Supported by design |
| TV-IP572PI  | refer to TV-IP672W(1.1.2)   | H.264 MJPEG MPEG4 | 1        | 1280x800       | 2-way | -      | Yes | Yes            | Yes  | -        | Yes                  | Yes      | Supported by design |
| TV-IP572W   | refer to TV-IP672W(1.1.2)   | H.264 MJPEG MPEG4 | 1        | 1280x800       | 2-way | -      | Yes | Yes            | Yes  | -        | Yes                  | Yes      | Supported by design |
| TV-IP572WI  | refer to TV-IP672W(1.1.2)   | H.264 MJPEG MPEG4 | 1        | 1280x800       | 2-way | -      | Yes | Yes            | Yes  | -        | Yes                  | Yes      | Supported by design |
| TV-IP672P   | refer to TV-IP672W(1.1.2)   | H.264 MJPEG MPEG4 | 1        | 1280x800       | 2-way | -      | Yes | Yes            | Yes  | -        | Yes                  | Yes      | Supported by design |
| TV-IP672PI  | refer to TV-IP672W(1.1.2)   | H.264 MJPEG MPEG4 | 1        | 1280x800       | 2-way | -      | Yes | Yes            | Yes  | -        | Yes                  | Yes      | Supported by design |
| TV-IP672W   | 1.1.2   | H.264 MJPEG MPEG4 | 1        | 1280x800       | 2-way | -      | Yes | Yes            | Yes  | -        | Yes                  | Yes      |                     |
| Note:       | 1. Camera response slow due to digest authentication.(Camera Performace Issue)<br>2. Image setting for saturation will fail.(Camera Firmware Issue)   |                   |          |                |       |        |     |                |      |          |                      |          |                     |
| TV-IP672WI  | refer to TV-IP672W(1.1.2)   | H.264 MJPEG MPEG4 | 1        | 1280x800       | 2-way | -      | Yes | Yes            | Yes  | -        | Yes                  | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name   | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|---------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| TCS-200       | Enc: V1.104A-035   | H.264        | 1        | 720x576        | 1-way | 2/2    | Yes | Yes            | -    | Yes                  |                     |
| TCS-2000      | Enc: V1.103C-005   | H.264 MJPEG  | 1        | 1920x1080      | 1-way | 2/2    | Yes | Yes            | -    | Yes                  |                     |
| TCS-300       | Enc: V1.103C-005   | H.264 MJPEG  | 1        | 720x576        | 1-way | 2/2    | Yes | Yes            | -    | Yes                  |                     |
| TCAM-3xx      | Enc: V1.103C-005   | H.264 MJPEG  | 1        | 720x576        | 1-way | 0/0    | Yes | Yes            | -    | Yes                  |                     |
| Note:         | 1. TCAM-330, TCAM-352 and TCAM-370 are compatible with TCAM-3xx<br>2. Do not support NTSC on TCAM-3xx  |              |          |                |       |        |     |                |      |                      |                     |
| TCAM-530      | Enc: V1.103C-005   | H.264 MJPEG  | 1        | 1920x1280      | 1-way | 1/1    | -   | Yes            | -    | Yes                  |                     |
| TCAM-531      | Enc: V1.103C-005   | H.264 MJPEG  | 1        | 1280x960       | 1-way | 1/1    | -   | Yes            | -    | Yes                  |                     |
| TCAM-531BIR   |  | H.264 MJPEG  | 1        | 1280x960       | 1-way | 1/1    | -   | Yes            | -    | Yes                  | Supported by design |
| TCAM-540      | Enc: V1.103C-006   | H.264 MJPEG  | 1        | 1920x1280      | 1-way | 1/1    | -   | Yes            | -    | Yes                  |                     |
| Note:         | Get severe broken image at the highest resolution 1920x1280, which will be improved in future new camera FW. (approx. three months later)  |              |          |                |       |        |     |                |      |                      |                     |
| TCAM-551      |  | H.264 MJPEG  | 1        | 1280x960       | 1-way | 1/1    | -   | Yes            | -    | Yes                  | Supported by design |
| TCAM-570      | Enc: V1.103A-031   | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 2/2    | Yes | Yes            | -    | Yes                  |                     |
| Note:         | The resolution for dual stream is 352x240, however, the quality is bad on 352x240 by connecting through HTTP. Please switch to other protocols.  |              |          |                |       |        |     |                |      |                      |                     |
| Note:         | All cameras: The video @ H.264 with TCP protocol is not smooth in the conditions of high resolution, fps and bitrate, which will be improved in future camera FW. (approx. three months later) |              |          |                |       |        |     |                |      |                      |                     |
| TN-B200CE     | Refer to TN-B202CEIR(V3.311R01)  | H.264        | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |
| TN-B202CEIR   | V3.311R01  | H.264        | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |
| TN-D1202CE    | Refer to TN-B202CEIR(V3.311R01)  | H.264        | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |
| TN-P1220CS    | Refer to TN-P1222CGPLX(V3.311R01)  | H.264        | 1        | 1920x1080      | 1-way | -      | Yes | Yes            | Yes  | Yes                  |                     |
| TN-P1222CGPLX | V3.311R01  | H.264        | 1        | 1920x1080      | 1-way | -      | Yes | Yes            | Yes  | Yes                  |                     |
| TN-P1230CS    | Refer to TN-P1222CGPLX(V3.311R01)  | H.264        | 1        | 1920x1080      | 1-way | -      | Yes | Yes            | Yes  | Yes                  |                     |



- : not available on camera  
\*1: not available on software  
\*2: not test on software  
For multi stream support:  
Yes: multi stream fix to 500kbps/100kbps  
Yes\*: multi stream setting support

| Device Name  | Tested Firmware                   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|--------------|-----------------------------------|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| TN-P3220CS   | Refer to TN-P1222CGPLX(V3.311R01) | H.264        | 1        | 1920x1080      | 1-way | -      | Yes | Yes            | Yes  | Yes                  |         |
| TN-P3220CSIR | V3.311R01                         | H.264        | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | Yes                  |         |
| TN-P3220CTIR | Refer to TN-P3220CSIR(V3.311R01)  | H.264        | 1        | 1920x1080      | 1-way | 4/2    | Yes | Yes            | Yes  | Yes                  |         |





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name  | Tested Firmware               | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|--------------|-------------------------------|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| IPE1100      |                               | H.264<br>MPEG4<br>M-JPEG | 1        | 720x582        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| IPE3100      |                               | H.264<br>MPEG4<br>M-JPEG | 1        | 768x576        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| IPE3500      |                               | H.264<br>MPEG4<br>M-JPEG | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| IPE3500M     | 1.6.7                         | H.264<br>MPEG4<br>M-JPEG | 1        | 1600x1200      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| IPE4100      | 1.6.6                         | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576        | 1-way | 4/2    | Yes | Yes            | Yes  | Yes                  |                     |
| IPE5500      |                               | H.264<br>MPEG4<br>M-JPEG | 1        | 752x582        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| IPE6500      |                               | H.264<br>MPEG4<br>M-JPEG | 1        | 752x582        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| IPE7500      |                               | H.264<br>MPEG4<br>M-JPEG | 1        | 752x582        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | Supported by design |
| IPN100HD     | 1.4.0.11                      | H.264<br>M-JPEG          | 1        | 1280x720       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| IPN1202HD    | Refer to IPN3502HD (1.4.0.11) | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| IPN2102HD    | Refer to IPN3502HD (1.4.0.11) | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| IPN302HD     | Refer to IPN3502HD (1.4.0.11) | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| IPN3102HD    | Refer to IPN3502HD (1.4.0.11) | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| IPN3202HD    | Refer to IPN3502HD (1.4.0.11) | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| IPN3502HD    | 1.4.0.11                      | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| IPN3502HD IR | Refer to IPN3502HD (1.4.0.11) | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| IPN6602HD    | Refer to IPN3502HD (1.4.0.11) | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| IPN6802HD    | Refer to IPN3502HD (1.4.0.11) | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| IPX3302HD    | Refer to IPN3502HD (1.4.0.11) | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| IPX3702HD    | Refer to IPN3502HD (1.4.0.11) | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  |                     |
| IPX4202HD    | 1.4.1.8                       | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |
| IPX4602HD    | Refer to IPX4202HD (1.4.1.8)  | H.264<br>M-JPEG          | 1        | 1920x1080      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------|
| NVC1000     | 1.6.7   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576        | 1-way | 2/2    | Yes | Yes            | Yes  | Yes                  |         |
| NVC4000     | 1.6.7   | H.264<br>MPEG4<br>M-JPEG | 4        | 720x576        | 1-way | 2/1    | Yes | Yes            | Yes  | Yes                  |         |
| Note:       | 1. NVC4000-R12 and NVC4000-R40 are compatible with NVC4000<br>2. NVC4000 is 4IP x 4channels video server  |                          |          |                |       |        |     |                |      |                      |         |
| Note:       | UDP cameras are likely disconnected if configuring camera parameter frequently. This is the known issue from camera vendor. When encountering this issue, please reboot the camera                          |                          |          |                |       |        |     |                |      |                      |         |
| Note:       | UDP cameras are likely disconnected if setting up highest quality. This is the known issue from camera vendor. When encountering this issue, please reboot the camera, and do not set up this configuration |                          |          |                |       |        |     |                |      |                      |         |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name  | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|--------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| NVS202       | 2014.10.14_v.1.1.5.20  | H.264 MJPEG  | 1        | 960x576        | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:        | NVS202:<br>1. Snapshot supported only when main stream is in MJPEG format. (Camera Limitation Issue)<br>2. Transfer camera to different network segment will lead upnp search fail until camera update the latest IP in 24 hours. (Camera Limitation Issue)<br>3. Bitrate setting cannot be set more than 2M bps when camera is 960H and H.264 format. (Camera Firmware Issue) |              |          |                |       |        |     |                |      |                      |          |                     |
| M2TiA        | VISION_2014.09.10_v.1.1.5.19   | H264         | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:        | M2TiA:<br>1. Snapshot are not supported due to camera limitation with 2nd stream format set to MJPEG. (Camera limitation issue)<br>2. Brightness setting is not synchronized with camera web. (Camera limitation issue)<br>3. When resolution of main stream is VGA, resolution of 2nd stream is not synchronized with camera web. (Camera firmware issue)                     |              |          |                |       |        |     |                |      |                      |          |                     |
| MTi          | VISION 1.1.5.10 20140109   | H264         | 1        | 1280x1024      | -     | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| VD102i       | refer to M2TiA(VISION N 1.1.5.10 20140109)   | H264         | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| VD10M2       | refer to M2TiA(VISION N_2014.09.10_v.1.1.5.19)   | H264         | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| VN10M2       | refer to M2TiA(VISION N_2014.09.10_v.1.1.5.19)   | H264         | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| VN200i       | refer to M2TiA(VISION N 1.1.5.10 20140109)   | H264         | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:        | 1. Do not support MJPEG setting.<br>2. M2TiA series H264 D1 resolution can't be set. (camera firmware issue)<br>3. Brightness value can be changed, but has no effect.<br>4. NUUO use dual mode as connection.   |              |          |                |       |        |     |                |      |                      |          |                     |
| VN6XSM2Ti-IR | refre to VN7XSM2Ti-IR(VISION_2014.09.10_v.1.1.5.19)  | H.264        | 1        | 1920x1080      | 2-way | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| VN7XSM2Ti-IR | VISION_2014.09.10_v.1.1.5.19   | H.264        | 1        | 1920x1080      | 2-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:        | VN7XSM2Ti-IR:<br>1. Snapshot are not supported due to camera limitation with 2nd stream format set to MJPEG. (Camera limitation issue)<br>2. Brightness setting is not synchronized with camera web. (Camera limitation issue)   |              |          |                |       |        |     |                |      |                      |          |                     |

|                           |   |                |   |           |       |     |     |     |     |      |     |                        |
|---------------------------|---|----------------|---|-----------|-------|-----|-----|-----|-----|------|-----|------------------------|
| <b>VISION i</b>           | IP VISION<br>1.1.0.16<br>20120316   | MJPEG<br>H264  | 1 | 720x480   | 1-way | 1/1 | -   | Yes | -   | Yes  | -   |                        |
| Note:                     | VISION i Camera : Sometimes audio from machine would fail, but there is chance to recover after reboot. (Hardware issue)  |                |   |           |       |     |     |     |     |      |     |                        |
| <b>Vision Mi</b>          | 1.1.2.46.   | MJPEG<br>H264  | 1 | 1280x720  | 1-way | 1/1 | -   | Yes | -   | Yes  | -   |                        |
| Note:                     | 1. Does not support Quality with MJPEG. (camera firmware issue)<br>2. When setup maximum setting of camera parameters, the real FPS could not reach original value on Web, such as 15 fps of H.264 within 1920x1080, 30 fps, and 7 quality; 5-6 fps of MJPEG within 1280x720, 30fps<br>3. Does not support audio setup  |                |   |           |       |     |     |     |     |      |     |                        |
| <b>VISION M3i</b>         | 1.1.2.46.   | MJPEG<br>H264  | 1 | 1920x1080 | -     | 1/0 | Yes | Yes | -   | Yes  | -   |                        |
| Note:                     | 1. Some M3i sub modeltype like VN7XSM3i has support PTZ. But VDA110SM3i not.<br>2. Does not support Quality with MJPEG. (camera firmware issue)<br>3. When setup maximum setting of camera parameters, the real FPS could not reach original value on Web, such as 15 fps of H.264 within 1920x1080, 30 fps, and 7 quality; 5-6 fps of MJPEG within 1280x720, 30fps |                |   |           |       |     |     |     |     |      |     |                        |
| <b>VISION NVS102</b>      | IP VISION<br>1.1.0.16<br>20120316   | MJPEG<br>H264  | 1 | 720x480   | 1-way | 1/1 | Yes | Yes | -   | Yes  | -   |                        |
| Note:                     | VISION NVS102:<br>Support both of NTSC/PAL, but can be switched only on camera web.<br>PTZ speed : pan setting = tilt setting. Change one of pan or tilt, and then the other will change, too.  |                |   |           |       |     |     |     |     |      |     |                        |
| <b>Vision M3Ti</b>        | 1.1.5.13<br>20140227  | H264           | 1 | QXGA      | 1-way | 1/1 | Yes | Yes | Yes | Yes  | -   |                        |
| Note:                     | 1. It can not use Autofocus function. (camera firmware issue)<br>2. It will not support audio setup. (camera firmware issue)  |                |   |           |       |     |     |     |     |      |     |                        |
| <b>VISION VDA101SM2Ti</b> | refre to<br>VN7XSM2Ti-<br>IR(VISION_2<br>014.09.10_v.<br>1.1.5.19)  | H.264          | 1 | 1920x1080 | 2-way | -   | -   | Yes | Yes | Yes  | -   | Supported<br>by design |
| <b>VPD202BM2Ti-IR</b>     | 1.1.5.20<br>20141113  | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 4/2 | Yes | Yes | Yes | Yes* | Yes |                        |
| Note:                     | VPD202BM2Ti-IR:<br>1. In triple mode, bitrate of 2nd stream cannot reach to 500kbps. (Camera limitation issue)<br>2. Snapshot is only supported when 2nd stream format is MJPEG. (Camera limitation issue)  |                |   |           |       |     |     |     |     |      |     |                        |
| <b>VISION VPD101PM2Ti</b> | refre to<br>VN7XSM2Ti-<br>IR(VISION_2<br>014.09.10_v.<br>1.1.5.19)  | H.264          | 1 | 1920x1080 | 2-way | -   | -   | Yes | Yes | Yes  | -   | Supported<br>by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name         | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|---------------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| VK2-1080BIR35V16e   | refer to VK2-1080VRDIR35V16e(1.1.8)   | H.264 MPEG4  | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| VK2-1080BIR37e      | refer to VK2-1080VRDIR35V16e(1.1.8)   | H.264 MPEG4  | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| VK2-1080BIR3V9F     | 2.0.3-T4_Release  | H.264 MPEG4  | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:               | 1. Cannot setup the resolution to 1280x1024 and 1280x720 of Stream2 when the resolution of Stream 1 is 1920x1080. (Camera firmware issue)<br>2. Cannot setup the resolution to 1920x1080 and 1280x720 of Stream2 when the resolution of Stream 1 is 1280x1024. (Camera firmware issue)<br>3. Cannot setup the resolution to 1920x1080 and 1280x1024 of Stream2 when the resolution of Stream 1 is 1280x720. (Camera firmware issue)<br>4. Cannot setup the resolution to "Same as Stream 1" when the resolution of Stream 1 is equal to Stream 2. (Camera firmware issue)<br>5. Camera is unable to achieve maximum 25 FPS. (Camera firmware issue) |              |          |                |       |        |     |                |      |                      |          |                     |
| VK2-1080VFD3V9F     | 2.2.4-T3_Release  | H.264 MPEG4  | 1        | 1920x1080      | -     | 1/0    | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:               | 1.VK21080VFD3V9F PTZ only support zoom & focus  |              |          |                |       |        |     |                |      |                      |          |                     |
| VK2-1080VFDIR37e    | refer to VK2-1080VRDIR35V16e(1.1.8)   | H.264 MPEG4  | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| VK2-1080VRD         | 2.2.64  | H.264 M-JPEG | 1        | 1920x1080      | 1-way | 2/0    | -   | Yes            | Yes  | Yes                  | -        |                     |
| VK2-1080VRD3V9      | 1.8.8-T4_Release  | H.264 MPEG4  | 1        | 1920x1080      | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| VK2-1080VRDIR3V9F   | 1.7.0-T4_release  | H.264 MPEG4  | 1        | 1920x1080      | 1-way | 1/0    | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| VK2-1080VRDIR35V16e | 1.1.8-T8_Release  | H.264 MPEG4  | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| VK2-1080VRDIR37e    | refer to VK2-1080VRDIR35V16e(1.1.8)   | H.264 MPEG4  | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes                  | Yes      | Supported by design |
| VK2-1080XVRDPTZ     | 1.2.1-X1_release  | H.264        | 1        | 1920x1080      | 1-way | 1/0    | Yes | Yes            | Yes  | Yes                  | Yes      |                     |
| VK2-2MPVRD          | 2.2.64  | H.264 M-JPEG | 1        | 1600x1200      | 1-way | 2/0    | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:               | VK2-1080VRD/VK2-2MPVRD: on-edge motion of video with M-JPEG codec works only as stream 1 is enabled on camera web.  |              |          |                |       |        |     |                |      |                      |          |                     |
| Note:               | VK2-1080VRD/VK2-2MPVRD: camera may be disconnected if users configure format as H.264 on one NVR and configure format M-JPEG on another.  |              |          |                |       |        |     |                |      |                      |          |                     |
| VK2-540VRD          | 2.1.8-release   | H.264 MPEG4  | 1        | 704x576        | 1-way | 1/0    | -   | Yes            | Yes  | Yes                  | -        |                     |
| VK2-600PTZ          | 2.1.8-release   | H.264 MPEG4  | 1        | 704x576        | 1-way | 1/0    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| Note:               | The operation of setting preset point is special because setting password is a must. We suggest users finish preset point settings on camera web.   |              |          |                |       |        |     |                |      |                      |          |                     |



- : not available on camera  
\*1: not available on software  
\*2: not test on software  
For multi stream support:  
Yes: multi stream fix to 500kbps/100kbps  
Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks |
|-------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------|
| VK2-VGAVFD  | 1.7.4-T2_release  | H.264 MPEG4  | 1        | 640x480        | -     | 1/0    | -   | Yes            | Yes  | Yes                  | -        |         |
| Note:       | All cameras: modifying parameter frequently may lead to camera shutdown due to slow CGI response.   |              |          |                |       |        |     |                |      |                      |          |         |
| Note:       | All cameras: the port value we get is always 80 via UPnP search, which implies the cameras would be disconnected if users change HTTP port to another number on camera web. |              |          |                |       |        |     |                |      |                      |          |         |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch  | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|----------------|-------|---------|-----|----------------|------|----------------------|----------|---------------------|
| AF5127      | Refer to FE8172  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1920      | 2-way | *2      | -   | Yes            | *2   | Yes*                 | -        | Supported by design |
| AF5127V     | Refer to FE8172  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1920      | 2-way | *2      | -   | Yes            | *2   | Yes*                 | -        | Supported by design |
| Note:       | AF5127 and AF5127V are fisheye camera                        |                          |          |                |       |         |     |                |      |                      |          |                     |
| AB5353H     | Refer to IP8335H   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 2-way | *2      | -   | Yes            | *2   | Yes*                 | -        | Supported by design |
| BB5315      | Refer to IP8335  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | -     | 1/0     | -   | Yes            | Yes  | Yes*                 | -        | Supported by design |
| BB5116      | Refer to IP8161  | H.264<br>MPEG4<br>M-JPEG | 1        | 1600x1200      | 2-way | 1/1     | Yes | Yes            | Yes  | Yes*                 | -        | Supported by design |
| BD5115      | Refer to FD8134  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | -     | 1/0     | -   | Yes            | Yes  | Yes*                 | -        | Supported by design |
| CC8130      | 0100d  | H.264<br>M-JPEG          | 1        | 1280x800       | 1-way | 0/0     | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | fisheye camera   |                          |          |                |       |         |     |                |      |                      |          |                     |
| FD61x1      |  | MPEG4<br>M-JPEG          | 1        | 720x480        | 1-way | 1/1     | -   | Yes            | Yes  | -                    | -        | Supported by design |
| FD61x2      |  | MPEG4<br>M-JPEG          | 1        | 720x480        | 1-way | 1/1     | -   | Yes            | Yes  | -                    | -        | Supported by design |
| FD7130      | 0100e  | MPEG4<br>M-JPEG          | 1        | 640x480        | -     | -       | -   | Yes            | Yes  | Yes                  | -        |                     |
| FD7131      |  | MPEG4<br>M-JPEG          | 1        | 720x480        | 1-way | 1/1     | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| FD7132      | 0100f  | MPEG4<br>M-JPEG          | 1        | 640x480        | -     | 1/1     | -   | Yes            | Yes  | Yes                  | -        |                     |
| FD7141      | 0100g  | MPEG4<br>M-JPEG          | 1        | 720x480        | -     | 1/1     | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | MPEG4: Unable to connect through HTTP.                       |                          |          |                |       |         |     |                |      |                      |          |                     |
| FD7160      |  | MPEG4<br>M-JPEG          | 1        | 1600x1200      | -     | -       | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| FD8131      | Refer to FD8133  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | -     | 1/0     | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| FD8131V     | 0300d  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | -     | *2      | -   | Yes            | *2   | Yes*                 | Yes      |                     |
| FD8133      | Refer to FD8134  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | -     | 1/0     | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| FD8134      | 0100e  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | -     | 1/0     | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | FD8134-SS and FD8134-V are compatible with PD8134            |                          |          |                |       |         |     |                |      |                      |          |                     |
| FD8135H     | 0202C  | MPEG4<br>M-JPEG<br>H.264 | 1        | 1280x800       | 2-way | 3/1     | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | FW will casue I/O status incorrect and wrong resolution list |                          |          |                |       |         |     |                |      |                      |          |                     |
| FD8136      | 0100f  | MPEG4<br>M-JPEG<br>H.264 | 1        | 1280x800       | 1-way | 1/0     | Yes | Yes            | Yes  | Yes*                 | Yes      | Tested by link      |
| FD8137H     | 0101a  | H.264<br>M-JPEG          | 1        | 1280x800       | 1-way | 1/0(*2) | -   | Yes            | *2   | Yes*                 | Yes      |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch  | PTZ  | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------|----------|----------------|-------|---------|------|----------------|------|----------------------|----------|---------------------|
| FD8137HV    | Refer to FD8137H(0101a)  | H.264 M-JPEG       | 1        | 1280x800       | 1-way | 1/0(*2) | -    | Yes            | *2   | Yes*                 | Yes      | Supported by design |
| FD8138-H    | Refer to IB8338-H(0100e)   | H.264 M-JPEG       | 1        | 1280x800       | 2-way | 1/1     | -    | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| FD8151V     | 0100c  | H.264 M-JPEG       | 1        | 1280x1024      | 1-way | *2      | -    | Yes            | *2   | Yes*                 | Yes      | Tested by link      |
| FD8154      | 0100d  | H.264 MJPEG        | 1        | 1280x1024      | 1-way | 1/0     | -    | Yes            | Yes  | Yes*                 | Yes      |                     |
| FD8155H     | Refer to IP816A-HP(0100f)  | H.264 M-JPEG       | 1        | 1920x1080      | 2-way | 3/1     | Yes* | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| FD8161      | 0100h  | H.264 MPEG4 M-JPEG | 1        | 1600x1200      | 2-way | 1/1     | -    | Yes            | Yes  | Yes*                 | Yes      |                     |
| FD8162      | Refer to FD8362  | H.264 MPEG4 M-JPEG | 1        | 1920x1080      | 2-way | 1/1     | Yes  | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| FD8163      | 0101b  | H.264 MPEG4 M-JPEG | 1        | 1920x1080      | 2-way | *2      | -    | Yes            | *2   | Yes*                 | Yes      | Tested by link      |
| FD8164      | 0100d  | H.264 M-JPEG       | 1        | 1920x1080      | 1-way | 1/0     | -    | *2             | *2   | Yes*                 | Yes      | Tested by link      |
| FD8165H     | Refer to IP816A-HP(0100f)  | H.264 M-JPEG       | 1        | 1920x1080      | 2-way | 3/1     | Yes* | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| FD8166      | 0100g  | H.264 M-JPEG       | 1        | 1920x1080      | 1-way | *2      | -    | Yes            | *2   | Yes*                 | Yes      |                     |
| FD8168      | 0100e  | H.264 MJPEG        | 1        | 1920x1080      | 1-way | -       | -    | Yes            | *2   | Yes*                 | Yes      |                     |
| FD8169      | 0100f  | H.264 M-JPEG       | 1        | 1920x1080      | -     | -       | -    | Yes            | *2   | Yes*                 | Yes      |                     |
| FD8171      | 0100e  | H.264 MPEG4 M-JPEG | 1        | 2048x1536      | 1-way | *2      | -    | Yes            | *2   | Yes*                 | Yes      |                     |
| FD8181      | Refer to FD8381-EV(0101c)  | H.264 MJPEG        | 1        | 2560x1920      | 2-way | 1/1     | -    | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| FE8181      | 0200b  | H.264 MPEG4 M-JPEG | 1        | 1920x1920      | 2-way | 1/1     | Yes  | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | Fisheye camera<br>1. PTZ only support zoom.<br>2. Brightness & Contrast range is not synchronize with web.(Camera Firmware issue)<br>3. Snapshot will save stream3's resolution. (Camera Firmware issue) |                    |          |                |       |         |      |                |      |                      |          |                     |
| FD8335H     | 0101a  | H.264 MPEG4 M-JPEG | 1        | 1200x800       | 2-way | 3/1     | -    | Yes            | Yes  | Yes*                 | Yes      | Tested by link      |
| FD8338-HV   | Refer to IB8338-H(0100e)   | H.264 M-JPEG       | 1        | 1280x800       | 2-way | 1/1     | -    | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| FD8355EHV   | Refer to IP816A-HP(0100f)  | H.264 M-JPEG       | 1        | 1920x1080      | 2-way | 3/1     | Yes* | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| FD8355EHV   | 0100e  | H.264 M-JPEG       | 1        | 1280x1024      | 2-way | *2      | -    | Yes            | *2   | Yes*                 | Yes      | Tested by link      |





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ  | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|----------------|-------|--------|------|----------------|------|----------------------|----------|---------------------|
| FD8361      | 0100d1   | H.264<br>MPEG5<br>M-JPEG | 1        | 1600x1200      | 2-way | 1/1    | -    | Yes            | Yes  | Yes*                 | Yes      |                     |
| note:       | FD8361 can't set other resolution on stream 3. (camera FW 0202b fixed.)  |                          |          |                |       |        |      |                |      |                      |          |                     |
| Note:       | FD8361L is compatible with PD8361  |                          |          |                |       |        |      |                |      |                      |          |                     |
| FD8362      | 0100f  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way | 1/1    | Yes  | Yes            | Yes  | Yes*                 | Yes      |                     |
| FD8362E     | Refer to FD8362  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way | 1/1    | Yes  | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| FD8363      | 0102a  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way | 1/1    | -    | Yes            | Yes  | Yes*                 | Yes      |                     |
| FD8365EHV   | Refer to IP816A-HP(0100f)  | H.264<br>M-JPEG          | 1        | 1920x1080      | 2-way | 3/1    | Yes* | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| FD8365EHV   | 0100g  | M-JPEG<br>H.264          | 1        | 1920x1080      | 2-way | *2     | -    | Yes            | *2   | Yes*                 | Yes      | Tested by link      |
| FD8367-V    | 0101b  | M-JPEG<br>H.264          | 1        | 1920x1080      | 2-way | 1/1    | -    | Yes            | Yes  | Yes*                 | Yes      |                     |
| FD8367-TV   | 0101b  | M-JPEG<br>H.264          | 1        | 1920x1080      | 2-way | 1/1    | -    | Yes            | Yes  | Yes*                 | Yes      |                     |
| FD8371EV    | 0100i  | H.264<br>MPEG4<br>M-JPEG | 1        | 2048x1536      | 2-way | 1/1    | -    | Yes            | Yes  | Yes*                 | Yes      |                     |
| FD8372      | 0100f  | H.264<br>MPEG4<br>M-JPEG | 1        | 2560x1920      | 2-way | 3/1    | -    | Yes            | Yes  | Yes*                 | Yes      | Tested by link      |
| Note:       | Mpeg4 support first 2 maximum resolutions are 1920x1920 & 1920x1536  |                          |          |                |       |        |      |                |      |                      |          |                     |
| FD8381-EV   | 0101c  | H.264<br>MJPEG           | 1        | 2560x1920      | 2-way | 1/1    | -    | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | <ol style="list-style-type: none"> <li>1. When resolution large than 2048x2048, we don't support audio. (Camera firmware issue)</li> <li>2. Audio has noise. (Camera firmware issue)</li> <li>3. Snapshot's resolution is same as stream 3. (Camera limitation)</li> <li>4. Camera is unable to achieve high FPS.(Camera performance limitation)</li> <li>5. Smart stream will set fail. (Camera firmware issue)</li> </ol>                                      |                          |          |                |       |        |      |                |      |                      |          |                     |
| FE8171      | 0100d  | H.264<br>MPEG4<br>M-JPEG | 1        | 1600x1200      | 2-way | 1/1    | -    | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | fisheye camera   |                          |          |                |       |        |      |                |      |                      |          |                     |
| FE8172      | FE8172-VVTK-0100f  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1920      | 2-way | 1/1    | -    | -              | -    | Yes*                 | Yes      |                     |
| Note:       | <ol style="list-style-type: none"> <li>1. Not support CBR mode</li> <li>2. MJPEG not support audio</li> <li>3. Not support AAC audio</li> <li>4. When resolution is 1360x786, video stream would have a white line at the left-bottom of the frame.</li> <li>5. If set to Full HD mode, the low profile video stream would have a color line at the bottom of frame.</li> <li>6. Link can not test UPnP, motion detection.</li> <li>7. Fisheye camera</li> </ol> |                          |          |                |       |        |      |                |      |                      |          |                     |
| FE8172V     | Refer to FE8172  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1920      | 2-way | *2     | -    | -              | *2   | Yes*                 | Yes      |                     |
| FE8173      | 0100c  | H.264<br>MPEG4<br>M-JPEG | 1        | 1536x1536      | 2-way | *2     | -    | Yes            | *2   | Yes*                 | Yes      |                     |
| Note:       | fisheye camera   |                          |          |                |       |        |      |                |      |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name     | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-----------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| FE8174          | 0100e  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1920      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:           | fisheye camera   |                          |          |                |       |        |     |                |      |                      |          |                     |
| FE8174V         | Refer to<br>FE8174(0100e)  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1920      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| Note:           | fisheye camera   |                          |          |                |       |        |     |                |      |                      |          |                     |
| FE8180          | 0100f  | H.264<br>MJPEG           | 1        | 1920x1920      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:           | 1.The list of camera Mount Type is not synchronized with the one on camera's web.(Camera Firmware issue)<br>2. Frame rate can not achieve to setting value. (Camera performance limitation)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| FE8391-V        | 0100f  | H.264<br>MJPEG           | 1        | 2944x2944      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:           | 1. Camera is unable to achieve maximum FPS and Bit rate.(Camera performance limitation)<br>2. Talk has noise.(Camera performance limitation)<br>3.The list of camera bit rate control is not synchronized with the one on camera's web.(Camera Firmware issue) |                          |          |                |       |        |     |                |      |                      |          |                     |
| Generic         | 0101b  | H.264<br>MPEG4<br>M-JPEG | 1        | All            | 1-way | 8/8    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:           | Support generic dewarp   |                          |          |                |       |        |     |                |      |                      |          |                     |
| IB8338-H        | 0100e  | H.264<br>M-JPEG          | 1        | 1280x800       | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:           | 1. Audio has noise. (Camera firmware issue)<br>2. Snapshot's resolution is same as stream 3. (Camera limitation)<br>3. Smart stream will set fail. (Camera firmware issue)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| IB8367-RT       | 0100f  | H.264<br>MJPEG           | 1        | 1920x1080      | *2    | *2     | -   | *2             | *2   | Yes*                 | *2       |                     |
| IB8369          | 0100f  | H.264<br>M-JPEG          | 1        | 1920x1080      | -     | -      | -   | Yes            | *2   | Yes*                 | Yes      |                     |
| Note:           | Video parameter's range is displayed incorrectly. (Camera firmware issue)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| IB8381          | Refer to<br>FD8381-<br>EV(0101c)   | H.264<br>MJPEG           | 1        | 2560x1920      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| IP21x1          |  | M-JPEG                   | 1        | 720x576        | -     | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP21x2          |  | M-JPEG                   | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP3132          |  | H.263                    | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP3133          |  | H.263                    | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP3135          |  | H.263                    | 1        | 720x576        | 1-way | -      | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP3135-<br>PLNK |  | H.263                    | 1        | 720x576        | 1-way | 1/2    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP3136          |  | H.263                    | 1        | 720x576        | 1-way | -      | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP3136-<br>PLNK |  | H.263                    | 1        | 720x576        | 1-way | 1/2    | -   | Yes            | Yes  | -                    | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|-----------------|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| IP3137      |                 | H.263        | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP31x1      |                 | H.263        | 1        | 720x576        | -     | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP31x1TLFN  |                 | H.263        | 1        | 720x576        | -     | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP31x2      |                 | H.263        | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP31x7      |                 | H.263        | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP51x2      |                 | MPEG4        | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP51x4      |                 | MPEG4        | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP6114      |                 | MPEG4 M-JPEG | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP6124      |                 | MPEG4 M-JPEG | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP61x2      |                 | MPEG4 M-JPEG | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP61x4      |                 | MPEG4 M-JPEG | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP61X7      |                 | MPEG4 M-JPEG | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP7130      | 0100c           | MPEG4 M-JPEG | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| IP7131      |                 | MPEG4        | 1        | 704x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP7132      |                 | MPEG4        | 1        | 704x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP7133      | 0100b           | MPEG4 M-JPEG | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| IP7134      | 0100b           | MPEG4 M-JPEG | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| IP7135      |                 | MPEG4        | 1        | 704x576        | 1-way | -      | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP7137      |                 | MPEG4        | 1        | 704x576        | 1-way | -      | -   | Yes            | Yes  | -                    | -        | Supported by design |
| IP7138      | 0101h           | MPEG4 M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| IP7139      |                 | MPEG4 M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| IP7142      |                 | MPEG4 M-JPEG | 1        | 704x576        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| IP7151      |                 | MPEG4 M-JPEG | 1        | 704x576        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ  | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|------|----------------|------|----------------------|----------|---------------------|
| IP7152      |   | MPEG4<br>M-JPEG          | 1        | 704x576        | 1-way | 1/1    | -    | Yes            | Yes  | Yes                  | -        | Supported by design |
| IP7153      |   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -    | Yes            | Yes  | Yes                  | -        | Supported by design |
| IP7154      | 0100b   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | Yes  | Yes            | Yes  | Yes                  | -        |                     |
| IP7160      | 0101b   | MPEG4<br>M-JPEG          | 1        | 1600x1200      | 1-way | 1/1    | -    | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | IP7160-SS is compatible with IP7160   |                          |          |                |       |        |      |                |      |                      |          |                     |
| IP7161      |   | MPEG4<br>M-JPEG          | 1        | 1600x1200      | 1-way | 1/1    | -    | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:       | IP7161-SS is compatible with IP7161   |                          |          |                |       |        |      |                |      |                      |          |                     |
| IP71x7      |   | MPEG4                    | 1        | 704x576        | 1-way | 1/1    | -    | Yes            | Yes  | -                    | -        | Supported by design |
| IP7251      | 0100f   | MPEG4                    | 1        | 640x480        | 1-way | 1/1    | Yes  | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | MPEG4: Unable to connect through HTTP.  |                          |          |                |       |        |      |                |      |                      |          |                     |
| IP7330      |   | MPEG4<br>M-JPEG          | 1        | 640x480        | -     | 1/0    | -    | Yes            | Yes  | Yes                  | -        | Supported by design |
| IP7361      |   | MPEG4<br>M-JPEG          | 1        | 1600x1200      | 1-way | 1/1    | -    | Yes            | Yes  | Yes                  | -        | Supported by design |
| IP8130      | 0100e   | H.264<br>M-JPEG          | 1        | 1280x800       | 2-way | *2     | -    | Yes            | *2   | Yes*                 | Yes      |                     |
| IP8130W     | Refer to IP8130(0100e)  | H.264<br>M-JPEG          | 1        | 1280x800       | 2-way | *2     | -    | Yes            | *2   | Yes*                 | Yes      | Supported by design |
| IP8131      | Refer to IP8131W(0100e)   | H.264<br>M-JPEG          | 1        | 1280x800       | 2-way | *2     | -    | Yes            | *2   | Yes*                 | Yes      | Supported by design |
| IP8131W     | 0100e   | H.264<br>M-JPEG          | 1        | 1280x800       | 2-way | *2     | -    | Yes            | *2   | Yes*                 | Yes      |                     |
| IP8132      |   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 2-way | 1/0    | -    | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| IP8133W     | 0100c   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 2-way | 1/1    | -    | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| Note:       | Due to the parameter limitation of stream 1, we take stream 2 as main stream for recording and liveview.  |                          |          |                |       |        |      |                |      |                      |          |                     |
| IP8151      | 0200a   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 2-way | 1/1    | Yes  | Yes            | Yes  | Yes*                 | Yes      | *                   |
| Note:       | 1. IP8151-SS and IP8151P are compatible with IP8151<br>2. This camera FW is under testing by manufacturer, so there are two issues existed which should be fixed in the official release: video stream of M-JPEG is not continuous; there is an image problem on resolution 176x144 @H.264. |                          |          |                |       |        |      |                |      |                      |          |                     |
| IP8152      | 0100e   | H.264<br>M-JPEG          | 1        | 1280x1024      | 2-way | 1/0    | Yes  | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | IP8152: CGI return a wrong PTZ capability   |                          |          |                |       |        |      |                |      |                      |          |                     |
| IP8155HP    | Refer to IP816A-HP(0100f)   | H.264<br>M-JPEG          | 1        | 1920x1080      | 2-way | 3/1    | Yes* | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| IP8155HP    | 0100d   | H.264<br>M-JPEG          | 1        | 1280x1024      | 2-way | 3/1    | -    | Yes            | Yes  | Yes*                 | Yes      |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio         | I/O Ch  | PTZ  | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|---------------|---------|------|----------------|------|----------------------|----------|---------------------|
| IP816A-HP   | 0100f   | H.264<br>M-JPEG          | 1        | 1920x1080      | 2-way         | 3/1     | Yes* | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Audio has noise. (Camera firmware issue)<br>2. Snapshot's resolution is same as stream 3. (Camera limitation)<br>3. Camera is unable to achieve high FPS. (Camera performance limitation)<br>4. Can't use Home. (Camera firmware issue)<br>5. PTZ speed range will not sync. with web. (Camera firmware issue) |                          |          |                |               |         |      |                |      |                      |          |                     |
| IP8161      | 0100k   | H.264<br>MPEG4<br>M-JPEG | 1        | 1600x1200      | 2-way         | 1/1     | Yes  | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | IP8161-SS is compatible with IP8161   |                          |          |                |               |         |      |                |      |                      |          |                     |
| IP8162      | 0100f   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way         | 1/1     | -    | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. IP8162-SS and IP8162P are compatible with IP8162<br>2. The frame rate of main stream decrease to the half if watching dual stream video, which is the limitation of camera HW<br>3. MJPEG not support audio, Not support AAC audio   |                          |          |                |               |         |      |                |      |                      |          |                     |
| IP8165HP    | Refer to<br>IP816A-<br>HP(0100f)  | H.264<br>M-JPEG          | 1        | 1920x1080      | 2-way         | 3/1     | Yes* | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| IP8165HP    | 0100d   | H.264<br>M-JPEG          | 1        | 1920x1080      | 2-way         | 3/1     | -    | Yes            | Yes  | Yes*                 | Yes      |                     |
| IP8172      | 0100a0  | MPEG4<br>M-JPEG<br>H.264 | 1        | 2560x1920      | 2-way         | 1/1     | -    | Yes            | Yes  | Yes*                 | Yes      |                     |
| IP8173H     | 0100i   | MPEG4<br>M-JPEG<br>H.264 | 1        | 2048x1536      | 2-<br>way(*2) | 1/0(*2) | *2   | Yes            | *2   | Yes*                 | Yes      |                     |
| IP8330      | 0100e   | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | -             | 1/0     | -    | Yes            | Yes  | Yes*                 | Yes      |                     |
| IP8331      | 0100c   | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | -             | 1/0     | -    | Yes            | Yes  | Yes*                 | Yes      |                     |
| IP8332      |   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | -             | 1/0     | -    | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| Note:       | IP8332-SS is compatible with IP8332   |                          |          |                |               |         |      |                |      |                      |          |                     |
| IP8335H     | 0100h   | MPEG4<br>M-JPEG<br>H.264 | 1        | 1280x800       | 2-way         | 3/1     | -    | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | IP8335H: Audio, I/O, Upnp ,PTZ can't testing by link<br>Use Vivotek 2nd stream with MPEG4 format as NUUO main stream and Vivotek 1st stream as NUUO 2nd stream  |                          |          |                |               |         |      |                |      |                      |          |                     |
| IP8336W     | 0102b   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way         | 1/0(*2) | -    | Yes            | *2   | Yes*                 | Yes      |                     |
| IP8337H-C   | 0100b   | H.264<br>M-JPEG          | 1        | 1280x800       | -             | 1/0(*2) | -    | Yes            | *2   | Yes*                 | Yes      |                     |
| IP8352      | 0100g   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 2-way         | 1/1     | -    | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| Note:       | I/O status is abnormal, which input and output cannot be triggered at the same time. Vivotek will fix the bug in next release, please upgrade to new camera FW then.  |                          |          |                |               |         |      |                |      |                      |          |                     |
| IP8355EH    | Refer to<br>IP816A-<br>HP(0100f)  | H.264<br>M-JPEG          | 1        | 1920x1080      | 2-way         | 3/1     | Yes* | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| IP8355EH    | 0100e   | H.264<br>MJPEG           | 1        | 1280x1024      | 1-way         | *2      | -    | Yes            | *2   | Yes*                 | Yes      |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio     | I/O Ch  | PTZ  | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|----------------|-----------|---------|------|----------------|------|----------------------|----------|---------------------|
| IP8361      | 0100c  | H.264<br>MPEG4<br>M-JPEG | 1        | 1600x1200      | 2-way     | 1/1     | -    | Yes            | Yes  | Yes*                 | Yes      | Tested by link      |
| IP8362      | 0100d  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way     | 1/0     | -    | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| IP8364      | 0101a  | H.264<br>M-JPEG          | 1        | 1920x1080      | -         | 1/0(*2) | -    | Yes            | *2   | Yes*                 | Yes      |                     |
| IP8365EH    | Refer to IP816A-HP(0100f)  | H.264<br>M-JPEG          | 1        | 1920x1080      | 2-way     | 3/1     | Yes* | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| IP8365EH    | 0100e  | H.264<br>MJPEG           | 1        | 1920x1080      | 1-way     | *2      | -    | Yes            | *2   | Yes*                 | Yes      |                     |
| IP8371E     | 0100g  | MPEG4<br>M-JPEG<br>H.264 | 1        | 2048x1536      | 2-way(*2) | 1/1(*2) | -    | *2             | *2   | Yes*                 | Yes      |                     |
| IP8372      | 0100e  | MPEG4<br>M-JPEG<br>H.264 | 1        | 2560x1920      | 2-way     | *2      | -    | Yes            | *2   | Yes*                 | Yes      | Tested by link      |
| IZ7151      |  | MPEG4<br>M-JPEG          | 1        | 704x576        | 1-way     | 1/1     | Yes  | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:       | PTZ Support: zoom only.  |                          |          |                |           |         |      |                |      |                      |          |                     |
| MD7530      | 0100d  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way     | 1/0     | -    | Yes            | Yes  | Yes                  | -        |                     |
| MD7560      | 0100c  | H.264<br>MPEG4<br>M-JPEG | 1        | 1600x1200      | 1-way     | 1/0     | -    | Yes            | Yes  | Yes                  | -        |                     |
| MD7560X     | Refer to MD7560  | H.264<br>MPEG4<br>M-JPEG | 1        | 1600x1200      | 1-way     | 1/0     | -    | Yes            | Yes  | Yes                  | -        | Supported by design |
| MD8531H     | 0100h  | MPEG4<br>M-JPEG<br>H.264 | 1        | 1280x960       | 2-way     | *2      | -    | Yes            | *2   | Yes*                 | Yes      |                     |
| Note:       | Video parameter setting is incorrect displayed.  |                          |          |                |           |         |      |                |      |                      |          |                     |
| MD8562      | 0100c  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way     | 1/0     | -    | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | The frame rate of main stream decrease to the half if watching dual stream video, which is the limitation of camera HW.  |                          |          |                |           |         |      |                |      |                      |          |                     |
| MS8391-EV   | 0100e  | H.264<br>MJPEG           | 1        | 7552x1416      | *2        | *2      | -    | *2             | *2   | Yes*                 | *2       |                     |
| Note:       | 1. Framerate lists can not sync with web in resolution 768x144 & 7552x1416. (Camera Firmware Issue)<br>2. Brightness & Contrast range can not sync with web. (Camera Firmware Issue)<br>3. Camera is unable to achieve maximum FPS in maximum parameter. (Camera performance limitation) |                          |          |                |           |         |      |                |      |                      |          |                     |
| PD8136      | 0100e  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way     | 0/0     | Yes  | Yes            | *2   | Yes*                 | Yes      |                     |
| Note:       | PD8136: No support zoom.   |                          |          |                |           |         |      |                |      |                      |          |                     |
| PT3134      |  | H.263                    | 1        | 720x576        | 1-way     | 1/1     | Yes  | Yes            | Yes  | -                    | -        | Supported by design |
| PT31x2      |  | H.263                    | 1        | 720x576        | 1-way     | 1/1     | Yes  | Yes            | Yes  | -                    | -        | Supported by design |
| PT31x3      |  | H.263                    | 1        | 720x576        | 1-way     | 1/1     | Yes  | Yes            | Yes  | -                    | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware                        | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| PT31x4      |  | H.263                    | 1        | 720x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design |
| PT31x7      |  | H.263                    | 1        | 720x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design |
| PT7000      |  | MPEG4                    | 1        | 720x576        | 1-way | -      | Yes | Yes            | Yes  | -                    | -        | Supported by design |
| PT7135      |  | MPEG4                    | 1        | 720x576        | 1-way | -      | Yes | Yes            | Yes  | -                    | -        | Supported by design |
| PT7137      |  | MPEG4                    | 1        | 704x576        | 1-way | -      | Yes | Yes            | Yes  | -                    | -        | Supported by design |
| PT8133      | 0100g                                  | MPEG4<br>M-JPEG<br>H.264 | 1        | 1280x800       | 1-way | -      | Yes | Yes            | Yes  | Yes                  | Yes      | Tested by link      |
| PZ61x2      |  | MPEG4<br>M-JPEG          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design |
| PZ61x4      |  | MPEG4<br>M-JPEG          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design |
| PZ7131      | 0100b                                  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| PZ7132      |  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| PZ7151      | 0101b                                  | MPEG4<br>M-JPEG          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | MPEG4: Unable to connect through HTTP. |                          |          |                |       |        |     |                |      |                      |          |                     |
| PZ7152      |  | MPEG4<br>M-JPEG          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| PZ71X1      |  | MPEG4<br>M-JPEG          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| PZ71X2      |  | MPEG4<br>M-JPEG          | 1        | 704x576        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| PZ81x1      | 0100e                                  | H.264<br>MPEG4<br>M-JPEG | 1        | 720x480        | 2-way | 3/2    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| PZ81x1W     | Refer to PZ81x1                        | H.264<br>MPEG4<br>M-JPEG | 1        | 720x480        | 2-way | 3/2    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| SD61x2      |  | MPEG4<br>M-JPEG          | 1        | 720x576        | 1-way | 4/1    | Yes | Yes            | Yes  | -                    | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| SD7151      | 0101d   | MPEG4<br>M-JPEG          | 1        | 720x576        | 1-way | 4/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | No audio support in M-JPEG format.<br>MPEG4: Unable to connect through HTTP.  |                          |          |                |       |        |     |                |      |                      |          |                     |
| SD73X3      |   | MPEG4<br>M-JPEG          | 1        | 704x576        | 1-way | 4/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| SD81X1      | 0100e   | MPEG4<br>M-JPEG          | 1        | 704x576        | 2-way | 4/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. SD81x1-SS is compatible with SD81x1<br>2. SD81X1 : Audio, I/O, Upnp can't testing by link  |                          |          |                |       |        |     |                |      |                      |          |                     |
| SD8362E     | 0104a   | MPEG4<br>M-JPEG<br>H.264 | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      | Tested by link      |
| Note:       | 1. SD8362 and SD8362E-SS is compatible with SD8362E<br>2. SD8362E : Audio, I/O, Upnp can't testing by link<br>3. Work with SF8172 as PPTZ model   |                          |          |                |       |        |     |                |      |                      |          |                     |
| SD8363E     | 0202b   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way | *2     | Yes | Yes            | *2   | Yes*                 | Yes      |                     |
| Note:       | 1.Work with SF8172 as PPTZ model<br>2.Video parameter setting is incorrect displayed.   |                          |          |                |       |        |     |                |      |                      |          |                     |
| SD83x1E     | Refer to SD83x3   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x480        | 2-way | 3/2    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| Note:       | SD83x1E and SD83x2E are detected as SD83x3  |                          |          |                |       |        |     |                |      |                      |          |                     |
| SD83x2E     | Refer to SD83x3   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x480        | 2-way | 3/2    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| Note:       | SD83x1E and SD83x2E are detected as SD83x3  |                          |          |                |       |        |     |                |      |                      |          |                     |
| SD83x3      | 0102d   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x480        | 2-way | 3/2    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | SD83x3E-SS and SD83x3E are compatible with SD83x3   |                          |          |                |       |        |     |                |      |                      |          |                     |
| SD83x4      | 0200c   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x480        | 2-way | 4/2    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| SD83x6      | 0200c   | H.264<br>MPEG4<br>M-JPEG | 1        | 720x480        | 2-way | 4/2    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| SD8364E     | 0200d   | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 2-way | *2     | Yes | Yes            | *2   | Yes*                 | Yes      |                     |
| SF8172      | 0100d   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1920      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| SF8172V     | Refer to SF8172   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1920      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| Note:       | SF8172 and SF8172V:<br>1. Support PPTZ.<br>2. Fisheye camera.<br>3. The first 1080p stream connection to camera can reach up to 30 fps, but the second 1080p stream connection can't. It is because of the constrain by CPU decode performance of camera. |                          |          |                |       |        |     |                |      |                      |          |                     |





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| SF8174      | 0100c   | MPEG4<br>M-JPEG<br>H.264 | 1        | 1920x1920      | 2-way | *2     | -   | Yes            | *2   | Yes*                 | Yes      |                     |
| Note:       | 1. SD8363E and SF8174 as PPTZ<br>2. Fisheye camera.   |                          |          |                |       |        |     |                |      |                      |          |                     |
| TC5331      |   | MPEG4                    | 1        | 720x576        | 1-way | -      | -   | Yes            | Yes  | -                    | -        | Supported by design |
| TC5630      |   | MPEG4                    | 1        | 720x576        | 1-way | -      | -   | Yes            | Yes  | -                    | -        | Supported by design |
| TC5631      |   | MPEG4                    | 1        | 720x576        | 1-way | -      | -   | Yes            | Yes  | -                    | -        | Supported by design |
| VS2101      |   | M-JPEG                   | 1        | 720x576        | -     | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| VS2401      |   | M-JPEG                   | 4        | 720x576        | -     | 4/2    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| VS2402      |   | M-JPEG                   | 4        | 720x576        | -     | 4/2    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| VS2403      | 0103b   | M-JPEG                   | 4        | 720x576        | 1-way | 4/4    | Yes | Yes            | Yes  | -                    | -        |                     |
| VS3100      |   | H.263                    | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| VS3101      |   | H.263                    | 1        | 720x576        | -     | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| VS3102      |   | H.263                    | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| VS3102-XLTH |   | H.263                    | 1        | 720x576        | 1-way | 1/1    | -   | Yes            | Yes  | -                    | -        | Supported by design |
| VS7100      | 0101e   | MPEG4<br>M-JPEG          | 1        | 720x576        | -     | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| Note        | MPEG4: Unable to connect through HTTP.  |                          |          |                |       |        |     |                |      |                      |          |                     |
| VS8100      | 0100g   | H.264<br>MJPEG           | 1        | 720x576        | 1-way | 0/0    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| VS8102      | 0202c2  | H.264<br>MPEG4<br>M-JPEG | 1        | 720x576        | 2-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| VS8401      | 0201b   | H.264<br>MPEG4<br>M-JPEG | 4        | 720x480        | 2-way | 4/4    | Yes | Yes            | -    | Yes*                 | Yes      |                     |
| VS8801      | 0202a3  | H.264<br>MPEG4<br>M-JPEG | 8        | 720x576        | 2-way | 8/8    | Yes | Yes            | Yes  | Yes*                 | Yes      | *                   |
| Note:       | VS8801:<br>1. PTZ will be no response when Tilt speed 1~3<br>2. PTZ will be speed down when Pan speed 4~5   |                          |          |                |       |        |     |                |      |                      |          |                     |
| Note        | 1. One of the cameras in the system must support I/O functions in order to enable the snapshot feature. This is a known issue and we are looking to fix it with the next product version update.<br>2. Smart stream function support only if Vivotek camera supports this function. |                          |          |                |       |        |     |                |      |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name            | Tested Firmware   | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks |
|------------------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------|
| <b>MPIX-21DF</b>       | 2.420.WT00.0.T, build : 2014-06-19  | H.264 MJPEG  | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      |         |
| Note:                  | 1. The range of parameter on camera will change by other parameter, our parameter dialog can't synchronize with camera. (Camera firmware issue)<br>2. The camera can't be search by auto detection function and UPNP tool. (Camera firmware issue)<br>3. When framerate set to 1 and record dynamic picture, the picture's framerate may rise to 30 immediately. (Camera firmware issue)  |              |          |                |       |        |     |                |      |                      |          |         |
| <b>MPIX-30-VDV-IRM</b> | 2.420.WT00.0.T  | H.264 MJPEG  | 1        | 2048x1536      | -     | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |         |
| Note:                  | 1. The range of parameter on camera will be changed by other parameter setting, thus our parameter dialog can't synchronize with camera.(Camera firmware issue)<br>2. Not support Zoom and Focus.(Camera firmware issue)<br>3. Not support UPnP search.(Camera firmware issue)<br>4. Not support Auto Detection.(Camera firmware issue)<br>5. The range of bitrate and value are different from camera web under MJPEG.(Camera firmware issue)<br>6. Get camera config will be failed when triple stream are MJPEG with highest parameter.(Camera performance limitation) |              |          |                |       |        |     |                |      |                      |          |         |
| <b>MPIX-50BIMR</b>     | 2.210.WT00.0.R  | H.264 MJPEG  | 1        | 2560x1920      | 2-way | 2/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |         |
| Note:                  | 1. The range of parameter on camera will be changed by other parameter setting, our parameter dialog can't synchronize with camera.(Camera firmware issue)<br>2. Not support UPNP search.(Camera firmware issue)<br>3. Not support Auto Detection.(Camera firmware issue)<br>4. Audio in with 16 KHz sampling rate is not supported.<br>5. PCM in audio format can't be used.(Camera firmware issue)<br>6. Sub stream can't be used in MJPEG.(Camera firmware issue)  |              |          |                |       |        |     |                |      |                      |          |         |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmware | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks        |
|-------------|-----------------|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------------|
| WK-SD6000HD | v1.4.1.8        | H.264 MJPEG  | 1        | 1920x1080      | 1-way | -      | *2  | *2             | *2   | *2                   | Tested by link |

# Yudor

- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks           |
|-------------|--|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|-------------------|
| YUC-H626A   | Refer to YUC-H7A26A(VE1.0.20.10_Y)   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| YUC-H7926A  | Refer to YUC-H7A26A(VE1.0.20.10_Y)   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| YUC-H7926AM | Refer to YUC-H7A26A(VE1.0.20.10_Y)   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| YUC-H7982   | Refer to YUC-H7A82(VH1.0.0.3_Y)  | H.264 MJPEG  | 1        | 2688x1520      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| YUC-H7982M  | Refer to YUC-H7A82(VH1.0.0.3_Y)  | H.264 MJPEG  | 1        | 2688x1520      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| YUC-H79882  | Refer to YUC-H7A82(VH1.0.0.3_Y)  | H.264 MJPEG  | 1        | 2688x1520      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| YUC-H7A82   | VH1.0.0.3_Y  | H.264 MJPEG  | 1        | 2688x1520      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                   |
| Note:       | 1. Camera cannot achieve maximum FPS with MJPEG and high resolution. (Camera performance limitation)<br>2. Stream 1 cannot achieve maximum FPS when stream 2 connect with MJPEG and high resolution in the same time. (Camera performance limitation)<br>3. Resolution list and bitrate list does not synchronize with web. (Camera Firmware issue)<br>4. Audio has noise. (Camera Firmware issue) |              |          |                |       |        |     |                |      |                      |          |                   |
| YUC-H7A26A  | Refer to YUC-H7A26A(VE1.0.20.10_Y)   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| Note:       | 1. Stream2 cannot achieve maimum FPS with connecting two streams simultaneously. (Camera performance limitation)<br>2. Audio codec only can choose G711. (Camera Firmware issue)   |              |          |                |       |        |     |                |      |                      |          |                   |
| YUC-H7A855  | Refer to YUC-H7A26A(VE1.0.20.10_Y)   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| YUC-H7B82   | Refer to YUC-H7A82(VH1.0.0.3_Y)  | H.264 MJPEG  | 1        | 2688x1520      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| YUC-H7B82M  | Refer to YUC-H7A82(VH1.0.0.3_Y)  | H.264 MJPEG  | 1        | 2688x1520      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| YUC-H7B882  | Refer to YUC-H7A82(VH1.0.0.3_Y)  | H.264 MJPEG  | 1        | 2688x1520      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| YUC-HB26A   | Refer to YUC-H7A26A(VE1.0.20.10_Y)   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| YUC-HB855   | Refer to YUC-H7A26A(VE1.0.20.10_Y)   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| YUC-HC26A   | Refer to YUC-H7A26A(VE1.0.20.10_Y)   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |
| YUC-HC855   | Refer to YUC-H7A26A(VE1.0.20.10_Y)   | H.264 MJPEG  | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Support by design |

|                   |                                     |             |   |           |       |     |   |     |     |      |     |                   |
|-------------------|-------------------------------------|-------------|---|-----------|-------|-----|---|-----|-----|------|-----|-------------------|
| <b>YUC-HD26A</b>  | Refer to YUC-H7A26A(VE1.0.2 0.10_Y) | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-HD855</b>  | Refer to YUC-H7A26A(VE1.0.2 0.10_Y) | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-HH26A</b>  | Refer to YUC-H7A26A(VE1.0.2 0.10_Y) | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-HH855</b>  | Refer to YUC-H7A26A(VE1.0.2 0.10_Y) | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-Hi26A</b>  | Refer to YUC-H7A26A(VE1.0.2 0.10_Y) | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-Hi26AM</b> | Refer to YUC-H7A26A(VE1.0.2 0.10_Y) | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-Hi82</b>   | Refer to YUC-H7A82(VH1.0.0.3_Y)     | H.264 MJPEG | 1 | 2688x1520 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-Hi82M</b>  | Refer to YUC-H7A82(VH1.0.0.3_Y)     | H.264 MJPEG | 1 | 2688x1520 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-Hi882</b>  | Refer to YUC-H7A82(VH1.0.0.3_Y)     | H.264 MJPEG | 1 | 2688x1520 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-HK26A</b>  | Refer to YUC-H7A26A(VE1.0.2 0.10_Y) | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-HK855</b>  | Refer to YUC-H7A26A(VE1.0.2 0.10_Y) | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-HL26A</b>  | Refer to YUC-H7A26A(VE1.0.2 0.10_Y) | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-HL26AM</b> | Refer to YUC-H7A26A(VE1.0.2 0.10_Y) | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-HL82</b>   | Refer to YUC-H7A82(VH1.0.0.3_Y)     | H.264 MJPEG | 1 | 2688x1520 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-HL882</b>  | Refer to YUC-H7A82(VH1.0.0.3_Y)     | H.264 MJPEG | 1 | 2688x1520 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-HMi855</b> | Refer to YUC-H7A26A(VE1.0.2 0.10_Y) | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-HNi855</b> | Refer to YUC-H7A26A(VE1.0.2 0.10_Y) | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-HP82</b>   | Refer to YUC-H7A82(VH1.0.0.3_Y)     | H.264 MJPEG | 1 | 2688x1520 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-HQ26A</b>  | Refer to YUC-H7A26A(VE1.0.2 0.10_Y) | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |
| <b>YUC-HQ855</b>  | Refer to YUC-H7A26A(VE1.0.2 0.10_Y) | H.264 MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by design |

|                       |  |                |   |           |       |     |   |     |     |      |     |                      |
|-----------------------|--|----------------|---|-----------|-------|-----|---|-----|-----|------|-----|----------------------|
| <b>YUC-<br/>HS26A</b> | Refer to YUC-<br>H7A26A(VE1.0.2<br>0.10_Y) | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by<br>design |
| <b>YUC-<br/>HS855</b> | Refer to YUC-<br>H7A26A(VE1.0.2<br>0.10_Y) | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by<br>design |
| <b>YUC-<br/>HV26A</b> | Refer to YUC-<br>H7A26A(VE1.0.2<br>0.10_Y) | H.264<br>MJPEG | 1 | 1920x1080 | 2-way | 1/1 | - | Yes | Yes | Yes* | Yes | Support by<br>design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

Note: Turn on the Analog Video output will lead to unconnectable. (NUUO server limitation)

| Device Name  | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|--------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| <b>B5010</b> | Refer to Beward N600 (M2.0.9.13 .1_ENG)  | H.264<br>MPEG4<br>M-JPEG | 1        | 640x480        | -     | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>B5110</b> | MG.0.6.01_C1   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>B5111</b> | M2.1.6.02C045  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:        | 1. Camera with format MJPEG MPEG4 and high resolution is unable to achieve 30 fps. (Camera performance limitation)<br>2. Stream 2 & stream 3's resolution list can not sync with web. (Camera firmware issue)                        |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>B5210</b> | M2.1.6.05  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:        | 1. Resolution list can not sync with web in MPEG4. (Camera Firmware issue)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>B6110</b> | MG.0.6.01_C1   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>B6210</b> | 03_C002  | H.264<br>MJPEG           | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:        | 1. Framerate is unable to achieve setting value in MJPEG 1920x1080. (Camera performance limitation)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>B6320</b> | 01_C018  | H.264<br>H.265<br>MJPEG  | 1        | 2048x1536      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:        | 1. Display mosaic happen in 2304x1296 MJPEG. (Camera performance limitation)<br>2. Quality list can not sync with web. (Camera Firmware issue)<br>3. Bitrate list can not sync with web in MJPEG. (Camera Firmware issue)            |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>B6520</b> | 01_C018  | H.264<br>H.265<br>MJPEG  | 1        | 2560x1920      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:        | 1. Camera web does not have WDR setting. (Camara Firmware issue)<br>2. Quality list can not sync with web. (Camera Firmware issue)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>B7210</b> | M2.1.6.04  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way | 2/2    | -   | Yes            | Yes  | Yes                  | Yes      |                     |
| Note:        | 1. Setting will failed when setting the resolution to 640x360.(Camerat firmware issue)<br>2. Camera is unable to achieve maximum FPS.(Camera performance limitation)<br>3. Camera setting will fail randomly.(Camera firmware issue) |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>B7320</b> | M3.1.5.17  | M-JPEG<br>H.264          | 1        | 2048x1536      | 1-way | 2/2    | -   | Yes            | Yes  | Yes                  | -.       |                     |
| Note         | Not support audio in.  |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>B7510</b> | M3.1.5.19  | H264<br>MJPEG            | 1        | 2560x1920      | 1-way | 2/2    | -   | Yes            | Yes  | Yes                  | -        |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

Note: Turn on the Analog Video output will lead to unconnectable. (NUUO server limitation)

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| B8210       | 02_C022   | H.264<br>MJPEG           | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Audio has noise with AMR. (Camera Firmware issue)<br>2. Camera with highest resolution is unable to achieve maximum FPS. (Camera performance limitation)<br>3. Move can't not move to center. (Camera Firmware issue)<br>4. Speed range is not synchronize with web. (Camera Firmware issue)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| B8520       | 01_C013   | H.264<br>MJPEG           | 1        | 2560x1920      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Audio stutter with highest bitrate, quality, resolution. (Camera performance limitaiton)<br>2. Camera with highest resolution and MJPEG format is unable to achieve maximum fps. (Camera performance limitation)<br>3. Sever resolution list is not same as web page with MJPEG format. (Camera Firmware issue)<br>4. Not support G.726. (NUUO server limitation)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| B8220       | 01_C013   | H.264<br>MJPEG           | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Audio has noise with AMR. (Camera Firmware issue)<br>2. Camera is unable to achieve maximum FPS. (Camera performance limitation)<br>3. Move can't not move to center. (Camera Firmware issue)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| D3100       | M2.1.6.02.<br>0830  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | -     | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | 1. Not support audio.   |                          |          |                |       |        |     |                |      |                      |          |                     |
| D3200       | M2.1.6.02C<br>066   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | 1. There is no audio when using AMR 7.95<br>2. The talk function is unworked in AMR mode.<br>3. The max frame rate of MPEG4 is up to 20 FPS in 1920x1080 and 1280x800. It's the limitation of hardware  |                          |          |                |       |        |     |                |      |                      |          |                     |
| D4210       | M2.1.5.11   | H264<br>MJPEG            | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| D4211       | 02_C022   | H264<br>MJPEG            | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| D4320       | 01_C014   | H.264<br>H.265<br>MJPEG  | 1        | 2048x1536      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Audio has noise. (Camera Firmware issue)<br>2. Not G.726 support. (NUUO server limitation)<br>3. Quality list may not be synchronized with camera web. (Camera Firmware issue)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| D4520       | 01_C017   | H.264<br>H.265<br>MJPEG  | 1        | 2560x1920      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Quality list can not sync with web in MJPEG with high resolution. (Camera firmware issue)<br>2. Frame rate list can not sync with web. (Camera firmware issue)<br>3. Bitrate is unable to achieve setting value. (Camera performance limitation)<br>4. Frame rate is unable to achieve 30 fps in MJPEG with 1920x1080. (Camera performance limitation)<br>5. G.726 can not be used. (NUUO server limitation) |                          |          |                |       |        |     |                |      |                      |          |                     |
| D510E       | LM.1.6.16.<br>03  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| D5110       | Refer to<br>D5111   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | -     | 2/2    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| D5111       | MG.1.6.03P<br>7_app7  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | -     | 2/2    | Yes | Yes            | Yes  | Yes                  | -        |                     |





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Note: Turn on the Analog Video output will lead to unconnectable. (NUUO server limitation)

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| D5112       | Refer to D5113 (M2.1.6.01)  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x720       | -     | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| D5113       | M2.1.6.01   | H.264<br>MJPEG<br>MPEG4  | 1        | 1280x720       | -     | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| D520E       | LM.1.6.16.03  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| D5210       | M2.1.6.04   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | -     | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | Due to camera restriction, some video setting will fail. This situation will be same as camera web. (Camera performance limitation)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| D610A       | LM.1.6.16   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| D6111       | MG.0.6.01_C1  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| D611E       | LM.1.6.16   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| D6210       | 03_C002   | H.264<br>MJPEG           | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Framerate is unable to achieve setting value in MJPEG 1920x1080. (Camera performance limitation)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| D6320       | 01_C013   | H.264<br>H.265<br>MJPEG  | 1        | 2048x1520      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Display mosaic happen in 2304x1296 MJPEG. (Camera performance limitation)<br>2. Quality list can not sync with web. (Camera Firmware issue)<br>3. Bitrate list can not sync with web in MJPEG. (Camera Firmware issue) |                          |          |                |       |        |     |                |      |                      |          |                     |
| D6520       | Refer to B6520(01_C018)   | H.264<br>H.265<br>MJPEG  | 1        | 2560x1920      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| D7111       | Refer to D5113  | H.264<br>MJPEG<br>MPEG4  | 1        | 1280x720       | -     | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| D7210       | M2.1.6.02C066   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:       | 1. There is no audio when using AMR 7.95<br>2. The talk function is unworked in AMR mode.<br>3. The max frame rate of MPEG4 is up to 20 FPS in 1920x1080 and 1280x800. It's the limitation of hardware                    |                          |          |                |       |        |     |                |      |                      |          |                     |
| D7320       | M3.1.5.21   | H.264<br>M-JPEG          | 1        | 2048x1536      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | Frame rate can't reach setting value  |                          |          |                |       |        |     |                |      |                      |          |                     |
| D7510       | M3.04.15.C01  | H.264<br>M-JPEG          | 1        | 2560x1920      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | 1. Framerate support 1~15 only.<br>2. Connecting stream by RTSP over HTTP in high video quality will cause delayed image and broken voice.  |                          |          |                |       |        |     |                |      |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

Note: Turn on the Analog Video output will lead to unconnectable. (NUUO server limitation)

| Device Name | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| D8210       | 02_C022  | H.264<br>MJPEG           | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Audio has noise with AMR. (Camera Firmware issue)<br>2. Camera with highest resolution is unable to achieve maximum FPS. (Camera performance limitation)<br>3. PTZ only support zoom & focus. |                          |          |                |       |        |     |                |      |                      |          |                     |
| D8220       | 01_C013  | H.264<br>MJPEG           | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Audio has noise. (Camera Firmware issue)<br>2. G.726 does not supported. (NUUO server limitation)   |                          |          |                |       |        |     |                |      |                      |          |                     |
| D8520       | Refer to<br>B8520(01_010)  | H.264<br>MJPEG           | 1        | 2560x1920      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| F1100       | Refer to<br>F1105  | MJPEG                    | 1        | 1280x720       | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| F1105       | BP.1.6.01_01   | MJPEG                    | 1        | 1280x720       | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| F210A       | LM.1.6.15  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| F3100       | MG.0.6.01_01   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| F3101       | Refer to<br>F3106  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| F3102       | M2.1.6.02C045  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | 1. There is no audio when using AMR 7.95<br>2. The talk function is unworked in AMR mode.<br>3. The max frame rate of MPEG4 is up to 20 FPS in 1280x800. It's the limitation of hardware         |                          |          |                |       |        |     |                |      |                      |          |                     |
| F3105       | MG.0.6.01_01   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| F3106       | MG.1.6.0308  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| F3107       | M2.1.6.05  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. 1.Audio via AMR has noises. (Firmware issue)  |                          |          |                |       |        |     |                |      |                      |          |                     |
| F3110       | M2.1.6.02C045  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | 1. There is no audio when using AMR 7.95<br>2. The talk function is unworked in AMR mode.<br>3. The max frame rate of MPEG4 is up to 20 FPS in 1280x800. It's the limitation of hardware         |                          |          |                |       |        |     |                |      |                      |          |                     |
| F3115       | M2.1.6.02C045  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:       | 1. There is no audio when using AMR 7.95<br>2. The talk function is unworked in AMR mode.<br>3. The max frame rate of MPEG4 is up to 20 FPS in 1280x800. It's the limitation of hardware         |                          |          |                |       |        |     |                |      |                      |          |                     |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Note: Turn on the Analog Video output will lead to unconnectable. (NUUO server limitation)

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| F312A       | LM.1.6.16.03  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| F3201       | Refer to F3206  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        |                     |
| F3206       | M2.P2P_0314   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 2/2    | -   | Yes            | Yes  | Yes                  | -        |                     |
| F3210       | M2.1.6.03C019   | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | For F3210, Video resolution can not change when only setting resoluition.   |                          |          |                |       |        |     |                |      |                      |          |                     |
| F3215       | M2.1.6.05C016   | H.264<br>M-JPEG<br>MPEG4 | 1        | 1920x1080      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | Resolution list is not synchronized with camera web due to resolution setting limitation. (Camera limitation issue) |                          |          |                |       |        |     |                |      |                      |          |                     |
| F5100       | MG.0.6.01_C1  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| F5105       | MG.0.6.01_C1  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| F510E       | LM.1.6.16.03  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| F510W       | LM.1.6.16.03  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| F5110       | MG.0.6.01_C1  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| F5115       | MG.0.6.01_C1  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| F511E       | LM.1.6.16.03  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| F511W       | LM.1.6.16.03  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| F520E       | LM.1.6.16.03  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| F521E       | LM.1.6.16.03  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| F531E       | LM.1.6.18P9_testport2   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| F610A       | LM.1.6.16.03  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| F611E       | LM.1.6.16.007   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        |                     |
| F7110       | MG.1.6.03P3_r1072   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 2/2    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| F7115       | Refer to F7110  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 2/2    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Note: Turn on the Analog Video output will lead to unconnectable. (NUUO server limitation)

| Device Name    | Tested Firmware  | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|----------------|--|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| <b>F7210</b>   | M2.1.6.04  | H.264<br>MPEG4<br>M-JPEG | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| <b>F721A</b>   | LM.1.6.16.03   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | -      | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>F731E</b>   | LM.1.6.16.03   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | -   | Yes            | Yes  | Yes                  | -        | Supported by design |
| <b>Generic</b> | Tested by P6210(2.1.5.20)  | H.264<br>M-JPEG          | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | -    | Yes*                 | Yes      |                     |
| Note:          | Generic:<br>1. It may fail to set Profile 2 to 1920x1080 or 1280x720. (Camera Firmware Issue)<br>2. Not support to set profile 3 to 1920x1080 or 1280x720; while the setting is supported in camera web. (Camera Firmware Issue) |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>M510E</b>   | LM.1.6.16.03   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:          | PTZ Support: pan and tilt only   |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>M510W</b>   | LM.1.6.16.03   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:          | PTZ Support: pan and tilt only   |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>M511E</b>   | LM.1.6.16.03   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:          | PTZ Support: pan and tilt only   |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>M511W</b>   | LM.1.6.16.03   | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:          | PTZ Support: pan and tilt only   |                          |          |                |       |        |     |                |      |                      |          |                     |
| <b>N24320</b>  | Refer to P4320(01_C013)  | H.264<br>MJPEG           | 1        | 2048x1520      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| <b>N24520</b>  | Refer to P4520(01_C013)  | H.264<br>MJPEG           | 1        | 2560x1920      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| <b>N36210</b>  | Refer to B6210(03_C002)  | H.264<br>MJPEG           | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| <b>N36320</b>  | Refer to B6320(01_C018)  | H.264<br>H.265<br>MJPEG  | 1        | 2048x1536      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| <b>N36520</b>  | Refer to B6520(01_C018)  | H.264<br>H.265<br>MJPEG  | 1        | 2560x1920      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Note: Turn on the Analog Video output will lead to unconnectable. (NUUO server limitation)

| Device Name | Tested Firmware  | Video Format       | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|--|--------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| N38210      | Refer to B8210(02)   | H.264 MJPEG        | 1        | 1920x1080      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| N74320      | Refer to D4320 (01_C014)   | H.264 H.265 MJPEG  | 1        | 2048x1536      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| N74520      | Refer to D4520 (01_C017)   | H.264 H.265 MJPEG  | 1        | 2560x1920      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| N76210      | Refer to D6210(03_C002)  | H.264 MJPEG        | 1        | 1920x1080      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| N76320      | Refer to D6320(01_C013)  | H.264 H.265 MJPEG  | 1        | 2048x1520      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| N76520      | Refer to B6520(01_C018)  | H.264 H.265 MJPEG  | 1        | 2560x1920      | -     | -      | -   | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| N78520      | Refer to B8520(01_C010)  | H.264 MJPEG        | 1        | 2560x1920      | 2-way | 2/2    | Yes | Yes            | Yes  | Yes*                 | Yes      | Supported by design |
| P4320       | 01_C013  | H.264 MJPEG        | 1        | 2048x1520      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1. Quality list may not sync with web. (Camera Firmware issue)<br>2. Audio in G.726 can not we used. (NUUO server limitation)  |                    |          |                |       |        |     |                |      |                      |          |                     |
| P4520       | 01_C013  | H.264 MJPEG        | 1        | 2560x1920      | 2-way | 1/1    | -   | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | 1.Frame rate list does not sync with web. (Camera Firmware issue)<br>2.Quality list does not sync with web. (Camera Firmware issue)<br>3.Textures will be broken in MJPEG 2560x1920.(MJPEG 2560*1920會破圖)(Camera Firmware issue)<br>4.Multi-Stream Setting's auto mode can't setting correctly. (Camera Firmware issue) |                    |          |                |       |        |     |                |      |                      |          |                     |
| P5110       | MG.0.6.01_C1   | H.264 MPEG4 M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note:       | PTZ Support: pan and tilt only   |                    |          |                |       |        |     |                |      |                      |          |                     |
| P5111       | Refer to P5116   | H.264 MPEG4 M-JPEG | 1        | 1280x800       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Note: Turn on the Analog Video output will lead to unconnectable. (NUUO server limitation)

| Device Name | Tested Firmware   | Video Format             | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Snapshot | Remarks             |
|-------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|----------|---------------------|
| P5115       | MG.0.6.01_C1  | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x1024      | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | PTZ Support: pan and tilt only  |                          |          |                |       |        |     |                |      |                      |          |                     |
| P5116       | M2.1.6.02   | H.264<br>MPEG4<br>M-JPEG | 1        | 1280x800       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | 1. PTZ Support pan and tilt only.<br>2. There is no audio when using AMR 7.95<br>3. The max frame rate of MPEG4 and MJPEG is up to 20 FPS in 1280x800. It's the limitation of hardware.                                       |                          |          |                |       |        |     |                |      |                      |          |                     |
| P6210       | M2.1.5.11   | H.264<br>M-JPEG          | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| Note:       | P6210:<br>1. Stream 2 CGI setting will fail when resolution of Profile3 is 1920x1080 and 1280x720. (Camera limitation)<br>2. The camera with higher quality and MJPEG format is unable to achieve 30 fps. (Camera limitation) |                          |          |                |       |        |     |                |      |                      |          |                     |
| P6211       | 02_C022   | H.264<br>M-JPEG          | 1        | 1920x1080      | 2-way | 1/1    | Yes | Yes            | Yes  | Yes*                 | Yes      |                     |
| V1100       | M2.1.6.03   | H264<br>MJPEG<br>MPEG4   | 1        | 704x480        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        |                     |
| Note:       | 1.AMR can't be used in audio in/out.  |                          |          |                |       |        |     |                |      |                      |          |                     |
| V111T       | LM.1.6.16.03  | MPEG4<br>M-JPEG          | 1        | 640x480        | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | -        | Supported by design |
| Note        | If enable Zavio analog video output function, it will not be able to get 2 <sup>nd</sup> stream from zavio camera.  |                          |          |                |       |        |     |                |      |                      |          |                     |



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

| Device Name | Tested Firmware  | Video Format | Video Ch | Max Resolution  | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks             |
|-------------|--|--------------|----------|-----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| N1011       |  | H264 MJPEG   | 1        | 2560x1920       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N1012       |  | H264 MJPEG   | 1        | 2560x1920       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N1031       |  | H.264 M-JPEG | 1        | 2048x1536       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N1032       |  | H.264 M-JPEG | 1        | 2048x1536       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N3011       |  | H264 MJPEG   | 1        | 2560x1920       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N3012       |  | H264 MJPEG   | 1        | 2560x1920       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N3031       |  | H.264 M-JPEG | 1        | 2048x1536       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N3032       |  | H.264 M-JPEG | 1        | 2048x1536       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N3071       | Refer to 3S N3072  | H264 M-JPEG  | 1        | 1600x1200       | 1-way | -      | -   | Yes            | -    | Yes                  | Supported by design |
| N3072       | V1.13.0_STD-1  | H.264        | 1        | 1600x1200       | 2-way | 1/1    | Yes | Yes            | Yes  | Yes*                 |                     |
| Note        | 1. The bit rate via MJPEG is too high. (Camera performance limitation)<br>2. The frame rate via MJPEG is unable to achieve maximum FPS. (Camera performance limitation)<br>3. Connection lost when frame rate is set to 1 fps. (Camera performance limitation)<br>4. Pan and tilt speed will set together. (Camera Firmware issue)<br>5. Down left, Down right, up left and up right will pan first and then still tilt. (Camera Firmware issue) |              |          |                 |       |        |     |                |      |                      |                     |
| N5012       | V1.01_STD-1  | H.264 MJPEG  | 1        | 1920x1080       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |
| Note        | HTTP port always 80 when using UPnP search.  |              |          |                 |       |        |     |                |      |                      |                     |
| N5013       | V1.04_STD-1  | H.264 MJPEG  | 1        | 704x576         | 2-way | 1/1    | Yes | Yes            | Yes  | Yes                  |                     |
| N5071       | V1.03_STD-1  | H264 M-JPEG  | 1        | 704x576/704x480 | 1-way | 0/0    | Yes | Yes            | Yes  | Yes                  |                     |
| N6011       |  | H264 MJPEG   | 1        | 2560x1920       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N6012       |  | H264 MJPEG   | 1        | 2560x1920       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N6013       |  | H264 MJPEG   | 1        | 2560x1920       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N6014       |  | H264 MJPEG   | 1        | 2560x1920       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N6015       |  | H264 MJPEG   | 1        | 2560x1920       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |
| N6016       |  | H264 MJPEG   | 1        | 2560x1920       | 1-way | 1/1    | Yes | Yes            | Yes  | Yes                  | Supported by design |

|                |  |                 |   |           |       |     |     |     |     |      |                        |
|----------------|--|-----------------|---|-----------|-------|-----|-----|-----|-----|------|------------------------|
| <b>N6031</b>   |  | H.264<br>M-JPEG | 1 | 2048x1536 | 1-way | 1/1 | Yes | Yes | Yes | Yes  | Supported<br>by design |
| <b>N6032</b>   |  | H.264<br>M-JPEG | 1 | 2048x1536 | 1-way | 1/1 | Yes | Yes | Yes | Yes  | Supported<br>by design |
| <b>N6033</b>   |  | H.264<br>M-JPEG | 1 | 2048x1536 | 1-way | 1/1 | Yes | Yes | Yes | Yes  | Supported<br>by design |
| <b>N6034</b>   |  | H.264<br>M-JPEG | 1 | 2048x1536 | 1-way | 1/1 | Yes | Yes | Yes | Yes  | Supported<br>by design |
| <b>N6035</b>   |  | H.264<br>M-JPEG | 1 | 2048x1536 | 1-way | 1/1 | Yes | Yes | Yes | Yes  | Supported<br>by design |
| <b>N6036</b>   |  | H.264<br>M-JPEG | 1 | 2048x1536 | 1-way | 1/1 | Yes | Yes | Yes | Yes  | Supported<br>by design |
| <b>N6037</b>   |  | H.264<br>M-JPEG | 1 | 2048x1536 | 1-way | 1/1 | Yes | Yes | Yes | Yes  | Supported<br>by design |
| <b>N6038</b>   |  | H.264<br>M-JPEG | 1 | 2048x1536 | 1-way | 1/1 | Yes | Yes | Yes | Yes  | Supported<br>by design |
| <b>N6072</b>   | Refer to 3S<br>N6075   | H264<br>M-JPEG  | 1 | 1600x1200 | 1-way | 1/1 | -   | Yes | Yes | Yes  | Supported<br>by design |
| <b>N6073</b>   | Refer to 3S<br>N6075   | H264<br>M-JPEG  | 1 | 1600x1200 | 1-way | 1/1 | -   | Yes | Yes | Yes  | Supported<br>by design |
| <b>N6074</b>   | Refer to 3S<br>N6075   | H264<br>M-JPEG  | 1 | 1600x1200 | 1-way | 1/1 | -   | Yes | Yes | Yes  | Supported<br>by design |
| <b>N6075</b>   | V1.05_STD-1  | H264<br>M-JPEG  | 1 | 1600x1200 | 1-way | 1/1 | -   | Yes | Yes | Yes  |                        |
| <b>N6076</b>   | Refer to 3S<br>N6075   | H264<br>M-JPEG  | 1 | 1600x1200 | 1-way | 1/1 | -   | Yes | Yes | Yes  | Supported<br>by design |
| <b>N6077</b>   | Refer to 3S<br>N6075   | H264<br>M-JPEG  | 1 | 1600x1200 | 1-way | 1/1 | -   | Yes | Yes | Yes  | Supported<br>by design |
| <b>N6082</b>   | Refer to<br>N9085(V1.05.0)   | H.264           | 1 | 1600x1200 | -     | -   | -   | Yes | Yes | Yes* | Supported<br>by design |
| <b>N8011</b>   |  | H264<br>MJPEG   | 1 | 2560x1920 | 1-way | 1/1 | Yes | Yes | Yes | Yes  | Supported<br>by design |
| <b>N8012</b>   |  | H264<br>MJPEG   | 1 | 2560x1920 | 1-way | 1/1 | Yes | Yes | Yes | Yes  | Supported<br>by design |
| <b>N8031</b>   |  | H.264<br>M-JPEG | 1 | 2048x1536 | 1-way | 1/1 | Yes | Yes | Yes | Yes  | Supported<br>by design |
| <b>N8032</b>   |  | H.264<br>M-JPEG | 1 | 2048x1536 | 1-way | 1/1 | Yes | Yes | Yes | Yes  | Supported<br>by design |
| <b>N8072</b>   | V1.03_STD-1  | H264<br>M-JPEG  | 1 | 1600x1200 | 1-way | 0/0 | -   | Yes | -   | Yes  |                        |
| <b>N8072-C</b> | V1.04.0_STD-1  | H.264           | 1 | 1600x1200 | 2-way | -   | -   | Yes | Yes | Yes* |                        |
| Note:          | 1. The actual audio codec is different with the setting codec. (Camera Firmware issue)<br>2. The stream 3's fps range is different to web. (Camera Firmware issue) |                 |   |           |       |     |     |     |     |      |                        |
| <b>N9012</b>   |  | H264<br>MJPEG   | 1 | 2560x1920 | 1-way | 1/1 | Yes | Yes | Yes | Yes  | Supported<br>by design |
| <b>N9018</b>   | V1.01_STD-1  | H.264<br>MJPEG  | 1 | 1920x1080 | 2-way | 1/1 | -   | Yes | Yes | Yes  |                        |
| Note:          | Fisheye camera<br>1.Audio toned with G.726/32.[camera firmware issue]<br>2.The image of snapshot to FTP is use MJPEG stream.[camera firmware issue]                |                 |   |           |       |     |     |     |     |      |                        |



|              |   |                 |   |                     |       |     |     |     |     |      |                        |
|--------------|---|-----------------|---|---------------------|-------|-----|-----|-----|-----|------|------------------------|
| <b>N9032</b> |   | H.264<br>M-JPEG | 1 | 2048x1536           | 1-way | 1/1 | Yes | Yes | Yes | Yes  | Supported<br>by design |
| <b>N9033</b> |   | H.264<br>M-JPEG | 1 | 2048x1536           | 1-way | 1/1 | Yes | Yes | Yes | Yes  | Supported<br>by design |
| <b>N9034</b> |   | H.264<br>M-JPEG | 1 | 2048x1536           | 1-way | 1/1 | Yes | Yes | Yes | Yes  | Supported<br>by design |
| <b>N9071</b> | V1.06_STD-1   | H264<br>M-JPEG  | 1 | 1600x1200           | 1-way | 0/0 | -   | Yes | Yes | Yes  |                        |
| <b>N9073</b> | Refer to<br>N3072(V1.13.0<br>_STD-1)  | H.264           | 1 | 1600x1200           | 2-way | 1/1 | Yes | Yes | Yes | Yes* | Supported<br>by design |
| <b>N9074</b> | Refer to<br>N3072(V1.13.0<br>_STD-1)  | H.264           | 1 | 1600x1200           | 2-way | 1/1 | Yes | Yes | Yes | Yes* | Supported<br>by design |
| <b>N9082</b> | Refer to<br>N9085(V1.05.0)  | H.264           | 1 | 1600x1200           | -     | -   | -   | Yes | Yes | Yes* | Supported<br>by design |
| <b>N9085</b> | V1.05.0   | H.264           | 1 | 1600x1200           | -     | -   | -   | Yes | Yes | Yes* |                        |
| Note         | 1.The minimum stream's bitrate is too high. (Camera performance limitation)<br>2. The stream 3's fps range is different to web. (Camera Firmware issue) |                 |   |                     |       |     |     |     |     |      |                        |
| <b>S4071</b> | V1.04_STD-1   | H264<br>M-JPEG  | 4 | 704x576/<br>704x480 | 1-way | 4/4 | -   | Yes | Yes | Yes  |                        |
| Note         | 1. The quality setting of M-JPEG is unavailable.<br>2. When the server attaches two or more channels, the maximal framerate is unstable.                |                 |   |                     |       |     |     |     |     |      |                        |