

AXIS



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/A2A2100kbps
 Yes*: multi stream setting support

For PTZ:
 Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
205		M-JPEG	1	640x480	-	-	-	Yes	-	Yes	Supported by design
206		M-JPEG	1	640x480	-	-	-	Yes	Yes	Yes	Supported by design
206M		M-JPEG	1	1280x1024	-	-	-	Yes	Yes	Yes	Supported by design
206W		M-JPEG	1	640x480	-	-	-	Yes	Yes	Yes	Supported by design
207	4.40	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	
207MW		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	Supported by design
207W		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design
Note:	Not support audio in M-JPEG										
209FD		MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	Yes	Supported by design
209FD-R		MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	Yes	Supported by design
209MFD		MPEG4 M-JPEG	1	1280x1024	-	-	Yes*	Yes	Yes	Yes	
209MFD-R		MPEG4 M-JPEG	1	1280x1024	-	-	Yes*	Yes	Yes	Yes	Supported by design
210		MPEG4 M-JPEG	1	640x480	-	1/1	-	Yes	Yes	Yes	Supported by design
210A	4.40	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	
211		MPEG4 M-JPEG	1	640x480	-	1/1	-	Yes	Yes	Yes	Supported by design
211A		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design
211M		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	Supported by design

AXIS



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/A2A2100kbps
 Yes*: multi stream setting support

For PTZ:
 Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
211W		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design
212		MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes*	Yes	Yes	Yes	Supported by design
Note:	212 include 212 PTZ and 212 PTZ-V										
213		MPEG4 M-JPEG	1	704x576	1-way	2/3	Yes*	Yes	Yes	Yes	Supported by design
Note:	213 include 213 PTZ										
214	4.33	MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes*	Yes	Yes	Yes	
Note:	214 include 214 PTZ										
215		MPEG4 M-JPEG	1	704x576	1-way	1/1	Yes*	Yes	Yes	Yes	Supported by design
Note:	215 include 215 PTZ and 215 PTZ-E										
216FD		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design
216FD-V		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design
216MFD		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	Supported by design
216MFD-V		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	Supported by design
221		MPEG4 M-JPEG	1	640x480	-	2/1	-	Yes	Yes	Yes	Supported by design
223M		MPEG4 M-JPEG	1	1600x1200	1-way	2/1	-	Yes	Yes	Yes	Supported by design
225FD		MPEG4 M-JPEG	1	640x480	-	2/1	-	Yes	Yes	Yes	Supported by design
231D		MPEG4 M-JPEG	1	704x576	-	4/4	Yes*	Yes	Yes	Yes	Supported by design
Note:	231D include 231D+										
232D		MPEG4 M-JPEG	1	704x576	-	4/4	Yes*	Yes	Yes	Yes	Supported by design
Note:	232D include 232D+										

AXIS



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/A2A2100kbps
 Yes*: multi stream setting support

For PTZ:
 Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
233D		MPEG4 M-JPEG	1	704x576	1-way	4/4	Yes*	Yes	Yes	Yes	Supported by design
2400		M-JEPG	4	704x576	-	4/1	-	Yes	Yes	Yes	Supported by design
240Q		M-JEPG	4	704x576	-	4/4	-	Yes	Yes	Yes	Supported by design
240Q Blade		M-JEPG	4	704x576	-	4/4	-	Yes	Yes	Yes	Supported by design
241Q		MPEG4 M-JPEG	4	704x576	-	4/4	-	Yes	Yes	Yes	Supported by design
241Q Blade		MPEG4 M-JPEG	4	704x576	-	4/4	-	Yes	Yes	Yes	Supported by design
241QA	4.30	MPEG4 M-JPEG	4	704x576	1-way	4/4	-	Yes	Yes	Yes	
241S		MPEG4 M-JPEG	1	704x576	-	4/4	-	Yes	Yes	Yes	Supported by design
241S Blade		MPEG4 M-JPEG	1	704x576	-	4/4	-	Yes	Yes	Yes	Supported by design
241SA		MPEG4 M-JPEG	1	704x576	1-way	4/4	-	Yes	Yes	Yes	Supported by design
242S		MPEG4 M-JPEG	1	704x576	-	4/4	-	Yes	Yes	Yes	Supported by design
243Q		MPEG4 M-JPEG	1	704x576	-	1/1	-	Yes	Yes	Yes	Supported by design
243Q Blade		MPEG4 M-JPEG	1	704x576	-	1/1	-	Yes	Yes	Yes	Supported by design
243SA		MPEG4 M-JPEG	1	704x576	1-way	4/4	-	Yes	Yes	Yes	Supported by design
2460		M-JEPG	4	704x576	-	4/1	-	Yes	Yes	Yes	Supported by design
247S		MPEG4 M-JPEG	1	704x576	1-way	1/1	-	Yes	Yes	Yes	Supported by design

AXIS



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/A2A2100kbps
 Yes*: multi stream setting support

For PTZ:
 Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
Generic		MPEG4 M-JPEG	Max 4	by Camera	1-way	Max 4/4	Yes*	Yes	-	Yes	
Note:	Only guarantee stream works fine.										
M1004-W	5.40.5.1	H.264 MJPEG	1	1280x800	-	1/1	-	Yes	Yes	Yes*	
M1011	5.00	H.264 MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	Yes	
M1011-W	5.00	H.264 MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	Yes	
M1013	5.40.5.1	H.264 M-JPEG	1	800x600	1-way	-	-	Yes	Yes	Yes	
M1014	5.40.5	H.264 M-JPEG	1	1280x800	-	-	-	Yes	Yes	Yes	
M1025	5.40.5	H.264 MJPEG	1	1920x1080	-	-	-	*2	*2	Yes*	Tested by link
M1031-W	5.00	H.264 MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	Yes	
M1034-W	5.40beta1	H.264 M-JPEG	1	1280x800	1-way	-	-	Yes	Yes	Yes	
M1054	5.15	H.264 M-JPEG	1	1024x640	1-way	1/1	-	Yes	Yes	Yes	
M1103		H.264 M-JPEG	1	800x600	-	-	Yes*	Yes	Yes*	Yes	Supported by design
M1104	5.09	H.264 M-JPEG	1	1280x800	-	-	-	Yes	Yes*	Yes	
M1113	5.08	H.264 M-JPEG	1	800x600	-	-	Yes*	Yes	Yes	Yes	
M1114		H.264 M-JPEG	1	1280x800	-	-	-	Yes	Yes*	Yes	Supported by design
Note:	M1113-E is compatible with M1113, M1114-E is compatible with M1114										
M1143-L	5.40beta19	H.264 M-JPEG	1	800x600	-	1/1	-	Yes	Yes	Yes	

AXIS



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/A2A2100kbps
 Yes*: multi stream setting support

For PTZ:
 Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
M1144	5.40.10.4	H.264 M-JPEG	1	1280x800	-	1/1	-	Yes	Yes	Yes	
M2014	Refer to P1204(5.40.12)	H.264 M-JPEG	1	1280x720	1-way	1/1	-	Yes	Yes	Yes	Supported by design
M3004	5.50.5.1	H.264 M-JPEG	1	1280x800	-	-	-	*2	*2	Yes*	
M3005	5.40.5.3	H.264 M-JPEG	1	1920x1080	-	-	-	Yes	Yes	Yes	
M3006	5.40.13	H.264 M-JPEG	1	2048x1536	-	-	-	Yes	Yes	Yes	
M3007	5.55.1.1	H.264 M-JPEG	1	2592x1944	-	-	Yes*	Yes	Yes	Yes*	
Note:	Fisheye camera with manual calibration in Crystal										
M3011	5.01	H.264 MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	Yes	Supported by design
M3014		H.264 M-JPEG	1	1280x800	-	-	-	Yes	Yes	Yes	Supported by design
M3024-L	5.40.5	H.264 M-JPEG	1	1280x800	-	1/1	-	Yes	Yes	Yes	
M3025	5.50.5.1	H.264 M-JPEG	1	1920x1080	-	-	-	*2	*2	Yes*	
M3026	Refer to M3024-L(5.50.5)	H.264 M-JPEG	1	2048x1536	-	1/1	-	Yes	Yes	Yes	
M3027	refer to M3007(5.55.1.1)	H.264 M-JPEG	1	2592x1944	-	-	Yes*	Yes	Yes	Yes	Supported by design
Note:	Fisheye camera										
M3113-R		H.264 M-JPEG	1	800x600	-	-	Yes*	Yes	Yes	Yes	Supported by design
M3113-VE		H.264 M-JPEG	1	800x600	-	-	Yes*	Yes	Yes	Yes	Supported by design
M3114-R	5.11	H.264 M-JPEG	1	1280x800	-	-	Yes*	Yes	Yes	Yes	

AXIS



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/A2A2100kbps
 Yes*: multi stream setting support

For PTZ:
 Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
M3114-VE		H.264 M-JPEG	1	1280x800	-	-	Yes*	Yes	Yes	Yes	Supported by design
M3203		H.264 M-JPEG	1	800x600	-	-	-	Yes	Yes	Yes	Supported by design
Note:	M3203-V is compatible with M3203										
M3204		H.264 M-JPEG	1	1280x800	-	-	-	Yes	Yes	Yes	Supported by design
Note:	M3204-V is compatible with M3204										
M5013		H.264 M-JPEG	1	800x600	1-way	-	Yes*	Yes	Yes	Yes	Supported by design
M5014		H.264 MPEG4	1	1280x720	1-way	2/2	Yes*	Yes	Yes	Yes	Supported by design
M7001		H.264 M-JPEG	1	720x576	-	-	Yes*	Yes	Yes	Yes	Supported by design
M7010	5.40.6.1	H.264 M-JPEG	4	720x576	-	-	Yes*	Yes	Yes	Yes	
M7014	5.40.7.1	H.264 M-JPEG	4	720x576	-	-	Yes*	Yes	Yes	Yes	
P1204	5.40.12	H.264 M-JPEG	1	1280x720	1-way	1/1	-	Yes	Yes	Yes	
P1214	5.40.12	H.264 M-JPEG	1	1280x720	1-way	1/1	-	Yes	Yes	Yes	
P1311	5.01	H.264 MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	
P1343	5.06	H.264 M-JPEG	1	800*600	1-way	1/1	Yes*	Yes	Yes	Yes	
P1343-E		H.264 M-JPEG	1	640x480	1-way	1/1	Yes*	Yes	Yes	Yes	Supported by design
P1344		H.264 M-JPEG	1	1280x800	1-way	1/1	Yes*	Yes	Yes	Yes	Supported by design
P1344-E		H.264 M-JPEG	1	1280x800	1-way	1/1	Yes*	Yes	Yes	Yes	Supported by design

AXIS



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/A2A2100kbps
 Yes*: multi stream setting support

For PTZ:
 Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
P1346	5.06	H.264 M-JPEG	1	2048x1536	1-way	1/1	Yes*	Yes	Yes	Yes	
P1346-E		H.264 M-JPEG	1	2048x1536	1-way	1/1	Yes*	Yes	Yes	Yes	Supported by design
P1347	5.11	H.264 M-JPEG	1	2560x1920	1-way	1/1	Yes	Yes	Yes	Yes	
P1347-E		H.264 M-JPEG	1	2560x1920	1-way	1/1	Yes	Yes	Yes	Yes	Supported by design
P1353-E	refer to P1354 (5.40.14)	H.264 M-JPEG	1	800x600	1-way	1/1	-	Yes	Yes	Yes	Supported by design
P1354	5.60.1	H.264 M-JPEG	1	1280x960	1-way	1/1	Yes	*2	*2	Yes*	
Note:	H264 AAC not support in Titan v1.5.1 and above version										
P1355-E	refer to P1354 (5.40.14)	H.264 M-JPEG	1	800x600	1-way	1/1	-	Yes	Yes	Yes	Supported by design
P1357	5.40.19.1	H.264 M-JPEG	1	2592x1944	*2	*2	*2	Yes	*2	Yes	
P1428-E	5.55.1	H.264 M-JPEG	1	3840x2160	-	*2	Yes*	*2	*2	Yes*	
P3214-V	5.55.3.2	H.264 MJPEG	1	1280x960	-	*2	Yes	*2	*2	Yes*	
Note:	Zoom speed setting does not support.(Camera limitation)										
P3215-V	5.55.3.2	H.264 MJPEG	1	1920x1080	-	*2	Yes	*2	*2	Yes*	
P3301	5.11	H.264 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design
P3301-V		H.264 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design
P3304		H.264 M-JPEG	1	1280x800	1-way	1/1	Yes*	Yes	Yes	Yes	Supported by design
P3304-V		H.264 M-JPEG	1	1280x800	1-way	1/1	Yes*	Yes	Yes	Yes	Supported by design

AXIS



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/A2A2100kbps

Yes*: multi stream setting support

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
P3343	5.06	H.264 M-JPEG	1	800x600	1-way	1/1	Yes*	Yes	Yes	Yes	Supported by design
Note:	P3343-V and P3343-VE are compatible with P3343 P3343 supports digital PTZ only.										
P3344	5.06	H.264 M-JPEG	1	1280x800	1-way	1/1	Yes*	Yes	Yes	Yes	
Note:	P3344-V and P3344-VE are compatible with P3344 P3344 supports digital PTZ only.										
P3346	5.20	H.264 M-JPEG	1	2048x1536	1-way	1/1	Yes*	Yes	Yes*	Yes	
Note:	P3346-V and P3346-VE are compatible with P3346 P3346 supports digital PTZ only.										
P3353		H.264 M-JPEG	1	800x600	1-way	1/1	-	Yes	Yes	Yes	
P3354	5.40.10.2	H.264 M-JPEG	1	1280x960	1-way	1/1	-	Yes	Yes	Yes	tested by link
P3363	5.40.17.1	H.264 MJPEG	1	800x600	*2	*2	*2	*2	*2	Yes*	tested by link
P3364	5.40.10.2	H.264 M-JPEG	1	1280x960	1-way	1/1	-	Yes	Yes	Yes	tested by link
P3367	5.40.3	H.264 M-JPEG	1	2592x1944	1-way	1/1	-	Yes	Yes	Yes	tested by link
Note:	P3367-V, P3367-VE are compatible with P3367										
P3384	5.40.19	H.264 MJPEG	1	1280x960	*2	*2	-	*2	*2	Yes*	tested by link
P5414	5.55.1	H.264 M-JPEG	1	1280x720	1-way	4/4	Yes	Yes	Yes	Yes	tested by link
P5415	Refer to P5414(5.55.1)	H.264 M-JPEG	1	1920x1080	1-way	4/4	Yes	Yes	Yes	Yes	
P5512		H.264 M-JPEG	1	704x480	1-way	4/4	Yes*	Yes	Yes	Yes	Supported by design
P5512-E		H.264 M-JPEG	1	704x480	1-way	4/4	Yes*	Yes	Yes	Yes	Supported by design

AXIS



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/A2A2100kbps

Yes*: multi stream setting support

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
P5522		H.264 M-JPEG	1	720x480	1-way	4/4	Yes*	Yes	Yes	Yes	Supported by design
P5522-E		H.264 M-JPEG	1	720x480	1-way	4/4	Yes*	Yes	Yes	Yes	Supported by design
P5532	5.15	H.264 M-JPEG	1	720x480	1-way	2/2	Yes*	Yes	Yes*	Yes	
P5532-E		H.264 M-JPEG	1	720x480	1-way	2/2	Yes*	Yes	Yes	Yes	Supported by design
P5534	5.15.1	H.264 M-JPEG	1	1280x720	1-way	2/2	Yes*	Yes	Yes	Yes	Supported by design
P5534-E		H.264 M-JPEG	1	1280x720	1-way	2/2	Yes*	Yes	Yes	Yes	Supported by design
P5544	5.41.2.2	H.264 M-JPEG	1	1280x720	*2	*2	Yes	*2	*2	Yes*	
Note:	P5544 is a two-len (fisheye and PTZ) camera										
P7210	5.50.2	H.264 M-JPEG	20*	1536x1152	1-way	16/16	Yes*	Yes	Yes	Yes	
Note:	P7210 is 4IP x 5channels video server										
P7214	Refer to P7210	H.264 M-JPEG	4	720x576	1-way	4/4	Yes*	Yes	Yes	Yes	Supported by design
P7224	5.40.7	H.264 M-JPEG	4	720x576	1-way	4/4	Yes*	Yes	Yes	Yes	
Note:	P7224 can't use second audio input. First audio only support G.711										
P8221	5.10.1	*2	1	-	*2	*2	-	-	*2	-	
Note:	Network I/O audio module										
P8513	Refer to P8514	H.264 M-JPEG	1	800x600	-	0/0	-	Yes	Yes	Yes	Supported by design
P8514	5.21	H.264 M-JPEG	1	1280x800	-	0/0	-	Yes	Yes	Yes	
Q1602	5.40.3	H.264 M-JPEG	1	768x576	1-way	1/1	-	Yes	Yes	Yes	tested by link
Note:	P7210, P8514, Q1602 camera not testing Audio, I/O, UPNP capability Q1602-E is compatible with Q1602										

AXIS



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/A2A2100kbps

Yes*: multi stream setting support

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
Q1604	5.40.3.2	H.264 M-JPEG	1	1280x960	1-way	1/1	-	Yes	Yes	Yes	
Note:	1. Not support AAC when codec is MJPEG 2. Does not support H264 CBR mode										
Q1614	5.55.1	H.264 MJPEG	1	1280x960	*2	*2	-	*2	*2	Yes*	tested by link
Q1615	5.55.3	H.264 MJPEG	1	1920x1200	*2	*2	-	*2	*2	Yes*	tested by link
Note:	Q1614 and Q1615: Max framerate show 60 regardless of Axis Capture mode.										
Q1755	5.02	H.264 M-JPEG	1	1920x1080	1-way	1/1	Yes*	Yes	Yes	Yes	
Note:	M-JPEG: Due to the HW constraints, the frame rate and audio will be impacted if resolution and quality are high.										
Q1755-E		H.264 M-JPEG	1	1920x1080	1-way	1/1	Yes*	Yes	Yes	Yes	Supported by design
Q1765-LE	5.55.1	H.264 M-JPEG	1	1920x1080	1-way	2/2	Yes*	Yes	Yes	Yes	
Q1910	5.06	H.264 M-JPEG	1	720x576	1-way	1/1	Yes*	Yes	Yes	Yes	
Q1910-E		H.264 M-JPEG	1	720x576	1-way	1/1	Yes*	Yes	Yes	Yes	Supported by design
Q1921	5.11	H.264 M-JPEG	1	768x576	1-way	2/0	-	Yes	Yes*	Yes	
Note:	Q1921 camera not testing Audio, I/O, UPnP capability										
Q1921-E		H.264 M-JPEG	1	768x576	1-way	2/0	-	Yes	Yes	Yes	Supported by design
Q1922	Refer to Q1921	H.264 M-JPEG	1	800x600	1-way	1/1	-	Yes	Yes	Yes	Supported by design
Q1931-E	5.55.1	H.264 M-JPEG	1	768X576	1-way	2/2	-	Yes	*2	Yes	
Note:	1.Thermal camera 2.Up to 30 fps within EU, Norway, Switzerland, Canada, USA, Japan, Australia, New ZealandUp to 8.3 fps in other countriesa										

AXIS



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/A2A2100kbps

Yes*: multi stream setting support

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
Q6032		H.264 M-JPEG	1	752x480	1-way	4/4	Yes*	Yes	Yes	Yes	Supported by design
Q6032-E	5.05	H.264 M-JPEG	1	704x576	-	-	Yes*	Yes	Yes	Yes	
Q6034	5.20.3	H.264 M-JPEG	1	1280x720	1-way	2/2	Yes*	Yes	Yes*	Yes	
Q6034-E		H.264 M-JPEG	1	1280x720	1-way	2/2	Yes*	Yes	Yes	Yes	Supported by design
Q6035		H.264 M-JPEG	1	1920x1080	1-way	4/4	Yes*	Yes	Yes	Yes	Supported by design
Q6035-E		H.264 M-JPEG	1	1920x1080	1-way	-	Yes*	Yes	Yes	Yes	Supported by design
Q6042	5.55.1	H.264 M-JPEG	1	752x480	1-way	4/4	Yes*	Yes	*2	Yes	
Q6044	5.55.1	H.264 M-JPEG	1	1920x1080	1-way	4/4	Yes*	Yes	Yes	Yes	Supported by design
Q6045	5.55.1	H.264 M-JPEG	1	1920x1080	1-way	4/4	Yes*	Yes	Yes	Yes	Tested by link
Q7401		H.264 M-JPEG	1	704x576	1-way	2/2	Yes*	Yes	Yes	Yes	Supported by design
Q7404	5.02	H.264 M-JPEG	4	768x576	1-way	1/1	Yes*	Yes	Yes	Yes	
Q7406	5.11.1	H.264 M-JPEG	6	704x576	-	1/1	Yes*	Yes	Yes	Yes	
Q7411	5.40.13.1	H.264 M-JPEG	1	720x576	1-way	4/4	Yes*	Yes	Yes	Yes	
Q7414	5.25	H.264 M-JPEG	4	720x576(PAL) 720x480(NTSC)	1-way	1/1	Yes*	Yes	Yes	Yes	tested by link
Q7424-R	5.40.10	H.264 M-JPEG	4	720x576	1-way	4/4	Yes*	Yes	Yes	Yes	