



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
BB-HCE481		M-JPEG	1	640x480	2-way	2/1	-	Yes	Yes	-	-	Supported by design
BB-HCM100		M-JPEG	1	640x480	1-way	2/1	Yes	Yes	Yes	-	-	Supported by design
BB-HCM110		M-JPEG	1	640x480	1-way	2/1	Yes	Yes	Yes	-	-	Supported by design
BB-HCM311		M-JPEG	1	640x480	2-way	2/1	Yes	Yes	Yes	-	-	Supported by design
BB-HCM331	1.3	M-JPEG	1	640x480	2-way	2/1	Yes	Yes	Yes	-	-	
BB-HCM371		M-JPEG	1	640x480	1-way	2/1	-	Yes	Yes	-	-	Supported by design
BB-HCM381	1.32	M-JPEG	1	640x480	2-way	1/1	Yes	Yes	Yes	-	-	
BB-HCM403		M-JPEG	1	640x480	2-way	2/1	-	Yes	Yes	-	-	Supported by design
BB-HCM511	3.20R01	MPEG4 M-JPEG	1	640x480	2-way	2/1	Yes	Yes	Yes	-	-	
BB-HCM515	3.14R01	MPEG4 M-JPEG	1	1280x1024	2-way	2/1	-	Yes	Yes	-	-	
Note:	No audio support in M-JPEG format @ 1280x1024.											
BB-HCM527	3.51R00	MPEG4 M-JPEG	1	640x480	2-way	2/1	-	Yes	Yes	-	-	
BB-HCM531	3.51R00	MPEG4 M-JPEG	1	640x480	2-way	2/1	-	Yes	Yes	-	-	
BB-HCM547	3.60R00	MPEG4 M-JPEG	1	640x480	2-way	2/1	Yes	Yes	Yes	-	-	
BB-HCM580		MPEG4 M-JPEG	1	640x480	2-way	2/1	-	Yes	Yes	-	-	Supported by design
BB-HCM581	3.21R00	MPEG4 M-JPEG	1	640x480	2-way	2/1	Yes	Yes	Yes	-	-	
BB-HCM701	4.30R00	H.264 MPEG4 M-JPEG	1	640x480	1-way	1/0	-	Yes	Yes	-	-	
BB-HCM705	4.30R00	H.264 MPEG4 M-JPEG	1	1280x960	1-way	1/0	Yes	Yes	Yes	-	-	
BB-HCM715	4.30R00	H.264 MPEG4 M-JPEG	1	1280x960	2-way	2/1	Yes	Yes	Yes	Yes	-	



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
<b>BB-HCM735</b>	4.30R00	H.264 MPEG4 M-JPEG	1	1280x960	2-way	2/1	Yes	Yes	Yes	Yes	-	
<b>BB-HCS301</b>		M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	-	-	Supported by design
<b>BB-ST162</b>	refer to WV-ST162(1 Application: 1.81 2 Image data: 1.04)	H264 MJPEG	1	800x600	-	3/1	Yes	Yes	-	-	-	Supported by design
<b>BB-SW172</b>	refer to WV-ST162(1 Application: 1.81 2 Image data: 1.04)	H264 MJPEG	1	800x600	-	3/1	Yes	Yes	-	-	-	Supported by design
<b>BL-C1</b>		M-JPEG	1	640x480	-	-	-	Yes	Yes	-	-	Supported by design
<b>BL-C10</b>		M-JPEG	1	640x480	-	-	Yes	Yes	Yes	-	-	Supported by design
<b>BL-C20</b>		M-JPEG	1	640x480	-	-	-	Yes	Yes	-	-	Supported by design
<b>BL-C30</b>		M-JPEG	1	640x480	-	-	Yes	Yes	Yes	-	-	Supported by design
<b>BL-C101</b>	3.52R00	MPEG4 M-JPEG	1	640x480	1-way	1/0	-	Yes	Yes	-	-	
<b>BL-C111</b>	3.10R01	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	Yes	-	-	
<b>BL-C121</b>	3.52R00	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	-	-	
<b>BL-C131</b>		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	-	-	Supported by design
<b>BL-C140</b>	3.51R00	MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	-	-	
<b>BL-C160</b>	3.51R01	MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	-	-	
<b>BL-C210</b>	4.31R00	M-JPEG MPEG4 H.264	1	640x480	1-way	-	Yes	Yes	Yes	-	-	
<b>BL-C230</b>		M-JPEG MPEG4 H.264	1	640x480	1-way	-	Yes	Yes	Yes	-	-	Supported by design



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
<b>BL-VP101</b>	Application: 1.67	H264 MJPEG	1	640x480	-	-	-	Yes	-	-	-	
<b>BL-VP104</b>	Application: 1.67	H264 MJPEG	1	1280x720	-	-	-	Yes	-	-	-	
<b>BL-VP104W</b>	refer BL-VP104(FW Application: 1.67 )	H264 MJPEG	1	1280x720	-	-	-	Yes	-	-	-	Supported by design
<b>BL-VT164</b>	Application: 1.81	H264 MJPEG	1	1280x720	2-way	-	Yes	Yes	-	-	-	
<b>BL-VT164W</b>	refer BL-VT164(FW Application: 1.81)	H264 MJPEG	1	1280x720	2-way	-	Yes	Yes	-	-	-	Supported by design
<b>DG-GXE100</b>	2.02	H.264	1	720x480	-	-	*2	Yes	*2	*2	Yes*	
<b>DG-NF284</b>		MPEG4 M-JPEG	1	640x480	1-way	-	-	-	-	-	-	Supported by design
<b>DG-NF302</b>	1.5	MPEG4 M-JPEG	1	1280x960	1-way	-	-	-	-	-	-	
<b>DG-NP240</b>		MPEG4 M-JPEG	1	640x480	1-way	-	-	-	-	-	-	Supported by design
<b>DG-NP244</b>	1.70J2	MPEG4 M-JPEG	1	640x480	1-way	-	-	-	-	-	-	
<b>DG-NP304</b>	1.5	MPEG4 M-JPEG	1	1280x960	2-way	-	-	-	-	-	-	
<b>DG-NS202</b>		MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	-	-	Supported by design
<b>DG-NS202A</b>	2.60J3	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	-	-	
<b>DG-NS950</b>	1.5	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	-	-	
<b>DG-NS954</b>	1.5	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	-	-	
<b>DG-NW960</b>	1.5	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	-	-	
<b>DG-NW964</b>	1.5	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	-	-	



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
<b>DG-SC385</b>	Refer to WV-SC385 1 Application: 1.66 2 Driver: 1.39 3 Image data: 1.09	M-JPEG MPEG4 H.264	1	1280x960	*2	*2	Yes	Yes	-	Yes	-	Supported by design
<b>DG-SF132</b>	Refer to WV-SP102(1 Application: 1.81 2 Image data: 1.03)	H.264 M-JPEG	1	640x480	-	-	-	Yes	-	-	-	Supported by design
<b>DG-SF334</b>	1.00	M-JPEG MPEG4 H.264	1	1280x960	1-way	-	-	Yes	-	-	-	
<b>DG-SP102</b>	Refer to WV-SP102(1 Application: 1.81 2 Image data: 1.03)	H.264 M-JPEG	1	640x480	-	-	-	Yes	-	-	-	Supported by design
<b>DG-SW155</b>	Refer to WV-SW155/M	MJPEG H264	1	1280x960	-	-	-	Yes	-	-	-	Supported by design
<b>K-EF134L</b>	V2.42	MJPEG H264	1	1280x960	-	-	-	Yes	-	-	Yes*	
Note:	1. The bit-rate values in the combo box are not all valid, users have to choose a valid one (the range can be get from the web of the device) while setting. (NUUO Server limitation) 2. Video parameter setting and rotate function may result in failure by Day/Night profile. (Camera Firmware issue) 3. When format is MJPEG, and resource is too much, the image is not complete. (Camera performance limitation)											
<b>K-EW114L</b>	2.420.PS00.0. T, build:2014-09-19	MJPEG H264	1	1280x960	-	-	-	*2	*2	-	Yes*	
Note:	1. The bit-rate values in the combo box are not all valid, users have to choose a valid one (the range can be get from the web of the device) while setting. (NUUO Server limitation) 2. Video parameter setting and rotate function may result in failure by Day/Night profile. (Camera Firmware issue) 3. When format is MJPEG, and resource is too much, the image is not complete. (Camera performance limitation) 4. The bitrate ranges of server are different from camera web while image format is MJPEG.(Camera Firmware issue)											
<b>KX-HCM110</b>		M-JPEG	1	640x480	1-way	2/1	-	Yes	Yes	-	-	Supported by design
<b>KX-HCM280A</b>		M-JPEG	1	640x480	-	1/1	-	Yes	Yes	-	-	Supported by design
<b>WJ-GXE500</b>	1.04	M-JPEG MPEG4 H.264	4	720x480:D1 640x480:vga	2-way	*1	Yes	Yes	-	-	-	
<b>WJ-NT304</b>	1.04	M-JPEG	4	640x480	-	-	Yes	-	-	-	-	



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
<b>WJ-NT314</b>		M-JPEG	4	640x480	1-way	-	Yes	-	-	-	-	Supported by design
<b>WV-NF284</b>	v1.02	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	-	-	-	-	
<b>WV-NF302</b>	1.40E4_1.06	MPEG4 M-JPEG	1	1280x960	2-way	-	-	Yes	-	-	-	
<b>WV-NM100</b>		MPEG4 M-JPEG	1	640x480	-	-	Yes	-	-	-	-	Supported by design
<b>WV-NP1000</b>		M-JPEG	1	1280x960	1-way	-	-	-	-	-	-	Supported by design
<b>WV-NP1004</b>	1.21	M-JPEG	1	1280x960	1-way	-	-	-	-	-	-	
<b>WV-NP240</b>		MPEG4 M-JPEG	1	640x480	1-way	-	-	-	-	-	-	Supported by design
<b>WV-NP244</b>		MPEG4 M-JPEG	1	640x480	1-way	-	-	-	-	-	-	Supported by design
<b>WV-NP304</b>	1.50E5_1.06	MPEG4 M-JPEG	1	1280x960	2-way	-	-	Yes	-	-	-	
<b>WV-NP472</b>		M-JPEG	1	640x480	-	-	-	-	-	-	-	Supported by design
<b>WV-NP502</b>	1.00	H.264 MPEG4 M-JPEG	1	2048x1536	2-way	-	-	Yes	-	-	-	
<b>WV-NS202</b>		MPEG4 M-JPEG	1	640x480	2-way	-	Yes	Yes	-	-	-	Supported by design
<b>WV-NS202A</b>	2.6	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	-	-	
<b>WV-NS324</b>	2.01	M-JPEG	1	640x480	-	-	Yes	-	-	Yes	-	
<b>WV-NS950</b>	1.5	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	-	-	
<b>WV-NS954</b>	1.06E0	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	-	-	
Note:	Audio is abnormal in MPEG4 format.											
<b>WV-NW484</b>	1.10ED	MPEG4 M-JPEG	1	640x480	-	-	-	Yes	-	-	-	
<b>WV-NW502S</b>	1.00	H.264 MPEG4 M-JPEG	1	2048x1536	2-way	-	-	Yes	-	-	-	



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
<b>WV-NW960</b>	1.5	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	-	-	-	-	
<b>WV-NW964</b>	1.40E3	MPEG4 M-JPEG	1	640x480	2-way	-	Yes	Yes	-	-	-	
<b>WV-SC384</b>	1.46	M-JPEG MPEG4 H.264	1	1280x960	2-way	0~3/0 ~1	Yes	Yes	-	Yes	-	Supported by design
<b>WV-SC385</b>	Application: 2.10 Driver: 1.54	H.264	1	1280x960	2-way	3/1	Yes	Yes	Yes	Yes	Yes*	
Note:	1. Brightness value may not sync with web. (Camera Firmware issue) 2. Bit Rate Control(Transmission priority) only support Constant bit rate & Frame rate. (NUUO server limitation) 3. The flip status on camera web is opposite to server. (Camera Firmware issue)											
<b>WV-SC386</b>	1 Application: 1.44 2 Driver: 1.12 3 Image data: 1.05	M-JPEG MPEG4 H.264	1	1280x960	2-way	0~3/0 ~1	Yes	Yes	-	Yes	-	
<b>WV-SF132</b>	Refer to WV-SP102(FW1 Application: 1.81 2 Image data: 1.03)	H.264 M-JPEG	1	640x480	-	-	-	Yes	-	-	-	Supported by design
<b>WV-SF135</b>	Refer to WV-SW155/M	MJPEG H264	1	1280x960	-	-	-	Yes	-	-	-	Supported by design
<b>WV-SF332</b>		M-JPEG MPEG4 H.264	1	1280x960	2-way	0~1/0 ~1	-	Yes	-	-	-	Supported by design
<b>WV-SF335</b>		M-JPEG MPEG4 H.264	1	1280x960	2-way	0~1/0 ~1	-	Yes	-	-	-	Supported by design
Note:	WV-SF355 include WV-SF335E											
<b>WV-SF336</b>	1.05	M-JPEG MPEG4 H.264	1	1280x960	2-way	*1	-	Yes	-	-	-	
<b>WV-SF342</b>		M-JPEG MPEG4 H.264	1	1280x960	2-way	*1	-	Yes	-	-	-	Supported by design
<b>WV-SF346</b>		M-JPEG MPEG4 H.264	1	1280x960	2-way	*1	-	Yes	-	-	-	Supported by design
<b>WV-SF438</b>	1 Application: 1.04 2 Image data: 1.12	H264 MJPEG	1	2048x1536	2-way	3/1	-	Yes	-	-	-	
Note:	Talk cannot use G726 16 kbps Fisheye camera											



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software  
 For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
<b>WV-SF539</b>	1 Application: 1.60 2 Image data: 2.34	H.264	1	1920x1080	*2	*2	-	Yes	*2	-	Yes*	
Note:	1. Brightness value may not sync with web. (Camera Firmware issue) 2. We tested on camera web with the following parameters, and found camera will disconnect or image will delay. The following link lists some issues: <a href="https://docs.google.com/spreadsheets/d/1Ri44tFID29DKYhf-s6VQhDlmfYycbLV8nuhpASVlksW/edit#gid=0">https://docs.google.com/spreadsheets/d/1Ri44tFID29DKYhf-s6VQhDlmfYycbLV8nuhpASVlksW/edit#gid=0</a> 3. The 2nd stream cannot be set and connect while the image mode is 3mega pixel.(Camera Firmware issue)											
<b>WV-SFN310</b>	V1.71	H.264	1	1280x960	1-way	3/1	-	Yes	-	-	Yes*	
Note:	1. Setting higher bitrate may be fail (Camera firmware issue) 2. When 60fps mode , H.264(1) bitrate cannot be set less than 1024 (Camera firmware issue) 3. No Audio when audio codec is AAC (NUUO server limitation) 4. Bitrate list range is not synchronize with web(Camera firmware issue) 5.MJPEG framerate is affected by h264 stream. If h264 stream(1 or 2) open, MJPEG support 5 fps the most. (Camera performance limitation) 6.Brightness value may not sync with web.(Camera firmware issue) 7.Motion event snaphot resolution sync with stream3 instead of stream1.(Camera firmware issue)											
<b>WV-SFN311</b>	refer to WV-SFN310(1.71)	H.264	1	1280x960	1-way	3/1	-	Yes	-	-	Yes	Supported by design
<b>WV-SFN310J</b>	refer to WV-SFN310(1.71)	H.264	1	1280x960	1-way	3/1	-	Yes	-	-	Yes	Supported by design
<b>WV-SFV481</b>	1.12	H.264	1	2992x2992	2-way	3/1	-	Yes	Yes	-	Yes*	
Note:	Fisheye camera 1. Brightness Value may not sync with Camera Web Interface.(Camera Firmware issue) 2. Audio out 16Kbps was not supported.(NUUO server limitation) 3. Digital in and Digital out can not trigger continuously.(Camera Firmware issue) 4. Camera may not achieve maximum FPS.(Camera performance limitation) 5. The range of bitrate may not sync with camera web.(Camera Firmware issue) 6. The bit-rate & FPS values in the combo box are not all valid, users have to choose a valid one (the range can get from the web of the device) while setting.(NUUO server limitation) 7. Snapshot resolution may not sync with display resolution.(NUUO server limitation)											
<b>WV-SFV611L</b>	Refer to WV-SFV631L(V1.83)	H.264	1	2048x1536	*2	*2	-	Yes	*2	-	Yes*	Supported by design
<b>WV-SFV631L</b>	1.83	H.264	1	2048x1536	*2	3/1	-	Yes	*2	-	Yes*	
Note:	1. The bitrate list doesn't match the camera web.(Camera Firmware issue) 2. Zoom & focus can't be usde.(Camera Firmware issue) 3. Brightness value may not sync with web.(Camera Firmware issue) 4. Bit Rate Control(Tramsmission priority) only support Constant bit rate & Frame rate.(NUUO server limitation)											



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
<b>WV-SFV631LT</b>	Refer to WV-SFV631L(V1.83)	H.264	1	2048x1536	*2	*2	-	Yes	*2	-	Yes*	Supported by design
<b>WV-SP102</b>	1 Application: 1.81 2 Image data:	H.264 M-JPEG	1	640x480	-	-	-	Yes	-	-	-	Tested by link
<b>WV-SP105</b>	1 Application: 1.61 2 Image data:	M-JPEG H.264	1	1280x960	-	-	-	Yes	-	-	-	
<b>WV-SP302</b>		M-JPEG MPEG4 H.264	1	1280x960	2-way	*1	-	Yes	-	-	-	Supported by design
<b>WV-SP305</b>		M-JPEG MPEG4 H.264	1	1280x960	2-way	*1	-	Yes	-	-	-	Supported by design
<b>WV-SP306</b>	1.04	M-JPEG MPEG4 H.264	1	1280x960	2-way	*1	-	Yes	-	-	-	
<b>WV-SP508</b>	1 Application: 1.05 2 Image data: 2.05	MJPEG H264	1	2048x1536	-	0~1/0 ~1	-	Yes	-	-	-	Tested by link
<b>WV-SP509</b>	1 Application: 1.07 2 Image data: 2.11	MJPEG H264	1	2048x1536	2-way	0~3/0 ~1	-	Yes	-	-	-	
<b>WV-SPN311</b>	V1.71	H.264	1	1280x720	2-way	3/1	-	Yes	Yes	-	Yes	
<b>WV-SPN631</b>	Refer to WV-SFV631L(V1.83)	H.264	1	2048x1536	*2	*2	-	Yes	*2	-	Yes*	Supported by design
<b>WV-SPW631L</b>	Refer to WV-SFV631L(V1.83)	H.264	1	2048x1536	*2	*2	-	Yes	*2	-	Yes*	Supported by design
<b>WV-ST162</b>	1 Application: 1.81 2 Image data: 1.04	H264 MJPEG	1	800x600	-	3/1	Yes	Yes	-	-	-	Tested by link
<b>WV-ST165</b>	1 Application: 1.44 2 Image data: 1.03	MJPEG H264	1	1280x960	2-way	0~3/0 ~1	Yes	Yes	-	-	-	Tested by link
<b>WV-SW152/M</b>	Refer to WV-SW155/M	MJPEG H264	1	1280x960	-	-	-	-	-	-	-	Supported by design
<b>WV-SW155</b>	2.02	H.264	1	1280x720	-	*2	-	Yes	*2	-	Yes*	
Note:	Brightness value may not sync with web. (Camera Firmware issue)											





- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
<b>WV-SW155/M</b>	1.06	MJPEG H264	1	1280x960	-	-	-	-	-	-	-	Tested by link
<b>WV-SW158</b>	1.07	H.264 MJPEG	1	2048x1536	1-way	-	-	Yes	Yes	-	Yes*	
Note:	1. Mirror is not supported (Camera firmware issue) 2. It may have chance to fail to set higher bitrate (Cammera firmware issue)											
<b>WV-SW172</b>	refer to WV-ST162(FW1 Application: 1.81 2 Image data: 1.04)	H264 MJPEG	1	800x600	-	3/1	Yes	Yes	-	-	-	Supported by design
<b>WV-SW174W</b>	1.81	MJPEG H264	1	1280x960	2-way	0~3/0 ~1	Yes	Yes	Yes	-	-	
Note:	WV-SW174W Camera constraint: MJPEG framerate is affected by h264 stream. If h264 stream(1 or 2) open, MJPEG support 5 fps the most.											
<b>WV-SW175</b>	Refer to ST165	MJPEG H264	1	1280x960	2-way	0~3/0 ~1	Yes	Yes	-	-	-	Supported by design
<b>WV-SW314</b>	Refer to SW316/L	MJPEG H264	1	1280x960	-	-	-	Yes	-	-	-	Supported by design
<b>WV-SW316/L</b>	1Application: 1.46 2 Image data: 1.04	MJPEG H264	1	1280x960	2-way	0~1/0 ~1	-	Yes	-	-	-	Tested by link
<b>WV-SW352</b>		M-JPEG MPEG4 H.264	1	1280x960	2-way	*1	-	-	-	-	-	Supported by design
<b>WV-SW355</b>	1.01	M-JPEG MPEG4 H.264	1	1280x960	2-way	0~1/0 ~1	-	-	-	-	-	Tested by link
<b>WV-SW395</b>		M-JPEG MPEG4 H.264	1	1280x960	2-way	*1	Yes	-	-	Yes	-	Supported by design
<b>WV-SW396</b>	1.44	M-JPEG MPEG4 H.264	1	1280x960	2-way	0~3/0 ~1	Yes	Yes	-	Yes	-	
Note:	WV-SW396 support continuous PTZ											
<b>WV-SW458</b>	V1.60	H.264	1	1920x1080	2-way	3/1	-	Yes	Yes	-	Yes*	
Note:	Fisheye camera 1. G726/16Kbps has noise. (NUUO server limitation) 2. Brightness value may not sync with web.(Camera firmware issue) 3. MountType and DispalyMode UI only support English. (NUUO server limitation) 4. Camera is unable to achieve maximum FPS. (Camera Limitation) 5. Setting higher bitrate may be fail (Cammera firmware issue) 6. Motion event snapthot resolution may not sync with current stream (NUUO server limitation)											



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
<b>WV-SW558</b>	Refer to SP509	MJPEG H264	1	2048x1536	-	0~3/0~1	-	Yes	-	-	-	Supported by design
<b>WV-SW559</b>	Refer to SP509	MJPEG H264	1	2048x1536	2-way	0~3/0~1	-	Yes	-	-	-	Supported by design
<b>WV-SW598</b>	2.07	H.264	1	1920x1080	*2	*2	Yes	*2	*2	v	Yes*	
Note:	1. Brightness value may not sync with web.(Camera Firmware issue) 2. The flip status on camera web is opposite to server.(Camera Firmware issue) 3.The move function can not make live view to center. (Camera Firmware issue)											





















