

- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

Device	Tested	Video	Video	stick support Max		I/O Ch	PTZ	On-Edge	UPnP	Multi Stream	Remarks
Name	Firmware	Format	Ch	Resolution	Audio	1/0 CII	PIZ	Motion	UPIIP	Support	Remarks
BB-HCE481		M-JPEG	1	640x480	1-way	2/1	-	Yes	Yes	Yes	Supported by design
ВВ-НСМ100	1.3	M-JPEG	1	640x480	1-way	2/1	-	Yes	Yes	Yes	
ВВ-НСМ110	1.3	M-JPEG	1	640x480	1-way	2/1	Yes	Yes	Yes	Yes	
вв-нсм311		M-JPEG	1	640x480	1-way	2/1	Yes	Yes	Yes	Yes	Supported by design
вв-нсм331	1.3	M-JPEG	1	640x480	1-way	2/1	Yes	Yes	Yes	Yes	
BB-HCM371		M-JPEG	1	640x480	1-way	2/1	-	Yes	Yes	Yes	Supported by design
вв-нсм381	1.3	M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	Yes	
вв-нсм403		M-JPEG	1	640x480	1-way	2/1	-	Yes	Yes	Yes	Supported by design
BB-HCM511	1.3	MPEG4 M-JPEG	1	640x480	1-way	2/1	Yes	Yes	Yes	Yes	
BB-HCM515	3.11R01	MPEG4 M-JPEG	1	1280x1024	1-way	2/1	-	Yes	Yes	Yes	
Note:	No audio supp	ort in M-JPEC	6 @ 128	0x1024.							
BB-HCM527		MPEG4 M-JPEG	1	640x480	1-way	2/1	-	Yes	Yes	Yes	Supported by design
BB-HCM531	3.51R00	MPEG4 M-JPEG	1	640x480	1-way	2/1	-	Yes	Yes	Yes	
вв-нсм547	3.60R00	MPEG4 M-JPEG	1	640x480	1-way	2/1	Yes	Yes	Yes	Yes	
Note:	The camera is	tested by lin	k, so so	me functions c	an't be	verified.					
вв-нсм580		MPEG4 M-JPEG	1	640x480	-	2/1	-	Yes	Yes	Yes	Supported by design
BB-HCM581	1.3	MPEG4 M-JPEG	1	640x480	1-way	2/1	Yes	Yes	Yes	Yes	
BB-HCM701	4.30R00	H.264 MPEG4 M-JPEG	1	640x480	1-way	1/0	-	Yes	Yes	Yes	



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
вв-нсм705	4.11R01	H.264 MPEG4 M-JPEG	1	1280x960	1-way	1/0	-	Yes	Yes	Yes	
BB-HCM715		H.264 MPEG4 M-JPEG	1	1280x960	1-way	2/1	Yes	Yes	Yes	Yes	Supported by design
вв-нсм735	1.05-03 (100303-02)	H.264 MPEG4 M-JPEG	1	1280×960	1-way	2/1	Yes	Yes	Yes	Yes	
BB-HCS301		M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design
BB-ST162	refer to WV- ST162(FW 1 Application: 1.81 2 Image data: 1.04)	H264 MJPEG	1	800x600	-	3/1	Yes	Yes	-	Yes	Supported by design
BB-SW172	refer to WV- ST162(FW 1 Application: 1.81 2 Image data: 1.04)	H264 MJPEG	1	800x600	-	3/1	Yes	Yes	-	Yes	Supported by design
BL-C1		M-JPEG	1	640x480	-	-	-	Yes	Yes	Yes	Supported by design
BL-C10		M-JPEG	1	640x480	-	-	Yes	Yes	Yes	Yes	Supported by design
BL-C101	3.52R00	MPEG4 M-JPEG	1	640x480	1-way	1/0	-	Yes	Yes	Yes	
BL-C111	3.10R01	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	Yes	Yes	
BL-C121	3.52R00	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	
BL-C131		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	Yes	Supported by design
BL-C140	3.51R01	MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	Yes	
BL-C160	3.51R01	MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	Yes	
BL-C20		M-JPEG	1	640x480	-	-	-	Yes	Yes	Yes	Supported by design



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
BL-C210	4.31R00	H.264 MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	Yes	Yes	
BL-C230		H.264 MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	Yes	Yes	Supported by design
BL-C30		M-JPEG	1	640x480	-	-	Yes	Yes	Yes	Yes	Supported by design
BL-VP101	Application: 1.67	H264 MJPEG	1	640x480	-	ı	-	Yes	-	Yes	
BL-VP104	Application: 1.67	H264 MJPEG	1	1280x720	-	-	-	Yes	-	Yes	
BL-VP104W	refer BL- VP104(FW Application: 1.67)	H264 MJPEG	1	1280x720	-	-	-	Yes	-	Yes	Supported by design
BL-VT164	Application: 1.81	H264 MJPEG	1	1280x720	1-way	-	Yes	Yes	-	Yes	
BL-VT164W	refer BL- VT164(FW Application: 1.81)	H264 MJPEG	1	1280x720	1-way	-	Yes	Yes	-	Yes	Supported by design
KX-HCM110		M-JPEG	1	640x480	1-way	2/1	-	Yes	Yes	Yes	Supported by design
KX- HCM280A		M-JPEG	1	640x480	-	1/1	-	Yes	Yes	Yes	Supported by design
DG-GXE100	2.02	H.264	1	720x480	-	-	*2	Yes	*2	Yes*	
DG-NF282		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	-	Supported by design
DG-NF302	1.5	MPEG4 M-JPEG	1	1280x960	1-way	-	-	Yes	-	-	Supported by design
DG-NP240		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	-	Supported by design
DG-NP244		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	Yes	Supported by design
DG-NP304	1.5	MPEG4 M-JPEG	1	1280x960	1-way	-	-	Yes	-	Yes	Supported by design



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

		10	J . JOY	stick support	to com	TOTT IZ Spec	Ju III CI	yotai			
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
DG-NS202		MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Yes	Supported by design
DG-NS202A	2.6	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Yes	
DG-NS950	1.5	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Yes	Supported by design
DG-NS954	1.5	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Yes	Supported by design
DG-NW960	1.5	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Yes	Supported by design
DG-NW964	1.5	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Yes	Supported by design
DG-SC385	Refer to WV- SC385 1 Application: 1.66 2 Driver: 1.39 3 Image data: 1.09	M-JPEG MPEG4 H.264	1	1280x960	*2	*2	Yes	Yes	-	Yes	Supported by design
DG-SF132	Refer to WV- SP102(FW 1 Application: 1.81 2 Image data: 1.03)	H.264 M-JPEG	1	640×480	-	-	-	Yes	-	Yes	Supported by design
DG-SF334	1.03 1.05	H.264 MPEG4 M-JPEG	1	1280x960	1-way	-	-	Yes	-	Yes	
Note:	Disable H.264 ar	nd MPEG4	will get I	MJPEG stream	playing	more smoothl	у.				
DG-SP102	Refer to WV- SP102(FW 1 Application: 1.81 2 Image data: 1.03)	H.264 M-JPEG	1	640x480	-	-	-	Yes	-	Yes	Supported by design
DG-SW155	Refer to WV-SW155/M	H.264 M-JPEG	1	1280x960	1-way	-	-	Yes	-	Yes	Supported by design
K-EF134L	V2.42	H.264 M-JPEG	1	1280x960	-	-	-	Yes	Yes	Yes*	



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal														
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks			
Note:	1. The bit-rate view of the device 2. Video parame 3. When format 4. UPnP search format 1.	e) while se ter setting is MJPEG, a	tting. (Name and rotated and resonant and re	NUUO Server li ate function m ource is too mu	mitation ay result) in failure by	Day/Nig	ght profile. (Camera	Firmware	issue)			
K-EW114L	2.420.PS00.0.T, build:2014-09- 19	H.264 M-JPEG	1	1280x960	-	-	-	Yes	*2	Yes*				
Note:	web of the devic 2. Video parame 3. When format	The bit-rate values in the combo box are not all valid, users have to choose a valid one (the range can be get from the veb of the device) while setting. (NUUO Server limitation) Video parameter setting and rotate function may result in failure by Day/Night profile. (Camera Firmware issue) When format is MJPEG, and resource is too much, the image is not complete. (Camera performance limitation) The bitrate ranges of server are different from camera web while image format is MJPEG.(Camera Firmware issue)												
WJ-GXE500	1.03	H.264 MPEG4 M-JPEG	4	720x480	1-way	-	-	Yes	-	Yes				
Note:	Motion detection Not support PTZ		ormally	when "face de	etection"	function is er	nabled.							
WJ-NT304	1.04	M-JPEG	4	640x480	-	-	Yes	-	-	Yes				
WJ-NT314		M-JPEG	4	640x480	1-way	ı	Yes	-	-	Yes	Supported by design			
WV-NF284		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	Yes	Supported by design			
WV-NF302	1.40E4_1.06	MPEG4 M-JPEG	1	1280x960	1-way	-	-	Yes	-	Yes				
WV-NM100		MPEG4 M-JPEG	1	640x480	-	-	Yes	-	-	Yes	Supported by design			
WV-NP1000		M-JPEG	1	1280x960	1-way	-	-	Yes	-	Yes	Supported by design			
WV-NP1004	1.21	M-JPEG	1	1280x960	1-way	-	-	Yes	-	Yes				
WV-NP240		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	Yes	Supported by design			
WV-NP244		MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	-	Yes	Supported by design			
WV-NP304	1.50E5_1.06	MPEG4 M-JPEG	1	1280x960	1-way	-	-	Yes	-	Yes				



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
WV-NP472		M-JPEG	1	640x480	-	-	-	Yes	-	Yes	Supported by design
WV-NP502	1.00	H.264 MPEG4 M-JPEG	1	2048x1536	1-way	-	-	Yes	-	Yes	
WV-NS202		MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Yes	Supported by design
WV-NS202A	2.6	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Yes	Supported by design
WV-NS324		M-JPEG	1	640x480	-	-	Yes	Yes	-	Yes	Supported by design
WV-NS950	1.5	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Yes	Supported by design
WV-NS954	1.06E0	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Yes	
Note:	Audio is abnorm	al in MPEG	4 format	t.							
WV-SC384	1.46	H.264 MPEG4 M-JPEG	1	1280x960	1-way	0~3/0~1	Yes	Yes	-	Yes	Supported by design
WV-SC385	Application: 2.10 Driver: 1.54	H.264	1	1280x960	1-way	3/1	Yes*	Yes	Yes	Yes*	
Note:	Brightness va Bit Rate Conti The flip status	rol (Transm	nission p	riority) only su	ipport C	onstant bit ra			JUO ser	ver limitati	on)
wv-sc386	1 Application: 1.44 2 Driver: 1.12 3 Image data: 1.05	M-JPEG MPEG4 H.264	1	1280x960	1-way	0~3/0~1	Yes	Yes	-	Yes	
WV-SF132	Refer to WV- SP102(FW 1 Application: 1.81 2 Image data: 1.03)	H.264 M-JPEG	1	640x480	-	-	-	Yes	-	Yes	Supported by design
WV-SF135	Refer to WV-SW155/M	H.264 M-JPEG	1	1280x960	1-way	-	-	Yes	-	Yes	Supported by design



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

	Yes*: Joystick support to control PTZ speed in Crystal												
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks		
WV-SF332		H.264 MPEG4 M-JPEG	1	1280x960	1-way	0~1/0~1	Yes	Yes	-	Yes	Supported by design		
WV-SF335		H.264 MPEG4 M-JPEG	1	1280x960	1-way	0~1/0~1	Yes	Yes	-	Yes	Supported by design		
Note:	WV-SF355 includ	le WV-SF3	35E										
WV-SF336	1.05	H.264 MPEG4 M-JPEG	1	1280x960	1-way	-	Yes	Yes	-	Yes			
Note:	Motion detection	works abn	ormally	when "face de	tection"	function is er	nabled.						
WV-SF342	Refer to WV-SF332	H.264 MPEG4 M-JPEG	1	1280x960	1-way	-	Yes	Yes	-	Yes	Supported by design		
WV-SF346	Refer to WV-SF336	H.264 MPEG4 M-JPEG	1	1280x960	1-way	-	Yes	Yes	-	Yes	Supported by design		
WV-SF438	1 Application: 1.04 2 Image data:	H264 MJPEG	1	2048x1536	1-way	3/1	-	Yes	-	Yes			
Note:	Fisheye camera												
WV-SF539	1 Application: 1.60 2 Image data: 2.34	H.264	1	1920x1080	*2	*2	-	Yes	*2	Yes*			
Note:	1. Brightness val 2. We tested on following link list https://docs.goo 3. The 2nd strea	camera we s some iss gle.com/sp	eb with tus: oreadshe	the following pa	aramete ID29DK	rs, and found Yhf-s6VQhDln	nfYycbL'	V8nuhpASVI	ksw/edi	t#gid=0	·		
WV-SFN310	1.71	H.264	1	1280x960	1-way	3/1	-	Yes	-	Yes*			
Note:	1. Setting higher bitrate may be fail (Camera firmware issue) 2. When 60fps mode , H.264(1) bitrate cannot be set less than 1024 (Camera firmware issue) 3. No Audio when audio codec is AAC (NUUO server limitation) 4. Bitrate list range is not synchronize with web(Camera firmware issue) 5.MJPEG framerate is affected by h264 stream. If h264 stream(1 or 2) open, MJPEG support 5 fps the most. (Camera performance limitation) 6.Brightness value may not sync with web.(Camera firmware issue) 7.Motion event snapthot resolution sync with stream3 instead of stream1.(Camera firmware issue)												
WV- SFN310J	Refer to WV- SFN310(1.71)	H.264	1	1280x960	1-way	3/1	-	Yes	-	Yes*	Supported by design		
WV-SFN311	Refer to WV- SFN310(1.71)	H.264	1	1280x960	1-way	3/1	-	Yes	-	Yes*	Supported by design		



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

	Yes*: multi stream setting support in Crystal For PTZ: Yes*: Joystick support to control PTZ speed in Crystal														
Device Name	Tested Firmware	Video Format		Max Resolution		I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks				
WV-SFV481	1.12	Н.264	1	2992x2992	1-way	3/1	-	Yes	Yes	Yes*					
Note:	Fishey camera w 1. Brightness Va 2. Audio out 16K 3. Digital in and 4. Camera may r 5. The range of t 6. The bit-rate & from the web of 7. Snapshot reso	lue may no bps was no Digital out not achieve pitrate may FPS value the device	ot sync woot support of support o	with Camera Worted.(NUUO se trigger continum FPS.(Came oc with camera combo box are setting.(NUUO	erver lim uously.(era perfo a web.(C e not all server li	nitation) Camera Firmo ormance limita amera Firmo valid, users h mitation)	ware iss ation) are issu nave to	ue) ie) choose a va	lid one (the range	can be get				
WV- SFV611L	Refer to WV- SFV631L(V1.83)	H.264	1	2048x1536	*2	*2	-	Yes	*2	Yes*	Supported by design				
WV- SFV631L	1.83	H.264	1	2048x1536	*2	*2	-	Yes	*2	Yes*					
Note:	 Zoom & focus Brightness val 	. The bitrate list doesn't match the camera web.(Camera Firmware issue) . Zoom & focus can't be used.(Camera Firmware issue) . Brightness valus may not sync with web.(Camera Firmware issue) . Bit Rate Control (Transmission priority) only support Constant bit rate & Frmae rate.(NUUO server limitation)													
WV- SFV631LT	Refer to WV- SFV631L(V1.83)	H.264	1	2048x1536	*2	*2	-	Yes	*2	Yes*	Supported by design				
WV-SP102	1 Application: 1.81 2 Image data:	H.264 M-JPEG	1	640x480	-	-	-	Yes	-	Yes	Tested by link				
WV-SP105	1 Application: 1.61 2 Image data: 2.01	H.264 M-JPEG	1	1280x960	-	-	-	Yes	-	Yes					
WV-SP302		H.264 MPEG4 M-JPEG	1	1280x960	1-way	-	Yes	Yes	-	Yes	Supported by design				
WV-SP305		H.264 MPEG4 M-JPEG	1	1280x960	1-way	-	Yes	Yes	-	Yes	Supported by design				
WV-SP306	1.04	H.264 MPEG4 M-JPEG	1	1280x960	1-way	-	Yes	Yes	-	Yes					
Note:	Motion detection		normally	when "face de	etection"	function is en	nabled.								
WV-SP508	1Application: 1.05	MJPEG	1	2048x1536	-	0~1/0~1	-	Yes	-	Yes	Tested by				

H264

2 Image data:

2.05

link



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
WV-SP509	1Application: 1.07 2 Image data: 2.11	MJPEG H264	1	2048x1536	1-way	0~3/0~1	-	Yes	-	Yes	
WV-SPN311	V1.71	H.264	1	1280x720	1-way	3/1	-	Yes	Yes	Yes*	
WV-SPN631	Refer to WV- SFV631L(V1.83)	H.264	1	2048x1536	*2	*2	-	Yes	*2	Yes*	Supported by design
WV- SPW631L	Refer to WV- SFV631L(V1.83)	H.264	1	2048×1536	*2	*2	-	Yes	*2	Yes*	Supported by design
WV-ST162	1 Application: 1.81 2 Image data: 1.04	H264 MJPEG	1	800x600	-	3/1	Yes	Yes	-	Yes	Tested by link
WV-ST165	1Application: 1.44 2 Image data: 1.03	MJPEG H264	1	1280x960	1-way	0~3/0~1	Yes	Yes	-	Yes	Tested by link
Note	Enable "VMD add	lition infor	nation"	on camera we	b and re	boot to obtain	n Morior	Detection 1	Info	•	
WV-SW152	Refer to WV-SW155	H.264 M-JPEG	1	1280x960	1-way	-	-	Yes	-	Yes	Supported by design
WV-SW155	2.02	H.264	1	1280x720	-	*2	-	Yes	*2	Yes*	
Note:	Brightness value	may not s	ync with	n web. (Camera	a Firmwa	are issue)					
WV- SW155/M	1.03	H.264 M-JPEG	1	1280x960	1-way	-	-	Yes	-	Yes	
WV-SW158	1.07	M-JPEG	1	2048x1536	1-way	-	-	Yes	Yes	Yes*	
Note:	1. Mirror is not s 2. It may have c					era firmware	issue)			•	
WV-SW172	refer to WV- ST162(FW1 Application: 1.81 2 Image data: 1.04)	H264 MJPEG	1	800x600	-	3/1	Yes	Yes	-	Yes	Supported by design

Note:



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
WV- SW174W	1.81	MJPEG H264	1	1280x960	1-way	3/1	Yes	Yes	Yes	Yes	
Note:	WV-SW174W Ca MJPEG framerate			4 stream. If h	264 strea	am(1 or 2) op	en, MJP	EG support	5 fps th	e most.	
WV-SW175	Refer to ST165	MJPEG H264	1	1280x960	1-way	0~3/0~1	Yes	Yes	-	Yes	Supported by design
WV-SW314	Refer to SW316/L	MJPEG H264	1	1280x960	-	-	-	Yes	-	Yes	Supported by design
WV- SW316/L	1Application: 1.46 2 Image data: 1.04	MJPEG H264	1	1280x960	1-way	0~1/0~1	-	Yes	-	Yes	Tested by link
Note:	WV-SW316/L inc	lude WV-S	W316								
WV-SW352	Refer to WV-SW352	H.264 MPEG4 M-JPEG	1	1280x960	1-way	-	-	Yes	-	Yes	Supported by design
WV-SW355	1.41	H.264 MPEG4 M-JPEG	1	1280x960	1-way	0~1/0~1	-	Yes	-	Yes	
WV-SW395		H.264 MPEG4 M-JPEG	1	1280x960	1-way	-	Yes	Yes	-	Yes	Supported by design
WV-SW396	1.44	M-JPEG MPEG4 H.264	1	1280x960	1-way	0~3/0~1	Yes	Yes	-	Yes	
Note:	WV-SW396 supp	ort continu	ious PTz	7				_			
WV-SW458	V1.60	H.264	1	1920x1080	1-way	3/1	-	Yes	Yes	Yes*	

Fishey camera with manual calibration in Crystal

- 1. G726/16Kbps has noise. (NUUO server limitation)
- 2. Brightness value may not sync with web.(Camera Firmware issue)
- 3. MountType and DispalyMode UI only support English. (NUUO server limitation)
- 4. Camera is unable to achieve maximum FPS. (Camera performance limitation)
- 5. Setting higher bitrate may be fail (Cammera Firmware issue)
- 6. Motion event snapthot resolution may not sync with current stream (NUUO server limitation)

WV-SW558	Refer to SP509	MJPEG H264	1	2048x1536	ı	0~3/0~1	ı	Yes	ı	Yes	Supported by design
WV-SW558	Refer to SP509	MJPEG H264	1	2048x1536	1-way	0~3/0~1	ı	Yes	ı	Yes	Supported by design
WV-SW598	2.07	H.264	1	1920×1080	*2	*2	Yes*	Yes	*2	Yes*	



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video	Max Resolution				On-Edge	UPnP	Multi Stream Support	Remarks
Note:	1. Brightness val 2. The flip status 3.The move func	on camera	a web is	opposite to se	rver.(Ca	amera Firmwa		•		<u> ј</u> зиррогт	
WV-NW484	1.10ED	MPEG4 M-JPEG	1	640x480	-	-	-	Yes	-	Yes	
WV- NW502S	1.00	H.264 MPEG4 M-JPEG	1	2048x1536	1-way	-	-	Yes	-	Yes	
WV-NW960	1.5	MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Yes	Supported by design
WV-NW964		MPEG4 M-JPEG	1	640x480	1-way	-	Yes	Yes	-	Yes	Supported by design