



GLOBAL NETWORK SECURITY

- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Auto Pan	Multi Stream Support	Remarks
GNS		H264 MPEG4 M-JPEG	1		2-way	4/4	Yes	Yes	-	Yes	-	Yes	Supported by design
Note:	Fisheye camera												
A3102LE /A4102	4.11.23.5 1	H264 MJPEG	1	1280x960	1-way	-	-	Yes	-	Yes	-	Yes*	
Note:	1. Video format cannot be switched.(Camera Firmware issue) 2. Resolution 704x480 cannot be set. (Camera Firmware issue) 3. Resolution via MJPEG will show 800x592 when set to 800x600. (Camera Firmware issue) 4. The camera does not support functions including audio and talk. (Camera Firmware issue) 5. The video parameters may not be synchronized with actual streaming. (Camera Firmware issue) 6. Hue setting is not supported. (ONVIF limitation)												
A3101LE /A4101	4.0.30.51	H.264 MJPEG	1	1280x720	-	-	-	Yes	-	-	-	Yes*	
Note:	1. Video format cannot be switched.(Camera Firmware issue) 2. Resolution 704x480 cannot be set. (Camera Firmware issue) 3. Resolution via MJPEG will show 800x592 when set to 800x600. (Camera Firmware issue) 4. The camera does not support functions including audio and talk. (Camera Firmware issue) 5. The video parameters may not be synchronized with actual streaming. (Camera Firmware issue) 6. Hue setting is not supported. (ONVIF limitation)												
A3253LE /A3263	4.8.26.51	H264 MJPEG	1	1920x1080	2-way	1/1	Yes	Yes	-	-	-	Yes*	
Note:	1. Video format cannot be switched. (Camera Firmware issue) 2. The camera does not support functions including audio and talk. (Camera Firmware issue) 3. Resolution via MJPEG will show 640x352 when set to 640x360. (Camera Firmware issue) 4. Stream via UDP will disconnect in 20 seconds. (Camera Firmware issue) 5. Camera is unable to achieve maximum FPS and bit rate. (Camera Performance issue)												
B4251RLE	v1.8.0801 .1001.101 .0.66.1.0	H.264 MJPEG	1	1920x1080	*2	1/1	-	*2	*2	-	-	Yes*	
Note:	1. Bit rate list may not be synchronized with web. (Camera Firmware issue) 2. Bit rate may be set fail. (Camera Firmware issue)												
B2201	Refer to B4251RLE (v1.8.080 1.1001.10 1.0.66.1.0)	H.264 MJPEG	1	1920x1080	*2	1/1	-	*2	*2	-	-	Yes*	Supported by design
B3251LE	Refer to B4251RLE (v1.8.080 1.1001.10 1.0.66.1.0)	H.264 MJPEG	1	1920x1080	*2	1/1	-	*2	*2	-	-	Yes*	Supported by design

B3202LE	Refer to B4201RLE (v1.8.0801.1001.101.0.66.1.0)	H.264 MJPEG	1	1920x1080	*2	-	-	*2	*2	-	-	Yes*	Supported by design
B4201RLE	v1.8.0801.1001.101.0.66.1.0	H.264 MJPEG	1	1920x1080	*2	-	-	*2	*2	-	-	Yes*	
Note:	1. Resolution will show 192x144 when set to QCIF in stream 2. (Camera Firmware issue) 2. Bit rate list may not be synchronized with web. (Camera Firmware issue) 3. Bit rate may be set fail. (Camera Firmware issue)												
B5201E	Refer to B6232LE(v1.8.0801.1001.101.0.66.1.0)	H.264 MJPEG	1	1920x1080	*2	-	Yes	*2	*2	-	-	Yes*	Supported by design
B6231E	Refer to B6232LE(v1.8.0801.1001.101.0.66.1.0)	H.264 MJPEG	1	1920x1080	*2	-	Yes	*2	*2	-	-	Yes*	Supported by design
B6232LE	v1.8.0801.1001.101.0.66.1.0	H.264 MJPEG	1	1920x1080	*2	-	Yes	*2	*2	-	-	Yes*	
Note:	1. PTZ speed range will not sync with web. (Camera Firmware issue) 2. Bit rate list may not be synchronized with web. (Camera Firmware issue) 3. Bit rate may be set fail. (Camera Firmware issue)												
C1201L	V1.0.40	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Yes	
Note:	1. Audio only support G7.11. (Camera firmware issue)												
C3203LE	2.3.3073.74	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Yes*	
Note:	1. DO cannot be triggered. (Camera firmware issue) 2. Motion cannot be triggered when video format is MJPEG. (Camera firmware issue) 3. If change mode to corridor 90 or 270, the information of stream 3 is incorrect and stream 3 can not connect. (Camera firmware issue) 4. Camera is unable to achieve FPS when 3 streams are connecting. (Camera performance limitation)												