

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software
 For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Suppor	Snapshot	Remarks
ACM-B3000	1.02.09	H.264 MPEG4 M-JPEG	1	2048x1536	1-way	*2	-	Yes	Yes	-	Yes	-	
ACM-PT500	2.03.16	H.264 MPEG4	1	2048x1536	2-way	2/1	Yes	Yes	Yes	-	Yes	Yes	
Note:	Camera is unable to achieve maximum FPS. 無法達到最大FPS. (Camera performance limitation)												
ACM-R2001	1.02.09	H.264 MPEG4 M-JPEG	1	1920x1080	1-way	-	-	Yes	Yes	-	Yes	-	
Note:	Framerate may not enough about 2~8 fps due to camera issue.												
ACM-R3002	Refer to ACM-V3103(2.0 3.23A)	H264 MPEG4	1	2048x1536	Yes	2/1	Yes	Yes	Yes	-	Yes*	Yes	Supported by design
Note:	1.Frame rate can't meet the requirements.(Camera performance limitation) 2.Not support zoom and focus.												
ACM-R3006	1.02.05T	H.264 MPEG4 M-JPEG	1	2048x1536	1-way	*2	*2	Yes	Yes	-	Yes	-	
ACM-V3001	1.02.09	H.264 MPEG4 M-JPEG	1	2048x1536	1-way	*2	-	Yes	Yes	-	Yes	-	
ACM-V3002	Refer to ACM-V3103(2.0 3.23A)	H264 MPEG4	1	2048x1536	Yes	2/1	Yes	Yes	Yes	-	Yes*	Yes	Supported by design
Note:	1.Frame rate can't meet the requirements.(Camera performance limitation) 2.Not support zoom and focus.												
ACM-V3103	2.03.23A	H264 MPEG4	1	2048x1536	Yes	2/1	Yes	Yes	Yes	-	Yes*	Yes	
Note:	1.Audio in can't be work.(Camera Firmware issue) 2.RS-485 can't be work.(Camera Firmware issue) 3.Alarm out can't be work.(Camera Firmware issue)												
C3000/C3000-W	v3.2.2.3	H.264 MPEG4 M-JPEG	1	2048x1536	1-way	1/1	-	Yes	Yes	-	Yes	-	
CDB-4KM552	Refer to TCP-KM465(VK 2.0.4.5_F)	H.264 MJPEG	1	2592x1520	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
CDB-5VM551	Refer to TCP-VM559(VK 2.0.26.6_F)	H.264 M-JPEG	1	2592x1944	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
CDB-720F		H.264 MPEG4 M-JPEG	1	1280x800	1-way	1/1	-	Yes	*1	-	Yes	-	
CDB-720F/IR	V1.0.20_F	H.264 MPEG4 M-JPEG	1	1280x800	1-way	1/1	-	Yes	*1	-	Yes	-	

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Suppor	Snapshot	Remarks
CDB-720V	VB1.0.26_F	H.264 MPEG4 M-JPEG	1	1280x800	1-way	1-1	-	Yes	Yes	-	Yes	-	
CDB-720VIR	VB1.0.26_F	H.264 MPEG4 M-JPEG	1	1280x800	1-way	1/1	-	Yes	*1	-	Yes	-	
CDB-720VIR-H	VE2.0.14.2_F	H.264 MJPEG	1	1280x800	1-way	1/1	-	Yes	Yes	-	Yes	Yes	
Note:	1. (Camera issue): FPS could not reach up to 20/30. 2. (Known issue): The info. of stream profile display failure												
CDB-HD280	refer to TCP-HDVB800-H(VE2.0.16.8_F)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
CDB-HFD720	Refer to TCP-HDVB720-H(VE2.0.20.8)	H264 MJPEG	1	1280x800	-	-	-	Yes	Yes	-	Yes*	Yes	Supported by design
CDB-HFD728	refer to CDB-720VIR-H(VE2.0.14.2_F)	H.264 MJPEG	1	1280x800	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
CDB-HFD828	refer to TCP-HDVB800-H(VE2.0.16.8_F)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
CDB-MD602	refer to TCP-MZ602(VG1.0.14_F)	H.264 M-JPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
CDB-MV1080F	VB1.0.32_F	H.264 MPEG4 M-JPEG	1	1920x1080	-	1/1	-	Yes	Yes	-	Yes	-	
CDB-MV720F	VB1.0.28_F	H.264 MPEG4 M-JPEG	1	1280x800	-	1/1	-	Yes	Yes	-	Yes	-	
Note	Camera FW issue: framerate can not reach 30fps.												
CDB-MV720F-H	Refer to TCP-HDVB720-H(VE2.0.20.8)	H264 MJPEG	1	1280x800	-	-	-	Yes	Yes	-	Yes*	Yes	Supported by design
CDB-T5	A1D-500-V6.08.25-NB	H.264 M-JPEG	1	2592x1944	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	
Note:	Fisheye camera Only audio can ben exported while selecting MOV format in playback system. (NUUO server limitation)												

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software
 For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Suppor	Snapshot	Remarks
CDV-2M360	VB1.0.32_F	H.264 MPEG4 M-JPEG	1	1920x1080	1-way	1/1	Yes	Yes	Yes	-	Yes	-	
Note	Fisheye camera												
CDV-3F828	Refer to TCP-HDVB180(VE1.0.20.6 F)	H.264 MJPEG	1	1920x1080	-	-	-	Yes	Yes	-	Yes*	Yes	Supported by design
CDV-3V930		MPEG4 M-JPEG	1	720x480	1-way	1/1	-	Yes	-	-	-	-	Supported by design
CDV-3V930U		MPEG4 M-JPEG	1	720x480	1-way	1/1	-	Yes	-	-	-	-	Supported by design
CDV-3VM301		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	-	-	-	-	Supported by design
CDV-3VM501	refer to TCP-MH802(1.0.46)	M-JPEG H.264	1	1600x1200	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
CDV-3VM800	VC1.0.06_F	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes	-	
CDV-3VM800-H	refer to TCP-HDVB800-H(VE2.0.16.8 F)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
CDV-3VM800-H1	refer to TCP-HDVB800-H(VE2.0.16.8 F)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
CDV-3VM800Z3	refer to TCP-HDVB800Z3(VC2.0.24.2)	H.264 MJPEG	1	1920x1080	2-way	1/1	Yes	Yes	Yes	-	Yes*	Yes	Supported by design
CDV-3VM800Z4 2	VE1.0.20.2_F	H.264 MJPEG	1	1920x1080	2-way	1/1	Yes	Yes	Yes	-	Yes*	Yes	
Note:	1. The camera with highest resolution and MJPEG is unable to achieve highest fps. (Camera firmware issue) 2. If connect 2 or above streams, bitrate and frame rate will decrease. (Camera performance limitation)												
CDV-3VWD960	V1.0.16_F	H.264 M-JPEG	1	720x576	1-way	1/1	-	Yes	-	-	-	-	
CDV-3VWD960 H		H.264 M-JPEG	1	720x576	1-way	1/1	-	Yes	-	-	-	-	Supported by design
CDV-4KM502	Refer to TCP-KM465(VK	H.264 MJPEG	1	2592x1520	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Suppor	Snapshot	Remarks
CDV-4VM501	Refer to TCP-VM469(VH 1.0.0_F)	H.264 MJPEG	1	2688x1520	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
CDB-4VM551	Refer to TCP-VM469(VH 1.0.0_F)	H.264 MJPEG	1	2688x1520	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
CDV-5VM501	Refer to TCP-VM559(VC 2.0.26.6_F)	H.264 M-JPEG	1	2592x1944	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
CDV-5VM501Z3	VC2.0.26.4_F	H.264 M-JPEG	1	2592x1944	2-way	1/1	Yes	Yes	Yes	-	Yes*	Yes	
Note:	1. PTZ could only support zoom and autofocus.												
CDV-5VM501Z4 2	Refer to TCP-VM559Z42 (VC2.0.26.6)	H.264 MJPEG	1	2592x1944	2-way	1/1	Yes	Yes	Yes	-	Yes*	Yes	Supported by design
CDV-DT5	V6.08.25-NB	H.264 M-JPEG	1	2592x1944	1-way	-	-	Yes	Yes	-	Yes*	Yes	
Note:	Fisheye camera 1.Camera is unable to achieve maximum FPS. (Camera performance limitation) 2.Main console Flip/mirror checkbox not sync with Web interface. (NUUO server limitation)												
CDV-DT95IR	Refer to CDV-DT5(V6.08.25-NB)	H.264 M-JPEG	1	2592x1944	1-way	-	-	Yes	Yes	-	Yes*	Yes	Supported by design
CDV-MD602	refer to TCP-MZ602(VG 1.0.14 F)	H.264 M-JPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
CDV-MD605	refer to TCP-MZ602(VG 1.0.14 F)	H.264 M-JPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
CDV-MFB2000D	2.03.17	H.264 MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Yes	
Note:	1. Camera is unable to achieve maximum FPS. (Camera performance limitation) 2. The info. of stream profile display failure. (NUUO server limitation)												
CDV-MV1080F-H	refer to TCP-HDVB800-H(VE2.0.16.8 F)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Yes*	Supported by design

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software
 For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Suppor	Snapshot	Remarks
CDV-P360	refer to TCP-MH802(1.0.46)	M-JPEG H.264	1	1600x1200	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
Note:	Fisheye camera												
CDV-P360-5	VC2.0.26.4_F	H.264 M-JPEG	1	2592x1944	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	
Note:	Fisheye camera												
EDH-02H	V1.0.20_F	H.264 M-JPEG	1	720x480	1-way	1/1	Yes	Yes	-	-	-	-	
EP-201		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	-	Supported by design
EP-221		MPEG4 M-JPEG	1	720x480	1-way	1/0	Yes	Yes	-	-	-	-	Supported by design
EP-221DN		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	-	Supported by design
EP-601		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	-	Supported by design
EP-601HW		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	-	
EP-908		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	-	Supported by design
EP-908HW		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	-	Supported by design
EP-936		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	-	Supported by design
EP-936HW		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	-	Supported by design
EP-HTQ935	V3.2.56_F	MPEG4 M-JPEG	1	720x480	-	0/0	Yes	Yes	-	-	-	-	
EP-Q2018H-IP		H.264 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	-	Supported by design
EP-Q2018HW-IP	V1.0.8_F	H.264 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	-	
EP-Q2026H-IP		H.264 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	-	Supported by design
EP-Q2026HW-IP		H.264 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	-	Supported by design
EP-Q2036H-IP		H.264 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	-	Supported by design

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software
 For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Suppor	Snapshot	Remarks
EP-Q2036HW-IP	V1.0.46_F	H.264 M-JPEG	1	720x576	*2	*2	Yes	Yes	*2	-	Yes	Yes	
MD-D1200		MPEG4 M-JPEG	1	720x480	1-way	1/1	Yes	Yes	-	-	-	-	Supported by design
MD-D1322	V1.0.23.09_F	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	2/1	*1	Yes	Yes	-	Yes	-	
MD-D1612	V1.0.16_F	H.264 M-JPEG	1	720x576	1-way	1/1	Yes	Yes	-	-	-	-	
MD-D3622Q-H	VD1.0.12_04_F	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	Yes	-	Yes	-	
SP-HP2013C-IP	onvif_v2.4.2_20150327	M-JPEG H.264	1	1280x960	1-way	1/1	Yes	Yes	-	Yes	Yes*	Yes	
Note:	1. DI & DO can't be used. (Camera Firmware issue) 2. Bitrate list and quality list may not be synchronized with camera web. (Onvif limitation) 3. 704x288 is not shown in the resolution list of the second stream. (Camera Firmware issue) 4. Auto focus is not supported. (Camera performance limitation) [IP+]5. Video parameter setting does not synchronize to camera web. (Camera Firmware issue) [NAS]6. Focus and PTZ speed setting are not supported. (NUUO server limitation) [NAS]7. The image of snapshot doesn't update via Snapshot to FTP function.(Camera Firmware issue)												
SP-HP2020C-IP	onvif_v2.4.0_20141027	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes	Yes	-	Yes	Yes*	Yes	
Note:	1. DI does not function. (Camera Firmware issue) 2. DO is unable to turn off. (Camera Firmware issue) 3. Bitrate list and quality list may not be synchronized with camera web. (Onvif limitation) 4. 704x288 is not shown in the resolution list of the second stream. (Camera Firmware issue) 5. Flip and mirror are not supported. (Onvif limitation) 6. Auto pan is not supported. (Onvif limitation) 7. Auto focus is not supported. (Camera performance limitation) 8. Hue setting is not supported. (Onvif limitation) 9. Video parameter setting does not synchronize to camera web. (Camera Firmware issue) [NAS] 10. Focus and PTZ speed setting are not supported. (NUUO server limitation)												
SP-HP2020CM-IP	Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes	Yes	-	Yes	Yes*	Yes	Supported by design
SP-HP2020Q-IP	Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes	Yes	-	Yes	Yes*	Yes	Supported by design

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software
 For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Suppor	Snapshot	Remarks
SP-HP2030CM-IP	Refer to SP-HP2020C-IP(onvif_v 2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes	Yes	-	Yes	Yes*	Yes	Supported by design
SP-HP2030Q-IP	Refer to SP-HP2020C-IP(onvif_v 2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes	Yes	-	Yes	Yes*	Yes	Supported by design
SP-HP2313C-IP	Refer to SP-HP2013C-IP(onvif_v 2.4.2_20150327)	M-JPEG H.264	1	1280x960	1-way	1/1	Yes	Yes	-	Yes	Yes*	Yes	
SP-HP2320C-IP	Refer to SP-HP2020C-IP(onvif_v 2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes	Yes	-	Yes	Yes*	Yes	Supported by design
SP-HP2330C-IP	Refer to SP-HP2020C-IP(onvif_v 2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes	Yes	-	Yes	Yes*	Yes	Supported by design
SP-HP2330Q-IP	Refer to SP-HP2020C-IP(onvif_v 2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes	Yes	-	Yes	Yes*	Yes	Supported by design
SP-HP2336Q-IP	Refer to SP-HP2020C-IP(onvif_v 2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes	Yes	-	Yes	Yes*	Yes	Supported by design
SP-HP2620CP-IP	Refer to SP-HP2020C-IP(onvif_v 2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes	Yes	-	Yes	Yes*	Yes	Supported by design
SP-PTIR736A-IP	Refer to EP-Q2036HW-IP(V1.0.46_F)	H.264 M-JPEG	1	720x576	*2	*2	Yes	Yes	*2	-	Yes	Yes	Supported by design
SP-PTIR736B-IP	Refer to EP-Q2036HW-IP(V1.0.46_F)	H.264 M-JPEG	1	720x576	*2	*2	Yes	Yes	*2	-	Yes	Yes	Supported by design

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software
 For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Suppor	Snapshot	Remarks
SP-PTIR737-IP	V1.0.16_F	H.264 M-JPEG	1	720x576	1-way	-	Yes	Yes	-	-	-	-	
SP-PYIR737-LA-IP		H.264 M-JPEG	1	720x480	1-way	-	Yes	Yes	-	-	-	-	Supported by design
TCMA-99		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	-	-	-	-	Supported by design
TCMP-99		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	-	-	-	-	Supported by design
TCP-336AM	VB1.0.40_F	H.264 MPEG4 M-JPEG	1	2032x1536	1-way	1/1	-	Yes	Yes	-	Yes	-	
Note:	When format is set to MPEG4, resolution is 1920*180 and quality is excellent, the maximum FPS can only reach 20.												
TCP-1200AV	V1.0.26_F	H.264 M-JPEG	1	640x480	1-way	-	-	Yes	-	-	-	-	
TCP-1300AM	V1.0.26_F	H.264 M-JPEG	1	1280x1024	1-way	-	-	Yes	-	-	-	-	
TCP-2200AM	V1.0.30_F	H.264 MJPEG	1	1600x1200	1-way	-	-	-	Yes	-	Yes	-	
TCP-2200AM-H	refer to TCP-HDVB800-H(VE2.0.16.8_F)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-2700AM	refer to CDB-720VIR-H(VE1.0.12.2_F)	H.264 MJPEG	1	1280x800	1-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
TCP-2700AM-W	refer to CDB-720VIR-H(VE2.0.14.4)	H.264 MJPEG	1	1280x800	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
TCP-2800AM	refer to TCP-HDVB800-H(VE2.0.16.8_F)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-670DNU		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	-	-	-	Supported by design
TCP-680DNU		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	-	-	-	Supported by design
TCP-690		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	-	-	-	Supported by design

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software
 For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Suppor	Snapshot	Remarks
TCP-690DN		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	-	-	-	Supported by design
TCP-690U	V3.2.60_F	MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	-	-	-	
TCP-B365K	refer to TCP-HDVB800-	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-BF128	Refer to TCP-HDVB720-H (VE2.0.20.8)	H264 MJPEG	1	1280x800	-	-	-	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-BF108	Refer to TCP-HDVB720-H (VE2.0.20.8)	H264 MJPEG	1	1280x800	-	-	-	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-BF1080	refer to TCP-HDVB800-H(VE2.0.16.8_F)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
Note:	1. (Camera issue): FPS could not reach up to 20/30. 2. (Known issue): The info. of stream profile display failure												
TCP-BF208	Refer to TCP-HDVB180(VE1.0.20.6_F)	H.264 MJPEG	1	1920x1080	-	-	-	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-BF728IR	refer to CDB-720VIR-	H.264 MJPEG	1	1280x800	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
TCP-BF828IR	refer to TCP-HDVB800-H(VE2.0.16.8_F)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-HDVB110	Refer to TCP-HDVB720-H (VE2.0.20.8)	H264 MJPEG	1	1280x800	-	-	-	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-HDVB180	VE1.0.20.6_F	H.264 MJPEG	1	1920x1080	-	-	-	Yes	Yes	-	Yes*	Yes	
TCP-HDVB720P	V1.0.20_F	MPEG4 M-JPEG	1	1280x800	-	1/1	-	Yes	Yes	-	Yes	-	
TCP-HDVB720-H	VE2.0.20.8	H264 MJPEG	1	1280x800	-	-	-	Yes	Yes	-	Yes*	Yes	

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software
 For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Suppor	Snapshot	Remarks
Note:	1.Setting FPS have problems(Camera Firmware issue), example: (1)Stream1 & Stream2 format : JPEG, when stream1's resolution decrease, stream2's fps would increase a little (2)Stream1 & Stream2 format : H264, stream2's fps can't reach our setting (3)When this camera's users more than 1, fps would decrease												
TCP-HDVB800	VC1.0.18.2_F	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	-	Yes	-	Yes	-	
TCP-HDVB800-H	VE2.0.16.8_F	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	
Note:	1. Camera is unable to achieve maximum FPS. (Camera performance limitation) 2. Audio has noise. (Camera firmware issue) 3. Parameter setting will lead camera can't connect. (Camera firmware issue)												
TCP-HDVB800-H1	refer to TCP-HDVB800-H(VE2.0.16.8_F)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-HDVB800Z3	VC2.0.24.2_F	H.264 MJPEG	1	1920x1080	2-way	1/1	Yes	Yes	Yes	-	Yes*	Yes	
Note:	1. PTZ only support zoom.												
TCP-HDVB800Z42	Refer to CDV-3VM800Z42 (VE 1.0.20.2)	H.264 MJPEG	1	1920x1080	2-way	1/1	Yes	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-HDVB801		H.264 MPEG4 M-JPEG	1	1920x1080	1-way	1/1	-	-	Yes	-	Yes	-	
TCP-HFB720	VB1.0.28_F	H.264 MPEG4 M-JPEG	1	1280x800	-	1/1	-	Yes	Yes	-	Yes	-	
TCP-HFB720-H	Refer to TCP-HDVB720-H (VE2.0.20.8)	H264 MJPEG	1	1280x800	-	-	-	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-HFB1080D	2.03.10	H.264 MPEG4	1	1920x1080	-	-	-	Yes	Yes	-	Yes	-	
Note:	1.The response of camera setting is slow.												
TCP-HP1080	VC1.0.06_F	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes	-	

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software
 For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Suppor	Snapshot	Remarks
TCP-HP1080-H	refer to TCP-HDVB800-H(VE2.0.16.8_F)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-HP1080WI		H.264 MPEG4 M-JPEG	1	1920x1080	1-way	1/1	-	-	*1	-	Yes	-	
TCP-HP930		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	-	-	-	Supported by design
TCP-HP930U		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	-	-	-	Supported by design
TCP-HVB3100D	Refer to ACM-V3103(2.0 3.23A)	H264 MPEG4	1	2048x1536	Yes	2/1	Yes	Yes	Yes	-	Yes*	Yes	Supported by design
Note:	1.Frame rate can't meet the requirements.(Camera performance limitation) 2.Not support zoom and focus.												
TCP-HVB3105D	Refer to ACM-V3103(2.0 3.23A)	H264 MPEG4	1	2048x1536	Yes	2/1	Yes	Yes	Yes	-	Yes*	Yes	Supported by design
Note:	1.Frame rate can't meet the requirements.(Camera performance limitation)												
TCP-IPWD690		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	-	-	-	Supported by design
TCP-IPWD700 DN	V1.0.16_F	H.264 M-JPEG	1	720x576	1-way	1/1	-	Yes	-	-	-	-	
TCP-IR590-WD30	V1.0.20_F	H.264 M-JPEG	1	720x576	1-way	1/1	-	Yes	-	-	-	-	
TCP-IR590-WD50		H.264 M-JPEG	1	720x576	1-way	1/1	-	Yes	-	-	-	-	Supported by design
TCP-IRH5030C	refer to TCP-MH802(1.0.46)	M-JPEG H.264	1	1600x1200	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
TCP-IRH5040C	refer to TCP-MH802(1.0.46)	M-JPEG H.264	1	1600x1200	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
TCP-IRH5080-50	Refer to IRH5080-70(VC2.0.2 6.4_F)	H.264 M-JPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software
 For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Suppor	Snapshot	Remarks
TCP-IRH5080W-70	Refer to TCP-IRH5080-70(VC2.0.26.4)	H.264 M-JPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-IRH5080-70	VC2.0.26.4_F	H.264 M-JPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	
TCP-IRH5080W-50	Refer to TCP-IRH5080-70(VC2.0.26.4)	H.264 M-JPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-IRV540		MPEG4 M-JPEG	1	720x480	1-way	0/0	-	Yes	-	-	-	-	Supported by design
TCP-IRV560		MPEG4 M-JPEG	1	720x480	1-way	1/1	-	Yes	-	-	-	-	Supported by design
TCP-KM465	VK2.0.4.5_F	H.264 MJPEG	1	2592x1520	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	
Note:	1. H265 was not supported(NUUO server limitation)												
TCP-KZ462	Refer to TCP-KM465(VK 2.0.4.5_F)	H.264 MJPEG	1	2592x1520	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-M360K	refer to TCP-HDVB800-H(VE2.0.16.8_F)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-M912DN	V1.2.28_F	MPEG4 M-JPEG	1	MPEG4: 640x480 M-JPEG:	1-way	2/2	-	Yes	-	-	-	-	
TCP-MB602	refer to TCP-MZ602(VG 1.0.14_F)	H.264 M-JPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
TCP-MB685	refer to TCP-MZ602(VG 1.0.14_F)	H.264 M-JPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
TCP-MH802	1.0.46	M-JPEG H.264	1	1600x1200	2-way	1/1	-	Yes	Yes	-	Yes	Yes	
Note:	1. Framerate may be incorrect displayed with MJPEG format. (Canera firmware issue) 2. Camera is unable to achieve maximum FPS. (Camera performance limitation)												
TCP-MH859	Refer to TCP-VM559(VC 2.0.26.6_F)	H.264 M-JPEG	1	2592x1944	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software
 For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Suppor	Snapshot	Remarks
TCP-MZ602	VG1.0.14_F	H.264 M-JPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Yes	
Note:	Camera is unable to achieve maximum FPS. (Camera performance limitaion)												
TCP-MB605	refer to TCP-MZ602(VG 1.0.14_F)	H.264 M-JPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Yes	Supported by design
TCP-MZ605	refer to TCP-MZ602(VG 1.0.14_F)	H.264 M-JPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
TCP-VM201		MPEG4 M-JPEG	1	1280x1024	1-way	0/0	-	Yes	-	-	Yes	-	Supported by design
TCP-VM359	VC1.0.16_F	H.264 M-JPEG	1	2048x1536	1-way	1/1	-	Yes	Yes	-	Yes	-	
TCP-VM469	VH1.0.0_F	H.264 M-JPEG	1	2688x1520	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	
Note:	1. Resolution list & frame rate list may not sync with web. (Camera Firmware issue)												
TCP-VM501	refer to TCP-MH802(1.0)	M-JPEG H.264	1	1600x1200	2-way	1/1	-	Yes	Yes	-	Yes	Yes	Supported by design
TCP-VM559	VC2.0.26.6_F	H.264 M-JPEG	1	2592x1944	2-way	1/1	-	Yes	Yes	-	Yes*	Yes	
TCP-VM559Z3	refer to CDV-5VM501Z3 (VC2.0.26.4_F)	H.264 M-JPEG	1	2592x1944	2-way	1/1	Yes	Yes	Yes	-	Yes*	Yes	Supported by design
TCP-VM559Z42	VC2.0.26.6_F	H.264 MJPEG	1	2592x1944	2-way	1/1	Yes	Yes	Yes	-	Yes*	Yes	
WB-8211SD		MPEG4 M-JPEG	1	720x480	1-way	2/4	-	Yes	-	-	Yes	-	Supported by design
WB-8211SDU		MPEG4 M-JPEG	1	720x480	1-way	2/4	-	Yes	-	-	Yes	-	Supported by design
WB-8411		MPEG4 M-JPEG	4	720x480	1-way	4/1	-	Yes	-	-	Yes	-	Supported by design
WB-8412	V2.2.26_F	MPEG4 M-JPEG	4	688x448	1-way	4/4	Yes	Yes	-	-	Yes	-	
WB-H811	V1.0.44_F	M-JPEG H.264	1	720x576	2-way	2/2	Yes	Yes	Yes	-	Yes	Yes	
Note:	Resolution can't set to 4CIF.												
WB-H814	V1.0.82_F	H.264 M-JPEG	4	720x576	2-way	4/4	Yes	Yes	Yes	-	Yes	Yes	

Fine



- : not available on camera
*1: not available on software
*2: not test on software

For multi stream support:
Yes: multi stream fix to 500kbps/100kbps
Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Snapshot	Remarks
Note:	1. Support dual mode only. (Camera firmware issue) 2. Resolution can not be set correctly. (Camera firmware issue)												