

- : not avaliable on camera *1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps Yes*: multi stream setting support in Cystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks	
B5010	Refer to Beward N600 (M2.0.9.13.1	H.264 MPEG4 M-JPEG	1	640x480	-	-	-	Yes	Yes	Yes	Supported by design	
B5110	MG.0.6.01_C	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	Supported by design	
B5111	M2.1.6.02C0 45	H.264 MPEG4 M-JPEG	1	1280x800	-	-	-	Yes	Yes	Yes		
B5210	M2.1.6.02C0 14	H.264 MPEG4 M-JPEG	1	1920x1080	-	-	-	Yes	Yes	Yes		
Note:	For B5210, th	ne frame ra	ate is no	t enough wher	using T	CP and	HTTP co	onnection.				
B6110	MG.0.6.01_C	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	Supported by design	
B6210	02_C002	H.264 MJPEG	1	1920×1080	-	-	-	Yes	Yes	Yes*		
Note	Framerate range is not synchronize with web. (Camera Firmware issue) Camera is unable to achieve maximum FPS. (Camera performance limitation)											
B6320	01_c006	H.264 H.265 M-JPEG	1	2048×1520	-	-	-	Yes	Yes	Yes*		
B7210	M2.1.6.04	H.264 MPEG4 M-JPEG	1	1920x1080	1-way	2/2	-	Yes	Yes	Yes		
Note	2. Camera is	unable to	achieve	ng the resolution maximum FPS omly.(Camera f	.(Camer	a perfoi			ssue)			
B7320	M3.1.5.17	M-JPEG H.264	1	2048x1536	1-way	2/2	-	Yes	Yes	Yes		
Note	1.Not support	t audio in.		•				•	•	•	•	
B7510	M3.1.5.19	H264 MJPEG	1	2560x1920	1-way	2/2	-	Yes	Yes	Yes		
B8210	M2.1.5.20	H.264 MJPEG	1	1920×1080	1-way	2/2	Yes*	Yes	Yes	Yes*		



-: not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps Yes*: multi stream setting support in Cystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks	
Note:	 Audio has noise with AMR. (Camera Firmware issue) Camera with highest resolution is unable to achieve maximum FPS. (Camera performance limitation) Move can't not move to center. (Camera Firmware issue) Speed range is not synchronize with web. (Camera Firmware issue) 											
B8220	01_C007	H.264 H.265 MJPEG	1	1920×1080	1-way	2/2	Yes*	Yes	Yes	Yes*		
Note:	1.The max resolution of stream3 will not sync with camera web. (Camera firmware issue)2. Audio has noise with AMR. (Camera firmware issue)3. Not G.726 support. (NUUO server limitation)4. Camera is unable to achieve maximum FPS when audio codec is AMR. (Camera performance limitation)											
B8520	01_C010	H.264 H.265 MJPEG	1	2560x1920	1-way	2/2	Yes*	Yes	Yes	Yes*		
Note:	1. Audio stutter with highest bitrate, quality, resolution. (Camera performance limitaion) 2. Camera with highest resolution and MJPEG format is unable to achieve maximum fps. (Camera performance limitation) 3. Sever resolution list is not same as web page with MJPEG format. (Camera Firmware issue) 4. Not support G.726. (NUUO server limitation)											
D3100	M2.1.6.02.0 830	H.264 MPEG4 M-JPEG	1	1280x800	-	1/1	-	Yes	Yes	Yes		
Note:	1. Not suppor				•	•	•	•				
D3200	M2.1.6.02C0 66	H.264 MPEG4 M-JPEG	1	1920×1080	1-way	1/1	-	Yes	Yes	Yes		
Note:		audio who	nworked	d in AMR mode		20x108	0 and 1	280×800. It	's the li	mitation of hard	ware	
D4210	M2.1.5.11	H264 MJPEG	1	1920×1080	1-way	1/1	-	Yes	Yes	Yes*		
D4211	Refer to D4210(M2.1. 5.11)	H264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	Yes*	Supported by design	
D510E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design	
D5110	Refer to D5111	H.264 MPEG4 M-JPEG	1	1280x1024	-	2/2	Yes	Yes	Yes	Yes	Supported by design	



: not avaliable on camera*1: not avaliable on software*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps Yes*: multi stream setting support in Cystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks		
D5111	MG.1.6.03P7 _app7	H.264 MPEG4 M-JPEG	1	1280x1024	-	2/2	Yes	Yes	Yes	Yes			
D5112	Refer to D5113 (M2.1.6.01)	H.264 MPEG4 M-JPEG	1	1280x720	-	1/1	-	Yes	Yes	Yes	Supported by design		
D5113	M2.1.6.01	H.264 MJPEG MPEG4	1	1280x720	-	1/1	-	Yes	Yes	Yes			
D520E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design		
D5210	M2.1.6.04	H.264 MPEG4 M-JPEG	1	1920x1080	-	1/1	-	Yes	Yes	Yes*			
Note:	Due to camera restriction, some video setting will fail. This situation will be same as camera web. (Camera performance limitation)												
D610A	LM.1.6.16	MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	Yes			
D6111	MG.0.6.01_C	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	Supported by design		
D611E	LM.1.6.16	MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	Yes			
D6210	Refer to B6210(02_C 002)	H.264 MJPEG	1	1920x1080	-	-	-	Yes	Yes	Yes*	Supported by design		
D6320	Refer to B6320(01_c 006)	H.264 H.265 M-JPEG	1	2048x1520	-	-	-	Yes	Yes	Yes*	Supported by design		
D7110	MG.1.6.03P7 _app7	H.264 MPEG4 M-JPEG	1	1280x1024	-	1/1	-	Yes	Yes	Yes			
D7111	Refer to D5113	H.264 MJPEG MPEG4	1	1280x720	-	1/1	-	Yes	Yes	Yes	Supported by design		
D7210	M2.1.6.02C0 66	H.264 MPEG4 M-JPEG	1	1920×1080	1-way	1/1	-	Yes	Yes	Yes	Supported by design		
Note:		audio who	nworked	d in AMR mode		20x108	0 and 1	280×800. It	's the li	mitation of hard	ware		
D7320	M3.1.5.21	H.264 M-JPEG	1	2048x1536	1-way	1/1	-	Yes	Yes	Yes			
Note:	Frame rate ca	n't reach s	setting v	/alue	•	•	•	•	•	•	•		



-: not avaliable on camera
*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps Yes*: multi stream setting support in Cystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
D7510	M3.04.15.C0	H.264 M-JPEG	1	2560x1920	1-way	1/1	-	Yes	Yes	Yes	
Note:	Framerate Connecting				gh vide	o quality	will ca	use delayed	image a	and broken voice	э.
D8210	Refer to B8210(M2.1. 5.20)	H.264 MJPEG	1	1920x1080	1-way	2/2	Yes	Yes	Yes	Yes*	Supported by design
D8220	Refer to B8220(01_C 007)	H.264 H.265 MJPEG	1	1920x1080	1-way	2/2	Yes*	Yes	Yes	Yes*	Supported by design
F1100	Refer to F1105	MJPEG	1	1280x720	1-way	_	-	Yes	Yes	Yes	Supported by design
F1105	BP.1.6.01_C 1	MJPEG	1	1280x720	1-way	-	-	Yes	Yes	Yes	
F210A	LM.1.6.15	MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	Yes	
F3100	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	Yes	Yes	Supported by design
F3101	Refer to F3106	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	Yes	Yes	
F3102	M2.1.6.02C0 45	H.264 MPEG4 M-JPEG	1	1280x800	1-way	1/1	-	Yes	Yes	Yes	Supported by design
Note:		nction is u	nworked	AMR 7.95 I in AMR mode 4 is up to 20 F		80×800	. It's th	e limitation	of hardv	vare	
F3105	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	Yes	Yes	Supported by design
F3106	MG.1.6.03C8	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	Yes	Yes	
F3107	M2.1.6.05	H.264 MPEG4 M-JPEG	1	1280×800	1-way	1/1	-	Yes	Yes	Yes*	
Note:	1. 1.Audio via		noises.	(Firmware issu	e)				,		
F3110	M2.1.6.02C0 45	H.264 MPEG4 M-JPEG	1	1280x800	1-way	1/1	-	Yes	Yes	Yes	



-: not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps Yes*: multi stream setting support in Cystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks		
Note:		nction is u	nworked	J AMR 7.95 d in AMR mode 4 is up to 20 F		80×800	. It's th	e limitation	of hardv	vare			
F3115	M2.1.6.02C0 45	H.264 MPEG4 M-JPEG	1	1280x800	1-way	1/1	-	Yes	Yes	Yes	Supported by design		
Note:	 There is no audio when using AMR 7.95 The talk function is unworked in AMR mode. The max frame rate of MPEG4 is up to 20 FPS in 1280x800. It's the limitation of hardware 												
F312A	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	Yes			
F3201	Refer to F3206	H.264 MPEG4 M-JPEG	1	1920x1080	1-way	-	-	Yes	Yes	Yes			
F3206	M2.P2P_031 4	H.264 MPEG4 M-JPEG	1	1920×1080	1-way	2/2	-	Yes	Yes	Yes			
F3210	M2.1.6.03C0 19	H.264 MPEG4 M-JPEG	1	1920×1080	1-way	1/1	-	Yes	Yes	Yes			
Note:	For F3210, Vi	deo resolu	tion can	not change w	hen only	setting	resoltu	ion.			•		
F3215	M2.1.6.05C0 16	H.264 M-JPEG MPEG4	1	1920×1080	1-way	1/1	-	Yes	Yes	Yes*			
Note:	Resolution lis	t is not syr	nchroniz	ed with camera	a web dı	ie to res	solution	setting limit	ation. (Camera limitatio	n issue)		
F5100	MG.0.6.01_C	H.264 MPEG4 M-JPEG	1	1280×1024	1-way	1/1	-	Yes	Yes	Yes	Supported by design		
F5105	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	Supported by design		
F510E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design		
F510W	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design		
F5110	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	Supported by design		
F5115	MG.0.6.01_C 1	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	Supported by design		
F511E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design		



: not avaliable on camera*1: not avaliable on software*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps Yes*: multi stream setting support in Cystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks
F511W	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design
F520E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design
F521E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design
F531E	LM.1.6.18P9 _testport2	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design
F610A	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design
F611E	LM.1.6.16.00 7	M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	
F7110	MG.1.6.03P3 _r1072	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	2/2	Yes	Yes	Yes	Yes	
F7115	Refer to F7110	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	2/2	Yes	Yes	Yes	Yes	Supported by design
F7210	M2.1.6.04	H.264 MPEG4 M-JPEG	1	1920x1080	1-way	2/2	Yes	Yes	Yes	Yes*	
F721A	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	-	-	Yes	Yes	Yes	Supported by design
F731E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	Supported by design
Generic	Tested by P6210(2.1.5. 20)	H.264 M-JPEG	1	1920x1080	1-way	1/1	Yes	Yes	-	Yes*	
Note:		t to set pro		1920x1080 or 5 1920x1080 o						l in camera web.	(Camera
M510E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	Yes	Supported by design
Note:	PTZ Support:	pan and ti	It only								
M510W	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	Yes	Supported by design
Note:	PTZ Support:	pan and ti	lt only								



: not avaliable on camera*1: not avaliable on software*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps Yes*: multi stream setting support in Cystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Multi Stream Support	Remarks	
M511E	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	Yes	Supported by design	
Note:	PTZ Support:	pan and t	ilt only									
M511W	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	Yes	Supported by design	
Note:	PTZ Support: pan and tilt only											
P5110	MG.0.6.01_C	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	Yes	Yes	Supported by design	
Note:	PTZ Support:	pan and t	ilt only					,				
P5111	Refer to P5116	H.264 MPEG4 M-JPEG	1	1280x800	1-way	1/1	Yes	Yes	Yes	Yes	Supported by design	
P5115	MG.0.6.01_C	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	Yes	Yes		
Note:	PTZ Support:	pan and t	ilt only							-		
P5116	M2.1.6.02	H.264 MPEG4 M-JPEG	1	1280x800	1-way	1/1	Yes	Yes	Yes	Yes		
Note:	1. PTZ Suppo 2. There is no 3. The max fr	audio wh	en using	AMR 7.95	s up to 2	0 FPS i	n 1280x	800. It's the	e limitat	ion of hardware		
P6210	M2.1.5.11	H.264 M-JPEG	1	1920×1080	1-way	1/1	Yes	Yes	Yes	Yes*		
Note:				when resolution						(Camera limita	ition)	
P6211	02_C022	H.264 M-JPEG	1	1920×1080	1-way	1/1	Yes	Yes	Yes	Yes*		
V1100	M2.1.6.03	H264 MJPEG MPEG4	1	704x480	1-way	1/1	Yes	Yes	Yes	Yes		
Note:	AMR can't be	used in au	ıdio in/o	ut.								
V111T	LM.1.6.16.03	MPEG4 M-JPEG	1	640x480	1-way	1/1	Yes	Yes	Yes	Yes	Supported by design	
Note	If enable Zav	io analog v	video ou	tput function, i	t will no	t be abl	e to get	2^{nd} stream	from za	vio camera.		