

Grundig



- : not available on camera
 *1: not available on software
 *2: not test on software
 For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

| Device Name | Tested Firmware | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|---------------|---|--------------------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| GCI-0735P | | H.264 MPEG4 M-JPEG | 1 | 720x576 | 1-way | 4/1 | Yes | Yes | Yes | Yes | Supported by design |
| GCI-C0745P | 720110412NS | H.264 M-JPEG | 1 | 720x576 | 1-way | 4/1 | Yes | Yes | Yes | Yes | |
| GCI-G1536F | gr20140530NSA | H.264, MJPEG | 1 | 2592x1944 | 2-way | 1/1 | - | Yes | Yes | Yes | |
| Note: | Fisheye camera | | | | | | | | | | |
| GCI-H0503B | 720110422NS | H.264 MPEG4 M-JPEG | 1 | 1280x960 | 1-way | 1/1 | - | Yes | Yes | Yes | |
| GCI-H0522V | | H.264 MPEG4 M-JPEG | 1 | 1920x1080 | 1-way | 1/1 | - | Yes | Yes | Yes | Supported by design |
| GCI-H0602B | | H.264 MPEG4 M-JPEG | 1 | 1920x1080 | 1-way | 1/1 | - | Yes | Yes | Yes | Supported by design |
| GCI-H2505B | Refer to GCI-K2505B(gr20130417NSX) | H.264, MJPEG | 1 | 1920x1080 | 1-way | 1/1 | - | Yes | Yes | Yes | Supported by design |
| GCI-K0322V | 720110413NS | H.264 M-JPEG | 1 | 1920x1080 | 1-way | 1/1 | - | Yes | Yes | Yes | |
| GCI-K0503B | | H.264 MPEG4 M-JPEG | 1 | 1920x1080 | 1-way | 1/1 | - | Yes | Yes | Yes | Supported by design |
| GCI-K0512W | | H.264 MPEG4 M-JPEG | 1 | 1920x1080 | - | 1/1 | - | Yes | Yes | Yes | Supported by design |
| GCI-K0523T | | H.264 MPEG4 M-JPEG | 1 | 1920x1080 | 1-way | 1/1 | - | Yes | Yes | Yes | Supported by design |
| Note: | With HW restrictions, the video @ H.264 with TCP protocol is not smooth in the conditions of high resolution, fps and bitrate. We recommend to lower bitrate to 4000. | | | | | | | | | | |
| GCI-K0589T(H) | Refer to GCI-K1586V(gr20130621NSA) | H.264, MJPEG | 1 | 1920x1080 | 1-way | 1/1 | Yes | Yes | Yes | Yes | Supported by design |
| GCI-K0779P | gr20130621NSA | H.264, MJPEG | 1 | 1920x1080 | 1-way | 4/2 | Yes | Yes | Yes | Yes | |
| GCI-K1523VS | Refer to GCI-K2505B(gr20130417NSX) | H.264, MJPEG | 1 | 1920x1080 | 1-way | 1/1 | - | Yes | Yes | Yes | Supported by design |
| GCI-K1526V | gr20120522NSA | MJPEG, H.264 | 1 | 1920x1080 | 1-way | 1/1 | - | Yes | Yes | Yes | |

Grundig



- : not available on camera
 *1: not available on software
 *2: not test on software
 For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

| Device Name | Tested Firmware | Video Format | Video Ch | Max Resolution | Audio | I/O Ch | PTZ | On-Edge Motion | UPnP | Multi Stream Support | Remarks |
|--------------------|---|--------------|----------|----------------|-------|--------|-----|----------------|------|----------------------|---------------------|
| Note: | When we set the resolution, compression and frame rate in maximal value, the camera would not respond if we want to get camera parameter, and the audio we get is also unstable. Camera may not connect to if the frame rate is 1. We suggest to change the GOV length to lower value on camera web page. 1080P not support 2nd stream. | | | | | | | | | | |
| GCI-K1526VS | Refer to GCI-K2505B(gr20130417NSX) | H.264, MJPEG | 1 | 1920x1080 | 1-way | 1/1 | - | Yes | Yes | Yes | Supported by design |
| GCI-K1585V | Refer to GCI-K1586V(gr20130621NSA) | H.264, MJPEG | 1 | 1920x1080 | 1-way | 1/1 | Yes | Yes | Yes | Yes | Supported by design |
| GCI-K1586V | gr20130621NSA | H.264, MJPEG | 1 | 1920x1080 | 1-way | 1/1 | Yes | Yes | Yes | Yes | |
| Note: | FW: gr20130621NAS, gr20130417NSX 1. Audio has noise when camera setting is high. 2. Get parameter will ailed when camera setting is high. 3. GCI-K1586V, GCI-K0589T(H), GCI-K1585V PTZ only support zoom and focus. | | | | | | | | | | |
| GCI-K1812W | gr20120522NSA | H.264 | 1 | 1920x1080 | 1-way | - | - | Yes | Yes | Yes | |
| Note: | When we set the resolution, compression and frame rate in maximal value, the camera would not respond if we want to get camera parameter, and the audio we get is also unstable. Camera may not connect to if the frame rate is 1. We suggest to change the GOV length to lower value on camera web page. 1080P not support 2nd stream. | | | | | | | | | | |
| GCI-K2505B | gr20130417NSX | H.264, MJPEG | 1 | 1920x1080 | 1-way | 1/1 | - | Yes | Yes | Yes | |
| Note: | Framerate setting will failed when choosing TV system Autoiris WDR25fps, WDR 25fps and WDR 30fps. | | | | | | | | | | |