# SONY

- : not avaliable on camera

\*1: not avaliable on software

\*2: not test on software

For multi stream support:

				Yes*: mu	ונו אנו כנ	iiii sett	ing s		1-	I.a		
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On- Edge Motion	Camera Search Tool	Multi Stream Support	Snapshot	Remarks
Generic	1.7.0	H.264 M-JPEG	1	All	1-way	2/2	-	Yes	Yes	Yes	Yes	
Note:	by bandwidth	enarios i.e. n specificati	on.	igh frame rate				•			_	ave limitation
SNC-CH110	1.27.00	H.264 MPEG4 M-JPEG	1	1280x960	-	-	-	Yes	Yes	Yes*	-	
Note:	SNC-CH110/	B and SNC-	CH110/	S are campati	ble with	SNC-CH	1110					
SNC-CH120	1.80	H.264 MPEG4 M-JPEG	1	1280x1024	-	1/0	-	Yes	Yes	Yes	-	
Note:	SNC-CH120 i	not support	SolidPT	Z mode.								
SNC-CH140	1.07.00	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/2	-	Yes	Yes	Yes*	-	
SNC-CH160	1.82.01	H.264 M-JPEG	1	1280x1024	-	1/1	Yes	Yes	Yes	Yes*	Yes	
Note:	Camera with	resolution	1280x10	24 is unable	to achie	ve 30 fp	S					
SNC-CH180	1.26.01	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/2	-	Yes	Yes	Yes*	-	
SNC-CH210		H.264 MPEG4 M-JPEG	1	2048x1536	-	-	-	Yes	Yes	Yes*	-	
Note:	2. Dualstrear	n can not b er of conne	e enable	0/S are camp ed when H.264 1 for JEPG and	4, 1280	x 720, 3	30 fps	is selecte				
SNC-CH220	1.21.02	H.264 MPEG4 M-JPEG	1	1920x1440	-	1/1	-	Yes	Yes	Yes*	-	
SNC-CH240	1.10.01	H.264 MPEG4 M-JPEG	1	1920×1440	1-way	1/2	-	Yes	Yes	Yes*	-	
SNC-CH260		H.264 MPEG4 M-JPEG	1	1920×1440	-	1/1	-	Yes	Yes	Yes*	-	
Note:	2. DualStrea	m can not ber of conne	e enable	m tele/wide, ed when the H 1 for JEPG and	1264, 19	20x108	0, 30	FPS is se	lected for			
SNC-CH280	1.26.01	H.264 MPEG4 M-JPEG	1	1920x1440	1-way	1/2	-	Yes	Yes	Yes*	-	
SNC-CM120	1.00	MPEG4 M-JPEG	1	1280x960	1-way	1/2	-	Yes	Yes	Yes*	-	

#### SONY

- : not avaliable on camera

\*1: not avaliable on software

\*2: not test on software

For multi stream support:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch		On- Edge Motion	Camera Search Tool	Multi Stream Support	Snapshot	Remarks
SNC-CS10		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes*	-	Supported by design
SNC-CS11	1.05	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes*	-	
SNC-CS20		MPEG4 M-JPEG	1	768x576	1-way	1/2	-	Yes	Yes	Yes*	-	Supported by design
SNC-CS3		M-JPEG	1	736x480	-	1/2	-	-	Yes	Yes*	-	Supported by design
SNC-CS50	2.21	MPEG4 M-JPEG	1	640x480	1-way	2/2	-	Yes	Yes	Yes*	-	
SNC- CX600W	1.7.0	H.264 M-JPEG	1	1280x1024	2-way	-	-	Yes	Yes	Yes	Yes	
Note:	In certain sce by bandwidth For further inf	specification,	on.					•			-	ave limitation
SNC-DF50	1.11	H.264 MPEG4 M-JPEG	1	640x480	1-way	1/2	-	Yes	Yes	Yes*	-	
SNC-DF70	1.17	MPEG4 M-JPEG	1	640x480	1-way	1/2	-	Yes	Yes	Yes*	-	
SNC-DF80	1.11	H.264 MPEG4 M-JPEG	1	640x480	1-way	1/2	-	Yes	Yes	Yes*	-	
SNC-DF85		H.264 MPEG4 M-JPEG	1	640x480	1-way	1/2	-	Yes	Yes	Yes*	-	Supported by design
SNC-DH110	1.82.01	H.264 M-JPEG	1	1280x960	-	-	-	Yes	Yes	Yes*	Yes	
Note:	1. SNC-DH110 2. Change For	0/B and SN					C-DH1	10		•		1
SNC- DH110T	Refer to	H.264 MPEG4 M-JPEG	1	1280x960	-	-	-	Yes	Yes	Yes*	-	Supported by design
Note:	SNC-DH110T/	B and SNC	-DH110	T/W are camp	oatible v	vith SNC	-DH1	10T		-	-	-
SNC-DH120	1.78.00	H.264 MPEG4 M-JPEG	1	1280x1024	-	-	-	Yes	Yes	Yes*	-	
Note:	<ol> <li>PTZ function</li> <li>Dualstream</li> <li>The connect</li> <li>The number</li> </ol>	can not b	e enable t establi	ed when H.264 shed with hig	4, 1280 h probal	x 720, 3 pility wh	30 fps ien se	is selecte lected JPE	ed for Imag EG, high re	solution an	d high quali	ty.
SNC-DH140	1.07.00	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/2	-	Yes	Yes	Yes*	-	

#### SONY

- : not avaliable on camera

\*1: not avaliable on software

\*2: not test on software

For multi stream support:

				Yes*: mu	iti strea	ım sett	ing s					
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On- Edge Motion	Camera Search Tool	Multi Stream Support	Snapshot	Remarks
Note:	Motion detect	tion will be	turned o	off upon chang	ging to n	naximuı	n reso	olution. R	emember t	o enable it	in camera v	web.
SNC-DH160	1.13.00	H.264 MPEG4 M-JPEG	1	1280×1024	-	1/1	-	Yes	Yes	Yes*	-	
SNC-DH180	1.10.02	H.264 MPEG4 M-JPEG	1	1280×1024	1-way	1/2	-	Yes	Yes	Yes*	-	
SNC-DH210		H.264 MPEG4 M-JPEG	1	2048×1536	-	1	-	Yes	Yes	Yes*	-	Supported by design
Note:	SNC-DH210/I	B and SNC-	DH210/	W are campat	ible with	SNC-D	H210					
SNC- DH210T	1.27.00	H.264 MPEG4 M-JPEG	1	2048x1536	-	-	-	Yes	Yes	Yes*	-	
Note:	SNC-DH210T	/B and SNO	C-DH210	T/W are camp	oatible w	ith SNC	C-DH2	10T				
SNC-DH220	1.82.01	H.264 M-JPEG	1	1920x1440	-	-	Yes	Yes	Yes	Yes*	Yes	
SNC- DH220T	Refer to SNC-DH220	H.264 MPEG4 M-JPEG	1	1920x1440	1-way	1/1	Yes	Yes	Yes	Yes*	-	Supported by design
SNC-DH240	1.11.00	H.264 MPEG4 M-JPEG	1	1920×1440	1-way	1/2	-	Yes	Yes	Yes*	-	
SNC-DH260	1.30.00	H.264 MPEG4 M-JPEG	1	1920x1440	-	1/1	-	Yes	Yes	Yes*	-	
SNC-DH280	1.26.01	H.264 MPEG4 M-JPEG	1	1921×1440	1-Way	1/2	-	Yes	Yes	Yes*	-	
SNC-DM110		MPEG4 M-JPEG	1	1280x960	1-way	1/2	-	Yes	Yes	Yes*	-	Supported by design
SNC-DM160	1.01	MPEG4 M-JPEG	1	1280x960	1-way	1/2	-	Yes	Yes	Yes*	-	
SNC-DS10	1.01	H.264 MPEG4 M-JPEG	1	768x576	1-way	1/2	-	Yes	Yes	Yes*	-	
SNC-DS60	1.00	MPEG4 M-JPEG	1	640×480	1-way	1/2	-	Yes	Yes	Yes*	-	
SNC-EB600	Refer to SNC- EB600B(1.9. 2)	H264 MJPEG	1	1280x1024	-	-	-	Yes	Yes	Yes	Yes	Supported by design
Note:	In certain sce by bandwidth For further in	specificati	on.							•		ave limitation

## SONY

- : not avaliable on camera

\*1: not avaliable on software

\*2: not test on software

For multi stream support:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On- Edge Motion	Camera Search Tool	Multi Stream Support	Snapshot	Remarks
SNC- EB602R	Refer to SNC- EB632R(2.1. 2)	H.264 M-JPEG	1	1920x1080	-	-	Yes	Yes	Yes	Yes*	Yes	Supported by design
SNC- EB600B	1.9.2	H264 MJPEG	1	1280×1024	-	-	-	Yes	Yes	Yes	Yes	
Note:	In certain sce by bandwidth For further inf	specification	on.									ave limitation
SNC-EB630	1.9.2	H.264 M-JPEG	1	1920×1080	-	-	-	Yes	Yes	Yes	Yes	
Note:	In certain sce by bandwidth For further inf	specification	on.	_				•			_	ave limitation
SNC- EB630B	Refer to SNC- EB630(1.9.2)	H.264 M-JPEG	1	1920×1080	-	-	-	Yes	Yes	Yes	Yes	Supported by design
Note:	In certain sce by bandwidth For further inf	specification	on.	_							_	ave limitation
SNC- EB632R	2.2.1	H.264 M-JPEG	1	1920×1080	-	-	Yes	Yes	Yes	Yes*	Yes	
Note:	PTZ only supp	ort zoom a	and focu	S.			•	•	•	•	•	•
SNC-EM600	Refer to SNC- EB600B(1.9. 2)	H264 MJPEG	1	1280x1024	-	-	-	Yes	Yes	Yes	Yes	Supported by design
Note:	In certain scen by bandwidth For further inf	specification	on.	_							_	ave limitation
SNC-EM601	Refer to SNC- EB600B(1.9. 2)	H264 MJPEG	1	1280x1024	-	-	-	Yes	Yes	Yes	Yes	Supported by design
Note:	In certain scen by bandwidth For further inf	specification	on.	_							_	ave limitation
SNC- EM602R	Refer to SNC- EB600B(1.9. 2)	H264 MJPEG	1	1280x1024	ı	-	-	Yes	Yes	Yes	Yes	Supported by design
Note:	In certain scently by bandwidth For further inf	specification	on.									ave limitation

# SONY.

- : not avaliable on camera

\*1: not avaliable on software

\*2: not test on software

For multi stream support:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On- Edge Motion		Multi Stream Support	Snapshot	Remarks
SNC-EM630	Refer to SNC- EB630(1.9.2)	H.264 M-JPEG	1	1920x1080	-	-	-	Yes	Yes	Yes	Yes	Supported by design
Note:	In certain sce by bandwidth For further inf	specification	on.	_						•	_	ave limitation
SNC-EM631	Refer to SNC- EB630(1.9.2)	H.264 M-JPEG	1	1920x1080	-	-	-	Yes	Yes	Yes	Yes	Supported by design
Note:	In certain scen by bandwidth For further inf	specification	on.							•		ave limitation
SNC- EM632R	1.9.2	H.264 M-JPEG	1	1920x1080	-	-	Yes	Yes	Yes	Yes	Yes	
Note:	In certain sce by bandwidth For further inf	specification,	on.	_						•	_	ave limitation
SNC-EP520	1.40.00	H.264 MPEG4 M-JPEG	1	720x480	1-way	2/1	Yes	Yes	Yes	Yes	-	
SNC-EP521	1.42.00	H.264 MPEG4 M-JPEG	1	720x576	1-way	2/1	Yes	Yes	Yes	Yes	-	
SNC-EP550	Refer to SNC-ER550	H.264 MPEG4 M-JPEG	1	1280x720	1-way	2/1	Yes	Yes	Yes	Yes	-	Supported by design
SNC-EP580	1.42.00	H.264 MPEG4 M-JPEG	1	1920x1080	1-way	2/1	Yes	Yes	Yes	Yes	-	
Note:	For performar	nce conside	eration,	users are una	ble to w	atch live	vide	os on bot	h NVR side	and came	ra side.	
SNC-ER520	1.42.00	H.264 MPEG4 M-JPEG	1	720x480	1-way	2/1	Yes	Yes	Yes	Yes	-	
SNC-ER521	1.42.00	H.264 MPEG4 M-JPEG	1	720x576	1-way	2/1	Yes	Yes	Yes	Yes	-	
SNC-ER550	1.78.00	H.264 MPEG4 M-JPEG	1	1280x720	1-way		Yes	Yes	Yes	Yes	-	
Note:	<ol> <li>Dualstream</li> <li>The numbe</li> <li>The connect</li> </ol>	r of connection canno	ction is :	1 for JEPG and	2 for H	1264 and	MPE	G4 at the	same time	! <b>.</b>	d high quali	ty.
SNC-ER580	1.82.01	H.264 M-JPEG	1	1920×1080	2-way	2/1	Yes	Yes	Yes	Yes*	Yes	

## SONY

- : not avaliable on camera

\*1: not avaliable on software

\*2: not test on software

For multi stream support:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On- Edge Motion	Camera Search Tool	Multi Stream Support	Snapshot	Remarks
Note:	For performa	nce conside	eration,	users are una	ble to w	atch live	e vide	os on bot	h NVR side	and came	ra side.	
SNC-ER585	1.78.00	H.264 MPEG4 M-JPEG	1	1920x1080	*2	*2	Yes	Yes	*2	Yes	-	Tested by link
SNC-HM662	1.1.1	H.264 MJPEG	1	2560x1920	1-way	1/1	-	Yes	-	Yes	Yes	
Note:	1. fisheye car 2. In certain s limitation by	scenarios i.		r high frame r ation.	ate and	resoluti	on wit	h multipl	e stream c	ondition, ca	amera migh	t have
SNC-P1	1.28	MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	Yes	Yes	-	
SNC-P5	1.11	MPEG4 M-JPEG	1	640x480	1-way	2/1	Yes	Yes	Yes	Yes	-	
SNC-RH124	1.84.00	H.264 M-JPEG	1	1280x720	2-way	4/2	Yes	Yes	Yes	Yes*	Yes	
Note:	2. The camer	a with MJPI	G form	at and resolut at is unable to n change the a	achieve	30fps			y disconne	ct.		
SNC-RH164	1.10.01	H.264 MPEG4 M-JPEG	1	1280x720	1-way	4/2	Yes	Yes	Yes	Yes	-	
SNC-RS44N		H.264 MPEG4 M-JPEG	1	720x480	1-way	4/2	Yes	Yes	Yes	Yes	-	Supported by design
SNC-RS44P		H.264 MPEG4 M-JPEG	1	720x576	1-way	4/2	Yes	Yes	Yes	Yes	-	Supported by design
SNC-RS46N		H.264 MPEG4 M-JPEG	1	720x480	1-way	4/2	Yes	Yes	Yes	Yes	-	Supported by design
SNC-RS46P	1.10.02	H.264 MPEG4 M-JPEG	1	720x576	1-way	4/2	Yes	Yes	Yes	Yes	-	
SNC-RS84N		H.264 MPEG4 M-JPEG	1	720x480	1-way	4/2	Yes	Yes	Yes	Yes	-	Supported by design
SNC-RS84P		H.264 MPEG4 M-JPEG	1	720x576	1-way	4/2	Yes	Yes	Yes	Yes	-	Supported by design
SNC-RS86N		H.264 MPEG4 M-JPEG	1	720x480	1-way	4/2	Yes	Yes	Yes	Yes	-	Supported by design

## SONY

- : not avaliable on camera

\*1: not avaliable on software

\*2: not test on software

For multi stream support:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ		Camera Search Tool	Multi Stream Support	Snapshot	Remarks
SNC-RS86P		H.264 MPEG4 M-JPEG	1	720x576	1-way	4/2	Yes	Yes	Yes	Yes	-	Supported by design
SNC-RX530	3.00	H.264 MPEG4 M-JPEG	1	640x480	1-way	2/2	Yes	Yes	Yes	Yes	-	
SNC-RX550		H.264 MPEG4 M-JPEG	1	640x480	1-way	2/2	Yes	Yes	Yes	Yes	-	Supported by design
SNC-RX570	3.01	H.264 MPEG4 M-JPEG	1	640x480	1-way	2/2	Yes	Yes	Yes	Yes	-	
SNC-RZ25	1.29	MPEG4 M-JPEG	1	640x480	1-way	2/2	Yes	Yes	Yes	Yes	-	
SNC-RZ30	3.14	M-JPEG	1	736x480	-	3/2	Yes	-	Yes	Yes	-	
SNC-RZ50	2.21	H.264 MPEG4 M-JPEG	1	640x480	1-way	2/2	Yes	Yes	Yes	Yes	-	
SNC-VB600	1.9.2	H.264 M-JPEG	1	1280x1024	2-way	2/2	-	Yes	Yes	Yes	Yes	
Note:	In certain sce by bandwidth For further inf	specification	on.									ave limitation
SNC- VB600B	1.7.0	H.264 M-JPEG	1	1280x1024	2-way	2/2	-	Yes	Yes	Yes	Yes	
Note:	In certain sce by bandwidth For further inf	specification	on.					•			-	ave limitation
SNC-VB630	2.2.1	H264 MJPEG	1	1920x1080	2-way	2/2	Yes	Yes	Yes	Yes*	Yes	
Note:	In certain sce by bandwidth For further inf	specification	on.									ave limitation
SNC-VB635	1.11.0	H264 MJPEG	1	1920×1080	2-way	2/2	Yes	Yes	Yes	Yes	Yes	
Note:	In certain scei by bandwidth For further inf Easy Focus	specification	on.								-	ave limitation
SNC-VM600	Refer to SNC- VB600(1.9.2)	H.264 M-JPEG	1	1280x1024	2-way	2/2	-	Yes	Yes	Yes	Yes	Supported by design

## SONY.

- : not avaliable on camera

\*1: not avaliable on software

\*2: not test on software

For multi stream support:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch		On- Edge Motion	Camera Search Tool	Multi Stream Support	Snapshot	Remarks
Note:	In certain sce by bandwidth For further inf	specification	on.					multiple s	tream cond	lition, cam		ave limitation
SNC- VM600B	Refer to SNC- VB600B(FW	H.264 M-JPEG	1	1280x1024	2-way	2/2	-	Yes	Yes	Yes	Yes	Supported by design
Note:	In certain sce by bandwidth For further inf	specification	on.	_				·			_	ave limitation
SNC-VM601	Refer to SNC- VB600(1.9.2)	H.264 M-JPEG	1	1280×1024	2-way	2/2	-	Yes	Yes	Yes	Yes	Supported by design
Note:	In certain sce by bandwidth For further inf	specification	on.									ave limitation
SNC- VM601B	Refer to SNC- VB600(1.9.2)	H.264 M-JPEG	1	1280x1024	2-way	2/2	-	Yes	-	-	-	Supported by design
Note:	In certain sce by bandwidth For further inf	specification	on.	_				·			_	ave limitation
SNC- VM602R	Refer to SNC- VB600(1.9.2)	H.264 M-JPEG	1	1280×1024	2-way	2/2	-	Yes	Yes	Yes	Yes	Supported by design
Note:	In certain sce by bandwidth For further inf	specification	on.	_				·			_	ave limitation
SNC-VM630	Refer to SNC- VM632R(1.9.	H264 MJPEG	1	1920×1080	2-way	2/2	-	Yes	Yes	Yes	Yes	Supported by design
Note:	In certain scel by bandwidth For further inf	specification	on.	_				·			_	ave limitation
SNC-VM631	Refer to SNC- VM632R(1.9.	H264 MJPEG	1	1920×1080	2-way	2/2	-	Yes	Yes	Yes	Yes	Supported by design
Note:	In certain scel by bandwidth For further inf	specification	on.					·		,		ave limitation
SNC- VM632R	1.9.2	H264 MJPEG	1	1920×1080	2-way	2/2	-	Yes	Yes	Yes	Yes	

#### SONY

- : not avaliable on camera

\*1: not avaliable on software

\*2: not test on software

For multi stream support:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On- Edge Motion	Camera Search Tool	Multi Stream Support	Snapshot	Remarks
Note:	In certain scer by bandwidth For further inf	specification	on.	_							-	ave limitation
SNC-WR600	1.11.0	H264 MJPEG	1	1280x1024	2-way	4/2	Yes	Yes	Yes	Yes	Yes	
SNC-WR602	Refer to SNC- WR600(1.11.	H264 MJPEG	1	1280×1024	2-way	4/2	Yes	Yes	Yes	Yes	Yes	Supported by design
SNC-WR630	1.11.0	H264 MJPEG	1	1920x1080	2-way	4/2	Yes	Yes	Yes	Yes	Yes	
Note:	In certain scer by bandwidth For further inf	specificati	on.									ave limitation
SNC-WR632	Refer to SNC-WR630 (1.11.0)	H264 MJPEG	1	1920×1080	2-way	4/2	Yes	Yes	Yes	Yes	Yes	Supported by design
Note:	In certain scen by bandwidth For further inf	specificati	on.	_				•			-	ave limitation
SNC-XM631	2.2.1	H.264 MJPEG	1	1920×1080	-	ı	ı	Yes	Yes	Yes*	Yes	
SNC-XM632	1.12.0	H.264 MJPEG	1	1920x1080	1-way	-	-	Yes	Yes	Yes	Yes	
Note:	In certain scer by bandwidth For further inf	specificati	on.					•		•		ave limitation
	Refer to SNC- XM632(1.12. 0)	H.264 MJPEG	1	1920x1080	1-way	-	-	Yes	Yes	Yes	Yes	Supported by design
Note:	In certain scei by bandwidth For further inf	specificati	on.					•		•		ave limitation
SNC-XM637	Refer to SNC- XM632(1.12.	H.264 MJPEG	1	1920x1080	1-way	-	-	Yes	Yes	Yes	Yes	Supported by design
Note:	In certain scer by bandwidth For further inf	specification	on.	_				•			-	ave limitation

#### SONY

- : not avaliable on camera

\*1: not avaliable on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On- Edge Motion	Camera Search Tool	Multi Stream Support	Snapshot	Remarks
SNC-Z20	1.06	M-JPEG	1	736x480	-	1/2	Yes	-	Yes	Yes	-	
Note:	PTZ Support	: zoom only										
SNC-ZB550	1.82.01	H.264 MJPEG	1	1280×1024	-	1/1	-	Yes	Yes	Yes*	Yes	
SNT-EP104		H.264 MPEG4 M-JPEG	4	720x480	-	-	-	Yes	Yes	Yes	-	Supported by design
SNT-EP154	1.10.01	H.264 MPEG4 M-JPEG	4	720x480	-	-	-	Yes	Yes	Yes	-	
SNT-EX101		H.264 MPEG4 M-JPEG	1	720x480	1-way	2/2	Yes	Yes	Yes	Yes	-	Supported by design
SNT- EX101E	1.10.01	H.264 MPEG4 M-JPEG	1	PAL:720x57 6 NTSC:720x4	1-way	2/2	Yes	Yes	Yes	Yes	-	
SNT-EX104	1.10.01	H.264 MPEG4 M-JPEG	4	PAL:720x57 6 NTSC:720x4	1-way	4/4	Yes	Yes	Yes	Yes	-	
SNT-EX154	1.10.01	H.264 MPEG4 M-JPEG	4	720x480	1-way	4/4	Yes	Yes	Yes	Yes	-	
SNT-V704	2.15	MPEG4 M-JPEG	4	720x480	1-way	1/4	-	-	Yes	Yes	-	
Note:				d "X" series, I e. The 1.7 and						to use.	-	
Note			,	m must suppo t with the next					able the sn	apshot fea	ture. This is	a known