



- : not available on camera
 *1: not available on software
 *2: not test on software
 For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
OSD-200A 20xp	gk20140422 NSA	H.264 MJPEG	1	1920x1080	*2	*2	Yes	Yes	*2	Yes	Yes*	
Note:	1. Snapshot supported when one of stream choose MJPEG. (Camera firmware issue) 2. Error preset point. (Camera firmware issue)											
30xN	v3.2.2.8	H.264 MJPEG MPEG4	1	2048x1536	2-way	1/1	Yes	Yes	Yes	-	Yes	
Note:	Fisheye camera 1. Brickcom 30xN can't record on H.264 format with MainConsole 3.5.53 2. Cover model: MD-300Np, FB-300Np, WFB-300Np, FD-302Np, VD-302Np, OB-302Np, OB-302Ne, WOB-302Ne, FB-200Np, OB-202Np, VD-202Np. VD-300Np, FD-300Np, OB-300Np, WOB-300Np, GOB-300Np with zoom feature. OB-300Np-AD, OB-200Np, VD-200Np with zoom and focus feature. MD-300Np-360 is fisheye camera 3. MD-300Np and MD-300Np-360 are no support DI/DO and one way audio only. 4. MD-300Np-360 not support MD when format is MJPEG and MPEG4. 5.The Zoom , Focus or Auto Focus function has no response via camera web or CGI command. 6.The Motion Detection always triggered when the frame rate is 1.											
130N series	v3.1.0.9	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	Yes	Yes	Yes	-	-	
Note:	OB-130Np, WOB-130Np, GOB-130Np, FD-130Np, VD-130Np. FB-130Np, WFB-130Np compare them with OB-130Np difference is w/o zoom control Smart Zoom/Focus will spent 15s every time											
50xA series	v3.2.2.8	H.264 MPEG4 M-JPEG	1	2592x1944	2-way	1/1	Yes	Yes	Yes	-	Yes	
Note:	Fisheye camera 1.Covered model:FB-500Ap, FD-301Af, WFB-500Ap, CB-500Ap, WCB-500Ap, CB-502Ap, WCB-502Ap, FD-500Ap, FD-502Ap, VD-301Af, VD-500Ap, VD-502Ap , OB-500Af, MB-500Ap, WMB-500Ap, MD-500Ap-360, FD-301A, VD-301AF, OB-200Ap, FB-202Ap, OB-202Ap, VD202Ap OB-200Ap and VD-200Ap with zoom and focus function. 2. switch video resolution higher than 1920x1080 need waiting a period to reconnect stream 3. MD-500Ap-360 is no support DI/DO and one way audio only. 4. MD-500Ap-360 not support MD when format is MJPEG and MPEG4. 5.Max framerate can't sync with Wide and Ultra-Wide mode on camera web. 6.The RTSP stream has been disconnected in 5 minutes when the protocol is use under HTTP. 7.The image is broken when the format is MJPEG and resolution is 2592x1944 or 2304x1728. 8.The Zoom or Focus function has on response via camera web or CGI command.											
CB-100A	v3.0.2.4	H.264 MPEG4 M-JPEG	1	1280x800	2-way	-	-	-	Yes	-	-	
CB-100Ae	v3.0.2.4	MPEG4 M-JPEG	1	1280x800	2-way	-	-	-	Yes	-	-	
FB-100A	v3.0.2.3	H.264 MPEG4 M-JPEG	1	1280x800	2-way	1/0	-	-	Yes	-	-	



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
FB-100Ae	v3.0.2.3	MPEG4 M-JPEG	1	1280x800	2-way	1/0	-	-	Yes	-	-	
FD-100A	v2.3.7.8	H.264 MPEG4 M-JPEG	1	1280x800	2-way	1/0	-	-	Yes	-	-	
FD-100Ae	v3.0.2.3	MPEG4 M-JPEG	1	1280x800	2-way	1/0	-	-	Yes	-	-	
MD-100A	Refer to CB-100A	H.264 MPEG4 M-JPEG	1	1280x800	2-way	-	-	-	Yes	-	-	Supported by design
Hydracam	v3.2.3.4	H.264	3	1280x720	2-way	2/2	-	-	Yes	-	Yes	
Note:	1. Audio function is not supported. 2. Resolution and bitrate list is not synchronized with the camera webpage. 3. The video does not play smoothly when the frame rate set to 1.											
OB-100A	v3.1.0.8	H.264 MPEG4 M-JPEG	1	1280x800	2-way	1/1	Yes	Yes	Yes	-	-	
OB-300Ap	v3.7.0.18A	H.264 MPEG4 M-JPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	
Note:	1. Upnp will find wrong model. (Camera Firmware issue) 2. Camera with highest resolution is unable to achieve maximum FPS in any format. (Camera performance limitation) 3. Talk has noise. (Camera Firmware issue)											
OB-300Np	v3.7.0.18A	H.264 MPEG4 M-JPEG	1	1920x1080	2-way	1/1	Yes	Yes	Yes	-	Yes*	
Note:	1. Upnp will find wrong model. (Camera Firmware issue) 2. Camera with highest resolution is unable to achieve maximum FPS in any format. (Camera performance limitation) 3. Talk has noise. (Camera Firmware issue)											
W/VS-01A	v3.1.0.6	H.264 MPEG4 M-JPEG	1	720x576	2-way	1/1	Yes	Yes	Yes	-	-	
VD-201Af	v3.2.3.5.6	H.264 MPEG4 M-JPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	
Note:	1.Upnp will find wrong model. (Camera firmware issue) 2.Camera with highest resolution is unable to achieve maximum FPS in any format.(Camera performance limitation) 3. I/O active contrary. (Camera firmware issue) 4.MJPEG resolution requirements shall be a multiple of 8, so cannot support 320x180, substituted resolution is 320x184. (Camera performance limitation)											
VS-04A	v1.0.0.7-03T	MPEG4 M-JPEG	4	720x480	2-way	2/2	Yes	-	Yes	-	-	



- : not available on camera
 *1: not available on software
 *2: not test on software
 For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
Note:	VS-04A not support PTZ focus, preset, patrol, home											
VS-04A v2	3.5.2.15	H.264 MJPEG	4	720x576	2-way	4/4	Yes	Yes	Yes	-	Yes	
Note:	1. PTZ does not work 2. Audio does not work 3. Resolution and bitrate list is not synchronized with the camera web.											
WCB-100A	v2.3.5.6.1	H.264 MPEG4 M-JPEG	1	1280x800	2-way	-	-	-	Yes	-	-	
WCB-100Ae	v3.0.2.4	MPEG4 M-JPEG	1	1280x800	2-way	-	-	-	Yes	-	-	
WFB-100A	v2.3.7.8	H.264 MPEG4 M-JPEG	1	1280x800	2-way	1/0	-	-	Yes	-	-	
WFB-100Ae	v3.0.2.3	MPEG4 M-JPEG	1	1280x800	2-way	1/0	-	-	Yes	-	-	
OSD/PZ-040D	v3.1.0.8	H.264 MPEG4 M-JPEG	1	720x480	2-way	1/1	Yes	Yes	Yes	-	-	
OSD/PZ-040E	v3.1.0.8	H.264 MPEG4 M-JPEG	1	720x576	2-way	1/1	Yes	Yes	Yes	-	-	