

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps
 Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
ACM-PT500	2.03.16	H.264 MPEG4	1	2048x1536	1-way	2/1	Yes	Yes	Yes	-	Yes	
Note:	Camera is unable to achieve maximum FPS. (Camera performance limitation)											
ACM-R2001	1.02.09	H.264 MPEG4 M-JPEG	1	1920x1080	1-way	-	-	Yes	Yes	-	Yes	
Note:	Framerate may not enough about 2~8 fps due to camera issue.											
ACM-R3002	Refer to ACM- V3103(FW 2.03.23A)	H.264 MPEG4	1	2048x1536	1-way	1/1	*2	Yes	Yes	-	Yes*	Supported by design
Note:	1.Frame rate can't meet the requirements.(Camera performance limitation) 2.Not support zoom and focus.											
ACM-R3006	1.02.05T	H.264 MPEG4 M-JPEG	1	2048x1536	1-way	*2	*2	Yes	Yes	-	Yes	
ACM-V3001	1.02.09	H.264 MPEG4 M-JPEG	1	2048x1536	1-way	*2	-	Yes	Yes	-	Yes	
ACM-V3103	2.03.23A	H264 MPEG4	1	2048x1536	1-way	2/1	*2	Yes	Yes	-	Yes*	
Note:	1.Audio in can't be work.(Camera Firmware issue) 2.RS-485 can't be work.(Camera Firmware issue) 3.Alarm out can't be work.(Camera Firmware issue)											
ACM-V3002	Refer to ACM- V3103(FW 2.03.23A)	H264 MPEG4	1	2048x1536	1-way	2/1	*2	Yes	Yes	-	Yes*	Supported by design
Note:	1.Frame rate can't meet the requirements.(Camera performance limitation) 2.Not support zoom and focus.											
C3000/C3000-W	v3.2.2.3	H.264 MPEG4 M-JPEG	1	2048x1536	1-way	1/1	-	Yes	Yes	-	Yes	
CDB-4KM552	Refer to TCP- KM465(VK2.0 .4.5 F)	H.264 MJPEG	1	2592x1520	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps
 Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
CDB-5VM551	Refer to TCP-VM559(VC2.0.26.6_F)	H.264 M-JPEG	1	2592x1944	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
CDB-720F		H.264 MPEG4 M-JPEG	1	1280x800	1-way	1/1	-	Yes	*1	-	Yes	
CDB-720F/IR	V1.0.20_F	H.264 MPEG4 M-JPEG	1	1280x800	1-way	1/1	-	Yes	*1	-	Yes	
CDB-720V	VB1.0.26_F	H.264 MPEG4 M-JPEG	1	1280x800	1-way	1-1	-	Yes	Yes	-	Yes	
CDB-720VIR	VB1.0.26_F	H.264 MPEG4 M-JPEG	1	1280x800	1-way	1/1	-	Yes	*1	-	Yes	
CDB-720VIR-H	VE2.0.14.2_F	H.264 MJPEG	1	1280x800	1-way	1/1	-	Yes	Yes	-	Yes	
Note:	1. (Camera issue): FPS could not reach up to 20/30. 2. (Known issue): The info. of stream profile display failure											
CDB-HD280	refer to TCP-HDVB800-H(VE2.0.16.8 F)	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
CDB-HFD720	Refer to TCP-HDVB720-H(VE2.0.20.8)	H264 MJPEG	1	1280x800	-	-	-	Yes	Yes	-	Yes*	Supported by design
CDB-HFD728	refer to CDB-720VIR-H(VE2.0.14.2 F)	H.264 MJPEG	1	1280x800	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
CDB-HFD828	refer to TCP-HDVB800-H(VE2.0.16.8 F)	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
CDB-HFD828W	refer to TCP-HDVB800-H(VE2.0.16.8 F)	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps
 Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
CDB-MD602	refer to TCP-MZ602(VG1.0.14 F)	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
CDB-MV1080F	VB1.0.32_F	H.264 MPEG4 M-JPEG	1	1920x1080	-	1/1	-	Yes	Yes	-	Yes	
CDB-MV720F	VB1.0.28_F	H.264 MPEG4 M-JPEG	1	1280x800	-	1/1	-	Yes	Yes	-	Yes	
Note:	Camera FW issue: framerate can not reach 30fps.											
CDB-MV720F-H	Refer to TCP-HDVB720-H(VE2.0.20.8)	H264 MJPEG	1	1280x800	-	-	-	Yes	Yes	-	Yes*	Supported by design
CDB-T5	V6.08.25-NB	H.264 M-JPEG	1	2592x1944	1-way	1/1	-	Yes	Yes	-	Yes*	
Note:	Fisheye camera with manual calibration in Crystal Only audio can ben exported while selecting MOV format in playback system. (NUUO server limitation)											
CDV-2M360	VB1.0.32_F	H.264 MPEG4 M-JPEG	1	1920x1080	1-way	1/1	Yes	Yes	Yes	-	Yes	
Note:	Fisheye camera											
CDV-3F828	Refer to TCP-HDVB180(VE1.0.20.6_F)	H.264 MJPEG	1	1920x1080	-	-	-	Yes	Yes	-	Yes*	Supported by design
CDV-3V930		MPEG4 M-JPEG	1	720x480	1-way	1/1	-	Yes	-	-	-	Supported by design
CDV-3V930U		MPEG4 M-JPEG	1	720x480	1-way	1/1	-	Yes	-	-	-	Supported by design
CDV-3VM301		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	VC1.0.06_F	-	-	Supported by design
CDV-3VM501	refer to TCP-MH802(1.0.46)	M-JPEG H.264	1	1600x1200	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps
 Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
CDV-3VM800	VC1.0.06_F	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes	
CDV-3VM800-H	refer to TCP-HDVB800-H(VE2.0.16.8 F)	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
CDV-3VM800-H1	refer to TCP-HDVB800-H(VE2.0.16.8 F)	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
CDV-3VM800Z3	Refer to TCP-HDVB800Z3(VC2.0.24.2_F)	H.264 MJPEG	1	1920x1080	1-way	1/1	Yes	Yes	Yes	-	Yes*	Supported by design
CDV-3VM800Z42	VE1.0.20.2_F	H.264 MJPEG	1	1920x1080	1-way	1/1	Yes	Yes	Yes	-	Yes*	
Note:	1. The camera with highest resolution and MJPEG is unable to achieve highest fps. (Camera firmware issue) 2. If connect 2 or above streams, bitrate and frame rate will decrease. (Camera performance limitation)											
CDV-3VWD960	V1.0.16_F	H.264 M-JPEG	1	720x576	1-way	1/1	-	Yes	-	-	-	
CDV-3VWD960H		H.264 M-JPEG	1	720x576	1-way	1/1	-	Yes	-	-	-	Supported by design
CDV-4KM502	Refer to TCP-KM465(VK2.0.4.5 F)	H.264 MJPEG	1	2592x1520	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
CDV-4VM501	Refer to TCP-VM469(VH1.0.0_F)	H.264 MJPEG	1	2688x1520	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
CDV-4VM501Z42	Refer to TCP-VM469Z42(VH2.0.0.2)	H.264 MJPEG	1	2688x1520	1-way	1/1	Yes	Yes	Yes	-	Yes*	Supported by design
CDB-4VM551	Refer to TCP-VM469(VH1.0.0_F)	H.264 MJPEG	1	2688x1520	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps

Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
CDV-5VM501	Refer to TCP-VM559(VC2.0.26.6_F)	H.264 M-JPEG	1	2592x1944	1-way	1/1	-	Yes	Yes	-	Yes	
CDV-5VM501G	Refer to TCP-VM559G(VH2.0.0.6)	H.264 M-JPEG	1	2592x1944	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
CDV-5VM501Z3	VC2.0.26.4_F	H.264 M-JPEG	1	2592x1944	1-way	1/1	Yes	Yes	Yes	-	Yes*	
Note:	1. PTZ could only support zoom and autofocus.											
CDV-5VM501Z42	Refer to TCP-VM559Z42(VC2.0.26.6)	H.264 MJPEG	1	2592x1944	1-way	1/1	Yes	Yes	Yes	-	Yes*	Supported by design
CDB-5VM551G	Refer to TCP-VM559G(VH2.0.0.6)	H.264 M-JPEG	1	2592x1944	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
CDV-DT5	V6.08.25-NB	H.264 M-JPEG	1	2592x1944	1-way	-	-	Yes	Yes	-	Yes	
Note:	Fisheye camera with manual calibration in Crystal 1.Camera is unable to achieve maximum FPS. (Camera performance limitation) 2.Main console Flip/mirror checkbox not sync with Web interface. (NUUO server limitation)											
CDV-DT951R	Refer to CDV-DT5(V6.08.25-NB)	H.264 M-JPEG	1	2592x1944	1-way	-	-	Yes	Yes	-	Yes*	
CDV-MD602	refer to TCP-MZ602(VG1.0.14_F)	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
CDV-MD605	Refer to TCP-MZ602(VG1.0.14_F)	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
CDV-MFB2000D	2.03.17	H.264 MPEG4	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes	
Note:	1. Camera is unable to achieve maximum FPS. (Camera performance limitation) 2. The info. of stream profile display failure. (NUUO server limitation)											

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps

Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
CDV-MV1080F-H	refer to TCP-HDVB800-H(VE2.0.16.8 F)	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
CDV-P360	refer to TCP-MH802(1.0.4 6)	M-JPEG H.264	1	1600x1200	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
CDV-P360-5	VC2.0.26.4_F	H.264 M-JPEG	1	2592x1944	1-way	1/1	-	Yes	Yes	-	Yes*	
Note:	Fisheye camera with manual calibration in Crystal											
EDH-02H	V1.0.20_F	H.264 M-JPEG	1	720x480	1-way	1/1	Yes	Yes	-	-	-	
EP-201		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	Supported by design
EP-221		MPEG4 M-JPEG	1	720x480	1-way	1/0	Yes	Yes	-	-	-	Supported by design
EP-221DN		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	Supported by design
EP-601		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	Supported by design
EP-601HW		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	
EP-908		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	Supported by design
EP-908HW		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	Supported by design
EP-936		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	Supported by design
EP-936HW		MPEG4 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	Supported by design
EP-HTQ935	V3.2.56_F	MPEG4 M-JPEG	1	720x480	-	0/0	Yes	Yes	-	-	-	

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps
 Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
EP-Q2018H-IP		H.264 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	Supported by design
EP-Q2018HW-IP	V1.0.8_F	H.264 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	
EP-Q2026H-IP		H.264 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	Supported by design
EP-Q2026HW-IP		H.264 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	Supported by design
EP-Q2036H-IP		H.264 M-JPEG	1	720x480	1-way	0/0	Yes	Yes	-	-	-	Supported by design
EP-Q2036HW-IP	V1.0.46_F	H.264 M-JPEG	1	720x576	*2	*2	Yes	Yes	*2	-	Yes	
MD-D1200		MPEG4 M-JPEG	1	720x480	1-way	1/1	Yes	Yes	-	-	-	Supported by design
MD-D1322	V1.0.23.09_F	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	2/1	*1	Yes	Yes	-	Yes	
MD-D1612	V1.0.16_F	H.264 M-JPEG	1	720x576	1-way	1/1	Yes	Yes	-	-	-	
MD-D3622Q-H	VD1.0.12_04_F	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	Yes	-	Yes	
SP-HP2013C-IP	onvif_v2.4.2_20150327	M-JPEG H.264	1	1280x960	1-way	1/1	Yes*	Yes	-	Yes	Yes*	
Note:	1. DI & DO can't be used. (Camera Firmware issue) 2. Bitrate list and quality list may not be synchronized with camera web. (Onvif limitation) 3. 704x288 is not shown in the resolution list of the second stream. (Camera Firmware issue) 4. Auto focus is not supported. (Camera performance limitation) [IP+]5. Video parameter setting does not synchronize to camera web. (Camera Firmware issue) [NAS]6. Focus and PTZ speed setting are not supported. (NUUO server limitation) [NAS]7. The image of snapshot doesn't update via Snapshot to FTP function.(Camera Firmware issue)											
SP-HP2020C-IP	onvif_v2.4.0_20141027	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes*	Yes	-	Yes	Yes*	

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps
 Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
Note:	1. DI does not function. (Camera Firmware issue) 2. DO is unable to turn off. (Camera Firmware issue) 3. Bitrate list and quality list may not be synchronized with camera web. (Onvif limitation) 4. 704x288 is not shown in the resolution list of the second stream. (Camera Firmware issue) 5. Flip and mirror are not supported. (Onvif limitation) 6. Auto pan is not supported. (Onvif limitation) 7. Auto focus is not supported. (Camera performance limitation) 8. Hue setting is not supported. (Onvif limitation)											
SP-HP2020CM-IP	Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes*	Yes	-	Yes	Yes*	Supported by design
SP-HP2020Q-IP	Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes*	Yes	-	Yes	Yes*	Supported by design
SP-HP2030Q-IP	Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes*	Yes	-	Yes	Yes*	Supported by design
SP-HP2030C-IP	refer to SP-HP2330Q-IP(v2.3.1)	M-JPEG H.264	1	1920x1080	1-way	4/2	Yes	Yes	Yes	-	Yes	Supported by design
SP-HP2030CM-IP	Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes*	Yes	Yes	Yes	Yes*	Supported by design
SP-HP2313C-IP	Refer to SP-HP2013C-IP(onvif_v2.4.2_20150327)	M-JPEG H.264	1	1280x960	2-way	1/1	Yes*	Yes	-	Yes	Yes*	Supported by design
SP-HP2320C-IP	Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes*	Yes	-	Yes	Yes*	Supported by design
SP-HP2330C-IP	Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes*	Yes	-	Yes	Yes*	Supported by design

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps
 Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
SP-HP2330Q-IP	Refer to SP-HP2020C-IP(onvif_v2.4)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes*	Yes	-	Yes	Yes*	Supported by design
SP-HP2336Q-IP	Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes*	Yes	-	Yes	Yes*	Supported by design
SP-HP2620CP-IP	Refer to SP-HP2020C-IP(onvif_v2.4.0_20141027)	M-JPEG H.264	1	1920x1080	1-way	1/1	Yes*	Yes	-	Yes	Yes*	Supported by design
SP-HP4833-IP	A1D-500-V6.09.44-NB	M-JPEG H.264	1	2688x1520	1-way	4/2	Yes*	Yes	Yes	-	Yes*	
Note:	1.The camera with resolution 1920x1080 is unable to achieve 30 fps. (Camera performance limitation)											
SP-PTIR736A-IP	Refer to EP-Q2036HW-IP(V1.0.46_F)	H.264 M-JPEG	1	720x576	*2	*2	Yes	Yes	*2	-	Yes	Supported by design
SP-PTIR736B-IP	Refer to EP-Q2036HW-IP(V1.0.46_F)	H.264 M-JPEG	1	720x576	*2	*2	Yes	Yes	*2	-	Yes	Supported by design
SP-PTIR737-IP	V1.0.16_F	H.264 M-JPEG	1	720x576	1-way	0/0	Yes	Yes	-	-	-	
SP-PYIR737-LA-IP		H.264 M-JPEG	1	720x480	1-way	-	Yes	Yes	-	-	-	Supported by design
TCMA-99		MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	-	-	-	Supported by design
TCMP-99		MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	-	-	-	Supported by design
TCP-336AM	VB1.0.40_F	H.264 MPEG4 M-JPEG	1	2032x1536	1-way	1/1	-	Yes	Yes	-	Yes	
Note:	When format is set to MPEG4, resolution is 1920*180 and quality is excellent, the maximum FPS can only reach 20.											
TCP-1200AV	V1.0.26_F	H.264 M-JPEG	1	640x480	1-way	-	-	Yes	-	-	-	

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps

Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
TCP-1300AM	V1.0.26_F	H.264 M-JPEG	1	1280x1024	1-way	-	-	Yes	-	-	-	
TCP-2200AM	V1.0.30_F	H.264 MJPEG	1	1600x1200	1-way	-	-	-	Yes	-	Yes	
TCP-2200AM-H	refer to TCP-HDVB800-H(VE2.0.16.8_F)	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
TCP-2700AM	refer to CDB-720VIR-H(VE1.0.12.2_F)	H.264 MJPEG	1	1280x800	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
TCP-2700AM-W	refer to CDB-720VIR-H(VE2.0.14.4)	H.264 MJPEG	1	1280x800	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
TCP-2800AM	refer to TCP-HDVB800-H(VE2.0.16.8_F)	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
TCP-670DNU		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	-	-	Supported by design
TCP-680DNU		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	-	-	Supported by design
TCP-690		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	-	-	Supported by design
TCP-690DN		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	-	-	Supported by design
TCP-690U	V3.2.60_F	MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	-	-	
TCP-B365K	refer to TCP-HDVB800-H(VE2.0.16.8_F)	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps
 Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
TCP-BF108	Refer to TCP-HDVB720-H(VE2.0.20.8)	H264 MJPEG	1	1280x800	-	-	-	Yes	Yes	-	Yes*	Supported by design
TCP-BF128	Refer to TCP-HDVB720-H(VE2.0.20.8)	H264 MJPEG	1	1280x800	-	-	-	Yes	Yes	-	Yes*	Supported by design
TCP-BF1080	refer to TCP-HDVB800-H(VE2.0.16.8_F)	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
Note:	1. (Camera issue): FPS could not reach up to 20/30. 2. (Known issue): The info. of stream profile display failure											
TCP-BF208	Refer to TCP-HDVB180(VE1.0.20.6_F)	H.264 MJPEG	1	1920x1080	-	-	-	Yes	Yes	-	Yes*	Supported by design
TCP-BF728IR	refer to CDB-720VIR-H(VE2.0.14.2_F)	H.264 MJPEG	1	1280x800	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
TCP-BF828IR	refer to TCP-HDVB800-H(VE2.0.16.8_F)	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
TCP-HDVB110	Refer to TCP-HDVB720-H(VE2.0.20.8)	H264 MJPEG	1	1280x800	-	-	-	Yes	Yes	-	Yes*	Supported by design
TCP-HDVB180	VE1.0.20.6_F	H.264 MJPEG	1	1920x1080	-	-	-	Yes	Yes	-	Yes*	
TCP-HDVB720P	V1.0.20_F	H.264 MPEG4 M-JPEG	1	1280x800	-	1/1	-	Yes	Yes	-	Yes	
TCP-HDVB720-H	VE2.0.20.8	H264 MJPEG	1	1280x800	-	-	-	Yes	Yes	-	Yes*	
Note:	1.Setting FPS have problems(Camera Firmware issue), example: (1)Stream1 & Stream2 format : JPEG, when stream1's resolution decrease, stream2's fps would increase a little (2)Stream1 & Stream2 format : H264, stream2's fps can't reach our setting (3)When this camera's users more than 1, fps would decrease											

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps
 Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
TCP-HDVB800	VC1.0.18.2_F	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	-	Yes	-	Yes	
TCP-HDVB800-H	VE2.0.16.8_F	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	
Note:	1. Camera is unable to achieve maximum FPS.(Camera performance limitation) 2. Audio has noise.(Camera firmware issue) 3. Parameter setting will lead camera can't connect. (Camera firmware issue)											
TCP-HDVB800-H1	refer to TCP-HDVB800-H(VE2.0.16.8)	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
TCP-HDVB800Z3	VC2.0.24.2_F	H.264 MJPEG	1	1920x1080	1-way	1/1	Yes	Yes	Yes	-	Yes	
Note:	1. PTZ only support zoom.											
TCP-HDVB800Z4 2	Refer to CDV-3VM800Z42 (VE 1.0.20.2)	H.264 MJPEG	1	1920x1080	1-way	1/1	Yes	Yes	Yes	-	Yes*	Supported by design
TCP-HDVB801		H.264 MPEG4 M-JPEG	1	1920x1080	1-way	1/1	-	-	Yes	-	Yes	
TCP-HFB720	VB1.0.28_F	H.264 MPEG4 M-JPEG	1	1280x800	-	1/1	-	Yes	Yes	-	Yes	
TCP-HFB720-H	Refer to TCP-HDVB720-H(VE2.0.20.8)	H264 MJPEG	1	1280x800	-	-	-	Yes	Yes	-	Yes*	Supported by design
TCP-HFB1080D	2.03.10	H.264 MPEG4	1	1920x1080	-	-	-	Yes	*1	-	Yes	
Note:	1.The response of camera setting is slow.											

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps

Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
TCP-HP1080	VC1.0.06_F	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes	
TCP-HP1080-H	refer to TCP-HDVB800-H(VE2.0.16.8 F)	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
TCP-HP1080WI		H.264 MPEG4 M-JPEG	1	1920x1080	1-way	1/1	-	-	*1	-	Yes	
TCP-HP930		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	-	-	Supported by design
TCP-HP930U		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	-	-	Supported by design
TCP-HVB3100D	Refer to ACM-V3103(FW 2.03.23A)	H264 MPEG4	1	2048x1536	1-way	2/1	*2	Yes	Yes	-	Yes*	Supported by design
Note:	1.Frame rate can't meet the requirements.(Camera performance limitation) 2.Not support zoom and focus.											
TCP-HVB3105D	Refer to ACM-V3103(FW 2.03.23A)	H264 MPEG4	1	2048x1536	1-way	1/1	*2	Yes	Yes	-	Yes*	Supported by design
Note:	1.Frame rate can't meet the requirements.(Camera performance limitation)											
TCP-IPWD690		MPEG4 M-JPEG	1	720x480	1-way	2/2	-	Yes	-	-	-	Supported by design
TCP-IPWD700DN	V1.0.16_F	H.264 M-JPEG	1	720x576	1-way	1/1	-	Yes	-	-	-	

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps

Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
TCP-IR590-WD30	V1.0.20_F	H.264 M-JPEG	1	720x576	1-way	1/1	-	Yes	-	-	-	
TCP-IR590-WD50		H.264 M-JPEG	1	720x576	1-way	1/1	-	Yes	-	-	-	Supported by design
TCP-IRH5030C	refer to TCP-MH802(1.0.46)	M-JPEG H.264	1	1600x1200	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
TCP-IRH5040C	refer to TCP-MH802(1.0.46)	M-JPEG H.264	1	1600x1200	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
TCP-IRH5080-50	Refer to TCP-IRH5080-70(VC2.0.26.4_F)	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
TCP-IRH5080W-50	Refer to TCP-IRH5080-70(VC2.0.26.4)	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
TCP-IRH5080-70	VC2.0.26.4_F	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	
TCP-IRH5080W-70	Refer to TCP-IRH5080-70(VC2.0.26.4)	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
TCP-IRV540		MPEG4 M-JPEG	1	720x480	1-way	0/0	-	Yes	-	-	-	Supported by design
TCP-IRV560		MPEG4 M-JPEG	1	720x480	1-way	1/1	-	Yes	-	-	-	Supported by design
TCP-KM465	VK2.0.4.5_F	H.264 MJPEG	1	2592x1520	1-way	1/1	-	Yes	Yes	-	Yes*	
Note:	1. H265 was not supported(NUUO server limitation)											
TCP-KZ462	Refer to TCP-KM465(VK2.0.4.5_F)	H.264 MJPEG	1	2592x1520	1-way	1/1	-	Yes	Yes	-	Yes*	
TCP-M360K	refer to TCP-HDVB800-H(VE2.0.16.8F)	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps
 Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
TCP-M912DN	V1.2.28_F	MPEG4 M-JPEG	1	MPEG4: 640x480 M-JPEG: 1280x960	1-way	2/2	-	Yes	-	-	-	
TCP-MB602	refer to TCP-MZ602(VG1.0.14_F)	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
TCP-MB605	refer to TCP-MZ602(VG1.0.14_F)	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
TCP-MB685	refer to TCP-MZ602(VG1.0.14_F)	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
TCP-MH802	1.0.46	M-JPEG H.264	1	1600x1200	1-way	1/1	-	Yes	Yes	-	Yes	
Note:	1. Framerate may be incorrect displayed with MJPEG format. (Camera firmware issue) 2. Camera is unable to achieve maximum FPS. (Camera performance limitation)											
TCP-MH859	Refer to TCP-VM559(VC2.0.26.6_F)	H.264 M-JPEG	1	2592x1944	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
TCP-MZ602	VG1.0.14_F	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes	
Note:	Camera is unable to achieve maximum FPS. (Camera performance limitaion)											
TCP-MZ605	refer to TCP-MZ602 (FW: VG1.0.14)	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
TCP-VM201		MPEG4 M-JPEG	1	1280x1024	1-way	0/0	-	Yes	-	-	Yes	Supported by design
TCP-VM2210	3.0.0.8	H.264 M-JPEG MPEG4	1	1920x1080	1-way	1/0	Yes*	Yes	Yes	-	Yes*	

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps
 Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
Note:	1. Talk does not implement. (Camera Firmware issue) 2. Bitrate list does not sync with web. (Camera Firmware issue) 3. Camera with highest resolution is unable to achieve maximum FPS in MJPEG or MPEG4. (Camera performance limitation) 4. The bitrate list of stream3 does not sync with web (Camera Firmware issue) 5. PTZ speed does not sync with web. (Camera Firmware issue)											
TCP-VM359	VC1.0.16_F	H.264 M-JPEG	1	2048x1536	1-way	1/1	-	Yes	Yes	-	Yes	
TCP-VM469	VH1.0.0_F	H.264 / MJPEG	1	2688x1520	1-way	1/1	-	Yes	Yes	-	Yes*	
Note:	1. Resolution list & frame rate list may not sync with web.(Camera Firmware issue)											
TCP-VM469Z42	VH2.0.0.2	H.264 MJPEG	1	2688x1520	1-way	1/1	Yes	Yes	Yes	-	Yes*	
Note:	1. Camera is unable to achieve high FPS. (Camera performance limitation) 2. Sever resolution list is not same as web resolution list. (Camera Firmware issue)											
TCP-VM501	refer to TCP-MH802(1.0.4 6)	M-JPEG H.264	1	1600x1200	1-way	1/1	-	Yes	Yes	-	Yes	Supported by design
TCP-VM559	VC2.0.26.6_F	H.264 M-JPEG	1	2592x1944	1-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
TCP-VM559G	VH2.0.0.6_F	H.264 M-JPEG	1	2592x1944	1-way	1/1	-	Yes	Yes	-	Yes*	
Note:	1. Stream 2's bitrate list can not sync with web. (Camera Firmware issue) 2. G.726 can not be used. (Camera Firmware issue) 3. The camera with highest resolution is unable to achieve frame rate set value. (Camera performance limitation)											
TCP-VM559Z3	refer to CDV-5VM501Z3(V C2.0.26.4 F)	H.264 M-JPEG	1	2592x1944	1-way	1/1	Yes	Yes	Yes	-	Yes*	Supported by design
TCP-VM559Z42	VC2.0.26.6_F	H.264 MJPEG	1	2592x1944	1-way	1/1	Yes	Yes	Yes	-	Yes*	
WB-8211SD		MPEG4 M-JPEG	1	720x480	1-way	2/4	-	Yes	-	-	Yes	Supported by design
WB-8211SDU		MPEG4 M-JPEG	1	720x480	1-way	2/4	-	Yes	-	-	Yes	Supported by design
WB-8411		MPEG4 M-JPEG	4	720x480	1-way	4/1	-	Yes	-	-	Yes	Supported by design
WB-8412	V2.2.26_F	MPEG4 M-JPEG	4	688x448	1-way	4/4	Yes	Yes	-	-	Yes	

Fine



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps
 Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Multi Stream Support	Remarks
WB-H811	V1.0.44_F	M-JPEG H.264	1	720x576	1-way	2/2	Yes	Yes	Yes	-	Yes	
Note:	Resolution can't set to 4CIF.											
WB-H814	V1.0.82_F	H.264 M-JPEG	4	720x576	1-way	4/4	Yes	Yes	Yes	-	Yes	
Note:	1. Support dual mode only. (Camera firmware issue) 2. Resolution can not be set correctly. (Camera firmware issue)											