



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
ACD-3VM501	refer to ACDV-3VM501	H.264 M-JPEG	1	1600x1200	2-way *1	1/1 *1	-	-	-		-	Supported by design
Note: ACDV-3VM501 not support talk & DI/DO feature												
ACDV-3VM501	V1.0.26	H.264 M-JPEG	1	1600x1200	2-way *1	1/1 *1	-	-	-		-	Supported by design
AEP-Q2018H-IP	V1.0.26	H.264 M-JPEG	1	720x480	2-way	-	Yes	-	-		-	Supported by design
AEP-Q2018HW-IP	V1.0.26	H.264 M-JPEG	1	720x480	2-way	-	Yes	-	-		-	Supported by design
AEP-Q2026H-IP	V1.0.26	H.264 M-JPEG	1	720x480	2-way	-	Yes	-	-		-	Supported by design
AEP-Q2026HW-IP	V1.0.26	H.264 M-JPEG	1	720x480	2-way	-	Yes	-	-		-	Supported by design
AEP-Q2036H-IP	V1.0.26	H.264 M-JPEG	1	720x480	2-way	-	Yes	-	-		-	Supported by design
AEP-Q2036HW-IP	V1.0.26	H.264 M-JPEG	1	720x480	2-way	-	Yes	-	-		-	Tested by Manufacturer
ASP-PTIR737-IP	V1.0.26	H.264 M-JPEG	1	720x480	2-way	-	Yes	-	-		-	Supported by design
ASP-PTIR737-LA-IP	V1.0.26	H.264 M-JPEG	1	720x480	2-way	-	Yes	-	-		-	Supported by design
ATCP-IRH5030C	V1.0.26	H.264 M-JPEG	1	1600x1200	2-way	1/1	-	-	-		-	Supported by design
ATCP-IRH5040C	V1.0.26	H.264 M-JPEG	1	1600x1200	2-way	1/1	-	-	-		-	Supported by design
ATCP-MH802	V1.0.26	H.264 M-JPEG	1	1600x1200	2-way	1/1	-	-	-		-	Supported by design
ATCP-MH802DN	V1.0.26	H.264 M-JPEG	1	1600x1200	2-way	1/1	-	-	-		-	Supported by design
ATCP-MH802DN/WI	V1.0.26	H.264 M-JPEG	1	1600x1200	2-way	1/1	-	-	-		-	Supported by design
ATCP-MH802WI	V1.0.26	H.264 M-JPEG	1	1600x1200	2-way	1/1	-	-	-		-	Supported by design
ATCP-VM501	V1.0.26	H.264 M-JPEG	1	1600x1200	2-way	1/1	-	-	-		-	Supported by design
B0100	V1.0.1.14	H.264 M-JPEG	1	1280x800	2-way	1/1	-	-	-		-	Supported by design



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
B0202	V3.2.0.0	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	
B1100	V1.0.1.14	H.264 M-JPEG	1	1280x800	2-way	1/1	-	-	-	-	-	Supported by design
C1100	V1.0.1.14	H.264 M-JPEG	1	1280x800	2-way	-	-	-	-	-	-	Supported by design
C1100-W	V1.0.1.14	H.264 M-JPEG	1	1280x800	2-way	-	-	-	-	-	-	Supported by design
C2002	Refer to C2200	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
C2002-W	Refer to C2200-W	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
C2200	Refer to B0202(V3.2.0.0)	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
C2200-W	Refer to B0202(V3.2.0.0)	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
D0100	V1.0.1.14	H.264 M-JPEG	1	1280x800	2-way	-	-	-	-	-	-	Supported by design
D1100	V1.0.1.14	H.264 M-JPEG	1	1280x800	2-way	1/1	-	-	-	-	-	Supported by design
D2000-FD3	Refer to M4202-DB03	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
D2000-VD3	Refer to M4202-DB02	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
D2000-VP2	Refer to M7202-DB03	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
D2100	V1.0.1.14	H.264 M-JPEG	1	1280x800	2-way *1	1/1 *1	-	-	-	-	-	Tested by Manufacturer
Note:	D2100 not support talk & DI/DO feature											
FBU-200LWD	AgWT820012 2N06 V32 1401213F	H.264	1	1920x1080	2-way	0/1	Yes	Yes	Yes	-	Yes	
Note:	(Camera FW issue): Camera not support DI. (Camera FW issue): Camera snapshot function failed. (Known issue):It is probable that bitrate per second of low/minumun stream is unable to achieve 500bps/100bps under D1, SXGA resolution.											



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
FBU-201LWD	Refer to FBU-200LWD (FW AgWT820012 2N06 V32 1401213F)	H.264	1	1920x1080	2-way	0/1	Yes	Yes	Yes	-	Yes	Supported by design
FBU-300LWD	Refer to FVD-300LWD(Ag WT8300036N 06 V32 1401214F)	H.264	1	2048x1536	2-way	*2	Yes	Yes	Yes	-	Yes	Supported by design
FBU-301LWD	Refer to FVD-300LWD(Ag WT8300036N 06 V32 1401214F)	H.264	1	2048x1536	2-way	*2	Yes	Yes	Yes	-	Yes	Supported by design
FBS-1300 BX	AgWT813010 4N20_14052 82B	H.264	1	1280x1024	2-way	1/1	Yes	Yes	Yes	-	Yes	
FBS-1300BL	refer to FBS-1300BX(AgW T8130104N2 0_1405282B)	H.264	1	1280x1024	2-way	1/1	Yes	Yes	Yes	-	Yes	Supported by design
FBS-1300 ID	refer to FBS-1300BX(AgW T8130104N2 0_1405282B)	H.264	1	1280x1024	2-way	1/1	Yes	Yes	Yes	-	Yes	Supported by design
FBS-1300IDR	refer to FBS-1300BX(AgW T8130104N2 0_1405282B)	H.264	1	1280x1024	2-way	1/1	Yes	Yes	Yes	-	Yes	Supported by design
FBS-1300MID	refer to FBS-1300BX(AgW T8130104N2 0_1405282B)	H.264	1	1280x1024	2-way	1/1	Yes	Yes	Yes	-	Yes	Supported by design
FBS-1300MVD	refer to FBS-1300BX(AgW T8130104N2 0_1405282B)	H.264	1	1280x1024	2-way	1/1	Yes	Yes	Yes	-	Yes	Supported by design
FBS-1300VD	refer to FBS-1300BX(AgW T8130104N2 0_1405282B)	H.264	1	1280x1024	2-way	1/1	Yes	Yes	Yes	-	Yes	Supported by design
FBS-1300VDR	refer to FBS-1300BX(AgW T8130104N2 0_1405282B)	H.264	1	1280x1024	2-way	1/1	Yes	Yes	Yes	-	Yes	Supported by design
FBX-200		H.264 M-JPEG MPEG4	1	1920x1080	1-way	1/1	Yes	-	*1	-	-	Supported by design



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
FBX-200CL	Refer to FBU-200LWD (FW AgWT820012 2N06 V32 1401213F)	H.264	1	1920x1080	2-way	0/1	Yes	Yes	Yes	-	Yes	Supported by design
FBX-200LWD	Refer to FBU-200LWD (FW AgWT820012 2N06 V32 1401213F)	H.264	1	1920x1080	2-way	0/1	Yes	Yes	Yes	-	Yes	Supported by design
Note	1.Not support UPnP and auto detection. 2.Camera will crash if open camera web under winXP. 3.The setting of brightness was wrong via CGI command. It will sync setting of grayscale.											
FBX-300LWD	refer to FVD-300LWD(Ag WT8300036N 06 V32 1401214F)	H.264	1	2048x1536	2-way	*2	Yes	Yes	Yes	-	Yes	Supported by design
FBX-300WD		H.264 M-JPEG MPEG4	1	2048x1536	1-way	1/1	Yes	-	*1	-	-	Supported by design
FDM-200		H.264 M-JPEG MPEG4	1	1920x1080	1-way	1/1	Yes	-	*1	-	-	Supported by design
FDM-200LWD	Refer to FBU-200LWD (FW AgWT820012 2N06 V32 1401213F)	H.264	1	1920x1080	2-way	0/1	Yes	Yes	Yes	-	Yes	Supported by design
FDM-300LWD	Refer to FVD-300LWD(Ag WT8300036N 06 V32 1401214F)	H.264	1	2048x1536	2-way	*2	Yes	Yes	Yes	-	Yes	Supported by design
FVD-200		H.264 M-JPEG MPEG4	1	1920x1080	1-way	1/1	Yes	-	*1	-	-	Supported by design
FVD-200LWD	Refer to FBU-200LWD (FW AgWT820012 2N06 V32 1401213F)	H.264	1	1920x1080	2-way	0/1	Yes	Yes	Yes	-	Yes	Supported by design
FVD-200LWD	Refer to FBX-300WD	H.264 M-JPEG MPEG4	1	2048x1536	1-way	1/1	Yes	-	*1	-	-	Supported by design
FVD-300LWD	AgWT830003 6N06 V32 1401214F	H.264	1	2048x1536	2-way	*2	Yes	Yes	Yes	-	Yes	



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
Note:	(Camera FW issue) Camera replys no IO status. (Camera FW issue): Camera snapshot function failed. (Camera FW issue): FPS could not reach up to user setting by TCP protocol connection. (Known issue):It is probable that bitrate per second of low/minumun stream is unable to achieve 500bps/100bps under D1, SXGA, 3M resolution.											
FVD-300WD		H.264 M-JPEG MPEG4	1	2048x1536	1-way	1/1	Yes	-	*1	-	-	Supported by design
IPB-1080BL	Refer to IPD-1080CD (VC1.0.22.6_TG)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Supported by design
IPB-1080BM	Refer to IPD-1080CD (VC1.0.22.6)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Supported by design
IPB-1080E	VE1.0.14.18_TG	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	
Note:	1. Audio has noise. (Camera firmware issue)											
IPB-1080F	refer to IPB-1080E(VE1.0.14.18_TG)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Supported by design
IPB-1080F28	VE1.0.18.4_TG	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	
IPD-1080CD	VC1.0.22.6_TG	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	
IPD-1080E	refer to IPB-1080E(VE1.0.14.18_TG)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Supported by design
IPD-1080MF	refer to IPB-1080E(VE1.0.14.18_TG)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Supported by design
IPD-1080KF	refer to IPB-1080E(VE1.0.14.18_TG)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Supported by design
IPM-1080F	refer to IPB-1080E(VE1.0.14.18_TG)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Supported by design



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
IPM-1080RF	refer to IPB-1080E(VE1.0.14.18_TG)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Supported by design
IPT-1080F	refer to IPB-1080E(VE1.0.14.18_TG)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Supported by design
IPV-1080E	refer to IPB-1080E(VE1.0.14.18_TG)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Supported by design
IPV-1080CD	Refer to IPD-1080CD (VC1.0.22.6_TG)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Supported by design
IPV-1080F	refer to IPB-1080E(VE1.0.14.18_TG)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Supported by design
IPX-1080E	refer to IPB-1080E(VE1.0.14.18_TG)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Supported by design
IPX-1080DN	Refer to IPD-1080CD (VC1.0.22.6_TG)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes	Supported by design
IPB-1080WDR	refer to IPB-1080WDR(Forenix_rootfs_VG1.0.20_TG_20150129_101057)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
IPB-4065BM	VK1.0.6.0	H.264 H.265 MJPEG	1	2592x1520	2-way	1/1	-	Yes	Yes	-	Yes*	
Note:	1.The camera with highest quality and MJPEG format is unable to achieve 30 fps. (Camera performance issue)											
IPD-1080WDR	Forenix_rootfs_VG1.0.20_TG_20150129_101057	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	
Note:	1. Stream1 and stream2 framerate list is not as same as web. (Camera Firmware issue) 2. in 1080p HD 12bits 60fps(True WDR) mode, stream2 and stream3 can not connect, and can not get parameters.(Camera Firmware issue)											
IPV-1080WDR	Refer to IPD-1080WDR(Forenix_rootfs_VG1.0.20_TG_20150129	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Supported by design



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
IPX-1080WDR	Refer to IPD-1080WDR(Forenix_rootfs_VG1.0.20_TG20150129)	H.264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	Yes*	Supported by design
ISPD-2018	Refer to ISPD-2020(VC1.0.301204_TG)	H.264 MJPEG	1	1920x1080	2-way	4/1	Yes*	Yes	-	-	Yes*	Supported by design
ISPD-2020	VC1.0.301204_TG	H.264 MJPEG	1	1920x1080	2-way	4/1	Yes*	Yes	-	-	Yes*	
Note:	1.Not support Talk.(Camera Firmware issue) 2.Always trigger input-0 if alarm 1~4 has been triggered.(Camera Firmware issue) 3.Audio was broken with G.726.(Camera Firmware issue) 4.[NAS]Focus can't be used.(NUUO server limitation) 5.Not support camera search.(NUUO server limitation) 6.Not support auto detection.(NUUO server limitation)											
ISPDIII-3010	0.1.4960M	H.264 MJPEG	1	2048x1536	1-way	1/1	Yes	Yes	Yes	-	Yes*	
Note:	Fisheye camera 1. Fps and resolution list is not synchronized with the camera web due to onvif protocol mechanism. (Camera limitation issue) 2. Talk(audio out) are not supported due to there is no implementation mechanism from sdk document. (Camera issue)											
ISPD II-1312WD	AgWT8131312N20_1404185F	H.264	1	1280x1024	-	-	Yes	Yes	Yes	-	Yes	
Note:	1.Dual stream with main stream resolution SXGA, SXVGA, D1 is unable to achieve 500k/100k bps. (Camera performance limitation) 2. Camera with quality over 8192 is unable to achieve maximum FPS (Camera performance limitation) 3. Camera pan/tilt periodic moves per 30 seconds/2 minutes. After periodic moving, camera can't tilt for 1 minute.											
ISPD II-3018WD	AgWT8303018N20_1404185F	H.264	1	2048x1536	-	-	Yes	Yes	Yes	-	Yes	
Note:	1.Dual stream with main stream resolution 3M, SXGA, D1 is unable to achieve 500k/100k bps. (Camera performance limitation) 2.Camera with quality over 8192 is unable to achieve maximum FPS.(Camera firmware issue)											
M0202-BH01	Refer to B0202(V3.2.0.0)	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
M0202-BH02	Refer to B0202(V3.2.0.0)	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
M0202-BH03	Refer to B0202(V3.2.0.0)	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design



- : not available on camera
 *1: not available on software
 *2: not test on software

For multi stream support:
 Yes: multi stream fix to 500kbps/100kbps
 Yes*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
M4202-DB02	Refer to B0202(V3.2.0.0)	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
M4202-DB03	Refer to B0202(V3.2.0.0)	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
M7202-DB03	Refer to B0202(V3.2.0.0)	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
NPB-720	refer to NPB-720BM	H.264 M-JPEG MPEG4	1	1280x800	2-way *1	1/1	-	Yes	Yes	Yes	-	Supported by design
NPB-720A	refer to NPB-720BM	H.264 M-JPEG MPEG4	1	1280x800	2-way *1	1/1	-	Yes	Yes	Yes	-	Supported by design
NPB-720BM	VB1.0.26_TG	H.264 M-JPEG MPEG4	1	1280x800	2-way *1	1/1	-	Yes	-	-	-	
Note:	NPB-720BM dosen't support On-Edge Motion under TCP or UDP protocol, not support Talk.											
NPB-720U	refer to NPB-720BM	H.264 M-JPEG MPEG4	1	1280x800	2-way *1	1/1	-	Yes	Yes	Yes	-	Supported by design
NPD-720K	refer to NPB-720BM	H.264 M-JPEG MPEG4	1	1280x800	2-way *1	1/1	-	Yes	Yes	Yes	-	Supported by design
NPD-720R	refer to NPB-720BM	H.264 M-JPEG MPEG4	1	1280x800	2-way *1	1/1	-	Yes	Yes	Yes	-	Supported by design
T2000-FB1	Refer to M0202-BH01	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
T2000-FB2	Refer to M0202-BH02	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
T2000-VB3	Refer to M0202-BH03	H.264 M-JPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
VQ2100		MJPEG MPEG4 H.264	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
VQ2200		MJPEG MPEG4	1	1920x1080	1-way	-	-	Yes	Yes	-	-	Supported by design
VQ2210C		MJPEG MPEG4 H.264	1	1920x1080	2-way	1/1	Yes	Yes	Yes	-	-	Supported by design
VQ2300		MJPEG MPEG4	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
VQ2310		MJPEG MPEG4 H.264	1	1920x1080	2-way	1/1	Yes	Yes	Yes	-	-	Supported by design

All Forenix model can't be searched & AutoDetected (camera FW issue)