



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
SCC-C6475	2	MPEG4 M-JPEG	1	704x480	-	-	Yes	-	-	-	-	
SNB-1000	1.07_110407	H.264 MPEG4 M-JPEG	1	640x480	-	1/1	-	-	-	-	-	
SNB-1001	1.00_111226	H.264 M-JPEG	1	640x480	2-way	1/0	-	Yes	-	-	-	Test by link
SNB-2000		H.264 MPEG4 M-JPEG	1	720x576	-	2/2	-	-	-	-	-	Supported by design
SNB-3000		H.264 MPEG4 M-JPEG	1	720x576	2-way	2/2	-	-	-	-	-	Supported by design
SNB-3002	2.10_130416 refer to SND-3082/F	H.264 MPEG4 M-JPEG	1	704x576(PAL) 704x480(NTSC)	2-way	1/1	-	Yes	-	-	-	Supported by design
SNB-5000	v1.33_110218	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	Yes	-	-	-	
SNB-5000A	3.10_130416 refer to SND5080/F	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	Yes	-	-	-	Supported by design
SNB-5001	1.00_120521	H.264 M-JPEG	1	1280x1024	-	1/0	-	Yes	-	-	-	
SNB-5003	1.12_131031	H264 MJPEG	1	1280x1024	*2	*2	*2	Yes	*2	-	Yes*	Test by link
SNB-5004	1.12_131031	H264 MJPEG	1	1280x1024	2-way	1/1	Yes	Yes	Yes	-	Yes*	
Note:	For SNB-5003, SNB-5004, SND-5083, SND-5084 and SNV-5084: 1. Camera can support 128 preset points, but we are only support 64 preset points. 2. Before starting "talk", we do check that the talk's gain is greater than zero. If it is 0, we are going to adjust gain to default value 5. 3. If user do change audio setting in the website, then the previous connection will be interrupted and re-connect.											
SNB-6003	1.00_130412 refer to SND-6083	H264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
SNB-6004	refer to SND-6084(SNV-6084R-V3.01_140804)	H264 MJPEG	1	1920x1080	*2	*2	Yes	Yes	*2	-	Yes*	Supported by design
SND-6011R	1.11_131011	H.264 M-JPEG	1	1920x1080	-	*2	-	Yes	*2	-	Yes*	
SNB-7000	1.10_110819	H.264 MPEG4 M-JPEG	1	2048x1536	2-way	1/1	-	-	-	-	-	Tested by link



- : not available on camera

\*1: not available on software

\*2: not test on software

For multi stream support:

Yes: multi stream fix to 500kbps/100kbps

Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
<b>SNB-7001</b>	Refer to SND-7011	H.264 M-JPEG	1	2048x1536	-	1/0	-	Yes	-	-	-	Supported by design
<b>SNB-7002</b>	1.06_130402	H.264 M-JPEG	1	2048x1536	2-way	1/1	-	Yes	-	-	-	
<b>SNC-B2315</b>	2.11	MPEG4 M-JPEG	1	720x576	2-way	2/2	-	Yes	-	-	-	
<b>SNC-B2331</b>	1.00	H.264 MPEG4 M-JPEG	1	720x576	-	2/2	-	Yes	-	-	-	
<b>SNC-B2335</b>	1.01	H.264 MPEG4 M-JPEG	1	720x576	2-way	2/2	-	Yes	-	-	-	
<b>SNC-B5368</b>	1.00	H.264 MPEG4 M-JPEG	1	720x576	-	2/2	-	Yes	-	-	-	
<b>SNC-B5395</b>	2.10	MPEG4 M-JPEG	1	720x576	2-way	2/2	-	Yes	-	-	-	
<b>SNC-B5399</b>	1.01	H.264 MPEG4 M-JPEG	1	720x576	2-way	2/2	-	Yes	-	-	-	
<b>SNC-C6225</b>	1.01	MPEG4 M-JPEG	1	720x576	2-way	2/1	Yes	Yes	-	Yes	-	
<b>SNC-C7225</b>	1.01	MPEG4 M-JPEG	1	720x576	2-way	2/1	Yes	Yes	-	Yes	-	
<b>SNC-C7478</b>	v1.01_090625	MPEG4 M-JPEG	1	720x576	2-way	8/4	Yes	Yes	-	Yes	-	
<b>SNC-M300</b>	v2.11_090729	MPEG4 M-JPEG	1	2048x1536	2-way	2/2	-	Yes	-	-	-	
<b>SND-1011</b>	1.00_111226	H.264 M-JPEG	1	640x480	-	1/0	-	Yes	-	-	-	Test by link
<b>SND-1080</b>	1.00_111226	H.264 M-JPEG	1	640x480	2-way	1/0	-	Yes	-	-	-	Test by link
<b>SND-3080</b>		H.264 MPEG4 M-JPEG	1	720x576	-	2/2	-	-	-	-	-	Supported by design
<b>SND-3082</b>	refer to SND-3082/F (FW2.10_130416)	H.264 MPEG4 M-JPEG	1	704x576(PAL) 704x480(NTSC)	2-way	1/1	-	Yes	-	-	-	Supported by design
<b>SND-3082/F</b>	2.10_130416	H.264 MPEG4 M-JPEG	1	704x576(PAL) 704x480(NTSC)	2-way	1/1	-	Yes	-	-	-	
<b>SND-5010</b>	1.00_120626	H.264 M-JPEG	1	1280*1024	-	0/0	-	Yes	-	-	-	



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
SND-5011	1.00_120521	H.264 M-JPEG	1	1280x1024	-	1/0	-	Yes	-	-	-	
SND-5061	1.00_120521	H.264 M-JPEG	1	1280x1024	-	1/0	-	Yes	-	-	-	
SND-5080/F	3.10_130416	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	Yes	-	-	-	
SND-5083	1.12_131031 refer to SNB-5003	H264 MJPEG	1	1280x1024	2-way	1/1	Yes	Yes	Yes	-	Yes*	Supported by design
SND-5084	1.12_131031 refer to SNB-5004	H264 MJPEG	1	1280x1024	2-way	1/1	Yes	Yes	Yes	-	Yes*	Supported by design
SND-6083	1.00_130412	H264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	
SND-6084	SNV-6084R-V3.01_140804	H264 MJPEG	1	1920x1080	*2	*2	Yes	*2	*2	-	Yes*	
Note:	1. When camera using higher quality and resolution, it is unable to achieve 30 fps (Camera performance issue)											
SND-6084R	1.00_130316 refer to SNB-6004	H264 MJPEG	1	1920x1080	*2	*2	Yes	*2	*2	-	Yes*	Supported by design
SND-7080	2.00_110727	H.264 M-JPEG	1	2048x1536	2-way	1/1	-	-	-	-	-	
SNF-7010	1.00_130806	H264 MJPEG	1	2048x1536	2-way	-	-	Yes	Yes	-	-	
Note:	Fisheye camera											
SND-7011	1.00_120601	H.264 M-JPEG	1	2048x1536	-	1/0	-	Yes	-	-	-	
SND-7061	Refer to SND-7011	H.264 M-JPEG	1	2048x1536	-	1/0	-	Yes	-	-	-	Supported by design
SND-7082	1.00_120824	H.264 M-JPEG	1	2048x1536	2-way	1/1	-	Yes	-	-	-	
SND-7082/F	refer to SNB-7002	H.264 M-JPEG	1	2048x1536	2-way	1/1	-	Yes	-	-	-	Supported by design
SNF-8010	1.00_140719	H.264 M-JPEG	1	2560x2048	*2(2-way)	*2	-	*2	*2	-	Yes*	
Note:	1. The list of camera's stream 2 and stream 3 frame rate is not synchronized with the one on camera's web.(Camera Firmware issue) 2.To get OSD correct value need to reconnect by manual to connect the correct stream after parameters setting.(Camera Firmware issue)											
SNO-1080R	1.00_120125	H.264 M-JPEG	1	640x480	-	1/0	-	Yes	-	-	-	Test by link



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
SNO-5080R	3.10_130416	H.264 MPEG4 M-JPEG	1	1280x1024	-	1/1	-	Yes	-	-	-	
SNO-6011R	refer to SND-6011R(1.11_131011)	H.264 M-JPEG	1	1920x1080	-	*2	-	Yes	*2	-	Yes*	Supported by design
SNO-L6083R	1.00_150403	H.264 M-JPEG	1	1920x1080	*2	-	-	*2	*2	-	Yes*	
Note:	1. Frame rate list does not sync with web. (Camera Firmware issue)											
SNO-6084	refer to SND-6083	H264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
SNO-6084R	1.00_130316 refer to SNB-6004	H264 MJPEG	1	1920x1080	*2	*2	Yes	*2	*2	-	Yes*	Supported by design
SNO-7080R	2.00_121004	H.264 MJPEG	1	2048x1536	*2	*2	Yes	Yes	*2	-	Yes*	
SNO-7082R	refer to SNB-7002	H.264 M-JPEG	1	2048x1536	2-way	1/1	-	Yes	-	-	-	Supported by design
SNP-3120V	1.24_110816	H.264 MPEG4 M-JPEG	1	704x480	1-way	2/2	Yes	-	-	-	-	
SNP-3300A	2.8.4	MPEG4 M-JPEG	1	D1	-	-	-	-	-	-	-	
SNP-3301	1.21_110310	H.264 MPEG4 M-JPEG	1	4CIF	2-way	4/2	Yes	-	-	-	-	Tested by link
SNP-3302/H	Refer to SNP-3371/H/TH	H.264 MPEG4 M-JPEG	1	704x480	2-way	4/2	Yes	Yes	-	-	-	
SNP-3370	1.21_110310	H.264 MPEG4 M-JPEG	1	4CIF	2-way	4/2	Yes	-	-	-	-	
Note:	SNP-3301, SNP-3370: H264 can't support QCIF resolution											
SNP-3371/H/TH	S/W : 1.01_111104 ISP : 1.28	H.264 MPEG4 M-JPEG	1	704x480	2-way	4/2	Yes	Yes	-	-	-	Test by link
SNP-3430H	1.10_110818	H.264 MPEG4 M-JPEG	1	704x480	2-way	8/4	Yes	-	-	-	-	
SNP-5200	Refer to SNP-5200H	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	4/2	Yes	-	-	-	-	
SNP-5200H	1.04_110825	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	4/2	Yes	-	-	-	-	
SNP-5300	1.10_130523	H.264 M-JPEG	1	1280x1024	*2	*2	Yes	Yes	-	-	-	



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
SNP-6200	V1.00_120302	H.264 M-JPEG	1	1920x1080	2-way	4/2	Yes	Yes	-	-	-	
SNP-6200H	refer to SNP-6200	H.264 M-JPEG	1	1920x1080	2-way	4/2	Yes	Yes	-	-	-	Supported by design
SNP-6200HP	refer to SNP-6200	H.264 M-JPEG	1	1920x1080	2-way	4/2	Yes	Yes	-	-	-	Supported by design
SNP-6200P	refer to SNP-6200	H.264 M-JPEG	1	1920x1080	2-way	4/2	Yes	Yes	-	-	-	Supported by design
SNP-6200RH	3.02_140722	H.264 M-JPEG	1	1920x1080	2-way	4/2	Yes	Yes	Yes	-	Yes*	
Note:	Camera is unable to achieve maximum FPS with high quality / bitrate. (Camera performance limitation)											
SNP-6320H	1.01_141007	H.264 M-JPEG	1	1920x1080	2-way	4/2	Yes	Yes	*2	-	Yes*	
SNS-100	100331-v2.8.9-2	MPEG4 M-JPEG	1	704x480	1-way	2/2	Yes	-	-	-	-	
SNV-1080	Refer to SNO-1080R	H.264 M-JPEG	1	640x480	2-way	1/0	-	Yes	-	-	-	Supported by design
SNV-1080R	Refer to SNO-1080R	H.264 M-JPEG	1	640x480	2-way	1/0	-	Yes	-	-	-	Supported by design
SNV-3120	1.24_10816	H.264 MPEG4 M-JPEG	1	704x576	1-way	0/0	Yes	-	-	-	-	
Note:	SNV-3120: PTZ function only supports zoom and focus.											
SNV-3080		H.264 MPEG4 M-JPEG	1	720x576	2-way	2/2	-	-	-	-	-	Supported by design
Note:	Please uncheck the "RTSP time out" first.											
SNV-3082	refer to SNB-3002	H.264 MPEG4 M-JPEG	1	704x576(PAL) 704x480(NTSC)	2-way	1/1	-	Yes	-	-	-	Supported by design
SNV-5010	2.00_110727	H.264 MPEG4 M-JPEG	1	1280x1024	-	0/0	-	-	-	-	-	
SNV-5080	refer to SND-5080/F	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	Yes	-	-	-	Supported by design
SNV-5080R	3.10_130416	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	-	Yes	-	-	-	
SNV-5084	1.12_131031 refer to SNB-5004	H264 MJPEG	1	1280x1024	2-way	1/1	Yes	Yes	Yes	-	Yes	Supported by design
SNV-6012M	1.00_130704	H264 MJPEG	1	1920x1080	-	*2	-	*2	*2	-	Yes*	



- : not available on camera  
 \*1: not available on software  
 \*2: not test on software

For multi stream support:  
 Yes: multi stream fix to 500kbps/100kbps  
 Yes\*: multi stream setting support

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Auto Pan	Multi Stream Support	Remarks
<b>SNV-6084</b>	refere to SND-6083	H264 MJPEG	1	1920x1080	2-way	1/1	-	Yes	Yes	-	-	Supported by design
<b>SNV-6084R</b>	1.00_130316 refer to SNB-6004	H264 MJPEG	1	1920x1080	*2	*2	Yes	*2	*2	-	Yes*	Supported by design
<b>SNV-7080</b>	1.10_110819	H.264 M-JPEG	1	2048x1536	2-way	1/1	-	-	-	-	-	Tested by link
Note:	SNV-7080R compatable with SNV-7080											
<b>SNV-7080R</b>	2.00_121004	H.264 MJPEG	1	2048x1536	*2	*2	Yes	Yes	*2	-	Yes*	
<b>SNV-7082</b>	refer to SNB-7002	H.264 M-JPEG	1	2048x1536	2-way	1/1	-	Yes	-	-	-	Supported by design
<b>SNZ-5200</b>	1.04_110825	H.264 MPEG4 M-JPEG	1	1280x1024	2-way	1/1	Yes	-	-	-	-	
<b>SPE-100</b>	v1.19_110317_3	M-JPEG, MPEG4, H264	1	704x576	2-way	1/1	Yes	Yes	-	-	-	
<b>SPE-400</b>	S/W : 1.40_120201	H.264 MPEG4 M-JPEG	4	704x480	2-way	4/4	Yes	Yes	-	-	-	Test by link
Note:	<p>SNB-5000, SNV-3120, SND-5080/F, SNV-5080: do not support I/O, talk and TCP protocol.</p> <p>SNB-7000, SND-7080, SNP-3120V, SNP-3301, SNP-3370, SNP-3430H, SNP-5200, SNV-5080R, SNZ-5200 : do not support talk.</p> <p>SPE-400 video server needs to connect to 4 IP addresses to get 4 ch video.</p> <p>For Samsung SNB-7002, SNV-7082, SND7082/F and SNO-7082R, when Frame rate sets to 1, there is no image via RTSP.</p> <p>For Samsung SND-3082, SND-3082/F and SNB-3002, video parameter: brightness doesn't work.</p> <p>For Samsung SNB-7002, SNV-7082, SND7082/F and SNO-7082R, resolution sets to 800*450 &amp; 320*180, but actually 800*448 &amp; 320*176.</p>											