



Main Features

- Support up to 64 channels
- Support megapixel IP camera
- Support H.264 compression format
- Triple monitor display
- Support Joystick
- E-map
- Unique GUI recording schedule
- Digital PTZ and multi-view
- Smart detection of 6 events with 10 instant responses
- Counting application
- Intelligent playback system with 5 video analytics searches
- POS and I/O device integration
- Remote live viewer, remote playback, remote backup, remote I/O control and remote desktop configuration
- Supported by NUUO Central Management System
- Supports 36 brands of IP cameras and more than 560 models
- Supports 28 languages

Specifications

System, setting, management and integration:

- **Open Platform:** Supports over 560 IP cameras, megapixel cameras and video servers from 36 brands of network camera manufacturers; supports H.264, MPEG-4, MJPEG, MxPEG video formats; integrates various systems including point of sale (POS) and I/O device, as well as provides you SDK to integrate access control.

- **Multi-site/Multi-server:** Each NVR server supports up to 64 channels, from IP cameras and video encoders with analog cameras, and can be managed by NUUO CMS or remote live view client for centralized management in multi-site projects.
- **Multiple Video Clients:** NUUO NVR server can stream video to multiple Remote Live Viewers, web clients and mobile clients simultaneously.
- **Intelligent Video Analytics:** NUUO IVS supports 6 types of video analytics including general motion, missing object, camera occlusion, foreign object, focus lost and signal lost. Each IVS alarm can trigger up to 10 unique instant notifications.
- **Intelligent PTZ:** Joystick support on PTZ cameras and software enabled digital PTZ function are both available in NUUO NVR. Preset points and patrol functions are also available on many camera models.
- **GUI Recording Schedule:** Intuitive GUI recording schedule featuring continuous recording, motion recording and the 6 unique event recording modes. User can define the recording schedule for each camera on a day by day basis.
- **Triple Monitor:** Up to 64 channels of live view video can be displayed per monitor. Monitor 1 and monitor 2 can both display live view video or act as alarm monitor while the 3rd monitor can be used for playback
- **Transcoding:** Record and live display at different frame rate and resolution.
- **Advance E-Map:** Freedom to import custom image file, place the cameras and I/O on the map to indicate where events are getting triggered with a convenient video preview window.
- **User-Friendly Interface:** GUI recording schedule, camera drag and drop, I/O control menu and PTZ control menu.
- **Automatic Camera Model Detection:** automatically search for all of the IP cameras in the network (camera must support UPnP protocol). For cameras that don't support UPnP, user can manually insert the IP camera. The auto detection function will help the user to find the brand and model of the camera after specifying its IP address.
- **Counting Application:** intelligent 2-way (in and out) counting of object, people and traffic.
- **User Authority Management:** Support unlimited number of users with detailed and fully customizable user privilege on each user.
- **Network Flow Monitor:** The data streaming bandwidth of each remote client connection to the NVR server can be monitored and blocked if flow rate is too high.
- **Auto Recycle:** Automatically recycle recording files when the storage is full. Separate recycle schedule between recordings and varies log files.
- **Integration Support:** Open SDK for integration with third-party systems such as access control, automation, burglar alarm, video analytics and others.

Live Display:

- **Multi-view:** NUUO NVR can duplicate the same live view video onto multiple channels and digitally zone in to see the details of different spots on cloned channels without losing the original live view video.
- **Intelligent PTZ:** Joystick support on PTZ cameras and software enabled digital PTZ function are both available in

NUUO NVR. Preset points and patrol functions are also available on many camera models.

- **Monitor Resolution:** Supports 1024x768, 1200x900, 1280x1024, and 1600x1200 screen resolutions
- **Advanced E-Map:** Freedom to import custom image file, place the cameras and I/O on the map to indicate where events are getting triggered with a convenient video preview window.
- **Bandwidth Monitor:** Monitor and display the bandwidth usage of individual cameras and remote viewing clients.
- **Two-way Audio:** Listen and record audio from camera's microphone. Talk to IP camera's speaker.

Playback, Search, Export and Secure data:

- **Post-Recording Processing:** Search for 5 types of different analytics events, digital PTZ and video enhancement tool are all available in playback.
- **Multi-Channel Playback:** Play up to 16 channels of recorded video simultaneously both locally and remotely.
- **Video Enhancement:** Fine tune the image's visibility, sharpen, brightness, contrast or even grey scale.
- **Intelligent Search:** Search for 5 different special events (general motion, missing object, foreign object, camera occlusion and signal lost) in recorded files with date, time and log file.
- **Video Export:** Take a snapshot of the recording in JPEG/BMP format or export a section of the video in "AVI" and "ASF" format.
- **Backup:** Backup the recording for archiving purposes or backup the recording with an embedded player to watch at a separate location. NVR supports both local and remote backup to local HD, network drive, CD, and DVD.
- **Log data:** Unusual event, system log, counting application, POS log and export and backup can export to "xls" or "txt" file
- **Watermark:** Protect for original recording from alternation with our watermark verification tool.
- **DBTool:** Reconstruct, repair or relocate the recordings in local drive, external drive or network drive.

Remote operations:

- **Multiple Live View Display:** Streaming live video from multiple NUUO servers (NVR, DVR, and NDVR) simultaneously. Dual monitors support with up to 128 channels per monitor (64 channels per monitor in v3.2.0).
- **Multi Playback Channels Display:** Remote playback of 16 channels recording from any one of the NUUO servers (NVR, DVR, and NDVR).
- **Intelligent PTZ:** Joystick support on PTZ cameras and software enabled digital PTZ function are both available in NUUO NVR. Preset points and patrol functions are also available on many camera models.
- **I/O Event Control:** Easy to use input and output control panel to remotely trigger digital outputs and monitor input status.
- **E-Map:** A map view of where each camera and I/O devices are located with a convenient preview window.

- **Remote Backup:** Backup the video into .DAT format with a NUUO player attached for easy achieve and viewing purposes.
- **Web-browser (client):** Display up to 16 channels of live video stream or 16 channels of playback in I.E. from any single NUUO server.
- **PDA Viewer:** Up to 16 channels snapshot or 1 channel live display; PTZ and I/O control.

Extension Service

- **Central Management System:** Ultimate central monitoring solution for grand scale projects and projects with multiple sites. Fully compatible with all NUUO servers (NVR, DVR, NDVR and NVRmini).
- **Remote Desktop Service:** Embedded remote desktop server that will host for any NUUO remote desktop clients to remotely configure the NVR software (remote desktop client is installed separately).
- **3GPP Service:** NUUO NVR supports mobile devices through 3G network to stream live view video.

External Device

- **Point of Sale (POS):** NUUO Point of Sales system works on NUUO NVR by overlaying the transaction text from cash register onto live video channels. All POS recordings are searchable.
- **External I/O capacity:** Please refer to our I/O box section: C24/C26/C28 for more details.

Smart Guard:

- **Smart detection** of 6 camera events, 14 different user-defined POS events, digital input events and 4 system events. The combination of our smart guard events is a powerful tool to combat vandalism and provide a platform for operators to monitor and respond to live events immediately.
 - Camera Events:
 - General Motion
 - Missing Object
 - Foreign Object
 - Focus Lost
 - Camera Occlusion
 - Signal Lost
 - Signal Digital Input Event
 - System Event:
 - System alarm on Disk Space Exhausted
 - System alarm on System Health Unusual (CPU temperature)
 - System alarm on Resource Depleted (CPU loading)
 - System alarm on Network Congestion
- **Instant alarm notification** is the fastest and most cost efficient way to automatically respond to any smart detection event.
 - 10 automatic instant alarm responses:
 - On Screen Display
 - Play Sound
 - Send E-mail

NUUO NVR Specification

NUUO 3.2 version

- Phone Call
- PTZ Preset Go
- Signal Digital Output
- Send a SMS message
- Send to Central Server
- Send Snapshot to FTP
- Popup E-Map on Event

Specifications					
Model	SCB-IP+ Series				
IP Camera Input(s)	4,8,12,16,25,32,36,64				
Version	3.2.21				
IP Camera Brand(s) Supported	ACTi	Arecont	Atlantis	Axis	Basler
	Cisco	Digimerge	D-Link	Dynacolor	Etrovision
	EverFocus	Eyeview	Fine	HIKVision	Hitron
	Icantek	IQinvision	JVC	LevelOne	Linksys
	Loxex	Lumenera	Mobotix	Moxa	Panasonic(PCC)
	Panasonic(PSS)	Pixord	Planet	Samsung	Sanyo
	Seorim	Sony	Toshiba	Truen	Vivotek
	Y-cam	Zavio			
Digital PTZ	Supported in Live view and playback				
Multiple Show	Supported in Live view				
Triple Monitor	Enable maximum 64 channels with two screens to show live video and viewer recording video on third monitor.				
Audio & Video Recording	Audio & video recording in synchronization.				
Screen Division	1/4/6/9/10/13/16/25/36/49/64 divided screen.				
Compression Format	MPEG-4;M-JPEG;MxPEG;H.264				
Recording Type	Continuous record, record by digital input, motion record, event recording, record by schedule, manual record				
Playback Channels	Playback Maximum 16 channels under several modes & full screen.				
Playback Control	Playback, backward playback, fast forward/backward playback.				
Auto Recycling Recording	Auto recycling when storage disk is full.				
Available I/O Function	Supporting I/O Box				
Available POS Device	SCB-C31 RS232 to Ethernet Converter				
Hardware Watchdog	N/A				
System Minimum Requirements					
OS Supported	Windows XP / Windows 2003/ Windows Vista				
CPU	Pentium 4 – 2.8 GHz				
RAM	512 MB				
HDD	80 GB				
Mother-board	Intel 945 or 965 chip, Intel Chipset recommended				
Display	ATI Radeon 9200, nVIDIA GeForce FX-5200, Intel 945 / 965, or above (ATI recommended)				
Support Language					
Bulgaria	Chinese (Simplified)	Chinese (Traditional)	Czech		
Danish	English	Farsi	Finnish		
French	German	Greek	Hebrew		
Hungarian	Italian	Japanese	Korean		
Norway	Polish	Portuguese(Brazil)	Portuguese(Portugal)		
Romanian	Russian	Serbia	Slovak		
Spanish	Swedish	Thai	Turkey		

NUUO NVR Specification

NUUO 3.2 version

