

## SCB-IP+ Series



### Main Features

- Support up to 64\* channels
- Support megapixel IP camera
- Support H.264 compression format
- Triple monitor display
- Support Joystick
- E-map
- Instant Playback
- Unique GUI recording schedule
- Digital PTZ and multi-view
- Smart detection of 6 events with 10 instant responses
- Counting application
- Intelligent playback system with 5 video analytics searches
- POS and I/O device integration
- Up to 128\*\*CH remote live view
- Support transcode and multiple stream profile
- Support digital watermark
- Remote playback, remote backup, remote I/O control and remote desktop configuration
- Supported by NUUO Central Management System
- Supports 42 brands of IP cameras and more than 800 models
- Supports 30 languages
- Supports mobile client and I-phone browser

\* The maximum number of camera connections depends on the server's hardware configuration and the total bit rate of the IP cameras. Please check NUUO Calculator on <http://support.nuuo.com/calculator/>

\* \*The maximum number of camera connections depends on the server's and client's hardware configuration.

## Specifications

### System, setting, management and integration:

- **Open Platform:** Supports over 800 IP cameras, megapixel cameras and video servers from 42 brands of network camera manufacturers; supports H.264, MPEG-4, MJPEG, MxPEG video formats; integrates various systems including point of sale (POS) and I/O device, as well as provides you SDK to integrate access control.
- **Multi-site/Multi-server:** Each NVR server supports up to 64\* channels, from IP cameras and video encoders with analog cameras, and can be managed by NUUO CMS or remote live view client for centralized management in multi-site projects.  
\* The maximum number of camera connections depends on the server's hardware configuration and the total bit rate of the IP cameras. Please check NUUO Calculator on <http://support.nuuo.com/calculator/>
- **Multiple Video Clients:** NUUO NVR server can stream video to multiple Remote Live Viewers, web clients and mobile clients simultaneously.
- **Intelligent Video Analytics:** NUUO IVS supports 6 types of video analytics including general motion, missing object, camera occlusion, foreign object, focus lost and signal lost. Each IVS alarm can trigger up to 10 unique instant notifications.
- **Intelligent PTZ:** Joystick support on PTZ cameras and software enabled digital PTZ function are both available in NUUO NVR. Preset points and patrol functions are also available on many camera models.
- **GUI Recording Schedule:** Intuitive GUI recording schedule featuring continuous recording, motion recording and the 6 unique event recording modes. User can define the recording schedule for each camera on a day by day basis.
- **Triple Monitor:** Up to 64\* channels of live view video can be displayed per monitor. Monitor 1 and monitor 2 can both display live view video or act as alarm monitor while the 3<sup>rd</sup> monitor can be used for playback  
\* The maximum number of camera connections depends on the server's hardware configuration and the total bit rate of the IP cameras. Please check NUUO Calculator on <http://support.nuuo.com/calculator/>
- **Transcoding:** Record and live display at different frame rate and resolution.
- **Advance E-Map:** Freedom to import custom image file, place the cameras and I/O on the map to indicate where events are getting triggered with a convenient video preview window.
- **User-Friendly Interface:** GUI recording schedule, camera drag and drop, I/O control menu and PTZ control menu.
- **Automatic Camera Model Detection:** automatically search for all of the IP cameras in the network (camera must support UPnP protocol). For cameras that don't support UPnP, user can manually insert the IP camera. The auto detection function will help the user to find the brand and model of the camera after specifying its IP address.
- **Counting Application:** intelligent 2-way (in and out) counting of object, people and traffic.
- **User Authority Management:** Support unlimited number of users with detailed and fully customizable user privilege on each user.
- **Network Flow Monitor:** The data streaming bandwidth of each remote client connection to the NVR server can be monitored and blocked if flow rate is too high.
- **Auto Recycle:** Automatically recycle recording files when the storage is full. Separate recycle schedule between recordings and varies log files.

- **Integration Support:** Open SDK for integration with third-party systems such as access control, automation, burglar alarm, video analytics and others.

## Live Display:

- **Multi-view:** NUUO NVR can duplicate the same live view video onto multiple channels and digitally zone in to see the details of different spots on cloned channels without losing the original live view video.
- **Intelligent PTZ:** Joystick support on PTZ cameras and software enabled digital PTZ function are both available in NUUO NVR. Preset points and patrol functions are also available on many camera models.
- **Monitor Resolution:** Supports 1024x768, 1200x900, 1280x1024, and 1600x1200 screen resolutions
- **Advanced E-Map:** Freedom to import custom image file, place the cameras and I/O on the map to indicate where events are getting triggered with a convenient video preview window.
- **Bandwidth Monitor:** Monitor and display the bandwidth usage of individual cameras and remote viewing clients.
- **Two-way Audio:** Listen and record audio from camera's microphone. Talk to IP camera's speaker.
- **Instant Playback:** Allow to play the last few minutes of any live video channel on MainConsole and Remote Live View

## Playback, Search, Export and Secure data:

- **Post-Recording Processing:** Search for 5 types of different analytics events, digital PTZ and video enhancement tool are all available in playback.
- **Multi-Channel Playback:** Play up to 16 channels of recorded video simultaneously both locally and remotely.
- **Video Enhancement:** Fine tune the image's visibility, sharpen, brightness, contrast or even grey scale.
- **Intelligent Search:** Search for 5 different special events (general motion, missing object, foreign object, camera occlusion and signal lost) in recorded files with date, time and log file.
- **Video Export:** Take a snapshot of the recording in JPEG/BMP format or export a section of the video in "AVI" and "ASF" format.
- **Backup:** Backup the recording for archiving purposes or backup the recording with an embedded player to watch at a separate location. NVR supports both local and remote backup to local HD, CD, and DVD.
- **Log data:** Unusual event, system log, counting application, POS log and export and backup can export to "xls" or "txt" file
- **Watermark:** Protect for original recording from alternation with our watermark verification tool.
- **DBTool:** Reconstruct, repair or relocate the recordings in local drive, or external drive.

## Remote operations:

- **Multiple Live View Display:** Streaming live video from multiple NUUO servers (NVR, DVR, and NDVR) simultaneously. Dual monitors support with up to 128 channels per monitor (64\* channels per monitor).  
\* The maximum number of camera connections depends on the server's hardware configuration and the total bit rate of the IP cameras. Please check NUUO Calculator on <http://support.nuuo.com/calculator/>
- **Multi Playback Channels Display:** Remote playback of 16 channels recording from any one of the NUUO servers (NVR, DVR, and NDVR).
- **Intelligent PTZ:** Joystick support on PTZ cameras and software enabled digital PTZ function are both available in NUUO NVR. Preset points and patrol functions are also available on many camera models.
- **I/O Event Control:** Easy to use input and output control panel to remotely trigger digital outputs and monitor input status.
- **E-Map:** A map view of where each camera and I/O devices are located with a convenient preview window.
- **Remote Backup:** Backup the video into .DAT format with a NUUO player attached for easy achieve and viewing purposes.
- **Web-browser (client):** Display up to 64 channels of live video stream or 16 channels of playback in I.E. from any single NUUO server.
- **PDA Viewer:** Up to 16 channels snapshot or 1 channel live display; PTZ and I/O control.
- **I-Phone:** Support I-Phone browser (safari) to live view video and control PTZ function.

## Extension Service

- **Central Management System:** Ultimate central monitoring solution for grand scale projects and projects with multiple sites. Fully compatible with all NUUO servers (NVR, DVR, NDVR and NVRmini).
- **Remote Desktop Service:** Embedded remote desktop server that will host for any NUUO remote desktop clients to remotely configure the NVR software (remote desktop client is installed separately).
- **3GPP Service:** NUUO NVR supports mobile devices through 3G network to stream live view video.

## External Device

- **Point of Sale (POS):** NUUO Point of Sales system works on NUUO NVR by overlaying the transaction text from cash register onto live video channels. All POS recordings are searchable.
- **External I/O capacity:** Please refer to our I/O box section: C24/C26/C28 for more details.

## Smart Guard:

- **Smart detection** of 6 camera events, 14 different user-defined POS events, digital input events and 4 system



events. The combination of our smart guard events is a powerful tool to combat vandalism and provide a platform for operators to monitor and respond to live events immediately.

- Camera Events:
  - General Motion
  - Missing Object
  - Foreign Object
  - Focus Lost
  - Camera Occlusion
  - Signal Lost
- Signal Digital Input Event
- System Event:
  - System alarm on Disk Space Exhausted
  - System alarm on System Health Unusual (CPU temperature)
  - System alarm on Resource Depleted (CPU loading)
  - System alarm on Network Congestion

■ **Instant alarm notification** is the fastest and most cost efficient way to automatically respond to any smart detection event.

- 10 automatic instant alarm responses:
  - On Screen Display
  - Play Sound
  - Send E-mail
  - Phone Call
  - PTZ Preset Go
  - Signal Digital Output
  - Send a SMS message
  - Send to Central Server
  - Send Snapshot to FTP
  - Popup E-Map on Event

## Specifications

<b>Model</b>	SCB-IP+ Series				
<b>IP Camera Input(s)</b>	4, 8, 12, 16, 25, 32, 36, 64*				
<b>Version</b>	3.3.3				
<b>IP Camera Brand(s) Supported (with device pack v1.1.1)</b>	ACTi	Arecont	Atlantis	Axis	Basler
	Bosch	Brickcom	Cisco	CNB	Digimerge
	D-Link	Dynacolor	ENEO	Etrovision	EverFocus
	Eyeview	Fine	HIKVision	Hitron	Icantek
	IQinvision	JVC	LevelOne	Linksys	Lorex
	Lumenera	Mobotix	Moxa	Panasonic	Pixord
	Planet	Samsung	Sanyo	Santec	Seorim
	Sony	StarDot	Toshiba	Truen	Vivotek
	Y-cam	Zavio			
<b>Digital PTZ</b>	Supported in Live view and playback				
<b>Multiple Show</b>	Supported in Live view				
<b>Triple Monitor</b>	Enable maximum 64 channels with two screens to show live video and viewer recording video on third monitor.				
<b>Audio &amp; Video Recording</b>	Audio & video recording in synchronization.				
<b>Screen Division</b>	1/4/6/9/10/13/16/25/36/49/64 divided screen.				
<b>Compression Format</b>	H.264;MPEG-4;M-JPEG;MxPEG				
<b>Recording Type</b>	Continuous record, record by digital input, motion record, event recording, record by schedule, manual record				
<b>Playback Channels</b>	Playback Maximum 16 channels under several modes & full screen.				
<b>Playback Control</b>	Playback, backward playback, fast forward/backward playback.				

# NUUO NVR Specification

NUUO 3.3.3 version

<b>Auto Recycling Recording</b>	Auto recycling when storage disk is full.		
<b>Available I/O Function</b>	Supporting I/O Box		
<b>Available POS Device</b>	SCB-C31 RS232 to Ethernet Converter		
<b>Hardware Watchdog</b>	N/A		
<b>System Minimum Requirements</b>			
<b>OS Supported</b>	32bits: MS Windows XP pro SP3 / 2003/ Vista SP1 / Win 7 64bits: Win 7		
<b>CPU</b>	Intel Core 2 Duo E5300		
<b>RAM</b>	1 GB		
<b>HDD</b>	250 GB or above		
<b>Mother-board</b>	Intel 35 or 33 chip or above, MB vendor Asus, Gigabyte or Intel with Intel Chipset recommended		
<b>Display</b>	ATI Radeon 4650 , nVIDIA GeForce GF-9600 or above (ATI recommended)		
<b>Note</b>			
* The maximum number of camera connections depends on the server's hardware configuration and the total bit rate of the IP cameras. Please check NUUO Calculator on <a href="http://support.nuuo.com/calculator/">http://support.nuuo.com/calculator/</a>			
<b>Support Language</b>			
Bulgaria	Chinese (Simplified )	Chinese (Traditional)	Czech
Danish	Dutch	English	Farsi
Finnish	French	German	Greek
Hebrew	Hungarian	Italian	Japanese
Korean	Norway	Polish	Portuguese(Brazil)
Portuguese(Portugal)	Romanian	Russian	Serbia
Slovak	Slovenian	Spanish	Swedish
Thai	Turkey		

