

Release Version 1.1.2 (2011/12/19) for AP update

Modules

Item	Version	
Application (Mac)	NUUO Install Wizard	1.0.0.20
	NUUO NuClient	1.1.1.0
	NUUO Backup Player	1.1.1.0
	NUUO Offline License Tool	N/A
	NUUO Verification Tool	1.0.0.3

Bug Fixed

1. Fixed a critical issue that users cannot login to a server by NuClient (Mac version) if there is no E-map and Image Fusion configured on this server.

Release Version 1.1.2 (2011/12/7)

Modules

Item	Version	
FW	NVR	01.01.0000.0078
	Camera Package	01.01.0000.0078

New Feature

1. **Dual stream**
 - Dahua
 - Everfocus
 - Forenix
 - Samsung¹
 - Sunell
 - UDP

Bug Fixed

1. Fixed the issue that motion detection function doesn't work on Sony 3rd and 4th generation cameras².
2. Fixed the issue that camera parameter of Panasonic i-pro series cameras "may" be reset to default as camera reconnects after camera disconnected a while and NVR was trying to reconnect it.
3. Fixed the parameter settings of Panasonic WV-SP102 and WV-SP105.
4. Fixed the issue that bit rate of Panasonic DG-SF334 cannot be modified.
5. Fixed the issue that system doesn't detect Eneo camera motion right as motion is triggering.
6. Vivotek IP71XX series cameras are compatible with iViewer.
7. Upgrade camera FW to XNET.A1-1.1.11.0706 to fix IVP4030VR/IDP4030VR main stream disconnection issue as querying dual stream.

New Camera Supported

1. Arecont: AV1325, AV2825, AV8185DN

¹ SNB-1000, SNB-5000, SND-1010, SND-5080/F, SNO-5080R, SNP-3120/V/VH, SNP-3430H, SNP-5200, SNP-5200H, SNV-5080, SNV-5080R, SPE-100

² SNC-CM120, SNC-CS20, SNC-CS50, SNC-DF50, SNC-DF80, SNC-DF85, SNC-DM110, SNC-DM160, SNC-DS10, SNC-DS60, SNC-RX530, SNC-RX550, SNC-RX570, SNC-RZ50

Titan NVR Release Note

NUUO version 1.1.2 release date_2011.12

2. Axis: M3113-R, M3113-VE, M3114-VE, M5013, M5014, M7001, P3304, P3304-V, P5512, P5512-E, P5522, P5522-E, Q6032, Q6034-E, Q6035, Q6035-E
3. CNB: IDC4050F, IDC4050IR, IDC4050VF, IDC4050VR, IGC2050F, IS1765x, ISMC1063x, ISS2965x, ISSM2063x, IVC5055VF, IVC5055VR, IXC2050IR
4. **Dahua**: HDB3300N, HDB3300P, HDBW3300N, HDBW3300P, HF3110N, HF3110P, HF3211P, HF3300N, HF3300N-W, HF3300P, HF3300P-W
5. **Everfocus**: EAN3200, EAN800A, EAN800AW, EAN850A, EAN900, EDN3240, EDN800, EDN850H, EHN3200, EPN3100, EPN3600, EQN2200, EQN2201, EVS200A, EVS200AW, EVS410, EZN3240, EZN850
6. **Forenix**: ACDV-3VM501, AEP-Q2018HW-IP, AEP-Q2026HW-IP, AEP-Q2036HW-IP, ASP-PTIR737-IP, ASP-PTIR737-LA-IP, ATCP-IRH5030C, ATCP-IRH5040C, ATCP-MH802, ATCP-MH802DN, ATCP-MH802DN/WI, ATCP-MH802WI, ATCP-VM501, AWB-H811, AWB-H814, B0100, B1100, C1100, C1100-W, C2100, D0100, D1100, D2100, GE-100-VS
7. Mobotix: M24, T24
8. Samsung: SNB-1000, SNB-5000, SND-1010, SND-5080/F, SNO-5080R, SNP-3120/V/VH, SNP-3430H, SNP-5200, SNP-5200H, SNV-5080, SNV-5080R, SPE-100
9. **Sunell**: SN-IPC54/11DN, SN-IPC54/12DN, SN-IPC54/20DN, SN-IPC54/50DN, SN-IPD54/11DN, SN-IPD54/12DN, SN-IPR54/50DN, SN-IPS54/60DN/Z18, SN-IPS54/60DN/Z36, SN-IPV54/11DN, SN-IPV54/12DN, SN-IPV54/50DN, SN-IPV54/50DR
10. **UDP**: IPE1100M, IPE3100, IPE3500, IPE3500M, IPE4100, IPE5500, IPE6500, IPE7500, NVC1000, NVC4000, NVC4000-R12, NVC4000-R40
11. Vivotek: FE8171V, IP8133W, IP8352, IP8362, VS8102 (New FW)

Remote Client PC Requirement

Remote PC Minimum Requirements		
CPU	Intel Core 2 Duo, 2.6GHz	
Display Card	OpenGL 2.0 and later	
OS Supported	Windows XP 32 bit	Windows 7 32/64 bit Mac OS X 10.6/10.7
RAM	1GB	2GB
User Interface	<ol style="list-style-type: none"> 1. HTTP Web browser - Internet Explorer 8 and later and Firefox 7.0.1 2. NUUO client application program 	

Appendix

Stream profile (updated)

- Original
- Low: under 300kbps; designed for mobile client single-view
- Minimum: under 100 kbps; designed for mobile client multi-view

Brand/Series	Low Profile		Minimum Profile	
	Resolution	Framerate	Resolution	Framerate
ACTi	CIF	3~6	CIF	1~2
Arecont	half	3	half	1
Axis	CIF	5	QCIF	5
Brickcom	CIF	10	CIF	4
CNB 1	CIF~SXGA	0.1~10	CIF~SXGA	0.1~10
CNB 2	QVGA~D1	0.1~10	QVGA~D1	0.1~10
CNB 3	QVGA~D1	0.1~10	QVGA~D1	0.1~10
Dahua	CIF	5	CIF	2
Dahua (HF3211P)	D1~1080p	0.1~10	D1~1080p	0.1~10
Dynacolor	QCIF~Full HD	0.1~10	QCIF~Full HD	0.1~10

Titan NVR Release Note

NUUO version 1.1.2 release date_2011.12

Eneo 1	QCIF~Full D1	0.1~10	QCIF~Full D1	0.1~10
Eneo 2	QCIF~Half D1	0.1~10	QCIF~Half D1	0.1~10
Eneo 3	CIF~Full D1	0.1~10	CIF~Full D1	0.1~10
Eneo 4	CIF	5	CIF	2
Eneo 5	CIF	15	CIF	5
EverFocus (ONVIF)	QCIF~UXGA	0.1~6	QCIF~UXGA	0.1~6
EverFocus (Others)	QVGA	5	QVGA	1.5
Fine	CIF	1~3	CIF	0.1~1.5
Forenix	CIF	1~3	CIF	0.1~0.5
Grundig	QCIF~FullHD	0.1~10	QCIF~FullHD	0.1~10
Honeywell	640x368	15	640x368	5
Mobotix	CIF	3	QCIF	2
NetworkCamera	CIF	10	CIF	4
Panasonic BB/BL	CIF	4	QCIF	2
Panasonic i-pro 3 megapixel	VGA	1	VGA	0.5
Panasonic i-pro others	CIF	2	CIF	1
Pelco	CIF~D1	0.1~10	CIF~D1	0.1~10
Samsung	CIF	6	CIF	2
SANTEC (D1)	VGA	1~3	VGA	0.3~0.8
SANTEC (1.3 Mega)	VGA~D1	1~3	VGA~D1	0.3~0.8
SANTEC (3 Mega)	VGA~3M	1~3	VGA~3M	0.3~0.8
SANTEC (video server)	VGA~D1	1~3	VGA~D1	0.3~0.8
Sanyo HD1, HD3, HD4	CIF~VGA	3	CIF~VGA	1
Sanyo HD2	CIF~4 Mega	0.1~3	CIF~4 Mega	0.1~3
Sony	QCIF~Full HD	0.1~10	QCIF~Full HD	0.1~10
StarDot	CIF	3	CIF	1
Sunell	D1~QCIF	0.1~10	D1~QCIF	0.1~10
TRUEN	CIF~Full D1	0.1~10	CIF~Full D1	0.1~10
UDP	QVGA~VGA	0.1~10	QVAG~VGA	0.1~10
Videosec 1	QVGA	5	QQVGA	5
Videosec 2	CIF~Full HD	0.1 ~ 10	CIF~Full HD	0.1 ~ 10
Vivotek 7000v2/8000 (General)	CIF	5	CIF	2
Vivotek 7000v2/8000 (2 Mega)	CIF	3	QCIF	3
Vivotek 8000 (VS series)	QCIF~D1	0.1~10	QCIF~D1	0.1~10
Vivotek 8000 (IP8330/IP8332/IP8352)	CIF	3	CIF	1
Vivotek 8000 (IP8362)	CIF	5	CIF	3
Zavio	CIF	5	QCIF	3
Zavio (Mega)	CIF	7	CIF	2

CNB 1: IGx10xx, ixP40xx ixP4000xx

CNB 2: INS2000/IBxxxx/Xpeed IP

Titan NVR Release Note

NUUO version 1.1.2 release date_2011.12

CNB 3: IGx2050F, IDC4050xx, IXC8050IR, IVC5050xx, IVP5055xx, IDP5055xx, IXP3055VR
 Eneo 1: GLS-1701/IR
 Eneo 2: GLS-2104
 Eneo 3: GLS-2301H
 Eneo 4: NLC-1401, NLD-1401, NLS-1401
 Eneo 5: NXC-1301M, NXC-1302M, NXC-1401M, NXC-1402M, NXD-1301M, NXD-1302M, NXD-1401M, NXD-1402M
 EverFocus (ONVIF): EQN2200, EQN220
 Samsung: SNB-1000, SNB-5000, SND-1010, SND-5080/F, SNO-5080R, SNP-3120/V/VH, SNP-3430H, SNP-5200, SNP-5200H, SNV-5080, SNV-5080R, SPE-100
 Sanyo HD1: VCC-HD2500, VDC-HD3500
 Sanyo HD2: VCC-HD2100, VCC-HD2300, VDC-HD3100, VDC-HD3300
 Sanyo HD3: VCC-HD5400, VCC-HD5600
 Sanyo HD4: VCC-HD4600
 Videosec 1: IBF-211, IDA-210, IP-206M, IS-240
 Videosec 2: ICS-13, ICS-20F, ID-20

New Camera Support

Arecont



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Camera Search Tool	Remarks
AV1325		H.264 M-JPEG	1	1280x1024	-	-	-	Yes	-	Yes	Supported by design
AV2825		H.264 M-JPEG	1	1920x1080	-	1/1	-	Yes	-	Yes	Supported by design
AV8185DN		H.264 M-JPEG	4	1600x1200	-	-	-	Yes	-	Yes	Supported by design

AXIS



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
M3113-R		H.264 M-JPEG	1	800x600	-	-	Yes	Yes	Yes	Supported by design
M3113-VE		H.264 M-JPEG	1	800x600	-	-	Yes	Yes	Yes	Supported by design
M3114-VE		H.264 M-JPEG	1	1280x800	-	-	Yes	Yes	Yes	Supported by design
M5013		H.264 M-JPEG	1	800x600	1-way	-	Yes	Yes	Yes	Supported by design
M5014		H.264 MPEG4	1	1280x720	1-way	2/2	Yes	Yes	Yes	Supported by design
M7001		H.264 M-JPEG	1	720x576	-	-	Yes	Yes	Yes	Supported by design

Titan NVR Release Note

NUUO version 1.1.2 release date_2011.12

P3304		H.264 M-JPEG	1	1280x800	1-way	1/1	Yes	Yes	Yes	Supported by design
P3304-V		H.264 M-JPEG	1	1280x800	1-way	1/1	Yes	Yes	Yes	Supported by design
P5512		H.264 M-JPEG	1	704x480	1-way	4/4	Yes	Yes	Yes	Supported by design
P5512-E		H.264 M-JPEG	1	704x480	1-way	4/4	Yes	Yes	Yes	Supported by design
P5522		H.264 M-JPEG	1	720x480	1-way	4/4	Yes	Yes	Yes	Supported by design
P5522-E		H.264 M-JPEG	1	720x480	1-way	4/4	Yes	Yes	Yes	Supported by design
Q6032		H.264 M-JPEG	1	752x480	1-way	4/4	Yes	Yes	Yes	Supported by design
Q6034-E		H.264 M-JPEG	1	1280x720	1-way	2/2	Yes	Yes	Yes	Supported by design
Q6035		H.264 M-JPEG	1	1280x720	1-way	4/4	Yes	Yes	Yes	Supported by design
Q6035-E		H.264 M-JPEG	1	1280x720	1-way	-	Yes	Yes	Yes	Supported by design

CNB



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IDC4050F	Refer to IDC4050IR	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	-	Yes	Supported by design
IDC4050IR	XNET.M1-1.10.11.0822	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	
IDC4050VF	Refer to IDC4050IR	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	-	Yes	Supported by design
IDC4050VR	Refer to IDC4050IR	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	-	Yes	Supported by design

Note: Camera issue: image may be broken apparently under high parameter settings.

IGC2050F	Refer to IDC4050IR	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	-	Yes	Supported by design
IS1765x	Refer to ISMC1063x	H.264 MPEG4 M-JPEG	1	704x480(N) 704x576(P)	1-way	1/1	Yes	-	Yes	Supported by design
ISMC1063x	XNET.A1-1.01.11.0125	H.264 MPEG4 M-JPEG	1	704x480(N) 704x576(P)	1-way	4/0	Yes	Yes	Yes	
ISS2965x	Refer to ISMC1063x	H.264 MPEG4 M-JPEG	1	704x480(N) 704x576(P)	1-way	4/0	Yes	-	Yes	Supported by design

Titan NVR Release Note

NUUO version 1.1.2 release date_2011.12

ISSM2063x	Refer to ISMC1063x	H.264 MPEG4 M-JPEG	1	704x480(N) 704x576(P)	1-way	4/0	Yes	-	Yes	Supported by design
IVC5055VF	Refer to IDC4050IR	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	-	Yes	Supported by design
IVC5055VR	Refer to IDC4050IR	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	-	Yes	Supported by design
IXC2050IR	Refer to IDC4050IR	H.264 M-JPEG	1	1920x1080	1-way	1/1	-	-	Yes	Supported by design

Dahua



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
HDB3300N		H.264 M-JPEG	1	2048×1536	1-way	2/1	Yes	Yes	-	Supported by design
HDB3300P		H.264 M-JPEG	1	2048×1536	1-way	2/1	Yes	Yes	-	Supported by design
HDBW3300N	V2.000 , Update 2011.10.22	H.264 M-JPEG	1	2048×1536	1-way	2/1	Yes	Yes	-	
HDBW3300P		H.264 M-JPEG	1	2048×1536	1-way	2/1	Yes	Yes	-	Supported by design
HF3110N		H.264 M-JPEG	1	1280x960	1-way	1/1	Yes	Yes	-	Supported by design
HF3110P	V2.000 , Update 2011.10.22	H.264 M-JPEG	1	1280x960	1-way	1/1	Yes	Yes	-	
HF3211P	V2.000 , Update 2011.10.22	H.264 M-JPEG	1	1920x1080	1-way	2/1	Yes	Yes	-	
HF3300N	V2.000 , Update 2011.10.22	H.264 M-JPEG	1	2048×1536	1-way	1/1	Yes	Yes	-	
HF3300N-W		H.264 M-JPEG	1	2048×1536	1-way	1/1	Yes	Yes	-	Supported by design
HF3300P		H.264 M-JPEG	1	2048×1536	1-way	1/1	Yes	Yes	-	Supported by design
HF3300P-W		H.264 M-JPEG	1	2048×1536	1-way	1/1	Yes	Yes	-	Supported by design

Note: HP3300 series: there may be image noise of dual stream, which can be observed from the camera web as well.


Note: Setting preset point doesn't work properly.

Note: PTZ is only supported by external RS-485 device.

Everfocus

Titan NVR Release Note

NUUO version 1.1.2 release date_2011.12

										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
EAN3200	1.0.14	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	
EAN800A	1.2.5	H.264 MPEG4 MJPEG	1	704x576	1-way	1/1	-	Yes	Yes	
EAN800AW	1.2.5	H.264 MPEG4 MJPEG	1	704x576	1-way	1/1	-	Yes	Yes	Supported by design
EAN850A	1.2.5	H.264 MPEG4 MJPEG	1	704x576	1-way	1/1	-	Yes	Yes	
EAN900	1.2.5	H.264 MPEG4 MJPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	
Note:	Fix stream 1 as recording stream and fix stream 2 for mobile client used.									
EDN3240	1.0.14	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	
EDN800	1.2.5	H.264 MPEG4 MJPEG	1	704x576	1-way	1/1	-	Yes	Yes	
EDN850H	1.2.5	H.264 MPEG4 MJPEG	1	704x576	1-way	1/1	-	Yes	Yes	
EHN3200	1.0.14	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	
EPN3100	1.2.14	H.264 MPEG4 MJPEG	1	704x576	1-way	4/2	Yes	Yes	Yes	Supported by design
EPN3600	1.2.14	H.264 MPEG4 MJPEG	1	704x576	1-way	4/2	Yes	Yes	Yes	
EQN2200	1.0.27	H.264 MJPEG	1	1600x1200	1-way	1/1	-	Yes	Yes	Supported by design
EQN2201	1.0.27	H.264 MJPEG	1	1600x1200	1-way	1/1	-	Yes	Yes	Supported by design
EVS200A	1.2.8	H.264 MPEG4 MJPEG	2	704x576	1-way	2/2	Yes	Yes	Yes	
EVS200AW	1.2.8	H.264 MPEG4 MJPEG	2	704x576	1-way	2/2	Yes	Yes	Yes	Supported by design
EDN3240	1.0.14	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	
Note:	EVS200A/EVS200AW: Fix stream 1 as recording stream and fix stream 2 for mobile client used. PTZ is only supported by external RS-485 device.									
EVS410	1.0.14	H.264 MJPEG	4	704x480	1-way	4/1	Yes	Yes	Yes	

Titan NVR Release Note

NUUO version 1.1.2 release date_2011.12

Note:	PTZ is only supported by external RS-485 device.									
EZN3240	1.0.14	H.264 MJPEG	1	1920x1080	1-way	1/1	-	Yes	Yes	
EZN850	1.2.5	H.264 MPEG4 MJPEG	1	704x576	1-way	1/1	Yes	Yes	Yes	
Note:	PTZ: support focus only.									

Forenix



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
ACDV-3VM501		H.264 M-JPEG	1	1600x1200	-	1/1	-	Yes	Yes	Supported by design
AEP-Q2018HW-IP		H.264 M-JPEG	1	720x480	-	-	Yes	Yes	Yes	Supported by design
AEP-Q2026HW-IP		H.264 M-JPEG	1	720x480	-	-	Yes	Yes	Yes	Supported by design
AEP-Q2036HW-IP		H.264 M-JPEG	1	720x480	-	-	Yes	Yes	Yes	Supported by design
ASP-PTIR737-IP		H.264 M-JPEG	1	720x576	-	-	Yes	Yes	Yes	Supported by design
ASP-PTIR737-LA-IP		H.264 M-JPEG	1	720x576	-	-	Yes	Yes	Yes	Supported by design
ATCP-IRH503 0C		H.264 M-JPEG	1	1600x1200	-	1/1	-	Yes	Yes	Supported by design
ATCP-IRH504 0C		H.264 M-JPEG	1	1600x1200	-	1/1	-	Yes	Yes	Supported by design
ATCP-MH802		H.264 M-JPEG	1	1600x1200	-	1/1	-	Yes	Yes	Supported by design
ATCP-MH802DN		H.264 M-JPEG	1	1600x1200	-	1/1	-	Yes	Yes	Supported by design
ATCP-MH802DN/WI		H.264 M-JPEG	1	1600x1200	-	1/1	-	Yes	Yes	Supported by design
ATCP-MH802WI		H.264 M-JPEG	1	1600x1200	-	1/1	-	Yes	Yes	Supported by design
ATCP-VM501		H.264 M-JPEG	1	1600x1200	-	1/1	-	Yes	Yes	Supported by design
AWB-H811		H.264 M-JPEG	1	720x480	-	2/2	Yes	Yes	Yes	Supported by design
AWB-H814		H.264 M-JPEG	1	720x576	-	4/4	-	Yes	Yes	Supported by design

Titan NVR Release Note

NUUO version 1.1.2 release date_2011.12

B0100		H.264 M-JPEG MPEG4	1	1280x800	1-way	1/0	-	Yes	Yes	Supported by design
B1100		H.264 M-JPEG MPEG4	1	1280x800	1-way	1/0	-	Yes	Yes	Supported by design
C1100		H.264 M-JPEG MPEG4	1	1280x800	1-way	-	-	Yes	Yes	Supported by design
C1100-W		H.264 M-JPEG MPEG4	1	1280x800	1-way	-	-	Yes	Yes	Supported by design
C2100		H.264 M-JPEG MPEG4	1	1280x800	1-way	-	-	Yes	Yes	Supported by design
D0100		H.264 M-JPEG MPEG4	1	1280x800	1-way	-	-	Yes	Yes	Supported by design
D1100		H.264 M-JPEG MPEG4	1	1280x800	1-way	1/0	-	Yes	Yes	Supported by design
D2100		H.264 M-JPEG MPEG4	1	1280x800	1-way	1/0	-	Yes	Yes	Supported by design
GE-100-VS		H.264 M-JPEG MPEG4	1	1280x800	1-way	-	-	Yes	Yes	Supported by design

Mobotix



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
M24	MX-V4.0.4.19	MxPEG M-JPEG	1	2048x1536	1-way	-	-	Yes	-	
T24	MX-V4.0.4.19	MxPEG M-JPEG	1	2048x1536	1-way	7/3	-	Yes	-	

Samsung



Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
SNB-1000	v1.07_110407	H.264 MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	-	
Note:	This is POE camera, but the device is unstable without AC power connection. We suggest connecting with AC power.									
Note:	I/O and MD is unstable, which is a known issue reported by Samsung. They won't do any change since the camera is discontinued.									
SNB-5000	v1.33_110218	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	-	
SND-1010	v1.07_110407	H.264 MPEG4 M-JPEG	1	640x480	-	1/1	-	Yes	-	

Titan NVR Release Note

NUUO version 1.1.2 release date_2011.12

Note:	This is POE camera, but the device is unstable without AC power connection. We suggest connecting with AC power.									
Note:	I/O and MD is unstable, which is a known issue reported by Samsung. They won't do any change since the camera is discontinued.									
SND-5080/F	v2.00_110608	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	-	
SNO-5080R	v1.00_110514	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	-	
SNP-3120/V/ VH	v1.24_110816	H.264 MPEG4 M-JPEG	1	704x480	1-way	2/2	Yes	Yes	-	
Note:	It takes a while to stop after users click stop patrol button.									
SNP-3430H	v1.10_110818	H.264 MPEG4 M-JPEG	1	704x480	1-way	8/4	Yes	Yes	-	
Note:	This is POE camera, but the device is unstable without AC power connection. We suggest connecting with AC power.									
Note:	There is a camera FW issue that we cannot get VBR/CBR info to show quality or bit rate correctly. Please upgrade to FW 1.11_111103 to fix it.									
Note:	Voice cracks in the video exported with ASF format, while the audio of video file is correctly recorded actually. Please choose to export with AVI format.									
Note:	Not support Area Zoom due to protocol limitation.									
Note:	The speed selections of PTZ and focus in LiveView is not synchronized with camera web due to protocol limitation.									
SNP-5200		H.264 MPEG4 M-JPEG	1	1280x1024	1-way	4/2	-	Yes	-	Supported by design
SNP-5200H	v1.02_110603	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	4/2	-	Yes	-	
Note:	SNP-5200/5200H: voice cracks in the video exported with ASF format, while the audio of video file is correctly recorded actually. Please choose to export with AVI format.									
Note:	SNP-5200/5200H: not support Area Zoom due to protocol limitation.									
Note:	SNP-5200/5200H: the speed selections of PTZ and focus in LiveView is not synchronized with camera web due to protocol limitation.									
SNV-5080		H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	-	Supported by design
SNV-5080R	v1.00_110421	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	-	
Note:	It's likely failed to query camera parameter in high resolution configuration. It happens on SNO-5080R most. When encountering this issue, please go to camera web.									
SPE-100	v1.19_110317	H.264 MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes	Yes	-	

Titan NVR Release Note

NUUO version 1.1.2 release date_2011.12

Note:	SPE-100 PTZ is abnormal, which PTZ may not be stopped after operating. This is camera FW bug, we can observe the same phenomenon on camera web.
Note:	All cameras: it's likely failed to query camera parameter in high resolution configuration. It happens on SNO-5080R most. When encountering this issue, please go to camera web.
Note:	All cameras: if configuring fixed frame rate on camera web, parameter selection on NVR web page won't be synchronized.

Sunell




Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
SN-IPC54/11 DN		H.264 M-JPEG	1	1280x720	1-way	-	-	Yes	-	Supported by design
SN-IPC54/12 DN		H.264 M-JPEG	1	1920x1080	1-way	-	-	Yes	-	Supported by design
SN-IPC54/20 DN	1.6_build044011_061	H.264 M-JPEG	1	704x576	1-way	-	-	Yes	-	
SN-IPC54/50 DN		H.264 M-JPEG	1	1280x720	1-way	-	-	Yes	-	Supported by design
SN-IPD54/11 DN		H.264 M-JPEG	1	1280x720	1-way	-	-	Yes	-	Supported by design
SN-IPD54/12 DN		H.264 M-JPEG	1	1920x1080	1-way	-	-	Yes	-	Supported by design
SN-IPR54/50 DN		H.264 M-JPEG	1	1280x720	1-way	-	-	Yes	-	Supported by design
SN-IPS54/60 DN/Z18		H.264 M-JPEG	1	704x576	1-way	-	-	Yes	-	Supported by design
SN-IPS54/60 DN/Z36		H.264 M-JPEG	1	704x576	1-way	-	-	Yes	-	Supported by design
SN-IPV54/11 DN		H.264 M-JPEG	1	1280x720	1-way	-	-	Yes	-	Supported by design
SN-IPV54/12 DN		H.264 M-JPEG	1	1920x1080	1-way	-	-	Yes	-	Supported by design
SN-IPV54/50 DN		H.264 M-JPEG	1	1280x720	1-way	-	-	Yes	-	Supported by design
SN-IPV54/50 DR		H.264 M-JPEG	1	1280x720	1-way	-	-	Yes	-	Supported by design
Note:	Do not support I/O due to camera FW limitation.									

UDP



Titan NVR Release Note

NUUO version 1.1.2 release date_2011.12

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
IPE1100M		H.264 MPEG4 M-JPEG	1	720x582	1-way	1/1	-	Yes	Yes	Supported by design
IPE3100		H.264 MPEG4 M-JPEG	1	768x576	1-way	1/1	-	Yes	Yes	Supported by design
IPE3500		H.264 MPEG4 M-JPEG	1	1600x1200	1-way	1/1	-	Yes	Yes	Supported by design
IPE3500M	1.6.7	H.264 MPEG4 M-JPEG	1	1600x1200	1-way	1/1	-	Yes	Yes	
IPE4100	1.6.6	H.264 MPEG4 M-JPEG	1	720x576	1-way	4/2	Yes	Yes	Yes	
IPE5500		H.264 MPEG4 M-JPEG	1	752x582	1-way	1/1	-	Yes	Yes	Supported by design
IPE6500		H.264 MPEG4 M-JPEG	1	752x582	1-way	1/1	-	Yes	Yes	Supported by design
IPE7500		H.264 MPEG4 M-JPEG	1	752x582	1-way	1/1	-	Yes	Yes	Supported by design
NVC1000	1.6.7	H.264 MPEG4 M-JPEG	1	720x576	1-way	2/2	Yes	Yes	Yes	
NVC4000	1.6.7	H.264 MPEG4 M-JPEG	1	720x576	1-way	2/1	Yes	Yes	Yes	
NVC4000-R12		H.264 MPEG4 M-JPEG	1	720x576	1-way	2/1	Yes	Yes	Yes	Supported by design
NVC4000-R40		H.264 MPEG4 M-JPEG	1	720x576	1-way	2/1	Yes	Yes	Yes	Supported by design
Note:	UDP cameras are likely disconnected if configuring camera parameter frequently. This is the known issue from camera vendor. When encountering this issue, please reboot the camera.									
Note:	UDP cameras are likely disconnected if setting up highest quality. This is the known issue from camera vendor. When encountering this issue, please reboot the camera, and do not set up this configuration.									
Vivotek										
										
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	UPnP	Remarks
FE8171V	0100d	H.264 MPEG4 M-JPEG	1	1600x1200	1-way	1/1	-	Yes	Yes	
Note:	De-wrap function is not integrated in this version.									
IP8133W	0100c	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
Note:	Due to the parameter limitation of stream 1, we take stream 2 as main stream for recording and liveview.									

Titan NVR Release Note

NUUO version 1.1.2 release date_2011.12

IP8352	0100g	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Supported by design
Note:	I/O status is abnormal, which input and output cannot be triggered at the same time. Vivotek will fix the bug in next release, please upgrade to new camera FW then.									
IP8362	0100d	H.264 MPEG4 M-JPEG	1	1920x1080	1-way	1/0	-	Yes	Yes	Supported by design
VS8102	0202c2	H.264 MPEG4 M-JPEG	1	720x576	1-way	1/1	-	Yes	Yes	

Release Version 1.1.0 (2011/11/1)

Modules

Item	Version	
FW	NVR	01.01.0000.0069
	Camera Package	01.01.0000.0069
Application (Windows)	NUUO Install Wizard	1.0.0.20
	NUUO NuClient	1.0.0.14
	NUUO Backup Player	1.0.0.14
	NUUO Offline License Tool	1.0.1.37
	NUUO Verification Tool	1.0.0.3
Application (Mac)	NUUO Install Wizard	1.0.0.20
	NUUO NuClient	1.1.0.9
	NUUO Backup Player	1.1.0.9
	NUUO Offline License Tool	N/A
	NUUO Verification Tool	1.0.0.3
Document	Titan Server User Manual	1.1.0
	NuClient User Manual	1.1.0
	Titan Quick Start Guide	1.1.0

New Feature

1. New OS support: Mac OS X 10.6/10.7
2. New browser support
 - Windows Firefox 7.0.1
 - Mac Safari 5.1 (7534.48.3) for configuration only
3. Verification Tool

Known Issue

[Titan Server]

1. The color of 5 megapixel video image is not correctly displayed on Local Display. This is the limitation of server graphic card.
2. The word of input field it's not grayed out apparently, while the function is disabled as design, which might be Safari's bug.

Titan NVR Release Note

NUUO version 1.1.2 release date_2011.12

[Client_Mac version]

1. Only .mov format is supported in video exportation, which is the current limitation of NuClient.
2. Not support magic mouse on some special operations (i.e. multi-touch function), which may cause error.
3. Cannot play exported high definition video (over 720p) properly by QuickTime player 10.1 with Mac OS X 10.7, while the same video plays well on QuickTime 10.0 with Mac OS X 10.6. This may be a limitation of QuickTime.

Note: The version is mainly on Mac support, issues of Client (Windows) in v1.0.0 aren't fixed yet.

Remote Client PC Requirement

Remote PC Minimum Requirements		
CPU	Intel Core 2 Duo, 2.6GHz	
Display Card	OpenGL 2.0 and later	
OS Supported	Windows XP 32 bit	Windows 7 32/64 bit Mac OS X 10.6/10.7
RAM	1GB	2GB
User Interface	3. HTTP Web browser - Internet Explorer 8 and later and Firefox 7.0.1 4. NUUO client application program	

Release Version 1.0.0 (2011/9)

Modules

Item	Version	
FW	NVR	01.00.0000.0065
	Camera Package	01.00.0000.0065
Application	NUUO Install Wizard	1.0.0.20
	NUUO NuClient	1.0.0.14
	NUUO Backup Player	1.0.0.14
	NUUO Offline License Tool	1.0.1.37
Document	Titan Server User Manual	1.0.0
	NuClient User Manual	1.0.0
	Titan Quick Start Guide	1.0.0

Known Issue

[Titan Server]

1. Video on Local Display may hang 0.3 second every 2 seconds. There is no this issue on LiveView and Playback.
2. Users can name the I/O devices with more than 64 characters in web client, but only 64 characters will be saved. We suggest users not keying in more than 64 characters.
3. There is no popup message as the maximum user connections of Live View and Playback has been reached. We suggest users setting maximum connections of Live View as 256 in server.³ If users have trouble of logging in, please reduce the concurrent connections.

³ Maximum connections of Playback is 128, which is defaulted and can't be modified

[Web Client]

1. For VIVOTEK PZ7131 camera, users can save more than 16 preset points in web client; however, users can only add up to 16 preset points in Client AP.
2. When clicking on the snapshot icon on view panel of web client, view panel may flash a lot before image pops up. It happens in view under image fusion, but it has no impact on function. The factor of this issue is IE browser, so there is no solution currently.
3. As web client minimizes to system tray, users can still hear camera audio, which isn't synchronized with the behavior of client AP.
4. Full screen is only supported in Client AP, but not in web client.
5. Do not support 64bit IE.

[NuClient]

1. If the network of slaves is not stable, please don't configure more than 5 slaves to a master.
2. AP may crash under long-time live viewing if receiving audio from some certain cameras, especially megapixel cameras.
3. Drag the scroll bar back to make the image complete, or you cannot use camera content tool bar.
4. If the graphic card you use is ATI 4350, the image is disappeared when doing digital PTZ.
5. If the version of ATI HD4800 driver is in the year of 2010, it's likely that time line is not updated as dragging camera to grid.
6. Videos cannot be displayed on the Client PC with on-board graphic card. Do not support on-board graphic card.⁴

[NuClient: Playback]

1. When playing back to the timeline without recording videos, the image will stay on the final frame of last video clip until playing to a new one.
2. In Playback mode, switch to single layout by double clicking a camera, and drag a camera to the grid, you may discover the timeline of this channel disappeared. Users can switch to other layouts when encountering this issue.
3. Some specific cameras, such as Arecont AV 2100, have floating FPS⁵ problem which may lead to temporarily repeating video images when playing back.
4. Frame may stay still for a while as searching in Motion Search, which will be improved in coming version.
5. It's impossible to search any DI event log in Playback if the selected source type is "all", which implies that the only way to search DI event is selecting source type as "DI".
6. It's likely that system cannot query any event if there are too many events searched. When encounter this issue, try not to select event name as "all".
7. When playing back videos with both ImmerVision and non-ImmerVision mode recording, there may be no ImmerVision function icon displayed on camera content toolbar, which will become normal as refreshing the view by switching LiveView/Playback or switching views and play again.
8. As megapixel ImmerVision Camera switches to Perimeter Mode, the system may hang in a short period. This is the restraint of ImmerVision and there is no impact on function. If it does matter to users, please try to lower the resolution to avoid this problem.
9. The keying function doesn't work on cue in/out time of selected video period on Backup Tool through Playback page, but it works on Backup Tool through LiveView. Recommend to select time by timeline bar or adjust it by mouse wheel.

[Other Application]

1. In Backup Player, video cannot be updated to the correct time when doing skip forward/backward under the condition of video pause. There is no this issue on NuClient.

⁴ User may not encounter this issue if the on-board graphic card supports OpenGL 2.0 and later

⁵ FPS stands for frame per second

Notice

1. Supported languages in this version includes English, Japanese, Traditional Chinese, Spanish, French, Italian, Russian, Korean, Português (Brasil) and Finnish.

Potential Risk

The following cameras are supported by design, which implies that they may contain potential error; if you encounter some problems, please contact our Support Team: service@nuuo.com.



Camera Package
Potential Risk

Remote Client PC Requirement

Remote PC Minimum Requirements		
CPU	Intel Core 2 Duo, 2.6GHz	
Display Card	nVidia or ATI with 1GB memory (OpenGL 2.0 and later)	
OS Supported	Windows XP 32 bit	Windows 7 32/64 bit
RAM	1GB	2GB
User Interface	5. HTTP Web browser - Internet Explorer 8 and later 6. NUUO client application program	